DATASHEET

GENERATED ON: 10 Nov 2026 | SYS.REF: MAZDA-LED



KIKI

MAZDA Model: SXR1812 Spot Light

Kik I is a ceiling adjustable beam angle, deep anti-glare, Die-cast aluminum ceiling spotlight. A variety of colors for decorative cover are available, suitable for a variety of decoration style and scene application. Multiple beam angles options, to meet different lighting requirements. Embedded LED chip design, cut-off angle more than 30, to protect human eyes effectively. Using high-quality LED chips, the light color is pure with excellent color consistency and high CRI;
Professional reflector design, different colors for decorative cover are optional; Embedded LED chip design for better glare control; Adjustable angle is optional , to meet the lighting requirements of different scenes and illumination objects.

ALL AVAILABLE VARIANTS

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
1	MAZDA-SXR181208W-2.7K-AC240-WH-10VDIM-A95 X B105 X C86 MM	08W	2700	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
2	MAZDA-SXR181208W-2.7K-AC240-WH-10VDIM-EM-A95 X B105 X C86 MM	08W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
3	MAZDA-SXR181208W-2.7K-AC240-BK-10VDIM-A95 X B105 X C86 MM	08W	2700	240VAC	BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
4	MAZDA-SXR181208W-2.7K-AC240-BK-10VDIM-EM-A95 X B105 X C86 MM	08W	2700	240VAC	BLACK	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
5	MAZDA-SXR181208W-2.7K-AC240-WH-PH-A95 X B105 X C86 MM	08W	2700	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
6	MAZDA-SXR181208W-2.7K-AC240-WH-PH-EM-A95 X B105 X C86 MM	08W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
7	MAZDA-SXR181208W-2.7K-AC240-BK-PH-A95 X B105 X C86 MM	08W	2700	240VAC	BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
8	MAZDA-SXR181208W-2.7K-AC240-BK-PH-EM-A95 X B105 X C86 MM	08W	2700	240VAC	BLACK	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
9	MAZDA-SXR181208W-2.7K-AC240-WH-DA-A95 X B105 X C86 MM	08W	2700	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
10	MAZDA-SXR181208W-2.7K-AC240-WH-DA-EM-A95 X B105 X C86 MM	08W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
11	MAZDA-SXR181208W-2.7K-AC240-BK-DA-A95 X B105 X C86 MM	08W	2700	240VAC	BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
12	MAZDA-SXR181208W-2.7K-AC240-BK-DA-EM-A95 X B105 X C86 MM	08W	2700	240VAC	BLACK	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
13	MAZDA-SXR181208W-2.7K-AC240-WH-ND-A95 X B105 X C86 MM	08W	2700	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
14	MAZDA-SXR181208W-2.7K-AC240-WH-ND-EM-A95 X B105 X C86 MM	08W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
15	MAZDA-SXR181208W-2.7K-AC240-BK-ND-A95 X B105 X C86 MM	08W	2700	240VAC	BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
16	MAZDA-SXR181208W-2.7K-AC240-BK-ND-EM-A95 X B105 X C86 MM	08W	2700	240VAC	BLACK	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
17	MAZDA-SXR181208W-3K-AC240-WH-10VDIM-A95 X B105 X C86 MM	08W	3000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
18	MAZDA-SXR181208W-3K-AC240-WH-10VDIM-EM-A95 X B105 X C86 MM	08W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	

DATASHEET

GENERATED ON: 10 Nov 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
19	MAZDA-SXR181208W-3K-AC240-BK-10VDIM-A95 X B105 X C86 MM	08W	3000	240VAC	BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
20	MAZDA-SXR181208W-3K-AC240-BK-10VDIM-EM-A95 X B105 X C86 MM	08W	3000	240VAC	BLACK	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
21	MAZDA-SXR181208W-3K-AC240-WH-PH-A95 X B105 X C86 MM	08W	3000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
22	MAZDA-SXR181208W-3K-AC240-WH-PH-EM-A95 X B105 X C86 MM	08W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
23	MAZDA-SXR181208W-3K-AC240-BK-PH-A95 X B105 X C86 MM	08W	3000	240VAC	BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
24	MAZDA-SXR181208W-3K-AC240-BK-PH-EM-A95 X B105 X C86 MM	08W	3000	240VAC	BLACK	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
25	MAZDA-SXR181208W-3K-AC240-WH-DA-A95 X B105 X C86 MM	08W	3000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
26	MAZDA-SXR181208W-3K-AC240-WH-DA-EM-A95 X B105 X C86 MM	08W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
27	MAZDA-SXR181208W-3K-AC240-BK-DA-A95 X B105 X C86 MM	08W	3000	240VAC	BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
28	MAZDA-SXR181208W-3K-AC240-BK-DA-EM-A95 X B105 X C86 MM	08W	3000	240VAC	BLACK	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
29	MAZDA-SXR181208W-3K-AC240-WH-ND-A95 X B105 X C86 MM	08W	3000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
30	MAZDA-SXR181208W-3K-AC240-WH-ND-EM-A95 X B105 X C86 MM	08W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
31	MAZDA-SXR181208W-3K-AC240-BK-ND-A95 X B105 X C86 MM	08W	3000	240VAC	BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
32	MAZDA-SXR181208W-3K-AC240-BK-ND-EM-A95 X B105 X C86 MM	08W	3000	240VAC	BLACK	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
33	MAZDA-SXR181208W-4K-AC240-WH-10VDIM-A95 X B105 X C86 MM	08W	4000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
34	MAZDA-SXR181208W-4K-AC240-WH-10VDIM-EM-A95 X B105 X C86 MM	08W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
35	MAZDA-SXR181208W-4K-AC240-BK-10VDIM-A95 X B105 X C86 MM	08W	4000	240VAC	BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
36	MAZDA-SXR181208W-4K-AC240-BK-10VDIM-EM-A95 X B105 X C86 MM	08W	4000	240VAC	BLACK	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
37	MAZDA-SXR181208W-4K-AC240-WH-PH-A95 X B105 X C86 MM	08W	4000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
38	MAZDA-SXR181208W-4K-AC240-WH-PH-EM-A95 X B105 X C86 MM	08W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
39	MAZDA-SXR181208W-4K-AC240-BK-PH-A95 X B105 X C86 MM	08W	4000	240VAC	BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
40	MAZDA-SXR181208W-4K-AC240-BK-PH-EM-A95 X B105 X C86 MM	08W	4000	240VAC	BLACK	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
41	MAZDA-SXR181208W-4K-AC240-WH-DA-A95 X B105 X C86 MM	08W	4000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
42	MAZDA-SXR181208W-4K-AC240-WH-DA-EM-A95 X B105 X C86 MM	08W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
43	MAZDA-SXR181208W-4K-AC240-BK-DA-A95 X B105 X C86 MM	08W	4000	240VAC	BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
44	MAZDA-SXR181208W-4K-AC240-BK-DA-EM-A95 X B105 X C86 MM	08W	4000	240VAC	BLACK	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
45	MAZDA-SXR181208W-4K-AC240-WH-ND-A95 X B105 X C86 MM	08W	4000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
46	MAZDA-SXR181208W-4K-AC240-WH-ND-EM-A95 X B105 X C86 MM	08W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
47	MAZDA-SXR181208W-4K-AC240-BK-ND-A95 X B105 X C86 MM	08W	4000	240VAC	BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	

DATASHEET

GENERATED ON: 10 Nov 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
48	MAZDA-SXR181208W-4K-AC240-BK-ND-EM-A95 X B105 X C86 MM	08W	4000	240VAC	BLACK	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
49	MAZDA-SXR181208W-5K-AC240-WH-10VDIM-A95 X B105 X C86 MM	08W	5000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
50	MAZDA-SXR181208W-5K-AC240-WH-10VDIM-EM-A95 X B105 X C86 MM	08W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
51	MAZDA-SXR181208W-5K-AC240-BK-10VDIM-A95 X B105 X C86 MM	08W	5000	240VAC	BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
52	MAZDA-SXR181208W-5K-AC240-BK-10VDIM-EM-A95 X B105 X C86 MM	08W	5000	240VAC	BLACK	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
53	MAZDA-SXR181208W-5K-AC240-WH-PH-A95 X B105 X C86 MM	08W	5000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
54	MAZDA-SXR181208W-5K-AC240-WH-PH-EM-A95 X B105 X C86 MM	08W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
55	MAZDA-SXR181208W-5K-AC240-BK-PH-A95 X B105 X C86 MM	08W	5000	240VAC	BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
56	MAZDA-SXR181208W-5K-AC240-BK-PH-EM-A95 X B105 X C86 MM	08W	5000	240VAC	BLACK	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
57	MAZDA-SXR181208W-5K-AC240-WH-DA-A95 X B105 X C86 MM	08W	5000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
58	MAZDA-SXR181208W-5K-AC240-WH-DA-EM-A95 X B105 X C86 MM	08W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
59	MAZDA-SXR181208W-5K-AC240-BK-DA-A95 X B105 X C86 MM	08W	5000	240VAC	BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
60	MAZDA-SXR181208W-5K-AC240-BK-DA-EM-A95 X B105 X C86 MM	08W	5000	240VAC	BLACK	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
61	MAZDA-SXR181208W-5K-AC240-WH-ND-A95 X B105 X C86 MM	08W	5000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
62	MAZDA-SXR181208W-5K-AC240-WH-ND-EM-A95 X B105 X C86 MM	08W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
63	MAZDA-SXR181208W-5K-AC240-BK-ND-A95 X B105 X C86 MM	08W	5000	240VAC	BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
64	MAZDA-SXR181208W-5K-AC240-BK-ND-EM-A95 X B105 X C86 MM	08W	5000	240VAC	BLACK	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
65	MAZDA-SXR181208W-6K-AC240-WH-10VDIM-A95 X B105 X C86 MM	08W	6000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
66	MAZDA-SXR181208W-6K-AC240-WH-10VDIM-EM-A95 X B105 X C86 MM	08W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
67	MAZDA-SXR181208W-6K-AC240-BK-10VDIM-A95 X B105 X C86 MM	08W	6000	240VAC	BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
68	MAZDA-SXR181208W-6K-AC240-BK-10VDIM-EM-A95 X B105 X C86 MM	08W	6000	240VAC	BLACK	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
69	MAZDA-SXR181208W-6K-AC240-WH-PH-A95 X B105 X C86 MM	08W	6000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
70	MAZDA-SXR181208W-6K-AC240-WH-PH-EM-A95 X B105 X C86 MM	08W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
71	MAZDA-SXR181208W-6K-AC240-BK-PH-A95 X B105 X C86 MM	08W	6000	240VAC	BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
72	MAZDA-SXR181208W-6K-AC240-BK-PH-EM-A95 X B105 X C86 MM	08W	6000	240VAC	BLACK	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
73	MAZDA-SXR181208W-6K-AC240-WH-DA-A95 X B105 X C86 MM	08W	6000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
74	MAZDA-SXR181208W-6K-AC240-WH-DA-EM-A95 X B105 X C86 MM	08W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
75	MAZDA-SXR181208W-6K-AC240-BK-DA-A95 X B105 X C86 MM	08W	6000	240VAC	BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
76	MAZDA-SXR181208W-6K-AC240-BK-DA-EM-A95 X B105 X C86 MM	08W	6000	240VAC	BLACK	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	

DATASHEET

GENERATED ON: 10 Nov 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
77	MAZDA-SXR181208W-6K-AC240-WH-ND-A95 X B105 X C86 MM	08W	6000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
78	MAZDA-SXR181208W-6K-AC240-WH-ND-EM-A95 X B105 X C86 MM	08W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
79	MAZDA-SXR181208W-6K-AC240-BK-ND-A95 X B105 X C86 MM	08W	6000	240VAC	BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
80	MAZDA-SXR181208W-6K-AC240-BK-ND-EM-A95 X B105 X C86 MM	08W	6000	240VAC	BLACK	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
81	MAZDA-SXR181208W-6.5K-AC240-WH-10VDIM-A95 X B105 X C86 MM	08W	6500	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
82	MAZDA-SXR181208W-6.5K-AC240-WH-10VDIM-EM-A95 X B105 X C86 MM	08W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
83	MAZDA-SXR181208W-6.5K-AC240-BK-10VDIM-A95 X B105 X C86 MM	08W	6500	240VAC	BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
84	MAZDA-SXR181208W-6.5K-AC240-BK-10VDIM-EM-A95 X B105 X C86 MM	08W	6500	240VAC	BLACK	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
85	MAZDA-SXR181208W-6.5K-AC240-WH-PH-A95 X B105 X C86 MM	08W	6500	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
86	MAZDA-SXR181208W-6.5K-AC240-WH-PH-EM-A95 X B105 X C86 MM	08W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
87	MAZDA-SXR181208W-6.5K-AC240-BK-PH-A95 X B105 X C86 MM	08W	6500	240VAC	BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
88	MAZDA-SXR181208W-6.5K-AC240-BK-PH-EM-A95 X B105 X C86 MM	08W	6500	240VAC	BLACK	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
89	MAZDA-SXR181208W-6.5K-AC240-WH-DA-A95 X B105 X C86 MM	08W	6500	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
90	MAZDA-SXR181208W-6.5K-AC240-WH-DA-EM-A95 X B105 X C86 MM	08W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
91	MAZDA-SXR181208W-6.5K-AC240-BK-DA-A95 X B105 X C86 MM	08W	6500	240VAC	BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
92	MAZDA-SXR181208W-6.5K-AC240-BK-DA-EM-A95 X B105 X C86 MM	08W	6500	240VAC	BLACK	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
93	MAZDA-SXR181208W-6.5K-AC240-WH-ND-A95 X B105 X C86 MM	08W	6500	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
94	MAZDA-SXR181208W-6.5K-AC240-WH-ND-EM-A95 X B105 X C86 MM	08W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
95	MAZDA-SXR181208W-6.5K-AC240-BK-ND-A95 X B105 X C86 MM	08W	6500	240VAC	BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
96	MAZDA-SXR181208W-6.5K-AC240-BK-ND-EM-A95 X B105 X C86 MM	08W	6500	240VAC	BLACK	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	960LM	A95 X B105 X C86 MM	
97	MAZDA-SXR181210W-2.7K-AC240-WH-10VDIM-A95 X B105 X C86 MM	10W	2700	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
98	MAZDA-SXR181210W-2.7K-AC240-WH-10VDIM-EM-A95 X B105 X C86 MM	10W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
99	MAZDA-SXR181210W-2.7K-AC240-BK-10VDIM-A95 X B105 X C86 MM	10W	2700	240VAC	BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
100	MAZDA-SXR181210W-2.7K-AC240-BK-10VDIM-EM-A95 X B105 X C86 MM	10W	2700	240VAC	BLACK	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
101	MAZDA-SXR181210W-2.7K-AC240-WH-PH-A95 X B105 X C86 MM	10W	2700	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
102	MAZDA-SXR181210W-2.7K-AC240-WH-PH-EM-A95 X B105 X C86 MM	10W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
103	MAZDA-SXR181210W-2.7K-AC240-BK-PH-A95 X B105 X C86 MM	10W	2700	240VAC	BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
104	MAZDA-SXR181210W-2.7K-AC240-BK-PH-EM-A95 X B105 X C86 MM	10W	2700	240VAC	BLACK	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
105	MAZDA-SXR181210W-2.7K-AC240-WH-DA-A95 X B105 X C86 MM	10W	2700	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	

DATASHEET

GENERATED ON: 10 Nov 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
106	MAZDA-SXR181210W-2.7K-AC240-WH-DA-EM-A95 X B105 X C86 MM	10W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
107	MAZDA-SXR181210W-2.7K-AC240-BK-DA-A95 X B105 X C86 MM	10W	2700	240VAC	BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
108	MAZDA-SXR181210W-2.7K-AC240-BK-DA-EM-A95 X B105 X C86 MM	10W	2700	240VAC	BLACK	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
109	MAZDA-SXR181210W-2.7K-AC240-WH-ND-A95 X B105 X C86 MM	10W	2700	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
110	MAZDA-SXR181210W-2.7K-AC240-WH-ND-EM-A95 X B105 X C86 MM	10W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
111	MAZDA-SXR181210W-2.7K-AC240-BK-ND-A95 X B105 X C86 MM	10W	2700	240VAC	BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
112	MAZDA-SXR181210W-2.7K-AC240-BK-ND-EM-A95 X B105 X C86 MM	10W	2700	240VAC	BLACK	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
113	MAZDA-SXR181210W-3K-AC240-WH-10VDIM-A95 X B105 X C86 MM	10W	3000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
114	MAZDA-SXR181210W-3K-AC240-WH-10VDIM-EM-A95 X B105 X C86 MM	10W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
115	MAZDA-SXR181210W-3K-AC240-BK-10VDIM-A95 X B105 X C86 MM	10W	3000	240VAC	BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
116	MAZDA-SXR181210W-3K-AC240-BK-10VDIM-EM-A95 X B105 X C86 MM	10W	3000	240VAC	BLACK	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
117	MAZDA-SXR181210W-3K-AC240-WH-PH-A95 X B105 X C86 MM	10W	3000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
118	MAZDA-SXR181210W-3K-AC240-WH-PH-EM-A95 X B105 X C86 MM	10W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
119	MAZDA-SXR181210W-3K-AC240-BK-PH-A95 X B105 X C86 MM	10W	3000	240VAC	BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
120	MAZDA-SXR181210W-3K-AC240-BK-PH-EM-A95 X B105 X C86 MM	10W	3000	240VAC	BLACK	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
121	MAZDA-SXR181210W-3K-AC240-WH-DA-A95 X B105 X C86 MM	10W	3000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
122	MAZDA-SXR181210W-3K-AC240-WH-DA-EM-A95 X B105 X C86 MM	10W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
123	MAZDA-SXR181210W-3K-AC240-BK-DA-A95 X B105 X C86 MM	10W	3000	240VAC	BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
124	MAZDA-SXR181210W-3K-AC240-BK-DA-EM-A95 X B105 X C86 MM	10W	3000	240VAC	BLACK	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
125	MAZDA-SXR181210W-3K-AC240-WH-ND-A95 X B105 X C86 MM	10W	3000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
126	MAZDA-SXR181210W-3K-AC240-WH-ND-EM-A95 X B105 X C86 MM	10W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
127	MAZDA-SXR181210W-3K-AC240-BK-ND-A95 X B105 X C86 MM	10W	3000	240VAC	BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
128	MAZDA-SXR181210W-3K-AC240-BK-ND-EM-A95 X B105 X C86 MM	10W	3000	240VAC	BLACK	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
129	MAZDA-SXR181210W-4K-AC240-WH-10VDIM-A95 X B105 X C86 MM	10W	4000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
130	MAZDA-SXR181210W-4K-AC240-WH-10VDIM-EM-A95 X B105 X C86 MM	10W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
131	MAZDA-SXR181210W-4K-AC240-BK-10VDIM-A95 X B105 X C86 MM	10W	4000	240VAC	BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
132	MAZDA-SXR181210W-4K-AC240-BK-10VDIM-EM-A95 X B105 X C86 MM	10W	4000	240VAC	BLACK	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
133	MAZDA-SXR181210W-4K-AC240-WH-PH-A95 X B105 X C86 MM	10W	4000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
134	MAZDA-SXR181210W-4K-AC240-WH-PH-EM-A95 X B105 X C86 MM	10W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	

DATASHEET

GENERATED ON: 10 Nov 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
135	**MAZDA-SXR181210W-4K-AC240-BK-PH-A95 X B105 X C86 MM**	10W	4000	240VAC	BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
136	**MAZDA-SXR181210W-4K-AC240-BK-PH-EM-A95 X B105 X C86 MM**	10W	4000	240VAC	BLACK	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
137	**MAZDA-SXR181210W-4K-AC240-WH-DA-A95 X B105 X C86 MM**	10W	4000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
138	**MAZDA-SXR181210W-4K-AC240-WH-DA-EM-A95 X B105 X C86 MM**	10W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
139	**MAZDA-SXR181210W-4K-AC240-BK-DA-A95 X B105 X C86 MM**	10W	4000	240VAC	BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
140	**MAZDA-SXR181210W-4K-AC240-BK-DA-EM-A95 X B105 X C86 MM**	10W	4000	240VAC	BLACK	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
141	**MAZDA-SXR181210W-4K-AC240-WH-ND-A95 X B105 X C86 MM**	10W	4000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
142	**MAZDA-SXR181210W-4K-AC240-WH-ND-EM-A95 X B105 X C86 MM**	10W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
143	**MAZDA-SXR181210W-4K-AC240-BK-ND-A95 X B105 X C86 MM**	10W	4000	240VAC	BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
144	**MAZDA-SXR181210W-4K-AC240-BK-ND-EM-A95 X B105 X C86 MM**	10W	4000	240VAC	BLACK	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
145	**MAZDA-SXR181210W-5K-AC240-WH-10VDIM-A95 X B105 X C86 MM**	10W	5000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
146	**MAZDA-SXR181210W-5K-AC240-WH-10VDIM-EM-A95 X B105 X C86 MM**	10W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
147	**MAZDA-SXR181210W-5K-AC240-BK-10VDIM-A95 X B105 X C86 MM**	10W	5000	240VAC	BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
148	**MAZDA-SXR181210W-5K-AC240-BK-10VDIM-EM-A95 X B105 X C86 MM**	10W	5000	240VAC	BLACK	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
149	**MAZDA-SXR181210W-5K-AC240-WH-PH-A95 X B105 X C86 MM**	10W	5000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
150	**MAZDA-SXR181210W-5K-AC240-WH-PH-EM-A95 X B105 X C86 MM**	10W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
151	**MAZDA-SXR181210W-5K-AC240-BK-PH-A95 X B105 X C86 MM**	10W	5000	240VAC	BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
152	**MAZDA-SXR181210W-5K-AC240-BK-PH-EM-A95 X B105 X C86 MM**	10W	5000	240VAC	BLACK	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
153	**MAZDA-SXR181210W-5K-AC240-WH-DA-A95 X B105 X C86 MM**	10W	5000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
154	**MAZDA-SXR181210W-5K-AC240-WH-DA-EM-A95 X B105 X C86 MM**	10W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
155	**MAZDA-SXR181210W-5K-AC240-BK-DA-A95 X B105 X C86 MM**	10W	5000	240VAC	BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
156	**MAZDA-SXR181210W-5K-AC240-BK-DA-EM-A95 X B105 X C86 MM**	10W	5000	240VAC	BLACK	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
157	**MAZDA-SXR181210W-5K-AC240-WH-ND-A95 X B105 X C86 MM**	10W	5000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
158	**MAZDA-SXR181210W-5K-AC240-WH-ND-EM-A95 X B105 X C86 MM**	10W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
159	**MAZDA-SXR181210W-5K-AC240-BK-ND-A95 X B105 X C86 MM**	10W	5000	240VAC	BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
160	**MAZDA-SXR181210W-5K-AC240-BK-ND-EM-A95 X B105 X C86 MM**	10W	5000	240VAC	BLACK	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
161	**MAZDA-SXR181210W-6K-AC240-WH-10VDIM-A95 X B105 X C86 MM**	10W	6000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
162	**MAZDA-SXR181210W-6K-AC240-WH-10VDIM-EM-A95 X B105 X C86 MM**	10W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
163	**MAZDA-SXR181210W-6K-AC240-BK-10VDIM-A95 X B105 X C86 MM**	10W	6000	240VAC	BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
164	MAZDA-SXR181210W-6K-AC240-BK-10VDIM-EM-A95 X B105 X C86 MM	10W	6000	240VAC	BLACK	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
165	MAZDA-SXR181210W-6K-AC240-WH-PH-A95 X B105 X C86 MM	10W	6000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
166	MAZDA-SXR181210W-6K-AC240-WH-PH-EM-A95 X B105 X C86 MM	10W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
167	MAZDA-SXR181210W-6K-AC240-BK-PH-A95 X B105 X C86 MM	10W	6000	240VAC	BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
168	MAZDA-SXR181210W-6K-AC240-BK-PH-EM-A95 X B105 X C86 MM	10W	6000	240VAC	BLACK	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
169	MAZDA-SXR181210W-6K-AC240-WH-DA-A95 X B105 X C86 MM	10W	6000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
170	MAZDA-SXR181210W-6K-AC240-WH-DA-EM-A95 X B105 X C86 MM	10W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
171	MAZDA-SXR181210W-6K-AC240-BK-DA-A95 X B105 X C86 MM	10W	6000	240VAC	BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
172	MAZDA-SXR181210W-6K-AC240-BK-DA-EM-A95 X B105 X C86 MM	10W	6000	240VAC	BLACK	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
173	MAZDA-SXR181210W-6K-AC240-WH-ND-A95 X B105 X C86 MM	10W	6000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
174	MAZDA-SXR181210W-6K-AC240-WH-ND-EM-A95 X B105 X C86 MM	10W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
175	MAZDA-SXR181210W-6K-AC240-BK-ND-A95 X B105 X C86 MM	10W	6000	240VAC	BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
176	MAZDA-SXR181210W-6K-AC240-BK-ND-EM-A95 X B105 X C86 MM	10W	6000	240VAC	BLACK	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
177	MAZDA-SXR181210W-6.5K-AC240-WH-10VDIM-A95 X B105 X C86 MM	10W	6500	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
178	MAZDA-SXR181210W-6.5K-AC240-WH-10VDIM-EM-A95 X B105 X C86 MM	10W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
179	MAZDA-SXR181210W-6.5K-AC240-BK-10VDIM-A95 X B105 X C86 MM	10W	6500	240VAC	BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
180	MAZDA-SXR181210W-6.5K-AC240-BK-10VDIM-EM-A95 X B105 X C86 MM	10W	6500	240VAC	BLACK	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
181	MAZDA-SXR181210W-6.5K-AC240-WH-PH-A95 X B105 X C86 MM	10W	6500	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
182	MAZDA-SXR181210W-6.5K-AC240-WH-PH-EM-A95 X B105 X C86 MM	10W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
183	MAZDA-SXR181210W-6.5K-AC240-BK-PH-A95 X B105 X C86 MM	10W	6500	240VAC	BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
184	MAZDA-SXR181210W-6.5K-AC240-BK-PH-EM-A95 X B105 X C86 MM	10W	6500	240VAC	BLACK	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
185	MAZDA-SXR181210W-6.5K-AC240-WH-DA-A95 X B105 X C86 MM	10W	6500	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
186	MAZDA-SXR181210W-6.5K-AC240-WH-DA-EM-A95 X B105 X C86 MM	10W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
187	MAZDA-SXR181210W-6.5K-AC240-BK-DA-A95 X B105 X C86 MM	10W	6500	240VAC	BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
188	MAZDA-SXR181210W-6.5K-AC240-BK-DA-EM-A95 X B105 X C86 MM	10W	6500	240VAC	BLACK	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
189	MAZDA-SXR181210W-6.5K-AC240-WH-ND-A95 X B105 X C86 MM	10W	6500	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
190	MAZDA-SXR181210W-6.5K-AC240-WH-ND-EM-A95 X B105 X C86 MM	10W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
191	MAZDA-SXR181210W-6.5K-AC240-BK-ND-A95 X B105 X C86 MM	10W	6500	240VAC	BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	
192	MAZDA-SXR181210W-6.5K-AC240-BK-ND-EM-A95 X B105 X C86 MM	10W	6500	240VAC	BLACK	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A95 X B105 X C86 MM	DIE CAST ALUMINUM	IP54	1200LM	A95 X B105 X C86 MM	