DATASHEET

GENERATED ON: 26 Nov 2026 | SYS.REF: MAZDA-LED



LIMA

MAZDA Model: DXR1844 Downlight

Lima gimbal downlight with larger rotation angle so that it can meet more lighting direction demands. It can be vertically rotated to 90 degrees to the extent that the light emitting surface of the lamp is completely perpendicular to the installation plane, horizontally rotated 350 degree to meet more lighting direction demands. Besides, it adopts brand COB light source to achieve a high lumen e ciency. Dimmable version achieves great dimming compatibility with worldwide brand dimmers, can be used in various applications.

ALL AVAILABLE VARIANTS

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
1	MAZDA-DXR184408W-2.7K-AC240-WH-10VDIM-A80XB74XC70MM	08W	2700	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A80XB74XC70MM	DIE CAST ALUMINUM	IP54	960LM	A80XB74XC70MM	
2	MAZDA-DXR184408W-2.7K-AC240-WH-PH-A80XB74XC70MM	08W	2700	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A80XB74XC70MM	DIE CAST ALUMINUM	IP54	960LM	A80XB74XC70MM	
3	MAZDA-DXR184408W-2.7K-AC240-WH-DA-A80XB74XC70MM	08W	2700	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A80XB74XC70MM	DIE CAST ALUMINUM	IP54	960LM	A80XB74XC70MM	
4	MAZDA-DXR184408W-2.7K-AC240-WH-ND-A80XB74XC70MM	08W	2700	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A80XB74XC70MM	DIE CAST ALUMINUM	IP54	960LM	A80XB74XC70MM	
5	MAZDA-DXR184408W-3K-AC240-WH-10VDIM-A80XB74XC70MM	08W	3000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A80XB74XC70MM	DIE CAST ALUMINUM	IP54	960LM	A80XB74XC70MM	
6	MAZDA-DXR184408W-3K-AC240-WH-PH-A80XB74XC70MM	08W	3000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A80XB74XC70MM	DIE CAST ALUMINUM	IP54	960LM	A80XB74XC70MM	
7	MAZDA-DXR184408W-3K-AC240-WH-DA-A80XB74XC70MM	08W	3000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A80XB74XC70MM	DIE CAST ALUMINUM	IP54	960LM	A80XB74XC70MM	
8	MAZDA-DXR184408W-3K-AC240-WH-ND-A80XB74XC70MM	08W	3000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A80XB74XC70MM	DIE CAST ALUMINUM	IP54	960LM	A80XB74XC70MM	
9	MAZDA-DXR184408W-4K-AC240-WH-10VDIM-A80XB74XC70MM	08W	4000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A80XB74XC70MM	DIE CAST ALUMINUM	IP54	960LM	A80XB74XC70MM	
10	MAZDA-DXR184408W-4K-AC240-WH-PH-A80XB74XC70MM	08W	4000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A80XB74XC70MM	DIE CAST ALUMINUM	IP54	960LM	A80XB74XC70MM	
11	MAZDA-DXR184408W-4K-AC240-WH-DA-A80XB74XC70MM	08W	4000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A80XB74XC70MM	DIE CAST ALUMINUM	IP54	960LM	A80XB74XC70MM	
12	MAZDA-DXR184408W-4K-AC240-WH-ND-A80XB74XC70MM	08W	4000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A80XB74XC70MM	DIE CAST ALUMINUM	IP54	960LM	A80XB74XC70MM	
13	MAZDA-DXR184408W-5K-AC240-WH-10VDIM-A80XB74XC70MM	08W	5000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A80XB74XC70MM	DIE CAST ALUMINUM	IP54	960LM	A80XB74XC70MM	
14	MAZDA-DXR184408W-5K-AC240-WH-PH-A80XB74XC70MM	08W	5000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A80XB74XC70MM	DIE CAST ALUMINUM	IP54	960LM	A80XB74XC70MM	
15	MAZDA-DXR184408W-5K-AC240-WH-DA-A80XB74XC70MM	08W	5000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A80XB74XC70MM	DIE CAST ALUMINUM	IP54	960LM	A80XB74XC70MM	
16	MAZDA-DXR184408W-5K-AC240-WH-ND-A80XB74XC70MM	08W	5000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A80XB74XC70MM	DIE CAST ALUMINUM	IP54	960LM	A80XB74XC70MM	
17	MAZDA-DXR184408W-6K-AC240-WH-10VDIM-A80XB74XC70MM	08W	6000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A80XB74XC70MM	DIE CAST ALUMINUM	IP54	960LM	A80XB74XC70MM	
18	MAZDA-DXR184408W-6K-AC240-WH-PH-A80XB74XC70MM	08W	6000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A80XB74XC70MM	DIE CAST ALUMINUM	IP54	960LM	A80XB74XC70MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
19	**MAZDA-DXR184408W-6K-AC240-WH-DA-A80XB74XC70MM**	08W	6000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A80XB74XC70MM	DIE CAST ALUMINUM	IP54	960LM	A80XB74XC70MM	
20	**MAZDA-DXR184408W-6K-AC240-WH-ND-A80XB74XC70MM**	08W	6000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A80XB74XC70MM	DIE CAST ALUMINUM	IP54	960LM	A80XB74XC70MM	
21	**MAZDA-DXR184408W-6.5K-AC240-WH-10VDIM-A80XB74XC70MM**	08W	6500	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A80XB74XC70MM	DIE CAST ALUMINUM	IP54	960LM	A80XB74XC70MM	
22	**MAZDA-DXR184408W-6.5K-AC240-WH-PH-A80XB74XC70MM**	08W	6500	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A80XB74XC70MM	DIE CAST ALUMINUM	IP54	960LM	A80XB74XC70MM	
23	**MAZDA-DXR184408W-6.5K-AC240-WH-DA-A80XB74XC70MM**	08W	6500	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A80XB74XC70MM	DIE CAST ALUMINUM	IP54	960LM	A80XB74XC70MM	
24	**MAZDA-DXR184408W-6.5K-AC240-WH-ND-A80XB74XC70MM**	08W	6500	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A80XB74XC70MM	DIE CAST ALUMINUM	IP54	960LM	A80XB74XC70MM	