



## LIMA

**MAZDA Model: DXR1844 Downlight**

Lima gimbal downlight with larger rotation angle so that it can meet more lighting direction demands. It can be vertically rotated to 90 degrees to the extent that the light emitting surface of the lamp is completely perpendicular to the installation plane, horizontally rotated 350 degree to meet more lighting direction demands. Besides, it adopts brand COB light source to achieve a high lumen efficiency. Dimmable version achieves great dimming compatibility with worldwide brand dimmers, can be used in various applications.

## ALL AVAILABLE VARIANTS

| #  | Code                                                | WATT | CCT  | Voltage | Body Color | Emergency Backup | Control                  | Beam Angle    | Dimension     | Material          | IP   | lumen | Dimensions    | Price |
|----|-----------------------------------------------------|------|------|---------|------------|------------------|--------------------------|---------------|---------------|-------------------|------|-------|---------------|-------|
| 1  | MAZDA-DXR184408W-2.7K-AC240-WH-10VDIM-A80XB74XC70MM | 08W  | 2700 | 240VAC  | WHITE      | NON EMERGENCY    | 0/1-10 V DIMMABLE DRIVER | 15°, 24°, 36° | A80XB74XC70MM | DIE CAST ALUMINUM | IP54 | 960LM | A80XB74XC70MM |       |
| 2  | MAZDA-DXR184408W-2.7K-AC240-WH-PH-A80XB74XC70MM     | 08W  | 2700 | 240VAC  | WHITE      | NON EMERGENCY    | PHASE CUT DIMMABLE       | 15°, 24°, 36° | A80XB74XC70MM | DIE CAST ALUMINUM | IP54 | 960LM | A80XB74XC70MM |       |
| 3  | MAZDA-DXR184408W-2.7K-AC240-WH-DA-A80XB74XC70MM     | 08W  | 2700 | 240VAC  | WHITE      | NON EMERGENCY    | DALI DIMMABLE DRIVER     | 15°, 24°, 36° | A80XB74XC70MM | DIE CAST ALUMINUM | IP54 | 960LM | A80XB74XC70MM |       |
| 4  | MAZDA-DXR184408W-2.7K-AC240-WH-ND-A80XB74XC70MM     | 08W  | 2700 | 240VAC  | WHITE      | NON EMERGENCY    | ON - OFF                 | 15°, 24°, 36° | A80XB74XC70MM | DIE CAST ALUMINUM | IP54 | 960LM | A80XB74XC70MM |       |
| 5  | MAZDA-DXR184408W-3K-AC240-WH-10VDIM-A80XB74XC70MM   | 08W  | 3000 | 240VAC  | WHITE      | NON EMERGENCY    | 0/1-10 V DIMMABLE DRIVER | 15°, 24°, 36° | A80XB74XC70MM | DIE CAST ALUMINUM | IP54 | 960LM | A80XB74XC70MM |       |
| 6  | MAZDA-DXR184408W-3K-AC240-WH-PH-A80XB74XC70MM       | 08W  | 3000 | 240VAC  | WHITE      | NON EMERGENCY    | PHASE CUT DIMMABLE       | 15°, 24°, 36° | A80XB74XC70MM | DIE CAST ALUMINUM | IP54 | 960LM | A80XB74XC70MM |       |
| 7  | MAZDA-DXR184408W-3K-AC240-WH-DA-A80XB74XC70MM       | 08W  | 3000 | 240VAC  | WHITE      | NON EMERGENCY    | DALI DIMMABLE DRIVER     | 15°, 24°, 36° | A80XB74XC70MM | DIE CAST ALUMINUM | IP54 | 960LM | A80XB74XC70MM |       |
| 8  | MAZDA-DXR184408W-3K-AC240-WH-ND-A80XB74XC70MM       | 08W  | 3000 | 240VAC  | WHITE      | NON EMERGENCY    | ON - OFF                 | 15°, 24°, 36° | A80XB74XC70MM | DIE CAST ALUMINUM | IP54 | 960LM | A80XB74XC70MM |       |
| 9  | MAZDA-DXR184408W-4K-AC240-WH-10VDIM-A80XB74XC70MM   | 08W  | 4000 | 240VAC  | WHITE      | NON EMERGENCY    | 0/1-10 V DIMMABLE DRIVER | 15°, 24°, 36° | A80XB74XC70MM | DIE CAST ALUMINUM | IP54 | 960LM | A80XB74XC70MM |       |
| 10 | MAZDA-DXR184408W-4K-AC240-WH-PH-A80XB74XC70MM       | 08W  | 4000 | 240VAC  | WHITE      | NON EMERGENCY    | PHASE CUT DIMMABLE       | 15°, 24°, 36° | A80XB74XC70MM | DIE CAST ALUMINUM | IP54 | 960LM | A80XB74XC70MM |       |
| 11 | MAZDA-DXR184408W-4K-AC240-WH-DA-A80XB74XC70MM       | 08W  | 4000 | 240VAC  | WHITE      | NON EMERGENCY    | DALI DIMMABLE DRIVER     | 15°, 24°, 36° | A80XB74XC70MM | DIE CAST ALUMINUM | IP54 | 960LM | A80XB74XC70MM |       |
| 12 | MAZDA-DXR184408W-4K-AC240-WH-ND-A80XB74XC70MM       | 08W  | 4000 | 240VAC  | WHITE      | NON EMERGENCY    | ON - OFF                 | 15°, 24°, 36° | A80XB74XC70MM | DIE CAST ALUMINUM | IP54 | 960LM | A80XB74XC70MM |       |
| 13 | MAZDA-DXR184408W-5K-AC240-WH-10VDIM-A80XB74XC70MM   | 08W  | 5000 | 240VAC  | WHITE      | NON EMERGENCY    | 0/1-10 V DIMMABLE DRIVER | 15°, 24°, 36° | A80XB74XC70MM | DIE CAST ALUMINUM | IP54 | 960LM | A80XB74XC70MM |       |
| 14 | MAZDA-DXR184408W-5K-AC240-WH-PH-A80XB74XC70MM       | 08W  | 5000 | 240VAC  | WHITE      | NON EMERGENCY    | PHASE CUT DIMMABLE       | 15°, 24°, 36° | A80XB74XC70MM | DIE CAST ALUMINUM | IP54 | 960LM | A80XB74XC70MM |       |
| 15 | MAZDA-DXR184408W-5K-AC240-WH-DA-A80XB74XC70MM       | 08W  | 5000 | 240VAC  | WHITE      | NON EMERGENCY    | DALI DIMMABLE DRIVER     | 15°, 24°, 36° | A80XB74XC70MM | DIE CAST ALUMINUM | IP54 | 960LM | A80XB74XC70MM |       |
| 16 | MAZDA-DXR184408W-5K-AC240-WH-ND-A80XB74XC70MM       | 08W  | 5000 | 240VAC  | WHITE      | NON EMERGENCY    | ON - OFF                 | 15°, 24°, 36° | A80XB74XC70MM | DIE CAST ALUMINUM | IP54 | 960LM | A80XB74XC70MM |       |
| 17 | MAZDA-DXR184408W-6K-AC240-WH-10VDIM-A80XB74XC70MM   | 08W  | 6000 | 240VAC  | WHITE      | NON EMERGENCY    | 0/1-10 V DIMMABLE DRIVER | 15°, 24°, 36° | A80XB74XC70MM | DIE CAST ALUMINUM | IP54 | 960LM | A80XB74XC70MM |       |
| 18 | MAZDA-DXR184408W-6K-AC240-WH-PH-A80XB74XC70MM       | 08W  | 6000 | 240VAC  | WHITE      | NON EMERGENCY    | PHASE CUT DIMMABLE       | 15°, 24°, 36° | A80XB74XC70MM | DIE CAST ALUMINUM | IP54 | 960LM | A80XB74XC70MM |       |

| #  | Code                                                | WATT | CCT  | Voltage | Body Color | Emergency Backup | Control                  | Beam Angle    | Dimension     | Material          | IP   | lumen | Dimensions    | Price |
|----|-----------------------------------------------------|------|------|---------|------------|------------------|--------------------------|---------------|---------------|-------------------|------|-------|---------------|-------|
| 19 | MAZDA-DXR184408W-6K-AC240-WH-DA-A80XB74XC70MM       | 08W  | 6000 | 240VAC  | WHITE      | NON EMERGENCY    | DALI DIMMABLE DRIVER     | 15°, 24°, 36° | A80XB74XC70MM | DIE CAST ALUMINUM | IP54 | 960LM | A80XB74XC70MM |       |
| 20 | MAZDA-DXR184408W-6K-AC240-WH-ND-A80XB74XC70MM       | 08W  | 6000 | 240VAC  | WHITE      | NON EMERGENCY    | ON - OFF                 | 15°, 24°, 36° | A80XB74XC70MM | DIE CAST ALUMINUM | IP54 | 960LM | A80XB74XC70MM |       |
| 21 | MAZDA-DXR184408W-6.5K-AC240-WH-10VDIM-A80XB74XC70MM | 08W  | 6500 | 240VAC  | WHITE      | NON EMERGENCY    | 0/1-10 V DIMMABLE DRIVER | 15°, 24°, 36° | A80XB74XC70MM | DIE CAST ALUMINUM | IP54 | 960LM | A80XB74XC70MM |       |
| 22 | MAZDA-DXR184408W-6.5K-AC240-WH-PH-A80XB74XC70MM     | 08W  | 6500 | 240VAC  | WHITE      | NON EMERGENCY    | PHASE CUT DIMMABLE       | 15°, 24°, 36° | A80XB74XC70MM | DIE CAST ALUMINUM | IP54 | 960LM | A80XB74XC70MM |       |
| 23 | MAZDA-DXR184408W-6.5K-AC240-WH-DA-A80XB74XC70MM     | 08W  | 6500 | 240VAC  | WHITE      | NON EMERGENCY    | DALI DIMMABLE DRIVER     | 15°, 24°, 36° | A80XB74XC70MM | DIE CAST ALUMINUM | IP54 | 960LM | A80XB74XC70MM |       |
| 24 | MAZDA-DXR184408W-6.5K-AC240-WH-ND-A80XB74XC70MM     | 08W  | 6500 | 240VAC  | WHITE      | NON EMERGENCY    | ON - OFF                 | 15°, 24°, 36° | A80XB74XC70MM | DIE CAST ALUMINUM | IP54 | 960LM | A80XB74XC70MM |       |