DATASHEET

GENERATED ON: 10 Nov 2026 | SYS.REF: MAZDA-LED



MISSA

MAZDA Model: SXR1844 Spot Light

Missa LED Spot Light is a mini and exquisite lamp with high light transmittance. it offers a very little size in manydesign styles, without forgetting about the functionality: all the range is characterized by the use high quality LED technology, so the result is a choice of accent light suitable for false ceiling, kitchen cabinet and not only. The possible applications are a multitude. This spotlights are all environmental friendly and very useful in a matter of energy and economical saving. The light result is bright, uniform and comfortable. Housing made by die cast aluminium powder coated with choice of RAL colors reflector

ALL AVAILABLE VARIANTS

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions Price
1	MAZDA-SXR184407W-2.7K-AC240-WH-10VDIM-A65 X B86 X C55MM	07W	2700	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A65 X B86 X C55MM	DIE CAST ALUMINUM	IP65	840LM	A65 X B86 X C55MM
2	MAZDA-SXR184407W-2.7K-AC240-WH-10VDIM-EM-A65 X B86 X C55MM	07W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A65 X B86 X C55MM	DIE CAST ALUMINUM	IP65	840LM	A65 X B86 X C55MM
3	MAZDA-SXR184407W-2.7K-AC240-WH-PH-A65 X B86 X C55MM	07W	2700	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A65 X B86 X C55MM	DIE CAST ALUMINUM	IP65	840LM	A65 X B86 X C55MM
4	MAZDA-SXR184407W-2.7K-AC240-WH-PH-EM-A65 X B86 X C55MM	07W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A65 X B86 X C55MM	DIE CAST ALUMINUM	IP65	840LM	A65 X B86 X C55MM
5	MAZDA-SXR184407W-2.7K-AC240-WH-DA-A65 X B86 X C55MM	07W	2700	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A65 X B86 X C55MM	DIE CAST ALUMINUM	IP65	840LM	A65 X B86 X C55MM
6	MAZDA-SXR184407W-2.7K-AC240-WH-DA-EM-A65 X B86 X C55MM	07W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A65 X B86 X C55MM	DIE CAST ALUMINUM	IP65	840LM	A65 X B86 X C55MM
7	MAZDA-SXR184407W-2.7K-AC240-WH-ND-A65 X B86 X C55MM	07W	2700	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A65 X B86 X C55MM	DIE CAST ALUMINUM	IP65	840LM	A65 X B86 X C55MM
8	MAZDA-SXR184407W-2.7K-AC240-WH-ND-EM-A65 X B86 X C55MM	07W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A65 X B86 X C55MM	DIE CAST ALUMINUM	IP65	840LM	A65 X B86 X C55MM
9	MAZDA-SXR184407W-3K-AC240-WH-10VDIM-A65 X B86 X C55MM	07W	3000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A65 X B86 X C55MM	DIE CAST ALUMINUM	IP65	840LM	A65 X B86 X C55MM
10	MAZDA-SXR184407W-3K-AC240-WH-10VDIM-EM-A65 X B86 X C55MM	07W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A65 X B86 X C55MM	DIE CAST ALUMINUM	IP65	840LM	A65 X B86 X C55MM
11	MAZDA-SXR184407W-3K-AC240-WH-PH-A65 X B86 X C55MM	07W	3000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A65 X B86 X C55MM	DIE CAST ALUMINUM	IP65	840LM	A65 X B86 X C55MM
12	MAZDA-SXR184407W-3K-AC240-WH-PH-EM-A65 X B86 X C55MM	07W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A65 X B86 X C55MM	DIE CAST ALUMINUM	IP65	840LM	A65 X B86 X C55MM
13	MAZDA-SXR184407W-3K-AC240-WH-DA-A65 X B86 X C55MM	07W	3000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A65 X B86 X C55MM	DIE CAST ALUMINUM	IP65	840LM	A65 X B86 X C55MM
14	MAZDA-SXR184407W-3K-AC240-WH-DA-EM-A65 X B86 X C55MM	07W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A65 X B86 X C55MM	DIE CAST ALUMINUM	IP65	840LM	A65 X B86 X C55MM
15	MAZDA-SXR184407W-3K-AC240-WH-ND-A65 X B86 X C55MM	07W	3000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A65 X B86 X C55MM	DIE CAST ALUMINUM	IP65	840LM	A65 X B86 X C55MM
16	MAZDA-SXR184407W-3K-AC240-WH-ND-EM-A65 X B86 X C55MM	07W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A65 X B86 X C55MM	DIE CAST ALUMINUM	IP65	840LM	A65 X B86 X C55MM
17	MAZDA-SXR184407W-4K-AC240-WH-10VDIM-A65 X B86 X C55MM	07W	4000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A65 X B86 X C55MM	DIE CAST ALUMINUM	IP65	840LM	A65 X B86 X C55MM
18	MAZDA-SXR184407W-4K-AC240-WH-10VDIM-EM-A65 X B86 X C55MM	07W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A65 X B86 X C55MM	DIE CAST ALUMINUM	IP65	840LM	A65 X B86 X C55MM
19	MAZDA-SXR184407W-4K-AC240-WH-PH-A65 X B86 X C55MM	07W	4000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A65 X B86 X C55MM	DIE CAST ALUMINUM	IP65	840LM	A65 X B86 X C55MM

DATASHEET

GENERATED ON: 10 Nov 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
20	MAZDA-SXR184407W-4K-AC240-WH-PH-EM-A65 X B86 X C55MM	07W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A65 X B86 X C55MM	DIE CAST ALUMINUM	IP65	840LM	A65 X B86 X C55MM	
21	MAZDA-SXR184407W-4K-AC240-WH-DA-A65 X B86 X C55MM	07W	4000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A65 X B86 X C55MM	DIE CAST ALUMINUM	IP65	840LM	A65 X B86 X C55MM	
22	MAZDA-SXR184407W-4K-AC240-WH-DA-EM-A65 X B86 X C55MM	07W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A65 X B86 X C55MM	DIE CAST ALUMINUM	IP65	840LM	A65 X B86 X C55MM	
23	MAZDA-SXR184407W-4K-AC240-WH-ND-A65 X B86 X C55MM	07W	4000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A65 X B86 X C55MM	DIE CAST ALUMINUM	IP65	840LM	A65 X B86 X C55MM	
24	MAZDA-SXR184407W-4K-AC240-WH-ND-EM-A65 X B86 X C55MM	07W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A65 X B86 X C55MM	DIE CAST ALUMINUM	IP65	840LM	A65 X B86 X C55MM	
25	MAZDA-SXR184407W-5K-AC240-WH-10VDIM-A65 X B86 X C55MM	07W	5000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A65 X B86 X C55MM	DIE CAST ALUMINUM	IP65	840LM	A65 X B86 X C55MM	
26	MAZDA-SXR184407W-5K-AC240-WH-10VDIM-EM-A65 X B86 X C55MM	07W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A65 X B86 X C55MM	DIE CAST ALUMINUM	IP65	840LM	A65 X B86 X C55MM	
27	MAZDA-SXR184407W-5K-AC240-WH-PH-A65 X B86 X C55MM	07W	5000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A65 X B86 X C55MM	DIE CAST ALUMINUM	IP65	840LM	A65 X B86 X C55MM	
28	MAZDA-SXR184407W-5K-AC240-WH-PH-EM-A65 X B86 X C55MM	07W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A65 X B86 X C55MM	DIE CAST ALUMINUM	IP65	840LM	A65 X B86 X C55MM	
29	MAZDA-SXR184407W-5K-AC240-WH-DA-A65 X B86 X C55MM	07W	5000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A65 X B86 X C55MM	DIE CAST ALUMINUM	IP65	840LM	A65 X B86 X C55MM	
30	MAZDA-SXR184407W-5K-AC240-WH-DA-EM-A65 X B86 X C55MM	07W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A65 X B86 X C55MM	DIE CAST ALUMINUM	IP65	840LM	A65 X B86 X C55MM	
31	MAZDA-SXR184407W-5K-AC240-WH-ND-A65 X B86 X C55MM	07W	5000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A65 X B86 X C55MM	DIE CAST ALUMINUM	IP65	840LM	A65 X B86 X C55MM	
32	MAZDA-SXR184407W-5K-AC240-WH-ND-EM-A65 X B86 X C55MM	07W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A65 X B86 X C55MM	DIE CAST ALUMINUM	IP65	840LM	A65 X B86 X C55MM	
33	MAZDA-SXR184407W-6K-AC240-WH-10VDIM-A65 X B86 X C55MM	07W	6000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A65 X B86 X C55MM	DIE CAST ALUMINUM	IP65	840LM	A65 X B86 X C55MM	
34	MAZDA-SXR184407W-6K-AC240-WH-10VDIM-EM-A65 X B86 X C55MM	07W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A65 X B86 X C55MM	DIE CAST ALUMINUM	IP65	840LM	A65 X B86 X C55MM	
35	MAZDA-SXR184407W-6K-AC240-WH-PH-A65 X B86 X C55MM	07W	6000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A65 X B86 X C55MM	DIE CAST ALUMINUM	IP65	840LM	A65 X B86 X C55MM	
36	MAZDA-SXR184407W-6K-AC240-WH-PH-EM-A65 X B86 X C55MM	07W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A65 X B86 X C55MM	DIE CAST ALUMINUM	IP65	840LM	A65 X B86 X C55MM	
37	MAZDA-SXR184407W-6K-AC240-WH-DA-A65 X B86 X C55MM	07W	6000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A65 X B86 X C55MM	DIE CAST ALUMINUM	IP65	840LM	A65 X B86 X C55MM	
38	MAZDA-SXR184407W-6K-AC240-WH-DA-EM-A65 X B86 X C55MM	07W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A65 X B86 X C55MM	DIE CAST ALUMINUM	IP65	840LM	A65 X B86 X C55MM	
39	MAZDA-SXR184407W-6K-AC240-WH-ND-A65 X B86 X C55MM	07W	6000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A65 X B86 X C55MM	DIE CAST ALUMINUM	IP65	840LM	A65 X B86 X C55MM	
40	MAZDA-SXR184407W-6K-AC240-WH-ND-EM-A65 X B86 X C55MM	07W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A65 X B86 X C55MM	DIE CAST ALUMINUM	IP65	840LM	A65 X B86 X C55MM	
41	MAZDA-SXR184407W-6.5K-AC240-WH-10VDIM-A65 X B86 X C55MM	07W	6500	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A65 X B86 X C55MM	DIE CAST ALUMINUM	IP65	840LM	A65 X B86 X C55MM	
42	MAZDA-SXR184407W-6.5K-AC240-WH-10VDIM-EM-A65 X B86 X C55MM	07W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A65 X B86 X C55MM	DIE CAST ALUMINUM	IP65	840LM	A65 X B86 X C55MM	
43	MAZDA-SXR184407W-6.5K-AC240-WH-PH-A65 X B86 X C55MM	07W	6500	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A65 X B86 X C55MM	DIE CAST ALUMINUM	IP65	840LM	A65 X B86 X C55MM	
44	MAZDA-SXR184407W-6.5K-AC240-WH-PH-EM-A65 X B86 X C55MM	07W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A65 X B86 X C55MM	DIE CAST ALUMINUM	IP65	840LM	A65 X B86 X C55MM	
45	MAZDA-SXR184407W-6.5K-AC240-WH-DA-A65 X B86 X C55MM	07W	6500	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A65 X B86 X C55MM	DIE CAST ALUMINUM	IP65	840LM	A65 X B86 X C55MM	
46	MAZDA-SXR184407W-6.5K-AC240-WH-DA-EM-A65 X B86 X C55MM	07W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A65 X B86 X C55MM	DIE CAST ALUMINUM	IP65	840LM	A65 X B86 X C55MM	
47	MAZDA-SXR184407W-6.5K-AC240-WH-ND-A65 X B86 X C55MM	07W	6500	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A65 X B86 X C55MM	DIE CAST ALUMINUM	IP65	840LM	A65 X B86 X C55MM	
48	MAZDA-SXR184407W-6.5K-AC240-WH-ND-EM-A65 X B86 X C55MM	07W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A65 X B86 X C55MM	DIE CAST ALUMINUM	IP65	840LM	A65 X B86 X C55MM	

DATASHEET

GENERATED ON: 10 Nov 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
49	MAZDA-SXR184407W-2.7K-AC240-WH-10VDIM-A85 X B105 X C75MM	07W	2700	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
50	MAZDA-SXR184407W-2.7K-AC240-WH-10VDIM-EM-A85 X B105 X C75MM	07W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
51	MAZDA-SXR184407W-2.7K-AC240-WH-PH-A85 X B105 X C75MM	07W	2700	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
52	MAZDA-SXR184407W-2.7K-AC240-WH-PH-EM-A85 X B105 X C75MM	07W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
53	MAZDA-SXR184407W-2.7K-AC240-WH-DA-A85 X B105 X C75MM	07W	2700	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
54	MAZDA-SXR184407W-2.7K-AC240-WH-DA-EM-A85 X B105 X C75MM	07W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
55	MAZDA-SXR184407W-2.7K-AC240-WH-ND-A85 X B105 X C75MM	07W	2700	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
56	MAZDA-SXR184407W-2.7K-AC240-WH-ND-EM-A85 X B105 X C75MM	07W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
57	MAZDA-SXR184407W-3K-AC240-WH-10VDIM-A85 X B105 X C75MM	07W	3000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
58	MAZDA-SXR184407W-3K-AC240-WH-10VDIM-EM-A85 X B105 X C75MM	07W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
59	MAZDA-SXR184407W-3K-AC240-WH-PH-A85 X B105 X C75MM	07W	3000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
60	MAZDA-SXR184407W-3K-AC240-WH-PH-EM-A85 X B105 X C75MM	07W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
61	MAZDA-SXR184407W-3K-AC240-WH-DA-A85 X B105 X C75MM	07W	3000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
62	MAZDA-SXR184407W-3K-AC240-WH-DA-EM-A85 X B105 X C75MM	07W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
63	MAZDA-SXR184407W-3K-AC240-WH-ND-A85 X B105 X C75MM	07W	3000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
64	MAZDA-SXR184407W-3K-AC240-WH-ND-EM-A85 X B105 X C75MM	07W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
65	MAZDA-SXR184407W-4K-AC240-WH-10VDIM-A85 X B105 X C75MM	07W	4000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
66	MAZDA-SXR184407W-4K-AC240-WH-10VDIM-EM-A85 X B105 X C75MM	07W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
67	MAZDA-SXR184407W-4K-AC240-WH-PH-A85 X B105 X C75MM	07W	4000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
68	MAZDA-SXR184407W-4K-AC240-WH-PH-EM-A85 X B105 X C75MM	07W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
69	MAZDA-SXR184407W-4K-AC240-WH-DA-A85 X B105 X C75MM	07W	4000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
70	MAZDA-SXR184407W-4K-AC240-WH-DA-EM-A85 X B105 X C75MM	07W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
71	MAZDA-SXR184407W-4K-AC240-WH-ND-A85 X B105 X C75MM	07W	4000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
72	MAZDA-SXR184407W-4K-AC240-WH-ND-EM-A85 X B105 X C75MM	07W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
73	MAZDA-SXR184407W-5K-AC240-WH-10VDIM-A85 X B105 X C75MM	07W	5000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
74	MAZDA-SXR184407W-5K-AC240-WH-10VDIM-EM-A85 X B105 X C75MM	07W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
75	MAZDA-SXR184407W-5K-AC240-WH-PH-A85 X B105 X C75MM	07W	5000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
76	MAZDA-SXR184407W-5K-AC240-WH-PH-EM-A85 X B105 X C75MM	07W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
77	MAZDA-SXR184407W-5K-AC240-WH-DA-A85 X B105 X C75MM	07W	5000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	

DATASHEET

GENERATED ON: 10 Nov 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
78	MAZDA-SXR184407W-5K-AC240-WH-DA-EM-A85 X B105 X C75MM	07W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
79	MAZDA-SXR184407W-5K-AC240-WH-ND-A85 X B105 X C75MM	07W	5000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
80	MAZDA-SXR184407W-5K-AC240-WH-ND-EM-A85 X B105 X C75MM	07W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
81	MAZDA-SXR184407W-6K-AC240-WH-10VDIM-A85 X B105 X C75MM	07W	6000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
82	MAZDA-SXR184407W-6K-AC240-WH-10VDIM-EM-A85 X B105 X C75MM	07W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
83	MAZDA-SXR184407W-6K-AC240-WH-PH-A85 X B105 X C75MM	07W	6000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
84	MAZDA-SXR184407W-6K-AC240-WH-PH-EM-A85 X B105 X C75MM	07W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
85	MAZDA-SXR184407W-6K-AC240-WH-DA-A85 X B105 X C75MM	07W	6000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
86	MAZDA-SXR184407W-6K-AC240-WH-DA-EM-A85 X B105 X C75MM	07W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
87	MAZDA-SXR184407W-6K-AC240-WH-ND-A85 X B105 X C75MM	07W	6000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
88	MAZDA-SXR184407W-6K-AC240-WH-ND-EM-A85 X B105 X C75MM	07W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
89	MAZDA-SXR184407W-6.5K-AC240-WH-10VDIM-A85 X B105 X C75MM	07W	6500	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
90	MAZDA-SXR184407W-6.5K-AC240-WH-10VDIM-EM-A85 X B105 X C75MM	07W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
91	MAZDA-SXR184407W-6.5K-AC240-WH-PH-A85 X B105 X C75MM	07W	6500	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
92	MAZDA-SXR184407W-6.5K-AC240-WH-PH-EM-A85 X B105 X C75MM	07W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
93	MAZDA-SXR184407W-6.5K-AC240-WH-DA-A85 X B105 X C75MM	07W	6500	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
94	MAZDA-SXR184407W-6.5K-AC240-WH-DA-EM-A85 X B105 X C75MM	07W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
95	MAZDA-SXR184407W-6.5K-AC240-WH-ND-A85 X B105 X C75MM	07W	6500	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
96	MAZDA-SXR184407W-6.5K-AC240-WH-ND-EM-A85 X B105 X C75MM	07W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
97	MAZDA-SXR184410W-2.7K-AC240-WH-10VDIM-A85 X B105 X C75MM	10W	2700	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
98	MAZDA-SXR184410W-2.7K-AC240-WH-10VDIM-EM-A85 X B105 X C75MM	10W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
99	MAZDA-SXR184410W-2.7K-AC240-WH-PH-A85 X B105 X C75MM	10W	2700	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
100	MAZDA-SXR184410W-2.7K-AC240-WH-PH-EM-A85 X B105 X C75MM	10W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
101	MAZDA-SXR184410W-2.7K-AC240-WH-DA-A85 X B105 X C75MM	10W	2700	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
102	MAZDA-SXR184410W-2.7K-AC240-WH-DA-EM-A85 X B105 X C75MM	10W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
103	MAZDA-SXR184410W-2.7K-AC240-WH-ND-A85 X B105 X C75MM	10W	2700	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
104	MAZDA-SXR184410W-2.7K-AC240-WH-ND-EM-A85 X B105 X C75MM	10W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
105	MAZDA-SXR184410W-3K-AC240-WH-10VDIM-A85 X B105 X C75MM	10W	3000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
106	MAZDA-SXR184410W-3K-AC240-WH-10VDIM-EM-A85 X B105 X C75MM	10W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	

DATASHEET

GENERATED ON: 10 Nov 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
107	MAZDA-SXR184410W-3K-AC240-WH-PH-A85 X B105 X C75MM	10W	3000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
108	MAZDA-SXR184410W-3K-AC240-WH-PH-EM-A85 X B105 X C75MM	10W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
109	MAZDA-SXR184410W-3K-AC240-WH-DA-A85 X B105 X C75MM	10W	3000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
110	MAZDA-SXR184410W-3K-AC240-WH-DA-EM-A85 X B105 X C75MM	10W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
111	MAZDA-SXR184410W-3K-AC240-WH-ND-A85 X B105 X C75MM	10W	3000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
112	MAZDA-SXR184410W-3K-AC240-WH-ND-EM-A85 X B105 X C75MM	10W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
113	MAZDA-SXR184410W-4K-AC240-WH-10VDIM-A85 X B105 X C75MM	10W	4000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
114	MAZDA-SXR184410W-4K-AC240-WH-10VDIM-EM-A85 X B105 X C75MM	10W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
115	MAZDA-SXR184410W-4K-AC240-WH-PH-A85 X B105 X C75MM	10W	4000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
116	MAZDA-SXR184410W-4K-AC240-WH-PH-EM-A85 X B105 X C75MM	10W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
117	MAZDA-SXR184410W-4K-AC240-WH-DA-A85 X B105 X C75MM	10W	4000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
118	MAZDA-SXR184410W-4K-AC240-WH-DA-EM-A85 X B105 X C75MM	10W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
119	MAZDA-SXR184410W-4K-AC240-WH-ND-A85 X B105 X C75MM	10W	4000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
120	MAZDA-SXR184410W-4K-AC240-WH-ND-EM-A85 X B105 X C75MM	10W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
121	MAZDA-SXR184410W-5K-AC240-WH-10VDIM-A85 X B105 X C75MM	10W	5000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
122	MAZDA-SXR184410W-5K-AC240-WH-10VDIM-EM-A85 X B105 X C75MM	10W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
123	MAZDA-SXR184410W-5K-AC240-WH-PH-A85 X B105 X C75MM	10W	5000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
124	MAZDA-SXR184410W-5K-AC240-WH-PH-EM-A85 X B105 X C75MM	10W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
125	MAZDA-SXR184410W-5K-AC240-WH-DA-A85 X B105 X C75MM	10W	5000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
126	MAZDA-SXR184410W-5K-AC240-WH-DA-EM-A85 X B105 X C75MM	10W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
127	MAZDA-SXR184410W-5K-AC240-WH-ND-A85 X B105 X C75MM	10W	5000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
128	MAZDA-SXR184410W-5K-AC240-WH-ND-EM-A85 X B105 X C75MM	10W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
129	MAZDA-SXR184410W-6K-AC240-WH-10VDIM-A85 X B105 X C75MM	10W	6000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
130	MAZDA-SXR184410W-6K-AC240-WH-10VDIM-EM-A85 X B105 X C75MM	10W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
131	MAZDA-SXR184410W-6K-AC240-WH-PH-A85 X B105 X C75MM	10W	6000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
132	MAZDA-SXR184410W-6K-AC240-WH-PH-EM-A85 X B105 X C75MM	10W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
133	MAZDA-SXR184410W-6K-AC240-WH-DA-A85 X B105 X C75MM	10W	6000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
134	MAZDA-SXR184410W-6K-AC240-WH-DA-EM-A85 X B105 X C75MM	10W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
135	MAZDA-SXR184410W-6K-AC240-WH-ND-A85 X B105 X C75MM	10W	6000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	

DATASHEET

GENERATED ON: 10 Nov 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
136	MAZDA-SXR184410W-6K-AC240-WH-ND-EM-A85 X B105 X C75MM	10W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
137	MAZDA-SXR184410W-6.5K-AC240-WH-10VDIM-A85 X B105 X C75MM	10W	6500	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
138	MAZDA-SXR184410W-6.5K-AC240-WH-10VDIM-EM-A85 X B105 X C75MM	10W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
139	MAZDA-SXR184410W-6.5K-AC240-WH-PH-A85 X B105 X C75MM	10W	6500	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
140	MAZDA-SXR184410W-6.5K-AC240-WH-PH-EM-A85 X B105 X C75MM	10W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
141	MAZDA-SXR184410W-6.5K-AC240-WH-DA-A85 X B105 X C75MM	10W	6500	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
142	MAZDA-SXR184410W-6.5K-AC240-WH-DA-EM-A85 X B105 X C75MM	10W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
143	MAZDA-SXR184410W-6.5K-AC240-WH-ND-A85 X B105 X C75MM	10W	6500	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
144	MAZDA-SXR184410W-6.5K-AC240-WH-ND-EM-A85 X B105 X C75MM	10W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
145	MAZDA-SXR184410W-2.7K-AC240-WH-10VDIM-A85 X B105 X C75MM	10W	2700	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
146	MAZDA-SXR184410W-2.7K-AC240-WH-10VDIM-EM-A85 X B105 X C75MM	10W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
147	MAZDA-SXR184410W-2.7K-AC240-WH-PH-A85 X B105 X C75MM	10W	2700	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
148	MAZDA-SXR184410W-2.7K-AC240-WH-PH-EM-A85 X B105 X C75MM	10W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
149	MAZDA-SXR184410W-2.7K-AC240-WH-DA-A85 X B105 X C75MM	10W	2700	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
150	MAZDA-SXR184410W-2.7K-AC240-WH-DA-EM-A85 X B105 X C75MM	10W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
151	MAZDA-SXR184410W-2.7K-AC240-WH-ND-A85 X B105 X C75MM	10W	2700	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
152	MAZDA-SXR184410W-2.7K-AC240-WH-ND-EM-A85 X B105 X C75MM	10W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
153	MAZDA-SXR184410W-3K-AC240-WH-10VDIM-A85 X B105 X C75MM	10W	3000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
154	MAZDA-SXR184410W-3K-AC240-WH-10VDIM-EM-A85 X B105 X C75MM	10W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
155	MAZDA-SXR184410W-3K-AC240-WH-PH-A85 X B105 X C75MM	10W	3000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
156	MAZDA-SXR184410W-3K-AC240-WH-PH-EM-A85 X B105 X C75MM	10W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
157	MAZDA-SXR184410W-3K-AC240-WH-DA-A85 X B105 X C75MM	10W	3000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
158	MAZDA-SXR184410W-3K-AC240-WH-DA-EM-A85 X B105 X C75MM	10W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
159	MAZDA-SXR184410W-3K-AC240-WH-ND-A85 X B105 X C75MM	10W	3000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
160	MAZDA-SXR184410W-3K-AC240-WH-ND-EM-A85 X B105 X C75MM	10W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
161	MAZDA-SXR184410W-4K-AC240-WH-10VDIM-A85 X B105 X C75MM	10W	4000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
162	MAZDA-SXR184410W-4K-AC240-WH-10VDIM-EM-A85 X B105 X C75MM	10W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
163	MAZDA-SXR184410W-4K-AC240-WH-PH-A85 X B105 X C75MM	10W	4000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
164	MAZDA-SXR184410W-4K-AC240-WH-PH-EM-A85 X B105 X C75MM	10W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	

DATASHEET

GENERATED ON: 10 Nov 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
165	**MAZDA-SXR184410W-4K-AC240-WH-DA-A85 X B105 X C75MM**	10W	4000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
166	**MAZDA-SXR184410W-4K-AC240-WH-DA-EM-A85 X B105 X C75MM**	10W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
167	**MAZDA-SXR184410W-4K-AC240-WH-ND-A85 X B105 X C75MM**	10W	4000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
168	**MAZDA-SXR184410W-4K-AC240-WH-ND-EM-A85 X B105 X C75MM**	10W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
169	**MAZDA-SXR184410W-5K-AC240-WH-10VDIM-A85 X B105 X C75MM**	10W	5000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
170	**MAZDA-SXR184410W-5K-AC240-WH-10VDIM-EM-A85 X B105 X C75MM**	10W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
171	**MAZDA-SXR184410W-5K-AC240-WH-PH-A85 X B105 X C75MM**	10W	5000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
172	**MAZDA-SXR184410W-5K-AC240-WH-PH-EM-A85 X B105 X C75MM**	10W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
173	**MAZDA-SXR184410W-5K-AC240-WH-DA-A85 X B105 X C75MM**	10W	5000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
174	**MAZDA-SXR184410W-5K-AC240-WH-DA-EM-A85 X B105 X C75MM**	10W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
175	**MAZDA-SXR184410W-5K-AC240-WH-ND-A85 X B105 X C75MM**	10W	5000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
176	**MAZDA-SXR184410W-5K-AC240-WH-ND-EM-A85 X B105 X C75MM**	10W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
177	**MAZDA-SXR184410W-6K-AC240-WH-10VDIM-A85 X B105 X C75MM**	10W	6000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
178	**MAZDA-SXR184410W-6K-AC240-WH-10VDIM-EM-A85 X B105 X C75MM**	10W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
179	**MAZDA-SXR184410W-6K-AC240-WH-PH-A85 X B105 X C75MM**	10W	6000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
180	**MAZDA-SXR184410W-6K-AC240-WH-PH-EM-A85 X B105 X C75MM**	10W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
181	**MAZDA-SXR184410W-6K-AC240-WH-DA-A85 X B105 X C75MM**	10W	6000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
182	**MAZDA-SXR184410W-6K-AC240-WH-DA-EM-A85 X B105 X C75MM**	10W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
183	**MAZDA-SXR184410W-6K-AC240-WH-ND-A85 X B105 X C75MM**	10W	6000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
184	**MAZDA-SXR184410W-6K-AC240-WH-ND-EM-A85 X B105 X C75MM**	10W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
185	**MAZDA-SXR184410W-6.5K-AC240-WH-10VDIM-A85 X B105 X C75MM**	10W	6500	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
186	**MAZDA-SXR184410W-6.5K-AC240-WH-10VDIM-EM-A85 X B105 X C75MM**	10W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
187	**MAZDA-SXR184410W-6.5K-AC240-WH-PH-A85 X B105 X C75MM**	10W	6500	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
188	**MAZDA-SXR184410W-6.5K-AC240-WH-PH-EM-A85 X B105 X C75MM**	10W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
189	**MAZDA-SXR184410W-6.5K-AC240-WH-DA-A85 X B105 X C75MM**	10W	6500	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
190	**MAZDA-SXR184410W-6.5K-AC240-WH-DA-EM-A85 X B105 X C75MM**	10W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
191	**MAZDA-SXR184410W-6.5K-AC240-WH-ND-A85 X B105 X C75MM**	10W	6500	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
192	**MAZDA-SXR184410W-6.5K-AC240-WH-ND-EM-A85 X B105 X C75MM**	10W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1200LM	A85 X B105 X C75MM	
193	**MAZDA-SXR184412W-2.7K-AC240-WH-10VDIM-A85 X B105 X C75MM**	12W	2700	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1440LM	A85 X B105 X C75MM	

DATASHEET

GENERATED ON: 10 Nov 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
194	MAZDA-SXR184412W-2.7K-AC240-WH-10VDIM-EM-A85 X B105 X C75MM	12W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1440LM	A85 X B105 X C75MM	
195	MAZDA-SXR184412W-2.7K-AC240-WH-PH-A85 X B105 X C75MM	12W	2700	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1440LM	A85 X B105 X C75MM	
196	MAZDA-SXR184412W-2.7K-AC240-WH-PH-EM-A85 X B105 X C75MM	12W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1440LM	A85 X B105 X C75MM	
197	MAZDA-SXR184412W-2.7K-AC240-WH-DA-A85 X B105 X C75MM	12W	2700	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1440LM	A85 X B105 X C75MM	
198	MAZDA-SXR184412W-2.7K-AC240-WH-DA-EM-A85 X B105 X C75MM	12W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1440LM	A85 X B105 X C75MM	
199	MAZDA-SXR184412W-2.7K-AC240-WH-ND-A85 X B105 X C75MM	12W	2700	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1440LM	A85 X B105 X C75MM	
200	MAZDA-SXR184412W-2.7K-AC240-WH-ND-EM-A85 X B105 X C75MM	12W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1440LM	A85 X B105 X C75MM	
201	MAZDA-SXR184412W-3K-AC240-WH-10VDIM-A85 X B105 X C75MM	12W	3000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1440LM	A85 X B105 X C75MM	
202	MAZDA-SXR184412W-3K-AC240-WH-10VDIM-EM-A85 X B105 X C75MM	12W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1440LM	A85 X B105 X C75MM	
203	MAZDA-SXR184412W-3K-AC240-WH-PH-A85 X B105 X C75MM	12W	3000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1440LM	A85 X B105 X C75MM	
204	MAZDA-SXR184412W-3K-AC240-WH-PH-EM-A85 X B105 X C75MM	12W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1440LM	A85 X B105 X C75MM	
205	MAZDA-SXR184412W-3K-AC240-WH-DA-A85 X B105 X C75MM	12W	3000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1440LM	A85 X B105 X C75MM	
206	MAZDA-SXR184412W-3K-AC240-WH-DA-EM-A85 X B105 X C75MM	12W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1440LM	A85 X B105 X C75MM	
207	MAZDA-SXR184412W-3K-AC240-WH-ND-A85 X B105 X C75MM	12W	3000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1440LM	A85 X B105 X C75MM	
208	MAZDA-SXR184412W-3K-AC240-WH-ND-EM-A85 X B105 X C75MM	12W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1440LM	A85 X B105 X C75MM	
209	MAZDA-SXR184412W-4K-AC240-WH-10VDIM-A85 X B105 X C75MM	12W	4000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1440LM	A85 X B105 X C75MM	
210	MAZDA-SXR184412W-4K-AC240-WH-10VDIM-EM-A85 X B105 X C75MM	12W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1440LM	A85 X B105 X C75MM	
211	MAZDA-SXR184412W-4K-AC240-WH-PH-A85 X B105 X C75MM	12W	4000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1440LM	A85 X B105 X C75MM	
212	MAZDA-SXR184412W-4K-AC240-WH-PH-EM-A85 X B105 X C75MM	12W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1440LM	A85 X B105 X C75MM	
213	MAZDA-SXR184412W-4K-AC240-WH-DA-A85 X B105 X C75MM	12W	4000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1440LM	A85 X B105 X C75MM	
214	MAZDA-SXR184412W-4K-AC240-WH-DA-EM-A85 X B105 X C75MM	12W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1440LM	A85 X B105 X C75MM	
215	MAZDA-SXR184412W-4K-AC240-WH-ND-A85 X B105 X C75MM	12W	4000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1440LM	A85 X B105 X C75MM	
216	MAZDA-SXR184412W-4K-AC240-WH-ND-EM-A85 X B105 X C75MM	12W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1440LM	A85 X B105 X C75MM	
217	MAZDA-SXR184412W-5K-AC240-WH-10VDIM-A85 X B105 X C75MM	12W	5000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1440LM	A85 X B105 X C75MM	
218	MAZDA-SXR184412W-5K-AC240-WH-10VDIM-EM-A85 X B105 X C75MM	12W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1440LM	A85 X B105 X C75MM	
219	MAZDA-SXR184412W-5K-AC240-WH-PH-A85 X B105 X C75MM	12W	5000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1440LM	A85 X B105 X C75MM	
220	MAZDA-SXR184412W-5K-AC240-WH-PH-EM-A85 X B105 X C75MM	12W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1440LM	A85 X B105 X C75MM	
221	MAZDA-SXR184412W-5K-AC240-WH-DA-A85 X B105 X C75MM	12W	5000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1440LM	A85 X B105 X C75MM	
222	MAZDA-SXR184412W-5K-AC240-WH-DA-EM-A85 X B105 X C75MM	12W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1440LM	A85 X B105 X C75MM	

DATASHEET

GENERATED ON: 10 Nov 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
223	MAZDA-SXR184412W-5K-AC240-WH-ND-A85 X B105 X C75MM	12W	5000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1440LM	A85 X B105 X C75MM	
224	MAZDA-SXR184412W-5K-AC240-WH-ND-EM-A85 X B105 X C75MM	12W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1440LM	A85 X B105 X C75MM	
225	MAZDA-SXR184412W-6K-AC240-WH-10VDIM-A85 X B105 X C75MM	12W	6000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1440LM	A85 X B105 X C75MM	
226	MAZDA-SXR184412W-6K-AC240-WH-10VDIM-EM-A85 X B105 X C75MM	12W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1440LM	A85 X B105 X C75MM	
227	MAZDA-SXR184412W-6K-AC240-WH-PH-A85 X B105 X C75MM	12W	6000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1440LM	A85 X B105 X C75MM	
228	MAZDA-SXR184412W-6K-AC240-WH-PH-EM-A85 X B105 X C75MM	12W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1440LM	A85 X B105 X C75MM	
229	MAZDA-SXR184412W-6K-AC240-WH-DA-A85 X B105 X C75MM	12W	6000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1440LM	A85 X B105 X C75MM	
230	MAZDA-SXR184412W-6K-AC240-WH-DA-EM-A85 X B105 X C75MM	12W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1440LM	A85 X B105 X C75MM	
231	MAZDA-SXR184412W-6K-AC240-WH-ND-A85 X B105 X C75MM	12W	6000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1440LM	A85 X B105 X C75MM	
232	MAZDA-SXR184412W-6K-AC240-WH-ND-EM-A85 X B105 X C75MM	12W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1440LM	A85 X B105 X C75MM	
233	MAZDA-SXR184412W-6.5K-AC240-WH-10VDIM-A85 X B105 X C75MM	12W	6500	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1440LM	A85 X B105 X C75MM	
234	MAZDA-SXR184412W-6.5K-AC240-WH-10VDIM-EM-A85 X B105 X C75MM	12W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1440LM	A85 X B105 X C75MM	
235	MAZDA-SXR184412W-6.5K-AC240-WH-PH-A85 X B105 X C75MM	12W	6500	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1440LM	A85 X B105 X C75MM	
236	MAZDA-SXR184412W-6.5K-AC240-WH-PH-EM-A85 X B105 X C75MM	12W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1440LM	A85 X B105 X C75MM	
237	MAZDA-SXR184412W-6.5K-AC240-WH-DA-A85 X B105 X C75MM	12W	6500	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1440LM	A85 X B105 X C75MM	
238	MAZDA-SXR184412W-6.5K-AC240-WH-DA-EM-A85 X B105 X C75MM	12W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1440LM	A85 X B105 X C75MM	
239	MAZDA-SXR184412W-6.5K-AC240-WH-ND-A85 X B105 X C75MM	12W	6500	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1440LM	A85 X B105 X C75MM	
240	MAZDA-SXR184412W-6.5K-AC240-WH-ND-EM-A85 X B105 X C75MM	12W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B105 X C75MM	DIE CAST ALUMINUM	IP65	1440LM	A85 X B105 X C75MM	
241	MAZDA-SXR184420W-2.7K-AC240-WH-10VDIM-A105 X B125 X C95MM	20W	2700	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A105 X B125 X C95MM	DIE CAST ALUMINUM	IP65	2400LM	A105 X B125 X C95MM	
242	MAZDA-SXR184420W-2.7K-AC240-WH-10VDIM-EM-A105 X B125 X C95MM	20W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A105 X B125 X C95MM	DIE CAST ALUMINUM	IP65	2400LM	A105 X B125 X C95MM	
243	MAZDA-SXR184420W-2.7K-AC240-WH-PH-A105 X B125 X C95MM	20W	2700	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A105 X B125 X C95MM	DIE CAST ALUMINUM	IP65	2400LM	A105 X B125 X C95MM	
244	MAZDA-SXR184420W-2.7K-AC240-WH-PH-EM-A105 X B125 X C95MM	20W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A105 X B125 X C95MM	DIE CAST ALUMINUM	IP65	2400LM	A105 X B125 X C95MM	
245	MAZDA-SXR184420W-2.7K-AC240-WH-DA-A105 X B125 X C95MM	20W	2700	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A105 X B125 X C95MM	DIE CAST ALUMINUM	IP65	2400LM	A105 X B125 X C95MM	
246	MAZDA-SXR184420W-2.7K-AC240-WH-DA-EM-A105 X B125 X C95MM	20W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A105 X B125 X C95MM	DIE CAST ALUMINUM	IP65	2400LM	A105 X B125 X C95MM	
247	MAZDA-SXR184420W-2.7K-AC240-WH-ND-A105 X B125 X C95MM	20W	2700	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A105 X B125 X C95MM	DIE CAST ALUMINUM	IP65	2400LM	A105 X B125 X C95MM	
248	MAZDA-SXR184420W-2.7K-AC240-WH-ND-EM-A105 X B125 X C95MM	20W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A105 X B125 X C95MM	DIE CAST ALUMINUM	IP65	2400LM	A105 X B125 X C95MM	
249	MAZDA-SXR184420W-3K-AC240-WH-10VDIM-A105 X B125 X C95MM	20W	3000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A105 X B125 X C95MM	DIE CAST ALUMINUM	IP65	2400LM	A105 X B125 X C95MM	
250	MAZDA-SXR184420W-3K-AC240-WH-10VDIM-EM-A105 X B125 X C95MM	20W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A105 X B125 X C95MM	DIE CAST ALUMINUM	IP65	2400LM	A105 X B125 X C95MM	
251	MAZDA-SXR184420W-3K-AC240-WH-PH-A105 X B125 X C95MM	20W	3000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A105 X B125 X C95MM	DIE CAST ALUMINUM	IP65	2400LM	A105 X B125 X C95MM	

DATASHEET

GENERATED ON: 10 Nov 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
252	MAZDA-SXR184420W-3K-AC240-WH-PH-EM-A105 X B125 X C95MM	20W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A105 X B125 X C95MM	DIE CAST ALUMINUM	IP65	2400LM	A105 X B125 X C95MM	
253	MAZDA-SXR184420W-3K-AC240-WH-DA-A105 X B125 X C95MM	20W	3000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A105 X B125 X C95MM	DIE CAST ALUMINUM	IP65	2400LM	A105 X B125 X C95MM	
254	MAZDA-SXR184420W-3K-AC240-WH-DA-EM-A105 X B125 X C95MM	20W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A105 X B125 X C95MM	DIE CAST ALUMINUM	IP65	2400LM	A105 X B125 X C95MM	
255	MAZDA-SXR184420W-3K-AC240-WH-ND-A105 X B125 X C95MM	20W	3000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A105 X B125 X C95MM	DIE CAST ALUMINUM	IP65	2400LM	A105 X B125 X C95MM	
256	MAZDA-SXR184420W-3K-AC240-WH-ND-EM-A105 X B125 X C95MM	20W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A105 X B125 X C95MM	DIE CAST ALUMINUM	IP65	2400LM	A105 X B125 X C95MM	
257	MAZDA-SXR184420W-4K-AC240-WH-10VDIM-A105 X B125 X C95MM	20W	4000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A105 X B125 X C95MM	DIE CAST ALUMINUM	IP65	2400LM	A105 X B125 X C95MM	
258	MAZDA-SXR184420W-4K-AC240-WH-10VDIM-EM-A105 X B125 X C95MM	20W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A105 X B125 X C95MM	DIE CAST ALUMINUM	IP65	2400LM	A105 X B125 X C95MM	
259	MAZDA-SXR184420W-4K-AC240-WH-PH-A105 X B125 X C95MM	20W	4000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A105 X B125 X C95MM	DIE CAST ALUMINUM	IP65	2400LM	A105 X B125 X C95MM	
260	MAZDA-SXR184420W-4K-AC240-WH-PH-EM-A105 X B125 X C95MM	20W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A105 X B125 X C95MM	DIE CAST ALUMINUM	IP65	2400LM	A105 X B125 X C95MM	
261	MAZDA-SXR184420W-4K-AC240-WH-DA-A105 X B125 X C95MM	20W	4000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A105 X B125 X C95MM	DIE CAST ALUMINUM	IP65	2400LM	A105 X B125 X C95MM	
262	MAZDA-SXR184420W-4K-AC240-WH-DA-EM-A105 X B125 X C95MM	20W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A105 X B125 X C95MM	DIE CAST ALUMINUM	IP65	2400LM	A105 X B125 X C95MM	
263	MAZDA-SXR184420W-4K-AC240-WH-ND-A105 X B125 X C95MM	20W	4000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A105 X B125 X C95MM	DIE CAST ALUMINUM	IP65	2400LM	A105 X B125 X C95MM	
264	MAZDA-SXR184420W-4K-AC240-WH-ND-EM-A105 X B125 X C95MM	20W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A105 X B125 X C95MM	DIE CAST ALUMINUM	IP65	2400LM	A105 X B125 X C95MM	
265	MAZDA-SXR184420W-5K-AC240-WH-10VDIM-A105 X B125 X C95MM	20W	5000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A105 X B125 X C95MM	DIE CAST ALUMINUM	IP65	2400LM	A105 X B125 X C95MM	
266	MAZDA-SXR184420W-5K-AC240-WH-10VDIM-EM-A105 X B125 X C95MM	20W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A105 X B125 X C95MM	DIE CAST ALUMINUM	IP65	2400LM	A105 X B125 X C95MM	
267	MAZDA-SXR184420W-5K-AC240-WH-PH-A105 X B125 X C95MM	20W	5000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A105 X B125 X C95MM	DIE CAST ALUMINUM	IP65	2400LM	A105 X B125 X C95MM	
268	MAZDA-SXR184420W-5K-AC240-WH-PH-EM-A105 X B125 X C95MM	20W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A105 X B125 X C95MM	DIE CAST ALUMINUM	IP65	2400LM	A105 X B125 X C95MM	
269	MAZDA-SXR184420W-5K-AC240-WH-DA-A105 X B125 X C95MM	20W	5000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A105 X B125 X C95MM	DIE CAST ALUMINUM	IP65	2400LM	A105 X B125 X C95MM	
270	MAZDA-SXR184420W-5K-AC240-WH-DA-EM-A105 X B125 X C95MM	20W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A105 X B125 X C95MM	DIE CAST ALUMINUM	IP65	2400LM	A105 X B125 X C95MM	
271	MAZDA-SXR184420W-5K-AC240-WH-ND-A105 X B125 X C95MM	20W	5000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A105 X B125 X C95MM	DIE CAST ALUMINUM	IP65	2400LM	A105 X B125 X C95MM	
272	MAZDA-SXR184420W-5K-AC240-WH-ND-EM-A105 X B125 X C95MM	20W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A105 X B125 X C95MM	DIE CAST ALUMINUM	IP65	2400LM	A105 X B125 X C95MM	
273	MAZDA-SXR184420W-6K-AC240-WH-10VDIM-A105 X B125 X C95MM	20W	6000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A105 X B125 X C95MM	DIE CAST ALUMINUM	IP65	2400LM	A105 X B125 X C95MM	
274	MAZDA-SXR184420W-6K-AC240-WH-10VDIM-EM-A105 X B125 X C95MM	20W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A105 X B125 X C95MM	DIE CAST ALUMINUM	IP65	2400LM	A105 X B125 X C95MM	
275	MAZDA-SXR184420W-6K-AC240-WH-PH-A105 X B125 X C95MM	20W	6000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A105 X B125 X C95MM	DIE CAST ALUMINUM	IP65	2400LM	A105 X B125 X C95MM	
276	MAZDA-SXR184420W-6K-AC240-WH-PH-EM-A105 X B125 X C95MM	20W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A105 X B125 X C95MM	DIE CAST ALUMINUM	IP65	2400LM	A105 X B125 X C95MM	
277	MAZDA-SXR184420W-6K-AC240-WH-DA-A105 X B125 X C95MM	20W	6000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A105 X B125 X C95MM	DIE CAST ALUMINUM	IP65	2400LM	A105 X B125 X C95MM	
278	MAZDA-SXR184420W-6K-AC240-WH-DA-EM-A105 X B125 X C95MM	20W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A105 X B125 X C95MM	DIE CAST ALUMINUM	IP65	2400LM	A105 X B125 X C95MM	
279	MAZDA-SXR184420W-6K-AC240-WH-ND-A105 X B125 X C95MM	20W	6000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A105 X B125 X C95MM	DIE CAST ALUMINUM	IP65	2400LM	A105 X B125 X C95MM	
280	MAZDA-SXR184420W-6K-AC240-WH-ND-EM-A105 X B125 X C95MM	20W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A105 X B125 X C95MM	DIE CAST ALUMINUM	IP65	2400LM	A105 X B125 X C95MM	

DATASHEET

GENERATED ON: 10 Nov 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
281	MAZDA-SXR184420W-6.5K-AC240-WH-10VDIM-A105 X B125 X C95MM	20W	6500	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A105 X B125 X C95MM	DIE CAST ALUMINUM	IP65	2400LM	A105 X B125 X C95MM	
282	MAZDA-SXR184420W-6.5K-AC240-WH-10VDIM-EM-A105 X B125 X C95MM	20W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A105 X B125 X C95MM	DIE CAST ALUMINUM	IP65	2400LM	A105 X B125 X C95MM	
283	MAZDA-SXR184420W-6.5K-AC240-WH-PH-A105 X B125 X C95MM	20W	6500	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A105 X B125 X C95MM	DIE CAST ALUMINUM	IP65	2400LM	A105 X B125 X C95MM	
284	MAZDA-SXR184420W-6.5K-AC240-WH-PH-EM-A105 X B125 X C95MM	20W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A105 X B125 X C95MM	DIE CAST ALUMINUM	IP65	2400LM	A105 X B125 X C95MM	
285	MAZDA-SXR184420W-6.5K-AC240-WH-DA-A105 X B125 X C95MM	20W	6500	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A105 X B125 X C95MM	DIE CAST ALUMINUM	IP65	2400LM	A105 X B125 X C95MM	
286	MAZDA-SXR184420W-6.5K-AC240-WH-DA-EM-A105 X B125 X C95MM	20W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A105 X B125 X C95MM	DIE CAST ALUMINUM	IP65	2400LM	A105 X B125 X C95MM	
287	MAZDA-SXR184420W-6.5K-AC240-WH-ND-A105 X B125 X C95MM	20W	6500	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A105 X B125 X C95MM	DIE CAST ALUMINUM	IP65	2400LM	A105 X B125 X C95MM	
288	MAZDA-SXR184420W-6.5K-AC240-WH-ND-EM-A105 X B125 X C95MM	20W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A105 X B125 X C95MM	DIE CAST ALUMINUM	IP65	2400LM	A105 X B125 X C95MM	
289	MAZDA-SXR184430W-2.7K-AC240-WH-10VDIM-A135 X B125 X C125MM	30W	2700	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A135 X B125 X C125MM	DIE CAST ALUMINUM	IP65	3600LM	A135 X B125 X C125MM	
290	MAZDA-SXR184430W-2.7K-AC240-WH-10VDIM-EM-A135 X B125 X C125MM	30W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A135 X B125 X C125MM	DIE CAST ALUMINUM	IP65	3600LM	A135 X B125 X C125MM	
291	MAZDA-SXR184430W-2.7K-AC240-WH-PH-A135 X B125 X C125MM	30W	2700	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A135 X B125 X C125MM	DIE CAST ALUMINUM	IP65	3600LM	A135 X B125 X C125MM	
292	MAZDA-SXR184430W-2.7K-AC240-WH-PH-EM-A135 X B125 X C125MM	30W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A135 X B125 X C125MM	DIE CAST ALUMINUM	IP65	3600LM	A135 X B125 X C125MM	
293	MAZDA-SXR184430W-2.7K-AC240-WH-DA-A135 X B125 X C125MM	30W	2700	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A135 X B125 X C125MM	DIE CAST ALUMINUM	IP65	3600LM	A135 X B125 X C125MM	
294	MAZDA-SXR184430W-2.7K-AC240-WH-DA-EM-A135 X B125 X C125MM	30W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A135 X B125 X C125MM	DIE CAST ALUMINUM	IP65	3600LM	A135 X B125 X C125MM	
295	MAZDA-SXR184430W-2.7K-AC240-WH-ND-A135 X B125 X C125MM	30W	2700	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A135 X B125 X C125MM	DIE CAST ALUMINUM	IP65	3600LM	A135 X B125 X C125MM	
296	MAZDA-SXR184430W-2.7K-AC240-WH-ND-EM-A135 X B125 X C125MM	30W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A135 X B125 X C125MM	DIE CAST ALUMINUM	IP65	3600LM	A135 X B125 X C125MM	
297	MAZDA-SXR184430W-3K-AC240-WH-10VDIM-A135 X B125 X C125MM	30W	3000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A135 X B125 X C125MM	DIE CAST ALUMINUM	IP65	3600LM	A135 X B125 X C125MM	
298	MAZDA-SXR184430W-3K-AC240-WH-10VDIM-EM-A135 X B125 X C125MM	30W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A135 X B125 X C125MM	DIE CAST ALUMINUM	IP65	3600LM	A135 X B125 X C125MM	
299	MAZDA-SXR184430W-3K-AC240-WH-PH-A135 X B125 X C125MM	30W	3000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A135 X B125 X C125MM	DIE CAST ALUMINUM	IP65	3600LM	A135 X B125 X C125MM	
300	MAZDA-SXR184430W-3K-AC240-WH-PH-EM-A135 X B125 X C125MM	30W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A135 X B125 X C125MM	DIE CAST ALUMINUM	IP65	3600LM	A135 X B125 X C125MM	
301	MAZDA-SXR184430W-3K-AC240-WH-DA-A135 X B125 X C125MM	30W	3000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A135 X B125 X C125MM	DIE CAST ALUMINUM	IP65	3600LM	A135 X B125 X C125MM	
302	MAZDA-SXR184430W-3K-AC240-WH-DA-EM-A135 X B125 X C125MM	30W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A135 X B125 X C125MM	DIE CAST ALUMINUM	IP65	3600LM	A135 X B125 X C125MM	
303	MAZDA-SXR184430W-3K-AC240-WH-ND-A135 X B125 X C125MM	30W	3000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A135 X B125 X C125MM	DIE CAST ALUMINUM	IP65	3600LM	A135 X B125 X C125MM	
304	MAZDA-SXR184430W-3K-AC240-WH-ND-EM-A135 X B125 X C125MM	30W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A135 X B125 X C125MM	DIE CAST ALUMINUM	IP65	3600LM	A135 X B125 X C125MM	
305	MAZDA-SXR184430W-4K-AC240-WH-10VDIM-A135 X B125 X C125MM	30W	4000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A135 X B125 X C125MM	DIE CAST ALUMINUM	IP65	3600LM	A135 X B125 X C125MM	
306	MAZDA-SXR184430W-4K-AC240-WH-10VDIM-EM-A135 X B125 X C125MM	30W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A135 X B125 X C125MM	DIE CAST ALUMINUM	IP65	3600LM	A135 X B125 X C125MM	
307	MAZDA-SXR184430W-4K-AC240-WH-PH-A135 X B125 X C125MM	30W	4000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A135 X B125 X C125MM	DIE CAST ALUMINUM	IP65	3600LM	A135 X B125 X C125MM	
308	MAZDA-SXR184430W-4K-AC240-WH-PH-EM-A135 X B125 X C125MM	30W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A135 X B125 X C125MM	DIE CAST ALUMINUM	IP65	3600LM	A135 X B125 X C125MM	
309	MAZDA-SXR184430W-4K-AC240-WH-DA-A135 X B125 X C125MM	30W	4000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A135 X B125 X C125MM	DIE CAST ALUMINUM	IP65	3600LM	A135 X B125 X C125MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
310	MAZDA-SXR184430W-4K-AC240-WH-DA-EM-A135 X B125 X C125MM	30W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A135 X B125 X C125MM	DIE CAST ALUMINUM	IP65	3600LM	A135 X B125 X C125MM	
311	MAZDA-SXR184430W-4K-AC240-WH-ND-A135 X B125 X C125MM	30W	4000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A135 X B125 X C125MM	DIE CAST ALUMINUM	IP65	3600LM	A135 X B125 X C125MM	
312	MAZDA-SXR184430W-4K-AC240-WH-ND-EM-A135 X B125 X C125MM	30W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A135 X B125 X C125MM	DIE CAST ALUMINUM	IP65	3600LM	A135 X B125 X C125MM	
313	MAZDA-SXR184430W-5K-AC240-WH-10VDIM-A135 X B125 X C125MM	30W	5000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A135 X B125 X C125MM	DIE CAST ALUMINUM	IP65	3600LM	A135 X B125 X C125MM	
314	MAZDA-SXR184430W-5K-AC240-WH-10VDIM-EM-A135 X B125 X C125MM	30W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A135 X B125 X C125MM	DIE CAST ALUMINUM	IP65	3600LM	A135 X B125 X C125MM	
315	MAZDA-SXR184430W-5K-AC240-WH-PH-A135 X B125 X C125MM	30W	5000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A135 X B125 X C125MM	DIE CAST ALUMINUM	IP65	3600LM	A135 X B125 X C125MM	
316	MAZDA-SXR184430W-5K-AC240-WH-PH-EM-A135 X B125 X C125MM	30W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A135 X B125 X C125MM	DIE CAST ALUMINUM	IP65	3600LM	A135 X B125 X C125MM	
317	MAZDA-SXR184430W-5K-AC240-WH-DA-A135 X B125 X C125MM	30W	5000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A135 X B125 X C125MM	DIE CAST ALUMINUM	IP65	3600LM	A135 X B125 X C125MM	
318	MAZDA-SXR184430W-5K-AC240-WH-DA-EM-A135 X B125 X C125MM	30W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A135 X B125 X C125MM	DIE CAST ALUMINUM	IP65	3600LM	A135 X B125 X C125MM	
319	MAZDA-SXR184430W-5K-AC240-WH-ND-A135 X B125 X C125MM	30W	5000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A135 X B125 X C125MM	DIE CAST ALUMINUM	IP65	3600LM	A135 X B125 X C125MM	
320	MAZDA-SXR184430W-5K-AC240-WH-ND-EM-A135 X B125 X C125MM	30W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A135 X B125 X C125MM	DIE CAST ALUMINUM	IP65	3600LM	A135 X B125 X C125MM	
321	MAZDA-SXR184430W-6K-AC240-WH-10VDIM-A135 X B125 X C125MM	30W	6000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A135 X B125 X C125MM	DIE CAST ALUMINUM	IP65	3600LM	A135 X B125 X C125MM	
322	MAZDA-SXR184430W-6K-AC240-WH-10VDIM-EM-A135 X B125 X C125MM	30W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A135 X B125 X C125MM	DIE CAST ALUMINUM	IP65	3600LM	A135 X B125 X C125MM	
323	MAZDA-SXR184430W-6K-AC240-WH-PH-A135 X B125 X C125MM	30W	6000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A135 X B125 X C125MM	DIE CAST ALUMINUM	IP65	3600LM	A135 X B125 X C125MM	
324	MAZDA-SXR184430W-6K-AC240-WH-PH-EM-A135 X B125 X C125MM	30W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A135 X B125 X C125MM	DIE CAST ALUMINUM	IP65	3600LM	A135 X B125 X C125MM	
325	MAZDA-SXR184430W-6K-AC240-WH-DA-A135 X B125 X C125MM	30W	6000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A135 X B125 X C125MM	DIE CAST ALUMINUM	IP65	3600LM	A135 X B125 X C125MM	
326	MAZDA-SXR184430W-6K-AC240-WH-DA-EM-A135 X B125 X C125MM	30W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A135 X B125 X C125MM	DIE CAST ALUMINUM	IP65	3600LM	A135 X B125 X C125MM	
327	MAZDA-SXR184430W-6K-AC240-WH-ND-A135 X B125 X C125MM	30W	6000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A135 X B125 X C125MM	DIE CAST ALUMINUM	IP65	3600LM	A135 X B125 X C125MM	
328	MAZDA-SXR184430W-6K-AC240-WH-ND-EM-A135 X B125 X C125MM	30W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A135 X B125 X C125MM	DIE CAST ALUMINUM	IP65	3600LM	A135 X B125 X C125MM	
329	MAZDA-SXR184430W-6.5K-AC240-WH-10VDIM-A135 X B125 X C125MM	30W	6500	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A135 X B125 X C125MM	DIE CAST ALUMINUM	IP65	3600LM	A135 X B125 X C125MM	
330	MAZDA-SXR184430W-6.5K-AC240-WH-10VDIM-EM-A135 X B125 X C125MM	30W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A135 X B125 X C125MM	DIE CAST ALUMINUM	IP65	3600LM	A135 X B125 X C125MM	
331	MAZDA-SXR184430W-6.5K-AC240-WH-PH-A135 X B125 X C125MM	30W	6500	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A135 X B125 X C125MM	DIE CAST ALUMINUM	IP65	3600LM	A135 X B125 X C125MM	
332	MAZDA-SXR184430W-6.5K-AC240-WH-PH-EM-A135 X B125 X C125MM	30W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A135 X B125 X C125MM	DIE CAST ALUMINUM	IP65	3600LM	A135 X B125 X C125MM	
333	MAZDA-SXR184430W-6.5K-AC240-WH-DA-A135 X B125 X C125MM	30W	6500	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A135 X B125 X C125MM	DIE CAST ALUMINUM	IP65	3600LM	A135 X B125 X C125MM	
334	MAZDA-SXR184430W-6.5K-AC240-WH-DA-EM-A135 X B125 X C125MM	30W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A135 X B125 X C125MM	DIE CAST ALUMINUM	IP65	3600LM	A135 X B125 X C125MM	
335	MAZDA-SXR184430W-6.5K-AC240-WH-ND-A135 X B125 X C125MM	30W	6500	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A135 X B125 X C125MM	DIE CAST ALUMINUM	IP65	3600LM	A135 X B125 X C125MM	
336	MAZDA-SXR184430W-6.5K-AC240-WH-ND-EM-A135 X B125 X C125MM	30W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A135 X B125 X C125MM	DIE CAST ALUMINUM	IP65	3600LM	A135 X B125 X C125MM	