DATASHEET

GENERATED ON: 10 Nov 2026 | SYS.REF: MAZDA-LED



QUARK

MAZDA Model: SXR1789 Spot Light

Quark Trimless LED Spot Light is a mini and exquisite lamp with high light transmittance. it offers a very little size in many design styles, without forgetting about the functionality: all the range is characterized by the use high quality LED technolo gy, so the result is a choice of accent light suitable for false ceiling, kitchen cabinet and not only. The possible applications are a multitude. This spotlights are all environmental friendly and very useful in a matter of energy and economical saving. The light result is bright, uniform and comfortable. Housing made by die cast aluminium powder coated with choice of RAL colors reflector

ALL AVAILABLE VARIANTS

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
1	MAZDA-SXR178915W-3K-AC240-WH-10VDIM-A71 X B102 MM	15W	3000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A71 X B102 MM	DIE CAST ALUMINUM	IP44	1500LM	A71 X B102 MM	
2	MAZDA-SXR178915W-3K-AC240-WH-10VDIM-EM-A71 X B102 MM	15W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A71 X B102 MM	DIE CAST ALUMINUM	IP44	1500LM	A71 X B102 MM	
3	MAZDA-SXR178915W-3K-AC240-WH-PH-A71 X B102 MM	15W	3000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A71 X B102 MM	DIE CAST ALUMINUM	IP44	1500LM	A71 X B102 MM	
4	MAZDA-SXR178915W-3K-AC240-WH-PH-EM-A71 X B102 MM	15W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A71 X B102 MM	DIE CAST ALUMINUM	IP44	1500LM	A71 X B102 MM	
5	MAZDA-SXR178915W-3K-AC240-WH-ND-A71 X B102 MM	15W	3000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A71 X B102 MM	DIE CAST ALUMINUM	IP44	1500LM	A71 X B102 MM	
6	MAZDA-SXR178915W-3K-AC240-WH-ND-EM-A71 X B102 MM	15W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A71 X B102 MM	DIE CAST ALUMINUM	IP44	1500LM	A71 X B102 MM	
7	MAZDA-SXR178915W-3K-AC240-WH-DA-A71 X B102 MM	15W	3000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A71 X B102 MM	DIE CAST ALUMINUM	IP44	1500LM	A71 X B102 MM	
8	MAZDA-SXR178915W-3K-AC240-WH-DA-EM-A71 X B102 MM	15W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A71 X B102 MM	DIE CAST ALUMINUM	IP44	1500LM	A71 X B102 MM	
9	MAZDA-SXR178915W-4K-AC240-WH-10VDIM-A71 X B102 MM	15W	4000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A71 X B102 MM	DIE CAST ALUMINUM	IP44	1500LM	A71 X B102 MM	
10	MAZDA-SXR178915W-4K-AC240-WH-10VDIM-EM-A71 X B102 MM	15W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A71 X B102 MM	DIE CAST ALUMINUM	IP44	1500LM	A71 X B102 MM	
11	MAZDA-SXR178915W-4K-AC240-WH-PH-A71 X B102 MM	15W	4000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A71 X B102 MM	DIE CAST ALUMINUM	IP44	1500LM	A71 X B102 MM	
12	MAZDA-SXR178915W-4K-AC240-WH-PH-EM-A71 X B102 MM	15W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A71 X B102 MM	DIE CAST ALUMINUM	IP44	1500LM	A71 X B102 MM	
13	MAZDA-SXR178915W-4K-AC240-WH-ND-A71 X B102 MM	15W	4000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A71 X B102 MM	DIE CAST ALUMINUM	IP44	1500LM	A71 X B102 MM	
14	MAZDA-SXR178915W-4K-AC240-WH-ND-EM-A71 X B102 MM	15W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A71 X B102 MM	DIE CAST ALUMINUM	IP44	1500LM	A71 X B102 MM	
15	MAZDA-SXR178915W-4K-AC240-WH-DA-A71 X B102 MM	15W	4000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A71 X B102 MM	DIE CAST ALUMINUM	IP44	1500LM	A71 X B102 MM	
16	MAZDA-SXR178915W-4K-AC240-WH-DA-EM-A71 X B102 MM	15W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A71 X B102 MM	DIE CAST ALUMINUM	IP44	1500LM	A71 X B102 MM	
17	MAZDA-SXR178915W-5K-AC240-WH-10VDIM-A71 X B102 MM	15W	5000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A71 X B102 MM	DIE CAST ALUMINUM	IP44	1500LM	A71 X B102 MM	

DATASHEET

GENERATED ON: 10 Nov 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
18	MAZDA-SXR178915W-5K-AC240-WH-10VDIM-EM-A71 X B102 MM	15W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A71 X B102 MM	DIE CAST ALUMINUM	IP44	1500LM	A71 X B102 MM	
19	MAZDA-SXR178915W-5K-AC240-WH-PH-A71 X B102 MM	15W	5000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A71 X B102 MM	DIE CAST ALUMINUM	IP44	1500LM	A71 X B102 MM	
20	MAZDA-SXR178915W-5K-AC240-WH-PH-EM-A71 X B102 MM	15W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A71 X B102 MM	DIE CAST ALUMINUM	IP44	1500LM	A71 X B102 MM	
21	MAZDA-SXR178915W-5K-AC240-WH-ND-A71 X B102 MM	15W	5000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A71 X B102 MM	DIE CAST ALUMINUM	IP44	1500LM	A71 X B102 MM	
22	MAZDA-SXR178915W-5K-AC240-WH-ND-EM-A71 X B102 MM	15W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A71 X B102 MM	DIE CAST ALUMINUM	IP44	1500LM	A71 X B102 MM	
23	MAZDA-SXR178915W-5K-AC240-WH-DA-A71 X B102 MM	15W	5000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A71 X B102 MM	DIE CAST ALUMINUM	IP44	1500LM	A71 X B102 MM	
24	MAZDA-SXR178915W-5K-AC240-WH-DA-EM-A71 X B102 MM	15W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A71 X B102 MM	DIE CAST ALUMINUM	IP44	1500LM	A71 X B102 MM	
25	MAZDA-SXR178915W-6K-AC240-WH-10VDIM-A71 X B102 MM	15W	6000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A71 X B102 MM	DIE CAST ALUMINUM	IP44	1500LM	A71 X B102 MM	
26	MAZDA-SXR178915W-6K-AC240-WH-10VDIM-EM-A71 X B102 MM	15W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A71 X B102 MM	DIE CAST ALUMINUM	IP44	1500LM	A71 X B102 MM	
27	MAZDA-SXR178915W-6K-AC240-WH-PH-A71 X B102 MM	15W	6000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A71 X B102 MM	DIE CAST ALUMINUM	IP44	1500LM	A71 X B102 MM	
28	MAZDA-SXR178915W-6K-AC240-WH-PH-EM-A71 X B102 MM	15W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A71 X B102 MM	DIE CAST ALUMINUM	IP44	1500LM	A71 X B102 MM	
29	MAZDA-SXR178915W-6K-AC240-WH-ND-A71 X B102 MM	15W	6000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A71 X B102 MM	DIE CAST ALUMINUM	IP44	1500LM	A71 X B102 MM	
30	MAZDA-SXR178915W-6K-AC240-WH-ND-EM-A71 X B102 MM	15W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A71 X B102 MM	DIE CAST ALUMINUM	IP44	1500LM	A71 X B102 MM	
31	MAZDA-SXR178915W-6K-AC240-WH-DA-A71 X B102 MM	15W	6000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A71 X B102 MM	DIE CAST ALUMINUM	IP44	1500LM	A71 X B102 MM	
32	MAZDA-SXR178915W-6K-AC240-WH-DA-EM-A71 X B102 MM	15W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A71 X B102 MM	DIE CAST ALUMINUM	IP44	1500LM	A71 X B102 MM	
33	MAZDA-SXR178915W-2.7K-AC240-WH-10VDIM-A71 X B102 MM	15W	2700	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A71 X B102 MM	DIE CAST ALUMINUM	IP44	1500LM	A71 X B102 MM	
34	MAZDA-SXR178915W-2.7K-AC240-WH-10VDIM-EM-A71 X B102 MM	15W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A71 X B102 MM	DIE CAST ALUMINUM	IP44	1500LM	A71 X B102 MM	
35	MAZDA-SXR178915W-2.7K-AC240-WH-PH-A71 X B102 MM	15W	2700	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A71 X B102 MM	DIE CAST ALUMINUM	IP44	1500LM	A71 X B102 MM	
36	MAZDA-SXR178915W-2.7K-AC240-WH-PH-EM-A71 X B102 MM	15W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A71 X B102 MM	DIE CAST ALUMINUM	IP44	1500LM	A71 X B102 MM	
37	MAZDA-SXR178915W-2.7K-AC240-WH-ND-A71 X B102 MM	15W	2700	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A71 X B102 MM	DIE CAST ALUMINUM	IP44	1500LM	A71 X B102 MM	
38	MAZDA-SXR178915W-2.7K-AC240-WH-ND-EM-A71 X B102 MM	15W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A71 X B102 MM	DIE CAST ALUMINUM	IP44	1500LM	A71 X B102 MM	
39	MAZDA-SXR178915W-2.7K-AC240-WH-DA-A71 X B102 MM	15W	2700	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A71 X B102 MM	DIE CAST ALUMINUM	IP44	1500LM	A71 X B102 MM	
40	MAZDA-SXR178915W-2.7K-AC240-WH-DA-EM-A71 X B102 MM	15W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A71 X B102 MM	DIE CAST ALUMINUM	IP44	1500LM	A71 X B102 MM	
41	MAZDA-SXR178915W-6.5K-AC240-WH-10VDIM-A71 X B102 MM	15W	6500	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A71 X B102 MM	DIE CAST ALUMINUM	IP44	1500LM	A71 X B102 MM	
42	MAZDA-SXR178915W-6.5K-AC240-WH-10VDIM-EM-A71 X B102 MM	15W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A71 X B102 MM	DIE CAST ALUMINUM	IP44	1500LM	A71 X B102 MM	
43	MAZDA-SXR178915W-6.5K-AC240-WH-PH-A71 X B102 MM	15W	6500	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A71 X B102 MM	DIE CAST ALUMINUM	IP44	1500LM	A71 X B102 MM	
44	MAZDA-SXR178915W-6.5K-AC240-WH-PH-EM-A71 X B102 MM	15W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A71 X B102 MM	DIE CAST ALUMINUM	IP44	1500LM	A71 X B102 MM	
45	MAZDA-SXR178915W-6.5K-AC240-WH-ND-A71 X B102 MM	15W	6500	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A71 X B102 MM	DIE CAST ALUMINUM	IP44	1500LM	A71 X B102 MM	

DATASHEET

GENERATED ON: 10 Nov 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
46	MAZDA-SXR178915W-6.5K-AC240-WH-ND-EM-A71 X B102 MM	15W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A71 X B102 MM	DIE CAST ALUMINUM	IP44	1500LM	A71 X B102 MM	
47	MAZDA-SXR178915W-6.5K-AC240-WH-DA-A71 X B102 MM	15W	6500	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A71 X B102 MM	DIE CAST ALUMINUM	IP44	1500LM	A71 X B102 MM	
48	MAZDA-SXR178915W-6.5K-AC240-WH-DA-EM-A71 X B102 MM	15W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A71 X B102 MM	DIE CAST ALUMINUM	IP44	1500LM	A71 X B102 MM	
49	MAZDA-SXR178910W-3K-AC240-WH-10VDIM-A71 X B90 MM	10W	3000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A71 X B90 MM	DIE CAST ALUMINUM	IP44	1000LM	A71 X B90 MM	
50	MAZDA-SXR178910W-3K-AC240-WH-10VDIM-EM-A71 X B90 MM	10W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A71 X B90 MM	DIE CAST ALUMINUM	IP44	1000LM	A71 X B90 MM	
51	MAZDA-SXR178910W-3K-AC240-WH-PH-A71 X B90 MM	10W	3000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A71 X B90 MM	DIE CAST ALUMINUM	IP44	1000LM	A71 X B90 MM	
52	MAZDA-SXR178910W-3K-AC240-WH-PH-EM-A71 X B90 MM	10W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A71 X B90 MM	DIE CAST ALUMINUM	IP44	1000LM	A71 X B90 MM	
53	MAZDA-SXR178910W-3K-AC240-WH-ND-A71 X B90 MM	10W	3000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A71 X B90 MM	DIE CAST ALUMINUM	IP44	1000LM	A71 X B90 MM	
54	MAZDA-SXR178910W-3K-AC240-WH-ND-EM-A71 X B90 MM	10W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A71 X B90 MM	DIE CAST ALUMINUM	IP44	1000LM	A71 X B90 MM	
55	MAZDA-SXR178910W-3K-AC240-WH-DA-A71 X B90 MM	10W	3000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A71 X B90 MM	DIE CAST ALUMINUM	IP44	1000LM	A71 X B90 MM	
56	MAZDA-SXR178910W-3K-AC240-WH-DA-EM-A71 X B90 MM	10W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A71 X B90 MM	DIE CAST ALUMINUM	IP44	1000LM	A71 X B90 MM	
57	MAZDA-SXR178910W-4K-AC240-WH-10VDIM-A71 X B90 MM	10W	4000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A71 X B90 MM	DIE CAST ALUMINUM	IP44	1000LM	A71 X B90 MM	
58	MAZDA-SXR178910W-4K-AC240-WH-10VDIM-EM-A71 X B90 MM	10W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A71 X B90 MM	DIE CAST ALUMINUM	IP44	1000LM	A71 X B90 MM	
59	MAZDA-SXR178910W-4K-AC240-WH-PH-A71 X B90 MM	10W	4000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A71 X B90 MM	DIE CAST ALUMINUM	IP44	1000LM	A71 X B90 MM	
60	MAZDA-SXR178910W-4K-AC240-WH-PH-EM-A71 X B90 MM	10W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A71 X B90 MM	DIE CAST ALUMINUM	IP44	1000LM	A71 X B90 MM	
61	MAZDA-SXR178910W-4K-AC240-WH-ND-A71 X B90 MM	10W	4000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A71 X B90 MM	DIE CAST ALUMINUM	IP44	1000LM	A71 X B90 MM	
62	MAZDA-SXR178910W-4K-AC240-WH-ND-EM-A71 X B90 MM	10W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A71 X B90 MM	DIE CAST ALUMINUM	IP44	1000LM	A71 X B90 MM	
63	MAZDA-SXR178910W-4K-AC240-WH-DA-A71 X B90 MM	10W	4000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A71 X B90 MM	DIE CAST ALUMINUM	IP44	1000LM	A71 X B90 MM	
64	MAZDA-SXR178910W-4K-AC240-WH-DA-EM-A71 X B90 MM	10W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A71 X B90 MM	DIE CAST ALUMINUM	IP44	1000LM	A71 X B90 MM	
65	MAZDA-SXR178910W-5K-AC240-WH-10VDIM-A71 X B90 MM	10W	5000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A71 X B90 MM	DIE CAST ALUMINUM	IP44	1000LM	A71 X B90 MM	
66	MAZDA-SXR178910W-5K-AC240-WH-10VDIM-EM-A71 X B90 MM	10W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A71 X B90 MM	DIE CAST ALUMINUM	IP44	1000LM	A71 X B90 MM	
67	MAZDA-SXR178910W-5K-AC240-WH-PH-A71 X B90 MM	10W	5000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A71 X B90 MM	DIE CAST ALUMINUM	IP44	1000LM	A71 X B90 MM	
68	MAZDA-SXR178910W-5K-AC240-WH-PH-EM-A71 X B90 MM	10W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A71 X B90 MM	DIE CAST ALUMINUM	IP44	1000LM	A71 X B90 MM	
69	MAZDA-SXR178910W-5K-AC240-WH-ND-A71 X B90 MM	10W	5000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A71 X B90 MM	DIE CAST ALUMINUM	IP44	1000LM	A71 X B90 MM	
70	MAZDA-SXR178910W-5K-AC240-WH-ND-EM-A71 X B90 MM	10W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A71 X B90 MM	DIE CAST ALUMINUM	IP44	1000LM	A71 X B90 MM	
71	MAZDA-SXR178910W-5K-AC240-WH-DA-A71 X B90 MM	10W	5000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A71 X B90 MM	DIE CAST ALUMINUM	IP44	1000LM	A71 X B90 MM	
72	MAZDA-SXR178910W-5K-AC240-WH-DA-EM-A71 X B90 MM	10W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A71 X B90 MM	DIE CAST ALUMINUM	IP44	1000LM	A71 X B90 MM	
73	MAZDA-SXR178910W-6K-AC240-WH-10VDIM-A71 X B90 MM	10W	6000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A71 X B90 MM	DIE CAST ALUMINUM	IP44	1000LM	A71 X B90 MM	

DATASHEET

GENERATED ON: 10 Nov 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
74	MAZDA-SXR178910W-6K-AC240-WH-10VDIM-EM-A71 X B90 MM	10W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A71 X B90 MM	DIE CAST ALUMINUM	IP44	1000LM	A71 X B90 MM	
75	MAZDA-SXR178910W-6K-AC240-WH-PH-A71 X B90 MM	10W	6000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A71 X B90 MM	DIE CAST ALUMINUM	IP44	1000LM	A71 X B90 MM	
76	MAZDA-SXR178910W-6K-AC240-WH-PH-EM-A71 X B90 MM	10W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A71 X B90 MM	DIE CAST ALUMINUM	IP44	1000LM	A71 X B90 MM	
77	MAZDA-SXR178910W-6K-AC240-WH-ND-A71 X B90 MM	10W	6000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A71 X B90 MM	DIE CAST ALUMINUM	IP44	1000LM	A71 X B90 MM	
78	MAZDA-SXR178910W-6K-AC240-WH-ND-EM-A71 X B90 MM	10W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A71 X B90 MM	DIE CAST ALUMINUM	IP44	1000LM	A71 X B90 MM	
79	MAZDA-SXR178910W-6K-AC240-WH-DA-A71 X B90 MM	10W	6000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A71 X B90 MM	DIE CAST ALUMINUM	IP44	1000LM	A71 X B90 MM	
80	MAZDA-SXR178910W-6K-AC240-WH-DA-EM-A71 X B90 MM	10W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A71 X B90 MM	DIE CAST ALUMINUM	IP44	1000LM	A71 X B90 MM	
81	MAZDA-SXR178910W-2.7K-AC240-WH-10VDIM-A71 X B90 MM	10W	2700	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A71 X B90 MM	DIE CAST ALUMINUM	IP44	1000LM	A71 X B90 MM	
82	MAZDA-SXR178910W-2.7K-AC240-WH-10VDIM-EM-A71 X B90 MM	10W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A71 X B90 MM	DIE CAST ALUMINUM	IP44	1000LM	A71 X B90 MM	
83	MAZDA-SXR178910W-2.7K-AC240-WH-PH-A71 X B90 MM	10W	2700	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A71 X B90 MM	DIE CAST ALUMINUM	IP44	1000LM	A71 X B90 MM	
84	MAZDA-SXR178910W-2.7K-AC240-WH-PH-EM-A71 X B90 MM	10W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A71 X B90 MM	DIE CAST ALUMINUM	IP44	1000LM	A71 X B90 MM	
85	MAZDA-SXR178910W-2.7K-AC240-WH-ND-A71 X B90 MM	10W	2700	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A71 X B90 MM	DIE CAST ALUMINUM	IP44	1000LM	A71 X B90 MM	
86	MAZDA-SXR178910W-2.7K-AC240-WH-ND-EM-A71 X B90 MM	10W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A71 X B90 MM	DIE CAST ALUMINUM	IP44	1000LM	A71 X B90 MM	
87	MAZDA-SXR178910W-2.7K-AC240-WH-DA-A71 X B90 MM	10W	2700	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A71 X B90 MM	DIE CAST ALUMINUM	IP44	1000LM	A71 X B90 MM	
88	MAZDA-SXR178910W-2.7K-AC240-WH-DA-EM-A71 X B90 MM	10W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A71 X B90 MM	DIE CAST ALUMINUM	IP44	1000LM	A71 X B90 MM	
89	MAZDA-SXR178910W-6.5K-AC240-WH-10VDIM-A71 X B90 MM	10W	6500	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A71 X B90 MM	DIE CAST ALUMINUM	IP44	1000LM	A71 X B90 MM	
90	MAZDA-SXR178910W-6.5K-AC240-WH-10VDIM-EM-A71 X B90 MM	10W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A71 X B90 MM	DIE CAST ALUMINUM	IP44	1000LM	A71 X B90 MM	
91	MAZDA-SXR178910W-6.5K-AC240-WH-PH-A71 X B90 MM	10W	6500	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A71 X B90 MM	DIE CAST ALUMINUM	IP44	1000LM	A71 X B90 MM	
92	MAZDA-SXR178910W-6.5K-AC240-WH-PH-EM-A71 X B90 MM	10W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A71 X B90 MM	DIE CAST ALUMINUM	IP44	1000LM	A71 X B90 MM	
93	MAZDA-SXR178910W-6.5K-AC240-WH-ND-A71 X B90 MM	10W	6500	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A71 X B90 MM	DIE CAST ALUMINUM	IP44	1000LM	A71 X B90 MM	
94	MAZDA-SXR178910W-6.5K-AC240-WH-ND-EM-A71 X B90 MM	10W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A71 X B90 MM	DIE CAST ALUMINUM	IP44	1000LM	A71 X B90 MM	
95	MAZDA-SXR178910W-6.5K-AC240-WH-DA-A71 X B90 MM	10W	6500	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A71 X B90 MM	DIE CAST ALUMINUM	IP44	1000LM	A71 X B90 MM	
96	MAZDA-SXR178910W-6.5K-AC240-WH-DA-EM-A71 X B90 MM	10W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A71 X B90 MM	DIE CAST ALUMINUM	IP44	1000LM	A71 X B90 MM	
97	MAZDA-SXR178907W-3K-AC240-WH-10VDIM-A51 X B89 MM	07W	3000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A51 X B89 MM	DIE CAST ALUMINUM	IP44	700LM	A51 X B89 MM	
98	MAZDA-SXR178907W-3K-AC240-WH-10VDIM-EM-A51 X B89 MM	07W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A51 X B89 MM	DIE CAST ALUMINUM	IP44	700LM	A51 X B89 MM	
99	MAZDA-SXR178907W-3K-AC240-WH-PH-A51 X B89 MM	07W	3000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A51 X B89 MM	DIE CAST ALUMINUM	IP44	700LM	A51 X B89 MM	
100	MAZDA-SXR178907W-3K-AC240-WH-PH-EM-A51 X B89 MM	07W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A51 X B89 MM	DIE CAST ALUMINUM	IP44	700LM	A51 X B89 MM	
101	MAZDA-SXR178907W-3K-AC240-WH-ND-A51 X B89 MM	07W	3000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A51 X B89 MM	DIE CAST ALUMINUM	IP44	700LM	A51 X B89 MM	

DATASHEET

GENERATED ON: 10 Nov 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
102	MAZDA-SXR178907W-3K-AC240-WH-ND-EM-A51 X B89 MM	07W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A51 X B89 MM	DIE CAST ALUMINUM	IP44	700LM	A51 X B89 MM	
103	MAZDA-SXR178907W-3K-AC240-WH-DA-A51 X B89 MM	07W	3000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A51 X B89 MM	DIE CAST ALUMINUM	IP44	700LM	A51 X B89 MM	
104	MAZDA-SXR178907W-3K-AC240-WH-DA-EM-A51 X B89 MM	07W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A51 X B89 MM	DIE CAST ALUMINUM	IP44	700LM	A51 X B89 MM	
105	MAZDA-SXR178907W-4K-AC240-WH-10VDIM-A51 X B89 MM	07W	4000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A51 X B89 MM	DIE CAST ALUMINUM	IP44	700LM	A51 X B89 MM	
106	MAZDA-SXR178907W-4K-AC240-WH-10VDIM-EM-A51 X B89 MM	07W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A51 X B89 MM	DIE CAST ALUMINUM	IP44	700LM	A51 X B89 MM	
107	MAZDA-SXR178907W-4K-AC240-WH-PH-A51 X B89 MM	07W	4000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A51 X B89 MM	DIE CAST ALUMINUM	IP44	700LM	A51 X B89 MM	
108	MAZDA-SXR178907W-4K-AC240-WH-PH-EM-A51 X B89 MM	07W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A51 X B89 MM	DIE CAST ALUMINUM	IP44	700LM	A51 X B89 MM	
109	MAZDA-SXR178907W-4K-AC240-WH-ND-A51 X B89 MM	07W	4000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A51 X B89 MM	DIE CAST ALUMINUM	IP44	700LM	A51 X B89 MM	
110	MAZDA-SXR178907W-4K-AC240-WH-ND-EM-A51 X B89 MM	07W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A51 X B89 MM	DIE CAST ALUMINUM	IP44	700LM	A51 X B89 MM	
111	MAZDA-SXR178907W-4K-AC240-WH-DA-A51 X B89 MM	07W	4000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A51 X B89 MM	DIE CAST ALUMINUM	IP44	700LM	A51 X B89 MM	
112	MAZDA-SXR178907W-4K-AC240-WH-DA-EM-A51 X B89 MM	07W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A51 X B89 MM	DIE CAST ALUMINUM	IP44	700LM	A51 X B89 MM	
113	MAZDA-SXR178907W-5K-AC240-WH-10VDIM-A51 X B89 MM	07W	5000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A51 X B89 MM	DIE CAST ALUMINUM	IP44	700LM	A51 X B89 MM	
114	MAZDA-SXR178907W-5K-AC240-WH-10VDIM-EM-A51 X B89 MM	07W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A51 X B89 MM	DIE CAST ALUMINUM	IP44	700LM	A51 X B89 MM	
115	MAZDA-SXR178907W-5K-AC240-WH-PH-A51 X B89 MM	07W	5000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A51 X B89 MM	DIE CAST ALUMINUM	IP44	700LM	A51 X B89 MM	
116	MAZDA-SXR178907W-5K-AC240-WH-PH-EM-A51 X B89 MM	07W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A51 X B89 MM	DIE CAST ALUMINUM	IP44	700LM	A51 X B89 MM	
117	MAZDA-SXR178907W-5K-AC240-WH-ND-A51 X B89 MM	07W	5000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A51 X B89 MM	DIE CAST ALUMINUM	IP44	700LM	A51 X B89 MM	
118	MAZDA-SXR178907W-5K-AC240-WH-ND-EM-A51 X B89 MM	07W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A51 X B89 MM	DIE CAST ALUMINUM	IP44	700LM	A51 X B89 MM	
119	MAZDA-SXR178907W-5K-AC240-WH-DA-A51 X B89 MM	07W	5000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A51 X B89 MM	DIE CAST ALUMINUM	IP44	700LM	A51 X B89 MM	
120	MAZDA-SXR178907W-5K-AC240-WH-DA-EM-A51 X B89 MM	07W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A51 X B89 MM	DIE CAST ALUMINUM	IP44	700LM	A51 X B89 MM	
121	MAZDA-SXR178907W-6K-AC240-WH-10VDIM-A51 X B89 MM	07W	6000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A51 X B89 MM	DIE CAST ALUMINUM	IP44	700LM	A51 X B89 MM	
122	MAZDA-SXR178907W-6K-AC240-WH-10VDIM-EM-A51 X B89 MM	07W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A51 X B89 MM	DIE CAST ALUMINUM	IP44	700LM	A51 X B89 MM	
123	MAZDA-SXR178907W-6K-AC240-WH-PH-A51 X B89 MM	07W	6000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A51 X B89 MM	DIE CAST ALUMINUM	IP44	700LM	A51 X B89 MM	
124	MAZDA-SXR178907W-6K-AC240-WH-PH-EM-A51 X B89 MM	07W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A51 X B89 MM	DIE CAST ALUMINUM	IP44	700LM	A51 X B89 MM	
125	MAZDA-SXR178907W-6K-AC240-WH-ND-A51 X B89 MM	07W	6000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A51 X B89 MM	DIE CAST ALUMINUM	IP44	700LM	A51 X B89 MM	
126	MAZDA-SXR178907W-6K-AC240-WH-ND-EM-A51 X B89 MM	07W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A51 X B89 MM	DIE CAST ALUMINUM	IP44	700LM	A51 X B89 MM	
127	MAZDA-SXR178907W-6K-AC240-WH-DA-A51 X B89 MM	07W	6000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A51 X B89 MM	DIE CAST ALUMINUM	IP44	700LM	A51 X B89 MM	
128	MAZDA-SXR178907W-6K-AC240-WH-DA-EM-A51 X B89 MM	07W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A51 X B89 MM	DIE CAST ALUMINUM	IP44	700LM	A51 X B89 MM	
129	MAZDA-SXR178907W-2.7K-AC240-WH-10VDIM-A51 X B89 MM	07W	2700	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A51 X B89 MM	DIE CAST ALUMINUM	IP44	700LM	A51 X B89 MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions Price
130	**MAZDA-SXR178907W-2.7K-AC240-WH-10VDIM-EM-A51 X B89 MM**	07W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A51 X B89 MM	DIE CAST ALUMINUM	IP44	700LM	A51 X B89 MM
131	**MAZDA-SXR178907W-2.7K-AC240-WH-PH-A51 X B89 MM**	07W	2700	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A51 X B89 MM	DIE CAST ALUMINUM	IP44	700LM	A51 X B89 MM
132	**MAZDA-SXR178907W-2.7K-AC240-WH-PH-EM-A51 X B89 MM**	07W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A51 X B89 MM	DIE CAST ALUMINUM	IP44	700LM	A51 X B89 MM
133	**MAZDA-SXR178907W-2.7K-AC240-WH-ND-A51 X B89 MM**	07W	2700	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A51 X B89 MM	DIE CAST ALUMINUM	IP44	700LM	A51 X B89 MM
134	**MAZDA-SXR178907W-2.7K-AC240-WH-ND-EM-A51 X B89 MM**	07W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A51 X B89 MM	DIE CAST ALUMINUM	IP44	700LM	A51 X B89 MM
135	**MAZDA-SXR178907W-2.7K-AC240-WH-DA-A51 X B89 MM**	07W	2700	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A51 X B89 MM	DIE CAST ALUMINUM	IP44	700LM	A51 X B89 MM
136	**MAZDA-SXR178907W-2.7K-AC240-WH-DA-EM-A51 X B89 MM**	07W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A51 X B89 MM	DIE CAST ALUMINUM	IP44	700LM	A51 X B89 MM
137	**MAZDA-SXR178907W-6.5K-AC240-WH-10VDIM-A51 X B89 MM**	07W	6500	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A51 X B89 MM	DIE CAST ALUMINUM	IP44	700LM	A51 X B89 MM
138	**MAZDA-SXR178907W-6.5K-AC240-WH-10VDIM-EM-A51 X B89 MM**	07W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A51 X B89 MM	DIE CAST ALUMINUM	IP44	700LM	A51 X B89 MM
139	**MAZDA-SXR178907W-6.5K-AC240-WH-PH-A51 X B89 MM**	07W	6500	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A51 X B89 MM	DIE CAST ALUMINUM	IP44	700LM	A51 X B89 MM
140	**MAZDA-SXR178907W-6.5K-AC240-WH-PH-EM-A51 X B89 MM**	07W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A51 X B89 MM	DIE CAST ALUMINUM	IP44	700LM	A51 X B89 MM
141	**MAZDA-SXR178907W-6.5K-AC240-WH-ND-A51 X B89 MM**	07W	6500	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A51 X B89 MM	DIE CAST ALUMINUM	IP44	700LM	A51 X B89 MM
142	**MAZDA-SXR178907W-6.5K-AC240-WH-ND-EM-A51 X B89 MM**	07W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A51 X B89 MM	DIE CAST ALUMINUM	IP44	700LM	A51 X B89 MM
143	**MAZDA-SXR178907W-6.5K-AC240-WH-DA-A51 X B89 MM**	07W	6500	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A51 X B89 MM	DIE CAST ALUMINUM	IP44	700LM	A51 X B89 MM
144	**MAZDA-SXR178907W-6.5K-AC240-WH-DA-EM-A51 X B89 MM**	07W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A51 X B89 MM	DIE CAST ALUMINUM	IP44	700LM	A51 X B89 MM