



SPEED

MAZDA Model: SXR1915 Spot Light

Speed Trimless led spotlight is designed for durability and reflector with deep anti-glare performance. It's a COB high power LED chip provides perfect combination of high quality aluminum profile provides excellent thermal dissipation with great heatsink designed for any ceiling installations. Commonly used in offices corridors, bedroom and living rooms

ALL AVAILABLE VARIANTS

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
1	MAZDA-SXR191507W-3K-AC240-WH-10VDIM-A130 X B155 MM	07W	3000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	840LM	A130 X B155 MM	
2	MAZDA-SXR191507W-3K-AC240-WH-10VDIM-EM-A130 X B155 MM	07W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	840LM	A130 X B155 MM	
3	MAZDA-SXR191507W-3K-AC240-WH-ND-A130 X B155 MM	07W	3000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	840LM	A130 X B155 MM	
4	MAZDA-SXR191507W-3K-AC240-WH-ND-EM-A130 X B155 MM	07W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	840LM	A130 X B155 MM	
5	MAZDA-SXR191507W-3K-AC240-WH-DA-A130 X B155 MM	07W	3000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	840LM	A130 X B155 MM	
6	MAZDA-SXR191507W-3K-AC240-WH-DA-EM-A130 X B155 MM	07W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	840LM	A130 X B155 MM	
7	MAZDA-SXR191507W-3K-AC240-WH-PH-A130 X B155 MM	07W	3000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	840LM	A130 X B155 MM	
8	MAZDA-SXR191507W-3K-AC240-WH-PH-EM-A130 X B155 MM	07W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	840LM	A130 X B155 MM	
9	MAZDA-SXR191507W-4K-AC240-WH-10VDIM-A130 X B155 MM	07W	4000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	840LM	A130 X B155 MM	
10	MAZDA-SXR191507W-4K-AC240-WH-10VDIM-EM-A130 X B155 MM	07W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	840LM	A130 X B155 MM	
11	MAZDA-SXR191507W-4K-AC240-WH-ND-A130 X B155 MM	07W	4000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	840LM	A130 X B155 MM	
12	MAZDA-SXR191507W-4K-AC240-WH-ND-EM-A130 X B155 MM	07W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	840LM	A130 X B155 MM	
13	MAZDA-SXR191507W-4K-AC240-WH-DA-A130 X B155 MM	07W	4000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	840LM	A130 X B155 MM	
14	MAZDA-SXR191507W-4K-AC240-WH-DA-EM-A130 X B155 MM	07W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	840LM	A130 X B155 MM	
15	MAZDA-SXR191507W-4K-AC240-WH-PH-A130 X B155 MM	07W	4000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	840LM	A130 X B155 MM	
16	MAZDA-SXR191507W-4K-AC240-WH-PH-EM-A130 X B155 MM	07W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	840LM	A130 X B155 MM	
17	MAZDA-SXR191507W-5K-AC240-WH-10VDIM-A130 X B155 MM	07W	5000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	840LM	A130 X B155 MM	



DATASHEET

GENERATED ON: 01 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
18	MAZDA-SXR191507W-5K-AC240-WH-10VDIM-EM-A130 X B155 MM	07W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	840LM	A130 X B155 MM	
19	MAZDA-SXR191507W-5K-AC240-WH-ND-A130 X B155 MM	07W	5000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	840LM	A130 X B155 MM	
20	MAZDA-SXR191507W-5K-AC240-WH-ND-EM-A130 X B155 MM	07W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	840LM	A130 X B155 MM	
21	MAZDA-SXR191507W-5K-AC240-WH-DA-A130 X B155 MM	07W	5000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	840LM	A130 X B155 MM	
22	MAZDA-SXR191507W-5K-AC240-WH-DA-EM-A130 X B155 MM	07W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	840LM	A130 X B155 MM	
23	MAZDA-SXR191507W-5K-AC240-WH-PH-A130 X B155 MM	07W	5000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	840LM	A130 X B155 MM	
24	MAZDA-SXR191507W-5K-AC240-WH-PH-EM-A130 X B155 MM	07W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	840LM	A130 X B155 MM	
25	MAZDA-SXR191507W-6K-AC240-WH-10VDIM-A130 X B155 MM	07W	6000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	840LM	A130 X B155 MM	
26	MAZDA-SXR191507W-6K-AC240-WH-10VDIM-EM-A130 X B155 MM	07W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	840LM	A130 X B155 MM	
27	MAZDA-SXR191507W-6K-AC240-WH-ND-A130 X B155 MM	07W	6000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	840LM	A130 X B155 MM	
28	MAZDA-SXR191507W-6K-AC240-WH-ND-EM-A130 X B155 MM	07W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	840LM	A130 X B155 MM	
29	MAZDA-SXR191507W-6K-AC240-WH-DA-A130 X B155 MM	07W	6000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	840LM	A130 X B155 MM	
30	MAZDA-SXR191507W-6K-AC240-WH-DA-EM-A130 X B155 MM	07W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	840LM	A130 X B155 MM	
31	MAZDA-SXR191507W-6K-AC240-WH-PH-A130 X B155 MM	07W	6000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	840LM	A130 X B155 MM	
32	MAZDA-SXR191507W-6K-AC240-WH-PH-EM-A130 X B155 MM	07W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	840LM	A130 X B155 MM	
33	MAZDA-SXR191507W-2.7K-AC240-WH-10VDIM-A130 X B155 MM	07W	2700	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	840LM	A130 X B155 MM	
34	MAZDA-SXR191507W-2.7K-AC240-WH-10VDIM-EM-A130 X B155 MM	07W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	840LM	A130 X B155 MM	
35	MAZDA-SXR191507W-2.7K-AC240-WH-ND-A130 X B155 MM	07W	2700	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	840LM	A130 X B155 MM	
36	MAZDA-SXR191507W-2.7K-AC240-WH-ND-EM-A130 X B155 MM	07W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	840LM	A130 X B155 MM	
37	MAZDA-SXR191507W-2.7K-AC240-WH-DA-A130 X B155 MM	07W	2700	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	840LM	A130 X B155 MM	
38	MAZDA-SXR191507W-2.7K-AC240-WH-DA-EM-A130 X B155 MM	07W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	840LM	A130 X B155 MM	
39	MAZDA-SXR191507W-2.7K-AC240-WH-PH-A130 X B155 MM	07W	2700	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	840LM	A130 X B155 MM	
40	MAZDA-SXR191507W-2.7K-AC240-WH-PH-EM-A130 X B155 MM	07W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	840LM	A130 X B155 MM	
41	MAZDA-SXR191507W-6.5K-AC240-WH-10VDIM-A130 X B155 MM	07W	6500	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	840LM	A130 X B155 MM	
42	MAZDA-SXR191507W-6.5K-AC240-WH-10VDIM-EM-A130 X B155 MM	07W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	840LM	A130 X B155 MM	
43	MAZDA-SXR191507W-6.5K-AC240-WH-ND-A130 X B155 MM	07W	6500	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	840LM	A130 X B155 MM	
44	MAZDA-SXR191507W-6.5K-AC240-WH-ND-EM-A130 X B155 MM	07W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	840LM	A130 X B155 MM	
45	MAZDA-SXR191507W-6.5K-AC240-WH-DA-A130 X B155 MM	07W	6500	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	840LM	A130 X B155 MM	



DATASHEET

GENERATED ON: 01 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
46	MAZDA-SXR191507W-6.5K-AC240-WH-DA-EM-A130 X B155 MM	07W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	840LM	A130 X B155 MM	
47	MAZDA-SXR191507W-6.5K-AC240-WH-PH-A130 X B155 MM	07W	6500	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	840LM	A130 X B155 MM	
48	MAZDA-SXR191507W-6.5K-AC240-WH-PH-EM-A130 X B155 MM	07W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	840LM	A130 X B155 MM	
49	MAZDA-SXR191510W-3K-AC240-WH-10VDIM-A130 X B155 MM	10W	3000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1200LM	A130 X B155 MM	
50	MAZDA-SXR191510W-3K-AC240-WH-10VDIM-EM-A130 X B155 MM	10W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1200LM	A130 X B155 MM	
51	MAZDA-SXR191510W-3K-AC240-WH-ND-A130 X B155 MM	10W	3000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1200LM	A130 X B155 MM	
52	MAZDA-SXR191510W-3K-AC240-WH-ND-EM-A130 X B155 MM	10W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1200LM	A130 X B155 MM	
53	MAZDA-SXR191510W-3K-AC240-WH-DA-A130 X B155 MM	10W	3000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1200LM	A130 X B155 MM	
54	MAZDA-SXR191510W-3K-AC240-WH-DA-EM-A130 X B155 MM	10W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1200LM	A130 X B155 MM	
55	MAZDA-SXR191510W-3K-AC240-WH-PH-A130 X B155 MM	10W	3000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1200LM	A130 X B155 MM	
56	MAZDA-SXR191510W-3K-AC240-WH-PH-EM-A130 X B155 MM	10W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1200LM	A130 X B155 MM	
57	MAZDA-SXR191510W-4K-AC240-WH-10VDIM-A130 X B155 MM	10W	4000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1200LM	A130 X B155 MM	
58	MAZDA-SXR191510W-4K-AC240-WH-10VDIM-EM-A130 X B155 MM	10W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1200LM	A130 X B155 MM	
59	MAZDA-SXR191510W-4K-AC240-WH-ND-A130 X B155 MM	10W	4000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1200LM	A130 X B155 MM	
60	MAZDA-SXR191510W-4K-AC240-WH-ND-EM-A130 X B155 MM	10W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1200LM	A130 X B155 MM	
61	MAZDA-SXR191510W-4K-AC240-WH-DA-A130 X B155 MM	10W	4000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1200LM	A130 X B155 MM	
62	MAZDA-SXR191510W-4K-AC240-WH-DA-EM-A130 X B155 MM	10W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1200LM	A130 X B155 MM	
63	MAZDA-SXR191510W-4K-AC240-WH-PH-A130 X B155 MM	10W	4000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1200LM	A130 X B155 MM	
64	MAZDA-SXR191510W-4K-AC240-WH-PH-EM-A130 X B155 MM	10W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1200LM	A130 X B155 MM	
65	MAZDA-SXR191510W-5K-AC240-WH-10VDIM-A130 X B155 MM	10W	5000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1200LM	A130 X B155 MM	
66	MAZDA-SXR191510W-5K-AC240-WH-10VDIM-EM-A130 X B155 MM	10W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1200LM	A130 X B155 MM	
67	MAZDA-SXR191510W-5K-AC240-WH-ND-A130 X B155 MM	10W	5000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1200LM	A130 X B155 MM	
68	MAZDA-SXR191510W-5K-AC240-WH-ND-EM-A130 X B155 MM	10W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1200LM	A130 X B155 MM	
69	MAZDA-SXR191510W-5K-AC240-WH-DA-A130 X B155 MM	10W	5000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1200LM	A130 X B155 MM	
70	MAZDA-SXR191510W-5K-AC240-WH-DA-EM-A130 X B155 MM	10W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1200LM	A130 X B155 MM	
71	MAZDA-SXR191510W-5K-AC240-WH-PH-A130 X B155 MM	10W	5000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1200LM	A130 X B155 MM	
72	MAZDA-SXR191510W-5K-AC240-WH-PH-EM-A130 X B155 MM	10W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1200LM	A130 X B155 MM	
73	MAZDA-SXR191510W-6K-AC240-WH-10VDIM-A130 X B155 MM	10W	6000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1200LM	A130 X B155 MM	



DATASHEET

GENERATED ON: 01 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
74	MAZDA-SXR191510W-6K-AC240-WH-10VDIM-EM-A130 X B155 MM	10W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1200LM	A130 X B155 MM	
75	MAZDA-SXR191510W-6K-AC240-WH-ND-A130 X B155 MM	10W	6000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1200LM	A130 X B155 MM	
76	MAZDA-SXR191510W-6K-AC240-WH-ND-EM-A130 X B155 MM	10W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1200LM	A130 X B155 MM	
77	MAZDA-SXR191510W-6K-AC240-WH-DA-A130 X B155 MM	10W	6000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1200LM	A130 X B155 MM	
78	MAZDA-SXR191510W-6K-AC240-WH-DA-EM-A130 X B155 MM	10W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1200LM	A130 X B155 MM	
79	MAZDA-SXR191510W-6K-AC240-WH-PH-A130 X B155 MM	10W	6000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1200LM	A130 X B155 MM	
80	MAZDA-SXR191510W-6K-AC240-WH-PH-EM-A130 X B155 MM	10W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1200LM	A130 X B155 MM	
81	MAZDA-SXR191510W-2.7K-AC240-WH-10VDIM-A130 X B155 MM	10W	2700	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1200LM	A130 X B155 MM	
82	MAZDA-SXR191510W-2.7K-AC240-WH-10VDIM-EM-A130 X B155 MM	10W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1200LM	A130 X B155 MM	
83	MAZDA-SXR191510W-2.7K-AC240-WH-ND-A130 X B155 MM	10W	2700	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1200LM	A130 X B155 MM	
84	MAZDA-SXR191510W-2.7K-AC240-WH-ND-EM-A130 X B155 MM	10W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1200LM	A130 X B155 MM	
85	MAZDA-SXR191510W-2.7K-AC240-WH-DA-A130 X B155 MM	10W	2700	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1200LM	A130 X B155 MM	
86	MAZDA-SXR191510W-2.7K-AC240-WH-DA-EM-A130 X B155 MM	10W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1200LM	A130 X B155 MM	
87	MAZDA-SXR191510W-2.7K-AC240-WH-PH-A130 X B155 MM	10W	2700	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1200LM	A130 X B155 MM	
88	MAZDA-SXR191510W-2.7K-AC240-WH-PH-EM-A130 X B155 MM	10W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1200LM	A130 X B155 MM	
89	MAZDA-SXR191510W-6.5K-AC240-WH-10VDIM-A130 X B155 MM	10W	6500	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1200LM	A130 X B155 MM	
90	MAZDA-SXR191510W-6.5K-AC240-WH-10VDIM-EM-A130 X B155 MM	10W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1200LM	A130 X B155 MM	
91	MAZDA-SXR191510W-6.5K-AC240-WH-ND-A130 X B155 MM	10W	6500	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1200LM	A130 X B155 MM	
92	MAZDA-SXR191510W-6.5K-AC240-WH-ND-EM-A130 X B155 MM	10W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1200LM	A130 X B155 MM	
93	MAZDA-SXR191510W-6.5K-AC240-WH-DA-A130 X B155 MM	10W	6500	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1200LM	A130 X B155 MM	
94	MAZDA-SXR191510W-6.5K-AC240-WH-DA-EM-A130 X B155 MM	10W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1200LM	A130 X B155 MM	
95	MAZDA-SXR191510W-6.5K-AC240-WH-PH-A130 X B155 MM	10W	6500	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1200LM	A130 X B155 MM	
96	MAZDA-SXR191510W-6.5K-AC240-WH-PH-EM-A130 X B155 MM	10W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1200LM	A130 X B155 MM	
97	MAZDA-SXR191515W-3K-AC240-WH-10VDIM-A130 X B155 MM	15W	3000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1800LM	A130 X B155 MM	
98	MAZDA-SXR191515W-3K-AC240-WH-10VDIM-EM-A130 X B155 MM	15W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1800LM	A130 X B155 MM	
99	MAZDA-SXR191515W-3K-AC240-WH-ND-A130 X B155 MM	15W	3000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1800LM	A130 X B155 MM	
100	MAZDA-SXR191515W-3K-AC240-WH-ND-EM-A130 X B155 MM	15W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1800LM	A130 X B155 MM	
101	MAZDA-SXR191515W-3K-AC240-WH-DA-A130 X B155 MM	15W	3000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1800LM	A130 X B155 MM	



DATASHEET

GENERATED ON: 01 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
102	MAZDA-SXR191515W-3K-AC240-WH-DA-EM-A130 X B155 MM	15W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1800LM	A130 X B155 MM	
103	MAZDA-SXR191515W-3K-AC240-WH-PH-A130 X B155 MM	15W	3000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1800LM	A130 X B155 MM	
104	MAZDA-SXR191515W-3K-AC240-WH-PH-EM-A130 X B155 MM	15W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1800LM	A130 X B155 MM	
105	MAZDA-SXR191515W-4K-AC240-WH-10VDIM-A130 X B155 MM	15W	4000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1800LM	A130 X B155 MM	
106	MAZDA-SXR191515W-4K-AC240-WH-10VDIM-EM-A130 X B155 MM	15W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1800LM	A130 X B155 MM	
107	MAZDA-SXR191515W-4K-AC240-WH-ND-A130 X B155 MM	15W	4000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1800LM	A130 X B155 MM	
108	MAZDA-SXR191515W-4K-AC240-WH-ND-EM-A130 X B155 MM	15W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1800LM	A130 X B155 MM	
109	MAZDA-SXR191515W-4K-AC240-WH-DA-A130 X B155 MM	15W	4000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1800LM	A130 X B155 MM	
110	MAZDA-SXR191515W-4K-AC240-WH-DA-EM-A130 X B155 MM	15W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1800LM	A130 X B155 MM	
111	MAZDA-SXR191515W-4K-AC240-WH-PH-A130 X B155 MM	15W	4000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1800LM	A130 X B155 MM	
112	MAZDA-SXR191515W-4K-AC240-WH-PH-EM-A130 X B155 MM	15W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1800LM	A130 X B155 MM	
113	MAZDA-SXR191515W-5K-AC240-WH-10VDIM-A130 X B155 MM	15W	5000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1800LM	A130 X B155 MM	
114	MAZDA-SXR191515W-5K-AC240-WH-10VDIM-EM-A130 X B155 MM	15W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1800LM	A130 X B155 MM	
115	MAZDA-SXR191515W-5K-AC240-WH-ND-A130 X B155 MM	15W	5000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1800LM	A130 X B155 MM	
116	MAZDA-SXR191515W-5K-AC240-WH-ND-EM-A130 X B155 MM	15W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1800LM	A130 X B155 MM	
117	MAZDA-SXR191515W-5K-AC240-WH-DA-A130 X B155 MM	15W	5000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1800LM	A130 X B155 MM	
118	MAZDA-SXR191515W-5K-AC240-WH-DA-EM-A130 X B155 MM	15W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1800LM	A130 X B155 MM	
119	MAZDA-SXR191515W-5K-AC240-WH-PH-A130 X B155 MM	15W	5000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1800LM	A130 X B155 MM	
120	MAZDA-SXR191515W-5K-AC240-WH-PH-EM-A130 X B155 MM	15W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1800LM	A130 X B155 MM	
121	MAZDA-SXR191515W-6K-AC240-WH-10VDIM-A130 X B155 MM	15W	6000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1800LM	A130 X B155 MM	
122	MAZDA-SXR191515W-6K-AC240-WH-10VDIM-EM-A130 X B155 MM	15W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1800LM	A130 X B155 MM	
123	MAZDA-SXR191515W-6K-AC240-WH-ND-A130 X B155 MM	15W	6000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1800LM	A130 X B155 MM	
124	MAZDA-SXR191515W-6K-AC240-WH-ND-EM-A130 X B155 MM	15W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1800LM	A130 X B155 MM	
125	MAZDA-SXR191515W-6K-AC240-WH-DA-A130 X B155 MM	15W	6000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1800LM	A130 X B155 MM	
126	MAZDA-SXR191515W-6K-AC240-WH-DA-EM-A130 X B155 MM	15W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1800LM	A130 X B155 MM	
127	MAZDA-SXR191515W-6K-AC240-WH-PH-A130 X B155 MM	15W	6000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1800LM	A130 X B155 MM	
128	MAZDA-SXR191515W-6K-AC240-WH-PH-EM-A130 X B155 MM	15W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1800LM	A130 X B155 MM	
129	MAZDA-SXR191515W-2.7K-AC240-WH-10VDIM-A130 X B155 MM	15W	2700	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1800LM	A130 X B155 MM	



DATASHEET

GENERATED ON: 01 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
130	MAZDA-SXR191515W-2.7K-AC240-WH-10VDIM-EM-A130 X B155 MM	15W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1800LM	A130 X B155 MM	
131	MAZDA-SXR191515W-2.7K-AC240-WH-ND-A130 X B155 MM	15W	2700	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1800LM	A130 X B155 MM	
132	MAZDA-SXR191515W-2.7K-AC240-WH-ND-EM-A130 X B155 MM	15W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1800LM	A130 X B155 MM	
133	MAZDA-SXR191515W-2.7K-AC240-WH-DA-A130 X B155 MM	15W	2700	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1800LM	A130 X B155 MM	
134	MAZDA-SXR191515W-2.7K-AC240-WH-DA-EM-A130 X B155 MM	15W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1800LM	A130 X B155 MM	
135	MAZDA-SXR191515W-2.7K-AC240-WH-PH-A130 X B155 MM	15W	2700	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1800LM	A130 X B155 MM	
136	MAZDA-SXR191515W-2.7K-AC240-WH-PH-EM-A130 X B155 MM	15W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1800LM	A130 X B155 MM	
137	MAZDA-SXR191515W-6.5K-AC240-WH-10VDIM-A130 X B155 MM	15W	6500	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1800LM	A130 X B155 MM	
138	MAZDA-SXR191515W-6.5K-AC240-WH-10VDIM-EM-A130 X B155 MM	15W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1800LM	A130 X B155 MM	
139	MAZDA-SXR191515W-6.5K-AC240-WH-ND-A130 X B155 MM	15W	6500	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1800LM	A130 X B155 MM	
140	MAZDA-SXR191515W-6.5K-AC240-WH-ND-EM-A130 X B155 MM	15W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1800LM	A130 X B155 MM	
141	MAZDA-SXR191515W-6.5K-AC240-WH-DA-A130 X B155 MM	15W	6500	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1800LM	A130 X B155 MM	
142	MAZDA-SXR191515W-6.5K-AC240-WH-DA-EM-A130 X B155 MM	15W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1800LM	A130 X B155 MM	
143	MAZDA-SXR191515W-6.5K-AC240-WH-PH-A130 X B155 MM	15W	6500	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1800LM	A130 X B155 MM	
144	MAZDA-SXR191515W-6.5K-AC240-WH-PH-EM-A130 X B155 MM	15W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	1800LM	A130 X B155 MM	
145	MAZDA-SXR191530W-3K-AC240-WH-10VDIM-A130 X B155 MM	30W	3000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	3600LM	A130 X B155 MM	
146	MAZDA-SXR191530W-3K-AC240-WH-10VDIM-EM-A130 X B155 MM	30W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	3600LM	A130 X B155 MM	
147	MAZDA-SXR191530W-3K-AC240-WH-ND-A130 X B155 MM	30W	3000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	3600LM	A130 X B155 MM	
148	MAZDA-SXR191530W-3K-AC240-WH-ND-EM-A130 X B155 MM	30W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	3600LM	A130 X B155 MM	
149	MAZDA-SXR191530W-3K-AC240-WH-DA-A130 X B155 MM	30W	3000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	3600LM	A130 X B155 MM	
150	MAZDA-SXR191530W-3K-AC240-WH-DA-EM-A130 X B155 MM	30W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	3600LM	A130 X B155 MM	
151	MAZDA-SXR191530W-3K-AC240-WH-PH-A130 X B155 MM	30W	3000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	3600LM	A130 X B155 MM	
152	MAZDA-SXR191530W-3K-AC240-WH-PH-EM-A130 X B155 MM	30W	3000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	3600LM	A130 X B155 MM	
153	MAZDA-SXR191530W-4K-AC240-WH-10VDIM-A130 X B155 MM	30W	4000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	3600LM	A130 X B155 MM	
154	MAZDA-SXR191530W-4K-AC240-WH-10VDIM-EM-A130 X B155 MM	30W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	3600LM	A130 X B155 MM	
155	MAZDA-SXR191530W-4K-AC240-WH-ND-A130 X B155 MM	30W	4000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	3600LM	A130 X B155 MM	
156	MAZDA-SXR191530W-4K-AC240-WH-ND-EM-A130 X B155 MM	30W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	3600LM	A130 X B155 MM	
157	MAZDA-SXR191530W-4K-AC240-WH-DA-A130 X B155 MM	30W	4000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	3600LM	A130 X B155 MM	



DATASHEET

GENERATED ON: 01 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
158	MAZDA-SXR191530W-4K-AC240-WH-DA-EM-A130 X B155 MM	30W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	3600LM	A130 X B155 MM	
159	MAZDA-SXR191530W-4K-AC240-WH-PH-A130 X B155 MM	30W	4000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	3600LM	A130 X B155 MM	
160	MAZDA-SXR191530W-4K-AC240-WH-PH-EM-A130 X B155 MM	30W	4000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	3600LM	A130 X B155 MM	
161	MAZDA-SXR191530W-5K-AC240-WH-10VDIM-A130 X B155 MM	30W	5000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	3600LM	A130 X B155 MM	
162	MAZDA-SXR191530W-5K-AC240-WH-10VDIM-EM-A130 X B155 MM	30W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	3600LM	A130 X B155 MM	
163	MAZDA-SXR191530W-5K-AC240-WH-ND-A130 X B155 MM	30W	5000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	3600LM	A130 X B155 MM	
164	MAZDA-SXR191530W-5K-AC240-WH-ND-EM-A130 X B155 MM	30W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	3600LM	A130 X B155 MM	
165	MAZDA-SXR191530W-5K-AC240-WH-DA-A130 X B155 MM	30W	5000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	3600LM	A130 X B155 MM	
166	MAZDA-SXR191530W-5K-AC240-WH-DA-EM-A130 X B155 MM	30W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	3600LM	A130 X B155 MM	
167	MAZDA-SXR191530W-5K-AC240-WH-PH-A130 X B155 MM	30W	5000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	3600LM	A130 X B155 MM	
168	MAZDA-SXR191530W-5K-AC240-WH-PH-EM-A130 X B155 MM	30W	5000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	3600LM	A130 X B155 MM	
169	MAZDA-SXR191530W-6K-AC240-WH-10VDIM-A130 X B155 MM	30W	6000	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	3600LM	A130 X B155 MM	
170	MAZDA-SXR191530W-6K-AC240-WH-10VDIM-EM-A130 X B155 MM	30W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	3600LM	A130 X B155 MM	
171	MAZDA-SXR191530W-6K-AC240-WH-ND-A130 X B155 MM	30W	6000	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	3600LM	A130 X B155 MM	
172	MAZDA-SXR191530W-6K-AC240-WH-ND-EM-A130 X B155 MM	30W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	3600LM	A130 X B155 MM	
173	MAZDA-SXR191530W-6K-AC240-WH-DA-A130 X B155 MM	30W	6000	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	3600LM	A130 X B155 MM	
174	MAZDA-SXR191530W-6K-AC240-WH-DA-EM-A130 X B155 MM	30W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	3600LM	A130 X B155 MM	
175	MAZDA-SXR191530W-6K-AC240-WH-PH-A130 X B155 MM	30W	6000	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	3600LM	A130 X B155 MM	
176	MAZDA-SXR191530W-6K-AC240-WH-PH-EM-A130 X B155 MM	30W	6000	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	3600LM	A130 X B155 MM	
177	MAZDA-SXR191530W-2.7K-AC240-WH-10VDIM-A130 X B155 MM	30W	2700	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	3600LM	A130 X B155 MM	
178	MAZDA-SXR191530W-2.7K-AC240-WH-10VDIM-EM-A130 X B155 MM	30W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	3600LM	A130 X B155 MM	
179	MAZDA-SXR191530W-2.7K-AC240-WH-ND-A130 X B155 MM	30W	2700	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	3600LM	A130 X B155 MM	
180	MAZDA-SXR191530W-2.7K-AC240-WH-ND-EM-A130 X B155 MM	30W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	3600LM	A130 X B155 MM	
181	MAZDA-SXR191530W-2.7K-AC240-WH-DA-A130 X B155 MM	30W	2700	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	3600LM	A130 X B155 MM	
182	MAZDA-SXR191530W-2.7K-AC240-WH-DA-EM-A130 X B155 MM	30W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	3600LM	A130 X B155 MM	
183	MAZDA-SXR191530W-2.7K-AC240-WH-PH-A130 X B155 MM	30W	2700	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	3600LM	A130 X B155 MM	
184	MAZDA-SXR191530W-2.7K-AC240-WH-PH-EM-A130 X B155 MM	30W	2700	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	3600LM	A130 X B155 MM	
185	MAZDA-SXR191530W-6.5K-AC240-WH-10VDIM-A130 X B155 MM	30W	6500	240VAC	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	3600LM	A130 X B155 MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angle	Dimension	Material	IP	lumen	Dimensions	Price
186	MAZDA-SXR191530W-6.5K-AC240-WH-10VDIM-EM-A130 X B155 MM	30W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	3600LM	A130 X B155 MM	
187	MAZDA-SXR191530W-6.5K-AC240-WH-ND-A130 X B155 MM	30W	6500	240VAC	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	3600LM	A130 X B155 MM	
188	MAZDA-SXR191530W-6.5K-AC240-WH-ND-EM-A130 X B155 MM	30W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	3600LM	A130 X B155 MM	
189	MAZDA-SXR191530W-6.5K-AC240-WH-DA-A130 X B155 MM	30W	6500	240VAC	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	3600LM	A130 X B155 MM	
190	MAZDA-SXR191530W-6.5K-AC240-WH-DA-EM-A130 X B155 MM	30W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	3600LM	A130 X B155 MM	
191	MAZDA-SXR191530W-6.5K-AC240-WH-PH-A130 X B155 MM	30W	6500	240VAC	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	3600LM	A130 X B155 MM	
192	MAZDA-SXR191530W-6.5K-AC240-WH-PH-EM-A130 X B155 MM	30W	6500	240VAC	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B155 MM	DIE CAST ALUMINUM	IP54	3600LM	A130 X B155 MM	