



LUCIAN

MAZDA Model: SIXR2923 External Wall Light

Lucian wall light with down light effect design. Adopt aluminum housing providing excellent thermal management. IP54 for outdoor use. The ideal application areas are pillars in open plan offices, rooms meeting, areas reception, stairwells and corridors

ALL AVAILABLE VARIANTS

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
1	MAZDA-SIXR292320W-3K-240V-BK-ND-A78 X B90MM	20W	3000	240V	BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
2	MAZDA-SIXR292320W-3K-240V-WH-ND-A78 X B90MM	20W	3000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
3	MAZDA-SIXR292320W-3K-240V-BK-DA-A78 X B90MM	20W	3000	240V	BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
4	MAZDA-SIXR292320W-3K-240V-WH-DA-A78 X B90MM	20W	3000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
5	MAZDA-SIXR292320W-3K-240V-BK-PH-A78 X B90MM	20W	3000	240V	BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
6	MAZDA-SIXR292320W-3K-240V-WH-PH-A78 X B90MM	20W	3000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
7	MAZDA-SIXR292320W-3K-240V-BK-10VDIM-A78 X B90MM	20W	3000	240V	BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
8	MAZDA-SIXR292320W-3K-240V-WH-10VDIM-A78 X B90MM	20W	3000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
9	MAZDA-SIXR292320W-4K-240V-BK-ND-A78 X B90MM	20W	4000	240V	BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
10	MAZDA-SIXR292320W-4K-240V-WH-ND-A78 X B90MM	20W	4000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
11	MAZDA-SIXR292320W-4K-240V-BK-DA-A78 X B90MM	20W	4000	240V	BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
12	MAZDA-SIXR292320W-4K-240V-WH-DA-A78 X B90MM	20W	4000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
13	MAZDA-SIXR292320W-4K-240V-BK-PH-A78 X B90MM	20W	4000	240V	BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
14	MAZDA-SIXR292320W-4K-240V-WH-PH-A78 X B90MM	20W	4000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
15	MAZDA-SIXR292320W-4K-240V-BK-10VDIM-A78 X B90MM	20W	4000	240V	BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	



DATASHEET

GENERATED ON: 03 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angle	Dimension	Material	IP	Dimensions	Price
16	MAZDA-SIXR292320W-4K-240V-WH-10VDIM-A78 X B90MM	20W	4000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
17	MAZDA-SIXR292320W-5K-240V-BK-ND-A78 X B90MM	20W	5000	240V	BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
18	MAZDA-SIXR292320W-5K-240V-WH-ND-A78 X B90MM	20W	5000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
19	MAZDA-SIXR292320W-5K-240V-BK-DA-A78 X B90MM	20W	5000	240V	BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
20	MAZDA-SIXR292320W-5K-240V-WH-DA-A78 X B90MM	20W	5000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
21	MAZDA-SIXR292320W-5K-240V-BK-PH-A78 X B90MM	20W	5000	240V	BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
22	MAZDA-SIXR292320W-5K-240V-WH-PH-A78 X B90MM	20W	5000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
23	MAZDA-SIXR292320W-5K-240V-BK-10VDIM-A78 X B90MM	20W	5000	240V	BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
24	MAZDA-SIXR292320W-5K-240V-WH-10VDIM-A78 X B90MM	20W	5000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
25	MAZDA-SIXR292320W-6K-240V-BK-ND-A78 X B90MM	20W	6000	240V	BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
26	MAZDA-SIXR292320W-6K-240V-WH-ND-A78 X B90MM	20W	6000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
27	MAZDA-SIXR292320W-6K-240V-BK-DA-A78 X B90MM	20W	6000	240V	BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
28	MAZDA-SIXR292320W-6K-240V-WH-DA-A78 X B90MM	20W	6000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
29	MAZDA-SIXR292320W-6K-240V-BK-PH-A78 X B90MM	20W	6000	240V	BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
30	MAZDA-SIXR292320W-6K-240V-WH-PH-A78 X B90MM	20W	6000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
31	MAZDA-SIXR292320W-6K-240V-BK-10VDIM-A78 X B90MM	20W	6000	240V	BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
32	MAZDA-SIXR292320W-6K-240V-WH-10VDIM-A78 X B90MM	20W	6000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
33	MAZDA-SIXR292320W-2.7K-240V-BK-ND-A78 X B90MM	20W	2700	240V	BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
34	MAZDA-SIXR292320W-2.7K-240V-WH-ND-A78 X B90MM	20W	2700	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
35	MAZDA-SIXR292320W-2.7K-240V-BK-DA-A78 X B90MM	20W	2700	240V	BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
36	MAZDA-SIXR292320W-2.7K-240V-WH-DA-A78 X B90MM	20W	2700	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
37	MAZDA-SIXR292320W-2.7K-240V-BK-PH-A78 X B90MM	20W	2700	240V	BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
38	MAZDA-SIXR292320W-2.7K-240V-WH-PH-A78 X B90MM	20W	2700	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
39	MAZDA-SIXR292320W-2.7K-240V-BK-10VDIM-A78 X B90MM	20W	2700	240V	BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
40	MAZDA-SIXR292320W-2.7K-240V-WH-10VDIM-A78 X B90MM	20W	2700	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	



DATASHEET

GENERATED ON: 03 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angle	Dimension	Material	IP	Dimensions	Price
41	MAZDA-SIXR292320W-6.5K-240V-BK-ND-A78 X B90MM	20W	6500	240V	BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
42	MAZDA-SIXR292320W-6.5K-240V-WH-ND-A78 X B90MM	20W	6500	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
43	MAZDA-SIXR292320W-6.5K-240V-BK-DA-A78 X B90MM	20W	6500	240V	BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
44	MAZDA-SIXR292320W-6.5K-240V-WH-DA-A78 X B90MM	20W	6500	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
45	MAZDA-SIXR292320W-6.5K-240V-BK-PH-A78 X B90MM	20W	6500	240V	BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
46	MAZDA-SIXR292320W-6.5K-240V-WH-PH-A78 X B90MM	20W	6500	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
47	MAZDA-SIXR292320W-6.5K-240V-BK-10VDIM-A78 X B90MM	20W	6500	240V	BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
48	MAZDA-SIXR292320W-6.5K-240V-WH-10VDIM-A78 X B90MM	20W	6500	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
49	MAZDA-SIXR292310W-3K-240V-BK-ND-A78 X B90MM	10W	3000	240V	BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
50	MAZDA-SIXR292310W-3K-240V-WH-ND-A78 X B90MM	10W	3000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
51	MAZDA-SIXR292310W-3K-240V-BK-DA-A78 X B90MM	10W	3000	240V	BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
52	MAZDA-SIXR292310W-3K-240V-WH-DA-A78 X B90MM	10W	3000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
53	MAZDA-SIXR292310W-3K-240V-BK-PH-A78 X B90MM	10W	3000	240V	BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
54	MAZDA-SIXR292310W-3K-240V-WH-PH-A78 X B90MM	10W	3000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
55	MAZDA-SIXR292310W-3K-240V-BK-10VDIM-A78 X B90MM	10W	3000	240V	BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
56	MAZDA-SIXR292310W-3K-240V-WH-10VDIM-A78 X B90MM	10W	3000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
57	MAZDA-SIXR292310W-4K-240V-BK-ND-A78 X B90MM	10W	4000	240V	BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
58	MAZDA-SIXR292310W-4K-240V-WH-ND-A78 X B90MM	10W	4000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
59	MAZDA-SIXR292310W-4K-240V-BK-DA-A78 X B90MM	10W	4000	240V	BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
60	MAZDA-SIXR292310W-4K-240V-WH-DA-A78 X B90MM	10W	4000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
61	MAZDA-SIXR292310W-4K-240V-BK-PH-A78 X B90MM	10W	4000	240V	BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
62	MAZDA-SIXR292310W-4K-240V-WH-PH-A78 X B90MM	10W	4000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
63	MAZDA-SIXR292310W-4K-240V-BK-10VDIM-A78 X B90MM	10W	4000	240V	BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
64	MAZDA-SIXR292310W-4K-240V-WH-10VDIM-A78 X B90MM	10W	4000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
65	MAZDA-SIXR292310W-5K-240V-BK-ND-A78 X B90MM	10W	5000	240V	BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	



DATASHEET

GENERATED ON: 03 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angle	Dimension	Material	IP	Dimensions	Price
66	MAZDA-SIXR292310W-5K-240V-WH-ND-A78 X B90MM	10W	5000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
67	MAZDA-SIXR292310W-5K-240V-BK-DA-A78 X B90MM	10W	5000	240V	BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
68	MAZDA-SIXR292310W-5K-240V-WH-DA-A78 X B90MM	10W	5000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
69	MAZDA-SIXR292310W-5K-240V-BK-PH-A78 X B90MM	10W	5000	240V	BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
70	MAZDA-SIXR292310W-5K-240V-WH-PH-A78 X B90MM	10W	5000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
71	MAZDA-SIXR292310W-5K-240V-BK-10VDIM-A78 X B90MM	10W	5000	240V	BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
72	MAZDA-SIXR292310W-5K-240V-WH-10VDIM-A78 X B90MM	10W	5000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
73	MAZDA-SIXR292310W-6K-240V-BK-ND-A78 X B90MM	10W	6000	240V	BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
74	MAZDA-SIXR292310W-6K-240V-WH-ND-A78 X B90MM	10W	6000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
75	MAZDA-SIXR292310W-6K-240V-BK-DA-A78 X B90MM	10W	6000	240V	BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
76	MAZDA-SIXR292310W-6K-240V-WH-DA-A78 X B90MM	10W	6000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
77	MAZDA-SIXR292310W-6K-240V-BK-PH-A78 X B90MM	10W	6000	240V	BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
78	MAZDA-SIXR292310W-6K-240V-WH-PH-A78 X B90MM	10W	6000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
79	MAZDA-SIXR292310W-6K-240V-BK-10VDIM-A78 X B90MM	10W	6000	240V	BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
80	MAZDA-SIXR292310W-6K-240V-WH-10VDIM-A78 X B90MM	10W	6000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
81	MAZDA-SIXR292310W-2.7K-240V-BK-ND-A78 X B90MM	10W	2700	240V	BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
82	MAZDA-SIXR292310W-2.7K-240V-WH-ND-A78 X B90MM	10W	2700	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
83	MAZDA-SIXR292310W-2.7K-240V-BK-DA-A78 X B90MM	10W	2700	240V	BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
84	MAZDA-SIXR292310W-2.7K-240V-WH-DA-A78 X B90MM	10W	2700	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
85	MAZDA-SIXR292310W-2.7K-240V-BK-PH-A78 X B90MM	10W	2700	240V	BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
86	MAZDA-SIXR292310W-2.7K-240V-WH-PH-A78 X B90MM	10W	2700	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
87	MAZDA-SIXR292310W-2.7K-240V-BK-10VDIM-A78 X B90MM	10W	2700	240V	BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
88	MAZDA-SIXR292310W-2.7K-240V-WH-10VDIM-A78 X B90MM	10W	2700	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
89	MAZDA-SIXR292310W-6.5K-240V-BK-ND-A78 X B90MM	10W	6500	240V	BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
90	MAZDA-SIXR292310W-6.5K-240V-WH-ND-A78 X B90MM	10W	6500	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
91	MAZDA-SIXR292310W-6.5K-240V-BK-DA-A78 X B90MM	10W	6500	240V	BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
92	MAZDA-SIXR292310W-6.5K-240V-WH-DA-A78 X B90MM	10W	6500	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
93	MAZDA-SIXR292310W-6.5K-240V-BK-PH-A78 X B90MM	10W	6500	240V	BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
94	MAZDA-SIXR292310W-6.5K-240V-WH-PH-A78 X B90MM	10W	6500	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
95	MAZDA-SIXR292310W-6.5K-240V-BK-10VDIM-A78 X B90MM	10W	6500	240V	BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	
96	MAZDA-SIXR292310W-6.5K-240V-WH-10VDIM-A78 X B90MM	10W	6500	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A78 X B90MM	DIE CAST ALUMINUM	IP54	A78 X B90MM	