



POON

MAZDA Model: WSXR3725 External Wall Light

Poon highly efficient LED system provides excellent result in luminous flux, light brightness, light uniformity and light pleasantness. Available in up or up and down light option. Poon LED wall light looks fabulous at the entrance to any modern home, with its light that can optionally be used either side of a door way for a beautiful framing effect.

ALL AVAILABLE VARIANTS

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
1	MAZDA-WSXR37252X5W-3K-240V-BL-ND-A65 X B215 X C118MM	2X5W	3000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A65 X B215 X C118MM	DIE CAST ALUMINUM	IK10	A65 X B215 X C118MM	
2	MAZDA-WSXR37252X5W-3K-240V-BL-DA-A65 X B215 X C118MM	2X5W	3000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A65 X B215 X C118MM	DIE CAST ALUMINUM	IK10	A65 X B215 X C118MM	
3	MAZDA-WSXR37252X5W-3K-240V-BL-PH-A65 X B215 X C118MM	2X5W	3000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A65 X B215 X C118MM	DIE CAST ALUMINUM	IK10	A65 X B215 X C118MM	
4	MAZDA-WSXR37252X5W-3K-240V-BL-10VDIM-A65 X B215 X C118MM	2X5W	3000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A65 X B215 X C118MM	DIE CAST ALUMINUM	IK10	A65 X B215 X C118MM	
5	MAZDA-WSXR37252X5W-4K-240V-BL-ND-A65 X B215 X C118MM	2X5W	4000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A65 X B215 X C118MM	DIE CAST ALUMINUM	IK10	A65 X B215 X C118MM	
6	MAZDA-WSXR37252X5W-4K-240V-BL-DA-A65 X B215 X C118MM	2X5W	4000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A65 X B215 X C118MM	DIE CAST ALUMINUM	IK10	A65 X B215 X C118MM	
7	MAZDA-WSXR37252X5W-4K-240V-BL-PH-A65 X B215 X C118MM	2X5W	4000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A65 X B215 X C118MM	DIE CAST ALUMINUM	IK10	A65 X B215 X C118MM	
8	MAZDA-WSXR37252X5W-4K-240V-BL-10VDIM-A65 X B215 X C118MM	2X5W	4000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A65 X B215 X C118MM	DIE CAST ALUMINUM	IK10	A65 X B215 X C118MM	
9	MAZDA-WSXR37252X5W-5K-240V-BL-ND-A65 X B215 X C118MM	2X5W	5000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A65 X B215 X C118MM	DIE CAST ALUMINUM	IK10	A65 X B215 X C118MM	
10	MAZDA-WSXR37252X5W-5K-240V-BL-DA-A65 X B215 X C118MM	2X5W	5000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A65 X B215 X C118MM	DIE CAST ALUMINUM	IK10	A65 X B215 X C118MM	
11	MAZDA-WSXR37252X5W-5K-240V-BL-PH-A65 X B215 X C118MM	2X5W	5000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A65 X B215 X C118MM	DIE CAST ALUMINUM	IK10	A65 X B215 X C118MM	
12	MAZDA-WSXR37252X5W-5K-240V-BL-10VDIM-A65 X B215 X C118MM	2X5W	5000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A65 X B215 X C118MM	DIE CAST ALUMINUM	IK10	A65 X B215 X C118MM	
13	MAZDA-WSXR37252X5W-6K-240V-BL-ND-A65 X B215 X C118MM	2X5W	6000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A65 X B215 X C118MM	DIE CAST ALUMINUM	IK10	A65 X B215 X C118MM	
14	MAZDA-WSXR37252X5W-6K-240V-BL-DA-A65 X B215 X C118MM	2X5W	6000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A65 X B215 X C118MM	DIE CAST ALUMINUM	IK10	A65 X B215 X C118MM	
15	MAZDA-WSXR37252X5W-6K-240V-BL-PH-A65 X B215 X C118MM	2X5W	6000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A65 X B215 X C118MM	DIE CAST ALUMINUM	IK10	A65 X B215 X C118MM	
16	MAZDA-WSXR37252X5W-6K-240V-BL-10VDIM-A65 X B215 X C118MM	2X5W	6000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A65 X B215 X C118MM	DIE CAST ALUMINUM	IK10	A65 X B215 X C118MM	
17	MAZDA-WSXR37252X5W-2.7K-240V-BL-ND-A65 X B215 X C118MM	2X5W	2700	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A65 X B215 X C118MM	DIE CAST ALUMINUM	IK10	A65 X B215 X C118MM	



DATASHEET

GENERATED ON: 02 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
18	MAZDA-WSXR37252X5W-2.7K-240V-BL-DA-A65 X B215 X C118MM	2X5W	2700	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A65 X B215 X C118MM	DIE CAST ALUMINUM	IK10	A65 X B215 X C118MM	
19	MAZDA-WSXR37252X5W-2.7K-240V-BL-PH-A65 X B215 X C118MM	2X5W	2700	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A65 X B215 X C118MM	DIE CAST ALUMINUM	IK10	A65 X B215 X C118MM	
20	MAZDA-WSXR37252X5W-2.7K-240V-BL-10VDIM-A65 X B215 X C118MM	2X5W	2700	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A65 X B215 X C118MM	DIE CAST ALUMINUM	IK10	A65 X B215 X C118MM	
21	MAZDA-WSXR37252X5W-6.5K-240V-BL-ND-A65 X B215 X C118MM	2X5W	6500	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A65 X B215 X C118MM	DIE CAST ALUMINUM	IK10	A65 X B215 X C118MM	
22	MAZDA-WSXR37252X5W-6.5K-240V-BL-DA-A65 X B215 X C118MM	2X5W	6500	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A65 X B215 X C118MM	DIE CAST ALUMINUM	IK10	A65 X B215 X C118MM	
23	MAZDA-WSXR37252X5W-6.5K-240V-BL-PH-A65 X B215 X C118MM	2X5W	6500	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A65 X B215 X C118MM	DIE CAST ALUMINUM	IK10	A65 X B215 X C118MM	
24	MAZDA-WSXR37252X5W-6.5K-240V-BL-10VDIM-A65 X B215 X C118MM	2X5W	6500	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A65 X B215 X C118MM	DIE CAST ALUMINUM	IK10	A65 X B215 X C118MM	
25	MAZDA-WSXR37252X10W-3K-240V-BL-ND-A90 X B310 X C155MM	2X10W	3000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A90 X B310 X C155MM	DIE CAST ALUMINUM	IK10	A90 X B310 X C155MM	
26	MAZDA-WSXR37252X10W-3K-240V-BL-DA-A90 X B310 X C155MM	2X10W	3000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A90 X B310 X C155MM	DIE CAST ALUMINUM	IK10	A90 X B310 X C155MM	
27	MAZDA-WSXR37252X10W-3K-240V-BL-PH-A90 X B310 X C155MM	2X10W	3000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A90 X B310 X C155MM	DIE CAST ALUMINUM	IK10	A90 X B310 X C155MM	
28	MAZDA-WSXR37252X10W-3K-240V-BL-10VDIM-A90 X B310 X C155MM	2X10W	3000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A90 X B310 X C155MM	DIE CAST ALUMINUM	IK10	A90 X B310 X C155MM	
29	MAZDA-WSXR37252X10W-4K-240V-BL-ND-A90 X B310 X C155MM	2X10W	4000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A90 X B310 X C155MM	DIE CAST ALUMINUM	IK10	A90 X B310 X C155MM	
30	MAZDA-WSXR37252X10W-4K-240V-BL-DA-A90 X B310 X C155MM	2X10W	4000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A90 X B310 X C155MM	DIE CAST ALUMINUM	IK10	A90 X B310 X C155MM	
31	MAZDA-WSXR37252X10W-4K-240V-BL-PH-A90 X B310 X C155MM	2X10W	4000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A90 X B310 X C155MM	DIE CAST ALUMINUM	IK10	A90 X B310 X C155MM	
32	MAZDA-WSXR37252X10W-4K-240V-BL-10VDIM-A90 X B310 X C155MM	2X10W	4000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A90 X B310 X C155MM	DIE CAST ALUMINUM	IK10	A90 X B310 X C155MM	
33	MAZDA-WSXR37252X10W-5K-240V-BL-ND-A90 X B310 X C155MM	2X10W	5000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A90 X B310 X C155MM	DIE CAST ALUMINUM	IK10	A90 X B310 X C155MM	
34	MAZDA-WSXR37252X10W-5K-240V-BL-DA-A90 X B310 X C155MM	2X10W	5000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A90 X B310 X C155MM	DIE CAST ALUMINUM	IK10	A90 X B310 X C155MM	
35	MAZDA-WSXR37252X10W-5K-240V-BL-PH-A90 X B310 X C155MM	2X10W	5000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A90 X B310 X C155MM	DIE CAST ALUMINUM	IK10	A90 X B310 X C155MM	
36	MAZDA-WSXR37252X10W-5K-240V-BL-10VDIM-A90 X B310 X C155MM	2X10W	5000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A90 X B310 X C155MM	DIE CAST ALUMINUM	IK10	A90 X B310 X C155MM	
37	MAZDA-WSXR37252X10W-6K-240V-BL-ND-A90 X B310 X C155MM	2X10W	6000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A90 X B310 X C155MM	DIE CAST ALUMINUM	IK10	A90 X B310 X C155MM	
38	MAZDA-WSXR37252X10W-6K-240V-BL-DA-A90 X B310 X C155MM	2X10W	6000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A90 X B310 X C155MM	DIE CAST ALUMINUM	IK10	A90 X B310 X C155MM	
39	MAZDA-WSXR37252X10W-6K-240V-BL-PH-A90 X B310 X C155MM	2X10W	6000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A90 X B310 X C155MM	DIE CAST ALUMINUM	IK10	A90 X B310 X C155MM	
40	MAZDA-WSXR37252X10W-6K-240V-BL-10VDIM-A90 X B310 X C155MM	2X10W	6000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A90 X B310 X C155MM	DIE CAST ALUMINUM	IK10	A90 X B310 X C155MM	
41	MAZDA-WSXR37252X10W-2.7K-240V-BL-ND-A90 X B310 X C155MM	2X10W	2700	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A90 X B310 X C155MM	DIE CAST ALUMINUM	IK10	A90 X B310 X C155MM	
42	MAZDA-WSXR37252X10W-2.7K-240V-BL-DA-A90 X B310 X C155MM	2X10W	2700	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A90 X B310 X C155MM	DIE CAST ALUMINUM	IK10	A90 X B310 X C155MM	
43	MAZDA-WSXR37252X10W-2.7K-240V-BL-PH-A90 X B310 X C155MM	2X10W	2700	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A90 X B310 X C155MM	DIE CAST ALUMINUM	IK10	A90 X B310 X C155MM	
44	MAZDA-WSXR37252X10W-2.7K-240V-BL-10VDIM-A90 X B310 X C155MM	2X10W	2700	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A90 X B310 X C155MM	DIE CAST ALUMINUM	IK10	A90 X B310 X C155MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
45	MAZDA-WSXR37252X10W-6.5K-240V-BL-ND-A90 X B310 X C155MM	2X10W	6500	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A90 X B310 X C155MM	DIE CAST ALUMINUM	IK10	A90 X B310 X C155MM	
46	MAZDA-WSXR37252X10W-6.5K-240V-BL-DA-A90 X B310 X C155MM	2X10W	6500	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A90 X B310 X C155MM	DIE CAST ALUMINUM	IK10	A90 X B310 X C155MM	
47	MAZDA-WSXR37252X10W-6.5K-240V-BL-PH-A90 X B310 X C155MM	2X10W	6500	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A90 X B310 X C155MM	DIE CAST ALUMINUM	IK10	A90 X B310 X C155MM	
48	MAZDA-WSXR37252X10W-6.5K-240V-BL-10VDIM-A90 X B310 X C155MM	2X10W	6500	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A90 X B310 X C155MM	DIE CAST ALUMINUM	IK10	A90 X B310 X C155MM	