



RAY

MAZDA Model: WSXR3752 External Wall Light

Ray stylishly clean wall luminaire giving attractive up and down light. Ray wall surface light with up and down light effect design. Adopt 6063 aluminum housing providing excellent thermal management. IP65 waterproof for outdoor use with out-Loop and in-Loop function.

ALL AVAILABLE VARIANTS

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
1	MAZDA-WSXR37522X5W-3K-240V-WH-ND-A170 X B60 X C105 MM	2X5W	3000	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A170 X B60 X C105 MM	DIE CAST ALUMINUM	IK10	A170 X B60 X C105 MM	
2	MAZDA-WSXR37522X5W-3K-240V-WH-DA-A170 X B60 X C105 MM	2X5W	3000	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A170 X B60 X C105 MM	DIE CAST ALUMINUM	IK10	A170 X B60 X C105 MM	
3	MAZDA-WSXR37522X5W-3K-240V-WH-PH-A170 X B60 X C105 MM	2X5W	3000	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A170 X B60 X C105 MM	DIE CAST ALUMINUM	IK10	A170 X B60 X C105 MM	
4	MAZDA-WSXR37522X5W-3K-240V-WH-10VDIM-A170 X B60 X C105 MM	2X5W	3000	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A170 X B60 X C105 MM	DIE CAST ALUMINUM	IK10	A170 X B60 X C105 MM	
5	MAZDA-WSXR37522X5W-4K-240V-WH-ND-A170 X B60 X C105 MM	2X5W	4000	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A170 X B60 X C105 MM	DIE CAST ALUMINUM	IK10	A170 X B60 X C105 MM	
6	MAZDA-WSXR37522X5W-4K-240V-WH-DA-A170 X B60 X C105 MM	2X5W	4000	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A170 X B60 X C105 MM	DIE CAST ALUMINUM	IK10	A170 X B60 X C105 MM	
7	MAZDA-WSXR37522X5W-4K-240V-WH-PH-A170 X B60 X C105 MM	2X5W	4000	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A170 X B60 X C105 MM	DIE CAST ALUMINUM	IK10	A170 X B60 X C105 MM	
8	MAZDA-WSXR37522X5W-4K-240V-WH-10VDIM-A170 X B60 X C105 MM	2X5W	4000	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A170 X B60 X C105 MM	DIE CAST ALUMINUM	IK10	A170 X B60 X C105 MM	
9	MAZDA-WSXR37522X5W-5K-240V-WH-ND-A170 X B60 X C105 MM	2X5W	5000	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A170 X B60 X C105 MM	DIE CAST ALUMINUM	IK10	A170 X B60 X C105 MM	
10	MAZDA-WSXR37522X5W-5K-240V-WH-DA-A170 X B60 X C105 MM	2X5W	5000	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A170 X B60 X C105 MM	DIE CAST ALUMINUM	IK10	A170 X B60 X C105 MM	
11	MAZDA-WSXR37522X5W-5K-240V-WH-PH-A170 X B60 X C105 MM	2X5W	5000	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A170 X B60 X C105 MM	DIE CAST ALUMINUM	IK10	A170 X B60 X C105 MM	
12	MAZDA-WSXR37522X5W-5K-240V-WH-10VDIM-A170 X B60 X C105 MM	2X5W	5000	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A170 X B60 X C105 MM	DIE CAST ALUMINUM	IK10	A170 X B60 X C105 MM	
13	MAZDA-WSXR37522X5W-6K-240V-WH-ND-A170 X B60 X C105 MM	2X5W	6000	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A170 X B60 X C105 MM	DIE CAST ALUMINUM	IK10	A170 X B60 X C105 MM	
14	MAZDA-WSXR37522X5W-6K-240V-WH-DA-A170 X B60 X C105 MM	2X5W	6000	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A170 X B60 X C105 MM	DIE CAST ALUMINUM	IK10	A170 X B60 X C105 MM	
15	MAZDA-WSXR37522X5W-6K-240V-WH-PH-A170 X B60 X C105 MM	2X5W	6000	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A170 X B60 X C105 MM	DIE CAST ALUMINUM	IK10	A170 X B60 X C105 MM	
16	MAZDA-WSXR37522X5W-6K-240V-WH-10VDIM-A170 X B60 X C105 MM	2X5W	6000	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A170 X B60 X C105 MM	DIE CAST ALUMINUM	IK10	A170 X B60 X C105 MM	
17	MAZDA-WSXR37522X5W-2.7K-240V-WH-ND-A170 X B60 X C105 MM	2X5W	2700	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A170 X B60 X C105 MM	DIE CAST ALUMINUM	IK10	A170 X B60 X C105 MM	



DATASHEET

GENERATED ON: 02 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
18	MAZDA-WSXR37522X5W-2.7K-240V-WH-DA-A170 X B60 X C105 MM	2X5W	2700	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A170 X B60 X C105 MM	DIE CAST ALUMINUM	IK10	A170 X B60 X C105 MM	
19	MAZDA-WSXR37522X5W-2.7K-240V-WH-PH-A170 X B60 X C105 MM	2X5W	2700	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A170 X B60 X C105 MM	DIE CAST ALUMINUM	IK10	A170 X B60 X C105 MM	
20	MAZDA-WSXR37522X5W-2.7K-240V-WH-10VDIM-A170 X B60 X C105 MM	2X5W	2700	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A170 X B60 X C105 MM	DIE CAST ALUMINUM	IK10	A170 X B60 X C105 MM	
21	MAZDA-WSXR37522X5W-6.5K-240V-WH-ND-A170 X B60 X C105 MM	2X5W	6500	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A170 X B60 X C105 MM	DIE CAST ALUMINUM	IK10	A170 X B60 X C105 MM	
22	MAZDA-WSXR37522X5W-6.5K-240V-WH-DA-A170 X B60 X C105 MM	2X5W	6500	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A170 X B60 X C105 MM	DIE CAST ALUMINUM	IK10	A170 X B60 X C105 MM	
23	MAZDA-WSXR37522X5W-6.5K-240V-WH-PH-A170 X B60 X C105 MM	2X5W	6500	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A170 X B60 X C105 MM	DIE CAST ALUMINUM	IK10	A170 X B60 X C105 MM	
24	MAZDA-WSXR37522X5W-6.5K-240V-WH-10VDIM-A170 X B60 X C105 MM	2X5W	6500	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A170 X B60 X C105 MM	DIE CAST ALUMINUM	IK10	A170 X B60 X C105 MM	
25	MAZDA-WSXR37522X10W-3K-240V-WH-ND-A200 X B76 X C121 MM	2X10W	3000	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A200 X B76 X C121 MM	DIE CAST ALUMINUM	IK10	A200 X B76 X C121 MM	
26	MAZDA-WSXR37522X10W-3K-240V-WH-DA-A200 X B76 X C121 MM	2X10W	3000	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A200 X B76 X C121 MM	DIE CAST ALUMINUM	IK10	A200 X B76 X C121 MM	
27	MAZDA-WSXR37522X10W-3K-240V-WH-PH-A200 X B76 X C121 MM	2X10W	3000	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A200 X B76 X C121 MM	DIE CAST ALUMINUM	IK10	A200 X B76 X C121 MM	
28	MAZDA-WSXR37522X10W-3K-240V-WH-10VDIM-A200 X B76 X C121 MM	2X10W	3000	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A200 X B76 X C121 MM	DIE CAST ALUMINUM	IK10	A200 X B76 X C121 MM	
29	MAZDA-WSXR37522X10W-4K-240V-WH-ND-A200 X B76 X C121 MM	2X10W	4000	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A200 X B76 X C121 MM	DIE CAST ALUMINUM	IK10	A200 X B76 X C121 MM	
30	MAZDA-WSXR37522X10W-4K-240V-WH-DA-A200 X B76 X C121 MM	2X10W	4000	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A200 X B76 X C121 MM	DIE CAST ALUMINUM	IK10	A200 X B76 X C121 MM	
31	MAZDA-WSXR37522X10W-4K-240V-WH-PH-A200 X B76 X C121 MM	2X10W	4000	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A200 X B76 X C121 MM	DIE CAST ALUMINUM	IK10	A200 X B76 X C121 MM	
32	MAZDA-WSXR37522X10W-4K-240V-WH-10VDIM-A200 X B76 X C121 MM	2X10W	4000	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A200 X B76 X C121 MM	DIE CAST ALUMINUM	IK10	A200 X B76 X C121 MM	
33	MAZDA-WSXR37522X10W-5K-240V-WH-ND-A200 X B76 X C121 MM	2X10W	5000	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A200 X B76 X C121 MM	DIE CAST ALUMINUM	IK10	A200 X B76 X C121 MM	
34	MAZDA-WSXR37522X10W-5K-240V-WH-DA-A200 X B76 X C121 MM	2X10W	5000	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A200 X B76 X C121 MM	DIE CAST ALUMINUM	IK10	A200 X B76 X C121 MM	
35	MAZDA-WSXR37522X10W-5K-240V-WH-PH-A200 X B76 X C121 MM	2X10W	5000	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A200 X B76 X C121 MM	DIE CAST ALUMINUM	IK10	A200 X B76 X C121 MM	
36	MAZDA-WSXR37522X10W-5K-240V-WH-10VDIM-A200 X B76 X C121 MM	2X10W	5000	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A200 X B76 X C121 MM	DIE CAST ALUMINUM	IK10	A200 X B76 X C121 MM	
37	MAZDA-WSXR37522X10W-6K-240V-WH-ND-A200 X B76 X C121 MM	2X10W	6000	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A200 X B76 X C121 MM	DIE CAST ALUMINUM	IK10	A200 X B76 X C121 MM	
38	MAZDA-WSXR37522X10W-6K-240V-WH-DA-A200 X B76 X C121 MM	2X10W	6000	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A200 X B76 X C121 MM	DIE CAST ALUMINUM	IK10	A200 X B76 X C121 MM	
39	MAZDA-WSXR37522X10W-6K-240V-WH-PH-A200 X B76 X C121 MM	2X10W	6000	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A200 X B76 X C121 MM	DIE CAST ALUMINUM	IK10	A200 X B76 X C121 MM	
40	MAZDA-WSXR37522X10W-6K-240V-WH-10VDIM-A200 X B76 X C121 MM	2X10W	6000	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A200 X B76 X C121 MM	DIE CAST ALUMINUM	IK10	A200 X B76 X C121 MM	
41	MAZDA-WSXR37522X10W-2.7K-240V-WH-ND-A200 X B76 X C121 MM	2X10W	2700	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A200 X B76 X C121 MM	DIE CAST ALUMINUM	IK10	A200 X B76 X C121 MM	
42	MAZDA-WSXR37522X10W-2.7K-240V-WH-DA-A200 X B76 X C121 MM	2X10W	2700	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A200 X B76 X C121 MM	DIE CAST ALUMINUM	IK10	A200 X B76 X C121 MM	
43	MAZDA-WSXR37522X10W-2.7K-240V-WH-PH-A200 X B76 X C121 MM	2X10W	2700	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A200 X B76 X C121 MM	DIE CAST ALUMINUM	IK10	A200 X B76 X C121 MM	
44	MAZDA-WSXR37522X10W-2.7K-240V-WH-10VDIM-A200 X B76 X C121 MM	2X10W	2700	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A200 X B76 X C121 MM	DIE CAST ALUMINUM	IK10	A200 X B76 X C121 MM	
45	MAZDA-WSXR37522X10W-6.5K-240V-WH-ND-A200 X B76 X C121 MM	2X10W	6500	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A200 X B76 X C121 MM	DIE CAST ALUMINUM	IK10	A200 X B76 X C121 MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
46	MAZDA-WSXR37522X10W-6.5K-240V-WH-DA-A200 X B76 X C121 MM	2X10W	6500	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A200 X B76 X C121 MM	DIE CAST ALUMINUM	IK10	A200 X B76 X C121 MM	
47	MAZDA-WSXR37522X10W-6.5K-240V-WH-PH-A200 X B76 X C121 MM	2X10W	6500	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A200 X B76 X C121 MM	DIE CAST ALUMINUM	IK10	A200 X B76 X C121 MM	
48	MAZDA-WSXR37522X10W-6.5K-240V-WH-10VDIM-A200 X B76 X C121 MM	2X10W	6500	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A200 X B76 X C121 MM	DIE CAST ALUMINUM	IK10	A200 X B76 X C121 MM	
49	MAZDA-WSXR37522X15W-3K-240V-WH-ND-A230 X B100 X C145 MM	2X15W	3000	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A230 X B100 X C145 MM	DIE CAST ALUMINUM	IK10	A230 X B100 X C145 MM	
50	MAZDA-WSXR37522X15W-3K-240V-WH-DA-A230 X B100 X C145 MM	2X15W	3000	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A230 X B100 X C145 MM	DIE CAST ALUMINUM	IK10	A230 X B100 X C145 MM	
51	MAZDA-WSXR37522X15W-3K-240V-WH-PH-A230 X B100 X C145 MM	2X15W	3000	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A230 X B100 X C145 MM	DIE CAST ALUMINUM	IK10	A230 X B100 X C145 MM	
52	MAZDA-WSXR37522X15W-3K-240V-WH-10VDIM-A230 X B100 X C145 MM	2X15W	3000	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A230 X B100 X C145 MM	DIE CAST ALUMINUM	IK10	A230 X B100 X C145 MM	
53	MAZDA-WSXR37522X15W-4K-240V-WH-ND-A230 X B100 X C145 MM	2X15W	4000	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A230 X B100 X C145 MM	DIE CAST ALUMINUM	IK10	A230 X B100 X C145 MM	
54	MAZDA-WSXR37522X15W-4K-240V-WH-DA-A230 X B100 X C145 MM	2X15W	4000	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A230 X B100 X C145 MM	DIE CAST ALUMINUM	IK10	A230 X B100 X C145 MM	
55	MAZDA-WSXR37522X15W-4K-240V-WH-PH-A230 X B100 X C145 MM	2X15W	4000	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A230 X B100 X C145 MM	DIE CAST ALUMINUM	IK10	A230 X B100 X C145 MM	
56	MAZDA-WSXR37522X15W-4K-240V-WH-10VDIM-A230 X B100 X C145 MM	2X15W	4000	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A230 X B100 X C145 MM	DIE CAST ALUMINUM	IK10	A230 X B100 X C145 MM	
57	MAZDA-WSXR37522X15W-5K-240V-WH-ND-A230 X B100 X C145 MM	2X15W	5000	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A230 X B100 X C145 MM	DIE CAST ALUMINUM	IK10	A230 X B100 X C145 MM	
58	MAZDA-WSXR37522X15W-5K-240V-WH-DA-A230 X B100 X C145 MM	2X15W	5000	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A230 X B100 X C145 MM	DIE CAST ALUMINUM	IK10	A230 X B100 X C145 MM	
59	MAZDA-WSXR37522X15W-5K-240V-WH-PH-A230 X B100 X C145 MM	2X15W	5000	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A230 X B100 X C145 MM	DIE CAST ALUMINUM	IK10	A230 X B100 X C145 MM	
60	MAZDA-WSXR37522X15W-5K-240V-WH-10VDIM-A230 X B100 X C145 MM	2X15W	5000	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A230 X B100 X C145 MM	DIE CAST ALUMINUM	IK10	A230 X B100 X C145 MM	
61	MAZDA-WSXR37522X15W-6K-240V-WH-ND-A230 X B100 X C145 MM	2X15W	6000	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A230 X B100 X C145 MM	DIE CAST ALUMINUM	IK10	A230 X B100 X C145 MM	
62	MAZDA-WSXR37522X15W-6K-240V-WH-DA-A230 X B100 X C145 MM	2X15W	6000	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A230 X B100 X C145 MM	DIE CAST ALUMINUM	IK10	A230 X B100 X C145 MM	
63	MAZDA-WSXR37522X15W-6K-240V-WH-PH-A230 X B100 X C145 MM	2X15W	6000	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A230 X B100 X C145 MM	DIE CAST ALUMINUM	IK10	A230 X B100 X C145 MM	
64	MAZDA-WSXR37522X15W-6K-240V-WH-10VDIM-A230 X B100 X C145 MM	2X15W	6000	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A230 X B100 X C145 MM	DIE CAST ALUMINUM	IK10	A230 X B100 X C145 MM	
65	MAZDA-WSXR37522X15W-2.7K-240V-WH-ND-A230 X B100 X C145 MM	2X15W	2700	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A230 X B100 X C145 MM	DIE CAST ALUMINUM	IK10	A230 X B100 X C145 MM	
66	MAZDA-WSXR37522X15W-2.7K-240V-WH-DA-A230 X B100 X C145 MM	2X15W	2700	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A230 X B100 X C145 MM	DIE CAST ALUMINUM	IK10	A230 X B100 X C145 MM	
67	MAZDA-WSXR37522X15W-2.7K-240V-WH-PH-A230 X B100 X C145 MM	2X15W	2700	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A230 X B100 X C145 MM	DIE CAST ALUMINUM	IK10	A230 X B100 X C145 MM	
68	MAZDA-WSXR37522X15W-2.7K-240V-WH-10VDIM-A230 X B100 X C145 MM	2X15W	2700	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A230 X B100 X C145 MM	DIE CAST ALUMINUM	IK10	A230 X B100 X C145 MM	
69	MAZDA-WSXR37522X15W-6.5K-240V-WH-ND-A230 X B100 X C145 MM	2X15W	6500	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A230 X B100 X C145 MM	DIE CAST ALUMINUM	IK10	A230 X B100 X C145 MM	
70	MAZDA-WSXR37522X15W-6.5K-240V-WH-DA-A230 X B100 X C145 MM	2X15W	6500	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A230 X B100 X C145 MM	DIE CAST ALUMINUM	IK10	A230 X B100 X C145 MM	
71	MAZDA-WSXR37522X15W-6.5K-240V-WH-PH-A230 X B100 X C145 MM	2X15W	6500	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A230 X B100 X C145 MM	DIE CAST ALUMINUM	IK10	A230 X B100 X C145 MM	
72	MAZDA-WSXR37522X15W-6.5K-240V-WH-10VDIM-A230 X B100 X C145 MM	2X15W	6500	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A230 X B100 X C145 MM	DIE CAST ALUMINUM	IK10	A230 X B100 X C145 MM	