DATASHEET

GENERATED ON: 10 Nov 2026 | SYS.REF: MAZDA-LED



LION

MAZDA Model: CVXR45200 Strip Light

Lion an LED strip light is a flexible circuit board that is populated with LEDs that you can stick almost anywhere you want
to add powerful lighting in a variety of colors and brightness. LED strip lights are flexible and can be bent vertically up to
90 degrees

ALL AVAILABLE VARIANTS

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	cable entry	Dimensions	Price
1	MAZDA-CVXR452004.8W-3K-24V DC-CL-NON-DIMMABLE / DIMMABLE-5000 X 10 X 2 MM-FRONT	4.8W	3000	24V DC	CLEAR	NON EMERGENCY	NON-DIMMABLE / DIMMABLE	120°	5000 X 10 X 2 MM	SILICON	IP44	FRONT CABLE ENTRY / SIDE CABLE ENTRY / BOTTOM CABLE ENTRY	5000 X 10 X 2 MM	
2	MAZDA-CVXR452004.8W-4K-24V DC-CL-NON-DIMMABLE / DIMMABLE-5000 X 10 X 2 MM-FRONT	4.8W	4000	24V DC	CLEAR	NON EMERGENCY	NON-DIMMABLE / DIMMABLE	120°	5000 X 10 X 2 MM	SILICON	IP44	FRONT CABLE ENTRY / SIDE CABLE ENTRY / BOTTOM CABLE ENTRY	5000 X 10 X 2 MM	
3	MAZDA-CVXR452004.8W-5K-24V DC-CL-NON-DIMMABLE / DIMMABLE-5000 X 10 X 2 MM-FRONT	4.8W	5000	24V DC	CLEAR	NON EMERGENCY	NON-DIMMABLE / DIMMABLE	120°	5000 X 10 X 2 MM	SILICON	IP44	FRONT CABLE ENTRY / SIDE CABLE ENTRY / BOTTOM CABLE ENTRY	5000 X 10 X 2 MM	
4	MAZDA-CVXR452004.8W-6K-24V DC-CL-NON-DIMMABLE / DIMMABLE-5000 X 10 X 2 MM-FRONT	4.8W	6000	24V DC	CLEAR	NON EMERGENCY	NON-DIMMABLE / DIMMABLE	120°	5000 X 10 X 2 MM	SILICON	IP44	FRONT CABLE ENTRY / SIDE CABLE ENTRY / BOTTOM CABLE ENTRY	5000 X 10 X 2 MM	
5	MAZDA-CVXR452004.8W-2.7K-24V DC-CL-NON-DIMMABLE / DIMMABLE-5000 X 10 X 2 MM-FRON	4.8W	2700	24V DC	CLEAR	NON EMERGENCY	NON-DIMMABLE / DIMMABLE	120°	5000 X 10 X 2 MM	SILICON	IP44	FRONT CABLE ENTRY / SIDE CABLE ENTRY / BOTTOM CABLE ENTRY	5000 X 10 X 2 MM	
6	MAZDA-CVXR452004.8W-6.5K-24V DC-CL-NON-DIMMABLE / DIMMABLE-5000 X 10 X 2 MM-FRON	4.8W	6500	24V DC	CLEAR	NON EMERGENCY	NON-DIMMABLE / DIMMABLE	120°	5000 X 10 X 2 MM	SILICON	IP44	FRONT CABLE ENTRY / SIDE CABLE ENTRY / BOTTOM CABLE ENTRY	5000 X 10 X 2 MM	
7	MAZDA-CVXR452009.6W-3K-24V DC-CL-NON-DIMMABLE / DIMMABLE-5000 X 10 X 2 MM-FRONT	9.6W	3000	24V DC	CLEAR	NON EMERGENCY	NON-DIMMABLE / DIMMABLE	120°	5000 X 10 X 2 MM	SILICON	IP44	FRONT CABLE ENTRY / SIDE CABLE ENTRY / BOTTOM CABLE ENTRY	5000 X 10 X 2 MM	

DATASHEET

GENERATED ON: 10 Nov 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	cable entry	Dimensions	Price
8	**MAZDA-CVXR452009.6W-4K-24V DC-CL-NON-DIMMABLE / DIMMABLE-5000 X 10 X 2 MM-FRONT**	9.6W	4000	24V DC	CLEAR	NON EMERGENCY	NON-DIMMABLE / DIMMABLE	120°	5000 X 10 X 2 MM	SILICON	IP44	FRONT CABLE ENTRY / SIDE CABLE ENTRY / BOTTOM CABLE ENTRY	5000 X 10 X 2 MM	
9	**MAZDA-CVXR452009.6W-5K-24V DC-CL-NON-DIMMABLE / DIMMABLE-5000 X 10 X 2 MM-FRONT**	9.6W	5000	24V DC	CLEAR	NON EMERGENCY	NON-DIMMABLE / DIMMABLE	120°	5000 X 10 X 2 MM	SILICON	IP44	FRONT CABLE ENTRY / SIDE CABLE ENTRY / BOTTOM CABLE ENTRY	5000 X 10 X 2 MM	
10	**MAZDA-CVXR452009.6W-6K-24V DC-CL-NON-DIMMABLE / DIMMABLE-5000 X 10 X 2 MM-FRONT**	9.6W	6000	24V DC	CLEAR	NON EMERGENCY	NON-DIMMABLE / DIMMABLE	120°	5000 X 10 X 2 MM	SILICON	IP44	FRONT CABLE ENTRY / SIDE CABLE ENTRY / BOTTOM CABLE ENTRY	5000 X 10 X 2 MM	
11	**MAZDA-CVXR452009.6W-2.7K-24V DC-CL-NON-DIMMABLE / DIMMABLE-5000 X 10 X 2 MM-FRON**	9.6W	2700	24V DC	CLEAR	NON EMERGENCY	NON-DIMMABLE / DIMMABLE	120°	5000 X 10 X 2 MM	SILICON	IP44	FRONT CABLE ENTRY / SIDE CABLE ENTRY / BOTTOM CABLE ENTRY	5000 X 10 X 2 MM	
12	**MAZDA-CVXR452009.6W-6.5K-24V DC-CL-NON-DIMMABLE / DIMMABLE-5000 X 10 X 2 MM-FRON**	9.6W	6500	24V DC	CLEAR	NON EMERGENCY	NON-DIMMABLE / DIMMABLE	120°	5000 X 10 X 2 MM	SILICON	IP44	FRONT CABLE ENTRY / SIDE CABLE ENTRY / BOTTOM CABLE ENTRY	5000 X 10 X 2 MM	
13	**MAZDA-CVXR4520014.4W-3K-24V DC-CL-NON-DIMMABLE / DIMMABLE-5000 X 10 X 2 MM-FRONT**	14.4W	3000	24V DC	CLEAR	NON EMERGENCY	NON-DIMMABLE / DIMMABLE	120°	5000 X 10 X 2 MM	SILICON	IP44	FRONT CABLE ENTRY / SIDE CABLE ENTRY / BOTTOM CABLE ENTRY	5000 X 10 X 2 MM	
14	**MAZDA-CVXR4520014.4W-4K-24V DC-CL-NON-DIMMABLE / DIMMABLE-5000 X 10 X 2 MM-FRONT**	14.4W	4000	24V DC	CLEAR	NON EMERGENCY	NON-DIMMABLE / DIMMABLE	120°	5000 X 10 X 2 MM	SILICON	IP44	FRONT CABLE ENTRY / SIDE CABLE ENTRY / BOTTOM CABLE ENTRY	5000 X 10 X 2 MM	
15	**MAZDA-CVXR4520014.4W-5K-24V DC-CL-NON-DIMMABLE / DIMMABLE-5000 X 10 X 2 MM-FRONT**	14.4W	5000	24V DC	CLEAR	NON EMERGENCY	NON-DIMMABLE / DIMMABLE	120°	5000 X 10 X 2 MM	SILICON	IP44	FRONT CABLE ENTRY / SIDE CABLE ENTRY / BOTTOM CABLE ENTRY	5000 X 10 X 2 MM	
16	**MAZDA-CVXR4520014.4W-6K-24V DC-CL-NON-DIMMABLE / DIMMABLE-5000 X 10 X 2 MM-FRONT**	14.4W	6000	24V DC	CLEAR	NON EMERGENCY	NON-DIMMABLE / DIMMABLE	120°	5000 X 10 X 2 MM	SILICON	IP44	FRONT CABLE ENTRY / SIDE CABLE ENTRY / BOTTOM CABLE ENTRY	5000 X 10 X 2 MM	
17	**MAZDA-CVXR4520014.4W-2.7K-24V DC-CL-NON-DIMMABLE / DIMMABLE-5000 X 10 X 2 MM-FRO**	14.4W	2700	24V DC	CLEAR	NON EMERGENCY	NON-DIMMABLE / DIMMABLE	120°	5000 X 10 X 2 MM	SILICON	IP44	FRONT CABLE ENTRY / SIDE CABLE ENTRY / BOTTOM CABLE ENTRY	5000 X 10 X 2 MM	
18	**MAZDA-CVXR4520014.4W-6.5K-24V DC-CL-NON-DIMMABLE / DIMMABLE-5000 X 10 X 2 MM-FRO**	14.4W	6500	24V DC	CLEAR	NON EMERGENCY	NON-DIMMABLE / DIMMABLE	120°	5000 X 10 X 2 MM	SILICON	IP44	FRONT CABLE ENTRY / SIDE CABLE ENTRY / BOTTOM CABLE ENTRY	5000 X 10 X 2 MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	cable entry	Dimensions	Price
19	**MAZDA-CVXR4520014.4W-3K-24V DC-CL-NON-DIMMABLE / DIMMABLE-5000 X 10 X 2 MM-FRONT**	14.4W	3000	24V DC	CLEAR	NON EMERGENCY	NON-DIMMABLE / DIMMABLE	120°	5000 X 10 X 2 MM	SILICON	IP44	FRONT CABLE ENTRY / SIDE CABLE ENTRY / BOTTOM CABLE ENTRY	5000 X 10 X 2 MM	
20	**MAZDA-CVXR4520014.4W-4K-24V DC-CL-NON-DIMMABLE / DIMMABLE-5000 X 10 X 2 MM-FRONT**	14.4W	4000	24V DC	CLEAR	NON EMERGENCY	NON-DIMMABLE / DIMMABLE	120°	5000 X 10 X 2 MM	SILICON	IP44	FRONT CABLE ENTRY / SIDE CABLE ENTRY / BOTTOM CABLE ENTRY	5000 X 10 X 2 MM	
21	**MAZDA-CVXR4520014.4W-5K-24V DC-CL-NON-DIMMABLE / DIMMABLE-5000 X 10 X 2 MM-FRONT**	14.4W	5000	24V DC	CLEAR	NON EMERGENCY	NON-DIMMABLE / DIMMABLE	120°	5000 X 10 X 2 MM	SILICON	IP44	FRONT CABLE ENTRY / SIDE CABLE ENTRY / BOTTOM CABLE ENTRY	5000 X 10 X 2 MM	
22	**MAZDA-CVXR4520014.4W-6K-24V DC-CL-NON-DIMMABLE / DIMMABLE-5000 X 10 X 2 MM-FRONT**	14.4W	6000	24V DC	CLEAR	NON EMERGENCY	NON-DIMMABLE / DIMMABLE	120°	5000 X 10 X 2 MM	SILICON	IP44	FRONT CABLE ENTRY / SIDE CABLE ENTRY / BOTTOM CABLE ENTRY	5000 X 10 X 2 MM	
23	**MAZDA-CVXR4520014.4W-2.7K-24V DC-CL-NON-DIMMABLE / DIMMABLE-5000 X 10 X 2 MM-FRO**	14.4W	2700	24V DC	CLEAR	NON EMERGENCY	NON-DIMMABLE / DIMMABLE	120°	5000 X 10 X 2 MM	SILICON	IP44	FRONT CABLE ENTRY / SIDE CABLE ENTRY / BOTTOM CABLE ENTRY	5000 X 10 X 2 MM	
24	**MAZDA-CVXR4520014.4W-6.5K-24V DC-CL-NON-DIMMABLE / DIMMABLE-5000 X 10 X 2 MM-FRO**	14.4W	6500	24V DC	CLEAR	NON EMERGENCY	NON-DIMMABLE / DIMMABLE	120°	5000 X 10 X 2 MM	SILICON	IP44	FRONT CABLE ENTRY / SIDE CABLE ENTRY / BOTTOM CABLE ENTRY	5000 X 10 X 2 MM	