



METEOR

MAZDA Model: IDXR2922 INDUSTRIAL & TRIPROOF LIGHT

Meteor Tri-Proof is IP65 luminaire for mounting on ceiling. Made of UV-stabilised polycarbonate. Meteor LED waterproof is a very hardy luminaire, especially suitable for farms and the like. The LED compartment is IP65K protected to withstand ammonia gasses in such environments. The luminaire housing is made of hard UV-stabilised and anti-chemical coated polycarbonate. The coating is resistant to ammonia, washing detergents etc, and makes the it suitable also for car wash halls and similar. It is easy to install by just snapping into mounting clips and using the unique one-hand closing mechanism at both ends. The looping options with double cable gland in each end and through wiring gives full flexibility for larger installations.

ALL AVAILABLE VARIANTS

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
1	MAZDA-IDXR292236W-3K-240V-GRY-ND-A590 X B68 X C72MM	36W	3000	240V	GREY	NON EMERGENCY	ON - OFF	120	A590 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A590 X B68 X C72MM	
2	MAZDA-IDXR292236W-3K-240V-GRY-ND-EM-A590 X B68 X C72MM	36W	3000	240V	GREY	3 HOUR EMERGENCY BACKUP	ON - OFF	120	A590 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A590 X B68 X C72MM	
3	MAZDA-IDXR292236W-3K-240V-GRY-DA-A590 X B68 X C72MM	36W	3000	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	120	A590 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A590 X B68 X C72MM	
4	MAZDA-IDXR292236W-3K-240V-GRY-DA-EM-A590 X B68 X C72MM	36W	3000	240V	GREY	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	120	A590 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A590 X B68 X C72MM	
5	MAZDA-IDXR292236W-3K-240V-GRY-PH-A590 X B68 X C72MM	36W	3000	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	120	A590 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A590 X B68 X C72MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
6	MAZDA-IDXR292236W-3K-240V-GRY-PH-EM-A590 X B68 X C72MM	36W	3000	240V	GREY	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	120	A590 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A590 X B68 X C72MM	
7	MAZDA-IDXR292236W-3K-240V-GRY-10VDIM-A590 X B68 X C72MM	36W	3000	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	120	A590 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A590 X B68 X C72MM	
8	MAZDA-IDXR292236W-3K-240V-GRY-10VDIM-EM-A590 X B68 X C72MM	36W	3000	240V	GREY	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	120	A590 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A590 X B68 X C72MM	
9	MAZDA-IDXR292236W-4K-240V-GRY-ND-A590 X B68 X C72MM	36W	4000	240V	GREY	NON EMERGENCY	ON - OFF	120	A590 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A590 X B68 X C72MM	
10	MAZDA-IDXR292236W-4K-240V-GRY-ND-EM-A590 X B68 X C72MM	36W	4000	240V	GREY	3 HOUR EMERGENCY BACKUP	ON - OFF	120	A590 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A590 X B68 X C72MM	
11	MAZDA-IDXR292236W-4K-240V-GRY-DA-A590 X B68 X C72MM	36W	4000	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	120	A590 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A590 X B68 X C72MM	
12	MAZDA-IDXR292236W-4K-240V-GRY-DA-EM-A590 X B68 X C72MM	36W	4000	240V	GREY	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	120	A590 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A590 X B68 X C72MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
13	MAZDA-IDXR292236W-4K-240V-GRY-PH-A590 X B68 X C72MM	36W	4000	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	120	A590 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A590 X B68 X C72MM	
14	MAZDA-IDXR292236W-4K-240V-GRY-PH-EM-A590 X B68 X C72MM	36W	4000	240V	GREY	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	120	A590 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A590 X B68 X C72MM	
15	MAZDA-IDXR292236W-4K-240V-GRY-10VDIM-A590 X B68 X C72MM	36W	4000	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	120	A590 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A590 X B68 X C72MM	
16	MAZDA-IDXR292236W-4K-240V-GRY-10VDIM-EM-A590 X B68 X C72MM	36W	4000	240V	GREY	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	120	A590 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A590 X B68 X C72MM	
17	MAZDA-IDXR292236W-5K-240V-GRY-ND-A590 X B68 X C72MM	36W	5000	240V	GREY	NON EMERGENCY	ON - OFF	120	A590 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A590 X B68 X C72MM	
18	MAZDA-IDXR292236W-5K-240V-GRY-ND-EM-A590 X B68 X C72MM	36W	5000	240V	GREY	3 HOUR EMERGENCY BACKUP	ON - OFF	120	A590 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A590 X B68 X C72MM	
19	MAZDA-IDXR292236W-5K-240V-GRY-DA-A590 X B68 X C72MM	36W	5000	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	120	A590 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A590 X B68 X C72MM	



DATASHEET

GENERATED ON: 04 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
20	MAZDA-IDXR292236W-5K-240V-GRY-DA-EM-A590 X B68 X C72MM	36W	5000	240V	GREY	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	120	A590 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A590 X B68 X C72MM	
21	MAZDA-IDXR292236W-5K-240V-GRY-PH-A590 X B68 X C72MM	36W	5000	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	120	A590 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A590 X B68 X C72MM	
22	MAZDA-IDXR292236W-5K-240V-GRY-PH-EM-A590 X B68 X C72MM	36W	5000	240V	GREY	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	120	A590 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A590 X B68 X C72MM	
23	MAZDA-IDXR292236W-5K-240V-GRY-10VDIM-A590 X B68 X C72MM	36W	5000	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	120	A590 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A590 X B68 X C72MM	
24	MAZDA-IDXR292236W-5K-240V-GRY-10VDIM-EM-A590 X B68 X C72MM	36W	5000	240V	GREY	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	120	A590 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A590 X B68 X C72MM	
25	MAZDA-IDXR292236W-6K-240V-GRY-ND-A590 X B68 X C72MM	36W	6000	240V	GREY	NON EMERGENCY	ON - OFF	120	A590 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A590 X B68 X C72MM	
26	MAZDA-IDXR292236W-6K-240V-GRY-ND-EM-A590 X B68 X C72MM	36W	6000	240V	GREY	3 HOUR EMERGENCY BACKUP	ON - OFF	120	A590 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A590 X B68 X C72MM	



DATASHEET

GENERATED ON: 04 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
27	MAZDA-IDXR292236W-6K-240V-GRY-DA-A590 X B68 X C72MM	36W	6000	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	120	A590 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A590 X B68 X C72MM	
28	MAZDA-IDXR292236W-6K-240V-GRY-DA-EM-A590 X B68 X C72MM	36W	6000	240V	GREY	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	120	A590 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A590 X B68 X C72MM	
29	MAZDA-IDXR292236W-6K-240V-GRY-PH-A590 X B68 X C72MM	36W	6000	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	120	A590 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A590 X B68 X C72MM	
30	MAZDA-IDXR292236W-6K-240V-GRY-PH-EM-A590 X B68 X C72MM	36W	6000	240V	GREY	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	120	A590 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A590 X B68 X C72MM	
31	MAZDA-IDXR292236W-6K-240V-GRY-10VDIM-A590 X B68 X C72MM	36W	6000	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	120	A590 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A590 X B68 X C72MM	
32	MAZDA-IDXR292236W-6K-240V-GRY-10VDIM-EM-A590 X B68 X C72MM	36W	6000	240V	GREY	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	120	A590 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A590 X B68 X C72MM	
33	MAZDA-IDXR292236W-2.7K-240V-GRY-ND-A590 X B68 X C72MM	36W	2700	240V	GREY	NON EMERGENCY	ON - OFF	120	A590 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A590 X B68 X C72MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
34	MAZDA-IDXR292236W-2.7K-240V-GRY-ND-EM-A590 X B68 X C72MM	36W	2700	240V	GREY	3 HOUR EMERGENCY BACKUP	ON - OFF	120	A590 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A590 X B68 X C72MM	
35	MAZDA-IDXR292236W-2.7K-240V-GRY-DA-A590 X B68 X C72MM	36W	2700	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	120	A590 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A590 X B68 X C72MM	
36	MAZDA-IDXR292236W-2.7K-240V-GRY-DA-EM-A590 X B68 X C72MM	36W	2700	240V	GREY	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	120	A590 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A590 X B68 X C72MM	
37	MAZDA-IDXR292236W-2.7K-240V-GRY-PH-A590 X B68 X C72MM	36W	2700	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	120	A590 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A590 X B68 X C72MM	
38	MAZDA-IDXR292236W-2.7K-240V-GRY-PH-EM-A590 X B68 X C72MM	36W	2700	240V	GREY	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	120	A590 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A590 X B68 X C72MM	
39	MAZDA-IDXR292236W-2.7K-240V-GRY-10VDIM-A590 X B68 X C72MM	36W	2700	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	120	A590 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A590 X B68 X C72MM	
40	MAZDA-IDXR292236W-2.7K-240V-GRY-10VDIM-EM-A590 X B68 X C72MM	36W	2700	240V	GREY	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	120	A590 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A590 X B68 X C72MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
41	MAZDA-IDXR292236W-6.5K-240V-GRY-ND-A590 X B68 X C72MM	36W	6500	240V	GREY	NON EMERGENCY	ON - OFF	120	A590 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A590 X B68 X C72MM	
42	MAZDA-IDXR292236W-6.5K-240V-GRY-ND-EM-A590 X B68 X C72MM	36W	6500	240V	GREY	3 HOUR EMERGENCY BACKUP	ON - OFF	120	A590 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A590 X B68 X C72MM	
43	MAZDA-IDXR292236W-6.5K-240V-GRY-DA-A590 X B68 X C72MM	36W	6500	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	120	A590 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A590 X B68 X C72MM	
44	MAZDA-IDXR292236W-6.5K-240V-GRY-DA-EM-A590 X B68 X C72MM	36W	6500	240V	GREY	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	120	A590 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A590 X B68 X C72MM	
45	MAZDA-IDXR292236W-6.5K-240V-GRY-PH-A590 X B68 X C72MM	36W	6500	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	120	A590 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A590 X B68 X C72MM	
46	MAZDA-IDXR292236W-6.5K-240V-GRY-PH-EM-A590 X B68 X C72MM	36W	6500	240V	GREY	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	120	A590 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A590 X B68 X C72MM	
47	MAZDA-IDXR292236W-6.5K-240V-GRY-10VDIM-A590 X B68 X C72MM	36W	6500	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	120	A590 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A590 X B68 X C72MM	



DATASHEET

GENERATED ON: 04 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
48	MAZDA-IDXR292236W-6.5K-240V-GRY-10VDIM-EM-A590 X B68 X C72MM	36W	6500	240V	GREY	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	120	A590 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A590 X B68 X C72MM	
49	MAZDA-IDXR292240W-3K-240V-GRY-ND-A1180 X B68 X C72MM	40W	3000	240V	GREY	NON EMERGENCY	ON - OFF	120	A1180 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1180 X B68 X C72MM	
50	MAZDA-IDXR292240W-3K-240V-GRY-ND-EM-A1180 X B68 X C72MM	40W	3000	240V	GREY	3 HOUR EMERGENCY BACKUP	ON - OFF	120	A1180 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1180 X B68 X C72MM	
51	MAZDA-IDXR292240W-3K-240V-GRY-DA-A1180 X B68 X C72MM	40W	3000	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	120	A1180 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1180 X B68 X C72MM	
52	MAZDA-IDXR292240W-3K-240V-GRY-DA-EM-A1180 X B68 X C72MM	40W	3000	240V	GREY	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	120	A1180 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1180 X B68 X C72MM	
53	MAZDA-IDXR292240W-3K-240V-GRY-PH-A1180 X B68 X C72MM	40W	3000	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	120	A1180 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1180 X B68 X C72MM	
54	MAZDA-IDXR292240W-3K-240V-GRY-PH-EM-A1180 X B68 X C72MM	40W	3000	240V	GREY	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	120	A1180 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1180 X B68 X C72MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
55	MAZDA-IDXR292240W-3K-240V-GRY-10VDIM-A1180 X B68 X C72MM	40W	3000	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	120	A1180 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1180 X B68 X C72MM	
56	MAZDA-IDXR292240W-3K-240V-GRY-10VDIM-EM-A1180 X B68 X C72MM	40W	3000	240V	GREY	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	120	A1180 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1180 X B68 X C72MM	
57	MAZDA-IDXR292240W-4K-240V-GRY-ND-A1180 X B68 X C72MM	40W	4000	240V	GREY	NON EMERGENCY	ON - OFF	120	A1180 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1180 X B68 X C72MM	
58	MAZDA-IDXR292240W-4K-240V-GRY-ND-EM-A1180 X B68 X C72MM	40W	4000	240V	GREY	3 HOUR EMERGENCY BACKUP	ON - OFF	120	A1180 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1180 X B68 X C72MM	
59	MAZDA-IDXR292240W-4K-240V-GRY-DA-A1180 X B68 X C72MM	40W	4000	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	120	A1180 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1180 X B68 X C72MM	
60	MAZDA-IDXR292240W-4K-240V-GRY-DA-EM-A1180 X B68 X C72MM	40W	4000	240V	GREY	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	120	A1180 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1180 X B68 X C72MM	
61	MAZDA-IDXR292240W-4K-240V-GRY-PH-A1180 X B68 X C72MM	40W	4000	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	120	A1180 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1180 X B68 X C72MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
62	MAZDA-IDXR292240W-4K-240V-GRY-PH-EM-A1180 X B68 X C72MM	40W	4000	240V	GREY	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	120	A1180 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1180 X B68 X C72MM	
63	MAZDA-IDXR292240W-4K-240V-GRY-10VDIM-A1180 X B68 X C72MM	40W	4000	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	120	A1180 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1180 X B68 X C72MM	
64	MAZDA-IDXR292240W-4K-240V-GRY-10VDIM-EM-A1180 X B68 X C72MM	40W	4000	240V	GREY	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	120	A1180 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1180 X B68 X C72MM	
65	MAZDA-IDXR292240W-5K-240V-GRY-ND-A1180 X B68 X C72MM	40W	5000	240V	GREY	NON EMERGENCY	ON - OFF	120	A1180 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1180 X B68 X C72MM	
66	MAZDA-IDXR292240W-5K-240V-GRY-ND-EM-A1180 X B68 X C72MM	40W	5000	240V	GREY	3 HOUR EMERGENCY BACKUP	ON - OFF	120	A1180 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1180 X B68 X C72MM	
67	MAZDA-IDXR292240W-5K-240V-GRY-DA-A1180 X B68 X C72MM	40W	5000	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	120	A1180 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1180 X B68 X C72MM	
68	MAZDA-IDXR292240W-5K-240V-GRY-DA-EM-A1180 X B68 X C72MM	40W	5000	240V	GREY	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	120	A1180 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1180 X B68 X C72MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
69	MAZDA-IDXR292240W-5K-240V-GRY-PH-A1180 X B68 X C72MM	40W	5000	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	120	A1180 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1180 X B68 X C72MM	
70	MAZDA-IDXR292240W-5K-240V-GRY-PH-EM-A1180 X B68 X C72MM	40W	5000	240V	GREY	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	120	A1180 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1180 X B68 X C72MM	
71	MAZDA-IDXR292240W-5K-240V-GRY-10VDIM-A1180 X B68 X C72MM	40W	5000	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	120	A1180 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1180 X B68 X C72MM	
72	MAZDA-IDXR292240W-5K-240V-GRY-10VDIM-EM-A1180 X B68 X C72MM	40W	5000	240V	GREY	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	120	A1180 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1180 X B68 X C72MM	
73	MAZDA-IDXR292240W-6K-240V-GRY-ND-A1180 X B68 X C72MM	40W	6000	240V	GREY	NON EMERGENCY	ON - OFF	120	A1180 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1180 X B68 X C72MM	
74	MAZDA-IDXR292240W-6K-240V-GRY-ND-EM-A1180 X B68 X C72MM	40W	6000	240V	GREY	3 HOUR EMERGENCY BACKUP	ON - OFF	120	A1180 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1180 X B68 X C72MM	
75	MAZDA-IDXR292240W-6K-240V-GRY-DA-A1180 X B68 X C72MM	40W	6000	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	120	A1180 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1180 X B68 X C72MM	



DATASHEET

GENERATED ON: 04 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
76	MAZDA-IDXR292240W-6K-240V-GRY-DA-EM-A1180 X B68 X C72MM	40W	6000	240V	GREY	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	120	A1180 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1180 X B68 X C72MM	
77	MAZDA-IDXR292240W-6K-240V-GRY-PH-A1180 X B68 X C72MM	40W	6000	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	120	A1180 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1180 X B68 X C72MM	
78	MAZDA-IDXR292240W-6K-240V-GRY-PH-EM-A1180 X B68 X C72MM	40W	6000	240V	GREY	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	120	A1180 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1180 X B68 X C72MM	
79	MAZDA-IDXR292240W-6K-240V-GRY-10VDIM-A1180 X B68 X C72MM	40W	6000	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	120	A1180 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1180 X B68 X C72MM	
80	MAZDA-IDXR292240W-6K-240V-GRY-10VDIM-EM-A1180 X B68 X C72MM	40W	6000	240V	GREY	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	120	A1180 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1180 X B68 X C72MM	
81	MAZDA-IDXR292240W-2.7K-240V-GRY-ND-A1180 X B68 X C72MM	40W	2700	240V	GREY	NON EMERGENCY	ON - OFF	120	A1180 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1180 X B68 X C72MM	
82	MAZDA-IDXR292240W-2.7K-240V-GRY-ND-EM-A1180 X B68 X C72MM	40W	2700	240V	GREY	3 HOUR EMERGENCY BACKUP	ON - OFF	120	A1180 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1180 X B68 X C72MM	



DATASHEET

GENERATED ON: 04 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
83	MAZDA-IDXR292240W-2.7K-240V-GRY-DA-A1180 X B68 X C72MM	40W	2700	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	120	A1180 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1180 X B68 X C72MM	
84	MAZDA-IDXR292240W-2.7K-240V-GRY-DA-EM-A1180 X B68 X C72MM	40W	2700	240V	GREY	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	120	A1180 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1180 X B68 X C72MM	
85	MAZDA-IDXR292240W-2.7K-240V-GRY-PH-A1180 X B68 X C72MM	40W	2700	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	120	A1180 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1180 X B68 X C72MM	
86	MAZDA-IDXR292240W-2.7K-240V-GRY-PH-EM-A1180 X B68 X C72MM	40W	2700	240V	GREY	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	120	A1180 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1180 X B68 X C72MM	
87	MAZDA-IDXR292240W-2.7K-240V-GRY-10VDIM-A1180 X B68 X C72MM	40W	2700	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	120	A1180 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1180 X B68 X C72MM	
88	MAZDA-IDXR292240W-2.7K-240V-GRY-10VDIM-EM-A1180 X B68 X C72MM	40W	2700	240V	GREY	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	120	A1180 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1180 X B68 X C72MM	
89	MAZDA-IDXR292240W-6.5K-240V-GRY-ND-A1180 X B68 X C72MM	40W	6500	240V	GREY	NON EMERGENCY	ON - OFF	120	A1180 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1180 X B68 X C72MM	



DATASHEET

GENERATED ON: 04 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
90	MAZDA-IDXR292240W-6.5K-240V-GRY-ND-EM-A1180 X B68 X C72MM	40W	6500	240V	GREY	3 HOUR EMERGENCY BACKUP	ON - OFF	120	A1180 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1180 X B68 X C72MM	
91	MAZDA-IDXR292240W-6.5K-240V-GRY-DA-A1180 X B68 X C72MM	40W	6500	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	120	A1180 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1180 X B68 X C72MM	
92	MAZDA-IDXR292240W-6.5K-240V-GRY-DA-EM-A1180 X B68 X C72MM	40W	6500	240V	GREY	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	120	A1180 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1180 X B68 X C72MM	
93	MAZDA-IDXR292240W-6.5K-240V-GRY-PH-A1180 X B68 X C72MM	40W	6500	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	120	A1180 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1180 X B68 X C72MM	
94	MAZDA-IDXR292240W-6.5K-240V-GRY-PH-EM-A1180 X B68 X C72MM	40W	6500	240V	GREY	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	120	A1180 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1180 X B68 X C72MM	
95	MAZDA-IDXR292240W-6.5K-240V-GRY-10VDIM-A1180 X B68 X C72MM	40W	6500	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	120	A1180 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1180 X B68 X C72MM	
96	MAZDA-IDXR292240W-6.5K-240V-GRY-10VDIM-EM-A1180 X B68 X C72MM	40W	6500	240V	GREY	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	120	A1180 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1180 X B68 X C72MM	



DATASHEET

GENERATED ON: 04 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
97	MAZDA-IDXR292244W-3K-240V-GRY-ND-A1480 X B68 X C72MM	44W	3000	240V	GREY	NON EMERGENCY	ON - OFF	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
98	MAZDA-IDXR292244W-3K-240V-GRY-ND-EM-A1480 X B68 X C72MM	44W	3000	240V	GREY	3 HOUR EMERGENCY BACKUP	ON - OFF	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
99	MAZDA-IDXR292244W-3K-240V-GRY-DA-A1480 X B68 X C72MM	44W	3000	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
100	MAZDA-IDXR292244W-3K-240V-GRY-DA-EM-A1480 X B68 X C72MM	44W	3000	240V	GREY	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
101	MAZDA-IDXR292244W-3K-240V-GRY-PH-A1480 X B68 X C72MM	44W	3000	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
102	MAZDA-IDXR292244W-3K-240V-GRY-PH-EM-A1480 X B68 X C72MM	44W	3000	240V	GREY	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
103	MAZDA-IDXR292244W-3K-240V-GRY-10VDIM-A1480 X B68 X C72MM	44W	3000	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	



DATASHEET

GENERATED ON: 04 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
104	MAZDA-IDXR292244W-3K-240V-GRY-10VDIM-EM-A1480 X B68 X C72MM	44W	3000	240V	GREY	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
105	MAZDA-IDXR292244W-4K-240V-GRY-ND-A1480 X B68 X C72MM	44W	4000	240V	GREY	NON EMERGENCY	ON - OFF	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
106	MAZDA-IDXR292244W-4K-240V-GRY-ND-EM-A1480 X B68 X C72MM	44W	4000	240V	GREY	3 HOUR EMERGENCY BACKUP	ON - OFF	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
107	MAZDA-IDXR292244W-4K-240V-GRY-DA-A1480 X B68 X C72MM	44W	4000	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
108	MAZDA-IDXR292244W-4K-240V-GRY-DA-EM-A1480 X B68 X C72MM	44W	4000	240V	GREY	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
109	MAZDA-IDXR292244W-4K-240V-GRY-PH-A1480 X B68 X C72MM	44W	4000	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
110	MAZDA-IDXR292244W-4K-240V-GRY-PH-EM-A1480 X B68 X C72MM	44W	4000	240V	GREY	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	



DATASHEET

GENERATED ON: 04 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
111	MAZDA-IDXR292244W-4K-240V-GRY-10VDIM-A1480 X B68 X C72MM	44W	4000	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
112	MAZDA-IDXR292244W-4K-240V-GRY-10VDIM-EM-A1480 X B68 X C72MM	44W	4000	240V	GREY	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
113	MAZDA-IDXR292244W-5K-240V-GRY-ND-A1480 X B68 X C72MM	44W	5000	240V	GREY	NON EMERGENCY	ON - OFF	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
114	MAZDA-IDXR292244W-5K-240V-GRY-ND-EM-A1480 X B68 X C72MM	44W	5000	240V	GREY	3 HOUR EMERGENCY BACKUP	ON - OFF	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
115	MAZDA-IDXR292244W-5K-240V-GRY-DA-A1480 X B68 X C72MM	44W	5000	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
116	MAZDA-IDXR292244W-5K-240V-GRY-DA-EM-A1480 X B68 X C72MM	44W	5000	240V	GREY	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
117	MAZDA-IDXR292244W-5K-240V-GRY-PH-A1480 X B68 X C72MM	44W	5000	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	



DATASHEET

GENERATED ON: 04 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
118	MAZDA-IDXR292244W-5K-240V-GRY-PH-EM-A1480 X B68 X C72MM	44W	5000	240V	GREY	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
119	MAZDA-IDXR292244W-5K-240V-GRY-10VDIM-A1480 X B68 X C72MM	44W	5000	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
120	MAZDA-IDXR292244W-5K-240V-GRY-10VDIM-EM-A1480 X B68 X C72MM	44W	5000	240V	GREY	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
121	MAZDA-IDXR292244W-6K-240V-GRY-ND-A1480 X B68 X C72MM	44W	6000	240V	GREY	NON EMERGENCY	ON - OFF	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
122	MAZDA-IDXR292244W-6K-240V-GRY-ND-EM-A1480 X B68 X C72MM	44W	6000	240V	GREY	3 HOUR EMERGENCY BACKUP	ON - OFF	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
123	MAZDA-IDXR292244W-6K-240V-GRY-DA-A1480 X B68 X C72MM	44W	6000	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
124	MAZDA-IDXR292244W-6K-240V-GRY-DA-EM-A1480 X B68 X C72MM	44W	6000	240V	GREY	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	



DATASHEET

GENERATED ON: 04 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
125	MAZDA-IDXR292244W-6K-240V-GRY-PH-A1480 X B68 X C72MM	44W	6000	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
126	MAZDA-IDXR292244W-6K-240V-GRY-PH-EM-A1480 X B68 X C72MM	44W	6000	240V	GREY	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
127	MAZDA-IDXR292244W-6K-240V-GRY-10VDIM-A1480 X B68 X C72MM	44W	6000	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
128	MAZDA-IDXR292244W-6K-240V-GRY-10VDIM-EM-A1480 X B68 X C72MM	44W	6000	240V	GREY	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
129	MAZDA-IDXR292244W-2.7K-240V-GRY-ND-A1480 X B68 X C72MM	44W	2700	240V	GREY	NON EMERGENCY	ON - OFF	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
130	MAZDA-IDXR292244W-2.7K-240V-GRY-ND-EM-A1480 X B68 X C72MM	44W	2700	240V	GREY	3 HOUR EMERGENCY BACKUP	ON - OFF	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
131	MAZDA-IDXR292244W-2.7K-240V-GRY-DA-A1480 X B68 X C72MM	44W	2700	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	



DATASHEET

GENERATED ON: 04 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
132	MAZDA-IDXR292244W-2.7K-240V-GRY-DA-EM-A1480 X B68 X C72MM	44W	2700	240V	GREY	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
133	MAZDA-IDXR292244W-2.7K-240V-GRY-PH-A1480 X B68 X C72MM	44W	2700	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
134	MAZDA-IDXR292244W-2.7K-240V-GRY-PH-EM-A1480 X B68 X C72MM	44W	2700	240V	GREY	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
135	MAZDA-IDXR292244W-2.7K-240V-GRY-10VDIM-A1480 X B68 X C72MM	44W	2700	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
136	MAZDA-IDXR292244W-2.7K-240V-GRY-10VDIM-EM-A1480 X B68 X C72MM	44W	2700	240V	GREY	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
137	MAZDA-IDXR292244W-6.5K-240V-GRY-ND-A1480 X B68 X C72MM	44W	6500	240V	GREY	NON EMERGENCY	ON - OFF	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
138	MAZDA-IDXR292244W-6.5K-240V-GRY-ND-EM-A1480 X B68 X C72MM	44W	6500	240V	GREY	3 HOUR EMERGENCY BACKUP	ON - OFF	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
139	MAZDA-IDXR292244W-6.5K-240V-GRY-DA-A1480 X B68 X C72MM	44W	6500	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
140	MAZDA-IDXR292244W-6.5K-240V-GRY-DA-EM-A1480 X B68 X C72MM	44W	6500	240V	GREY	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
141	MAZDA-IDXR292244W-6.5K-240V-GRY-PH-A1480 X B68 X C72MM	44W	6500	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
142	MAZDA-IDXR292244W-6.5K-240V-GRY-PH-EM-A1480 X B68 X C72MM	44W	6500	240V	GREY	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
143	MAZDA-IDXR292244W-6.5K-240V-GRY-10VDIM-A1480 X B68 X C72MM	44W	6500	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
144	MAZDA-IDXR292244W-6.5K-240V-GRY-10VDIM-EM-A1480 X B68 X C72MM	44W	6500	240V	GREY	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
145	MAZDA-IDXR292250W-3K-240V-GRY-ND-A1480 X B68 X C72MM	50W	3000	240V	GREY	NON EMERGENCY	ON - OFF	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	



DATASHEET

GENERATED ON: 04 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
146	MAZDA-IDXR292250W-3K-240V-GRY-ND-EM-A1480 X B68 X C72MM	50W	3000	240V	GREY	3 HOUR EMERGENCY BACKUP	ON - OFF	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
147	MAZDA-IDXR292250W-3K-240V-GRY-DA-A1480 X B68 X C72MM	50W	3000	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
148	MAZDA-IDXR292250W-3K-240V-GRY-DA-EM-A1480 X B68 X C72MM	50W	3000	240V	GREY	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
149	MAZDA-IDXR292250W-3K-240V-GRY-PH-A1480 X B68 X C72MM	50W	3000	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
150	MAZDA-IDXR292250W-3K-240V-GRY-PH-EM-A1480 X B68 X C72MM	50W	3000	240V	GREY	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
151	MAZDA-IDXR292250W-3K-240V-GRY-10VDIM-A1480 X B68 X C72MM	50W	3000	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
152	MAZDA-IDXR292250W-3K-240V-GRY-10VDIM-EM-A1480 X B68 X C72MM	50W	3000	240V	GREY	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
153	MAZDA-IDXR292250W-4K-240V-GRY-ND-A1480 X B68 X C72MM	50W	4000	240V	GREY	NON EMERGENCY	ON - OFF	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
154	MAZDA-IDXR292250W-4K-240V-GRY-ND-EM-A1480 X B68 X C72MM	50W	4000	240V	GREY	3 HOUR EMERGENCY BACKUP	ON - OFF	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
155	MAZDA-IDXR292250W-4K-240V-GRY-DA-A1480 X B68 X C72MM	50W	4000	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
156	MAZDA-IDXR292250W-4K-240V-GRY-DA-EM-A1480 X B68 X C72MM	50W	4000	240V	GREY	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
157	MAZDA-IDXR292250W-4K-240V-GRY-PH-A1480 X B68 X C72MM	50W	4000	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
158	MAZDA-IDXR292250W-4K-240V-GRY-PH-EM-A1480 X B68 X C72MM	50W	4000	240V	GREY	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
159	MAZDA-IDXR292250W-4K-240V-GRY-10VDIM-A1480 X B68 X C72MM	50W	4000	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
160	MAZDA-IDXR292250W-4K-240V-GRY-10VDIM-EM-A1480 X B68 X C72MM	50W	4000	240V	GREY	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
161	MAZDA-IDXR292250W-5K-240V-GRY-ND-A1480 X B68 X C72MM	50W	5000	240V	GREY	NON EMERGENCY	ON - OFF	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
162	MAZDA-IDXR292250W-5K-240V-GRY-ND-EM-A1480 X B68 X C72MM	50W	5000	240V	GREY	3 HOUR EMERGENCY BACKUP	ON - OFF	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
163	MAZDA-IDXR292250W-5K-240V-GRY-DA-A1480 X B68 X C72MM	50W	5000	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
164	MAZDA-IDXR292250W-5K-240V-GRY-DA-EM-A1480 X B68 X C72MM	50W	5000	240V	GREY	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
165	MAZDA-IDXR292250W-5K-240V-GRY-PH-A1480 X B68 X C72MM	50W	5000	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
166	MAZDA-IDXR292250W-5K-240V-GRY-PH-EM-A1480 X B68 X C72MM	50W	5000	240V	GREY	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	



DATASHEET

GENERATED ON: 04 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
167	MAZDA-IDXR292250W-5K-240V-GRY-10VDIM-A1480 X B68 X C72MM	50W	5000	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
168	MAZDA-IDXR292250W-5K-240V-GRY-10VDIM-EM-A1480 X B68 X C72MM	50W	5000	240V	GREY	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
169	MAZDA-IDXR292250W-6K-240V-GRY-ND-A1480 X B68 X C72MM	50W	6000	240V	GREY	NON EMERGENCY	ON - OFF	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
170	MAZDA-IDXR292250W-6K-240V-GRY-ND-EM-A1480 X B68 X C72MM	50W	6000	240V	GREY	3 HOUR EMERGENCY BACKUP	ON - OFF	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
171	MAZDA-IDXR292250W-6K-240V-GRY-DA-A1480 X B68 X C72MM	50W	6000	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
172	MAZDA-IDXR292250W-6K-240V-GRY-DA-EM-A1480 X B68 X C72MM	50W	6000	240V	GREY	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
173	MAZDA-IDXR292250W-6K-240V-GRY-PH-A1480 X B68 X C72MM	50W	6000	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
174	MAZDA-IDXR292250W-6K-240V-GRY-PH-EM-A1480 X B68 X C72MM	50W	6000	240V	GREY	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
175	MAZDA-IDXR292250W-6K-240V-GRY-10VDIM-A1480 X B68 X C72MM	50W	6000	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
176	MAZDA-IDXR292250W-6K-240V-GRY-10VDIM-EM-A1480 X B68 X C72MM	50W	6000	240V	GREY	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
177	MAZDA-IDXR292250W-2.7K-240V-GRY-ND-A1480 X B68 X C72MM	50W	2700	240V	GREY	NON EMERGENCY	ON - OFF	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
178	MAZDA-IDXR292250W-2.7K-240V-GRY-ND-EM-A1480 X B68 X C72MM	50W	2700	240V	GREY	3 HOUR EMERGENCY BACKUP	ON - OFF	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
179	MAZDA-IDXR292250W-2.7K-240V-GRY-DA-A1480 X B68 X C72MM	50W	2700	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
180	MAZDA-IDXR292250W-2.7K-240V-GRY-DA-EM-A1480 X B68 X C72MM	50W	2700	240V	GREY	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
181	MAZDA-IDXR292250W-2.7K-240V-GRY-PH-A1480 X B68 X C72MM	50W	2700	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
182	MAZDA-IDXR292250W-2.7K-240V-GRY-PH-EM-A1480 X B68 X C72MM	50W	2700	240V	GREY	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
183	MAZDA-IDXR292250W-2.7K-240V-GRY-10VDIM-A1480 X B68 X C72MM	50W	2700	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
184	MAZDA-IDXR292250W-2.7K-240V-GRY-10VDIM-EM-A1480 X B68 X C72MM	50W	2700	240V	GREY	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
185	MAZDA-IDXR292250W-6.5K-240V-GRY-ND-A1480 X B68 X C72MM	50W	6500	240V	GREY	NON EMERGENCY	ON - OFF	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
186	MAZDA-IDXR292250W-6.5K-240V-GRY-ND-EM-A1480 X B68 X C72MM	50W	6500	240V	GREY	3 HOUR EMERGENCY BACKUP	ON - OFF	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
187	MAZDA-IDXR292250W-6.5K-240V-GRY-DA-A1480 X B68 X C72MM	50W	6500	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
188	MAZDA-IDXR292250W-6.5K-240V-GRY-DA-EM-A1480 X B68 X C72MM	50W	6500	240V	GREY	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
189	MAZDA-IDXR292250W-6.5K-240V-GRY-PH-A1480 X B68 X C72MM	50W	6500	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
190	MAZDA-IDXR292250W-6.5K-240V-GRY-PH-EM-A1480 X B68 X C72MM	50W	6500	240V	GREY	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
191	MAZDA-IDXR292250W-6.5K-240V-GRY-10VDIM-A1480 X B68 X C72MM	50W	6500	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
192	MAZDA-IDXR292250W-6.5K-240V-GRY-10VDIM-EM-A1480 X B68 X C72MM	50W	6500	240V	GREY	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
193	MAZDA-IDXR292260W-3K-240V-GRY-ND-A1480 X B68 X C72MM	60W	3000	240V	GREY	NON EMERGENCY	ON - OFF	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
194	MAZDA-IDXR292260W-3K-240V-GRY-ND-EM-A1480 X B68 X C72MM	60W	3000	240V	GREY	3 HOUR EMERGENCY BACKUP	ON - OFF	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
195	MAZDA-IDXR292260W-3K-240V-GRY-DA-A1480 X B68 X C72MM	60W	3000	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
196	MAZDA-IDXR292260W-3K-240V-GRY-DA-EM-A1480 X B68 X C72MM	60W	3000	240V	GREY	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
197	MAZDA-IDXR292260W-3K-240V-GRY-PH-A1480 X B68 X C72MM	60W	3000	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
198	MAZDA-IDXR292260W-3K-240V-GRY-PH-EM-A1480 X B68 X C72MM	60W	3000	240V	GREY	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
199	MAZDA-IDXR292260W-3K-240V-GRY-10VDIM-A1480 X B68 X C72MM	60W	3000	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
200	MAZDA-IDXR292260W-3K-240V-GRY-10VDIM-EM-A1480 X B68 X C72MM	60W	3000	240V	GREY	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
201	MAZDA-IDXR292260W-4K-240V-GRY-ND-A1480 X B68 X C72MM	60W	4000	240V	GREY	NON EMERGENCY	ON - OFF	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	



DATASHEET

GENERATED ON: 04 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
202	MAZDA-IDXR292260W-4K-240V-GRY-ND-EM-A1480 X B68 X C72MM	60W	4000	240V	GREY	3 HOUR EMERGENCY BACKUP	ON - OFF	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
203	MAZDA-IDXR292260W-4K-240V-GRY-DA-A1480 X B68 X C72MM	60W	4000	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
204	MAZDA-IDXR292260W-4K-240V-GRY-DA-EM-A1480 X B68 X C72MM	60W	4000	240V	GREY	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
205	MAZDA-IDXR292260W-4K-240V-GRY-PH-A1480 X B68 X C72MM	60W	4000	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
206	MAZDA-IDXR292260W-4K-240V-GRY-PH-EM-A1480 X B68 X C72MM	60W	4000	240V	GREY	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
207	MAZDA-IDXR292260W-4K-240V-GRY-10VDIM-A1480 X B68 X C72MM	60W	4000	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
208	MAZDA-IDXR292260W-4K-240V-GRY-10VDIM-EM-A1480 X B68 X C72MM	60W	4000	240V	GREY	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	



DATASHEET

GENERATED ON: 04 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
209	MAZDA-IDXR292260W-5K-240V-GRY-ND-A1480 X B68 X C72MM	60W	5000	240V	GREY	NON EMERGENCY	ON - OFF	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
210	MAZDA-IDXR292260W-5K-240V-GRY-ND-EM-A1480 X B68 X C72MM	60W	5000	240V	GREY	3 HOUR EMERGENCY BACKUP	ON - OFF	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
211	MAZDA-IDXR292260W-5K-240V-GRY-DA-A1480 X B68 X C72MM	60W	5000	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
212	MAZDA-IDXR292260W-5K-240V-GRY-DA-EM-A1480 X B68 X C72MM	60W	5000	240V	GREY	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
213	MAZDA-IDXR292260W-5K-240V-GRY-PH-A1480 X B68 X C72MM	60W	5000	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
214	MAZDA-IDXR292260W-5K-240V-GRY-PH-EM-A1480 X B68 X C72MM	60W	5000	240V	GREY	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
215	MAZDA-IDXR292260W-5K-240V-GRY-10VDIM-A1480 X B68 X C72MM	60W	5000	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
216	MAZDA-IDXR292260W-5K-240V-GRY-10VDIM-EM-A1480 X B68 X C72MM	60W	5000	240V	GREY	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
217	MAZDA-IDXR292260W-6K-240V-GRY-ND-A1480 X B68 X C72MM	60W	6000	240V	GREY	NON EMERGENCY	ON - OFF	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
218	MAZDA-IDXR292260W-6K-240V-GRY-ND-EM-A1480 X B68 X C72MM	60W	6000	240V	GREY	3 HOUR EMERGENCY BACKUP	ON - OFF	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
219	MAZDA-IDXR292260W-6K-240V-GRY-DA-A1480 X B68 X C72MM	60W	6000	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
220	MAZDA-IDXR292260W-6K-240V-GRY-DA-EM-A1480 X B68 X C72MM	60W	6000	240V	GREY	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
221	MAZDA-IDXR292260W-6K-240V-GRY-PH-A1480 X B68 X C72MM	60W	6000	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
222	MAZDA-IDXR292260W-6K-240V-GRY-PH-EM-A1480 X B68 X C72MM	60W	6000	240V	GREY	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	



DATASHEET

GENERATED ON: 04 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
223	MAZDA-IDXR292260W-6K-240V-GRY-10VDIM-A1480 X B68 X C72MM	60W	6000	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
224	MAZDA-IDXR292260W-6K-240V-GRY-10VDIM-EM-A1480 X B68 X C72MM	60W	6000	240V	GREY	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
225	MAZDA-IDXR292260W-2.7K-240V-GRY-ND-A1480 X B68 X C72MM	60W	2700	240V	GREY	NON EMERGENCY	ON - OFF	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
226	MAZDA-IDXR292260W-2.7K-240V-GRY-ND-EM-A1480 X B68 X C72MM	60W	2700	240V	GREY	3 HOUR EMERGENCY BACKUP	ON - OFF	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
227	MAZDA-IDXR292260W-2.7K-240V-GRY-DA-A1480 X B68 X C72MM	60W	2700	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
228	MAZDA-IDXR292260W-2.7K-240V-GRY-DA-EM-A1480 X B68 X C72MM	60W	2700	240V	GREY	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
229	MAZDA-IDXR292260W-2.7K-240V-GRY-PH-A1480 X B68 X C72MM	60W	2700	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	



DATASHEET

GENERATED ON: 04 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
230	MAZDA-IDXR292260W-2.7K-240V-GRY-PH-EM-A1480 X B68 X C72MM	60W	2700	240V	GREY	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
231	MAZDA-IDXR292260W-2.7K-240V-GRY-10VDIM-A1480 X B68 X C72MM	60W	2700	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
232	MAZDA-IDXR292260W-2.7K-240V-GRY-10VDIM-EM-A1480 X B68 X C72MM	60W	2700	240V	GREY	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
233	MAZDA-IDXR292260W-6.5K-240V-GRY-ND-A1480 X B68 X C72MM	60W	6500	240V	GREY	NON EMERGENCY	ON - OFF	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
234	MAZDA-IDXR292260W-6.5K-240V-GRY-ND-EM-A1480 X B68 X C72MM	60W	6500	240V	GREY	3 HOUR EMERGENCY BACKUP	ON - OFF	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
235	MAZDA-IDXR292260W-6.5K-240V-GRY-DA-A1480 X B68 X C72MM	60W	6500	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
236	MAZDA-IDXR292260W-6.5K-240V-GRY-DA-EM-A1480 X B68 X C72MM	60W	6500	240V	GREY	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
237	MAZDA-IDXR292260W-6.5K-240V-GRY-PH-A1480 X B68 X C72MM	60W	6500	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
238	MAZDA-IDXR292260W-6.5K-240V-GRY-PH-EM-A1480 X B68 X C72MM	60W	6500	240V	GREY	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
239	MAZDA-IDXR292260W-6.5K-240V-GRY-10VDIM-A1480 X B68 X C72MM	60W	6500	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
240	MAZDA-IDXR292260W-6.5K-240V-GRY-10VDIM-EM-A1480 X B68 X C72MM	60W	6500	240V	GREY	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
241	MAZDA-IDXR292270W-3K-240V-GRY-ND-A1480 X B68 X C72MM	70W	3000	240V	GREY	NON EMERGENCY	ON - OFF	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
242	MAZDA-IDXR292270W-3K-240V-GRY-ND-EM-A1480 X B68 X C72MM	70W	3000	240V	GREY	3 HOUR EMERGENCY BACKUP	ON - OFF	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
243	MAZDA-IDXR292270W-3K-240V-GRY-DA-A1480 X B68 X C72MM	70W	3000	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	



#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
244	MAZDA-IDXR292270W-3K-240V-GRY-DA-EM-A1480 X B68 X C72MM	70W	3000	240V	GREY	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
245	MAZDA-IDXR292270W-3K-240V-GRY-PH-A1480 X B68 X C72MM	70W	3000	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
246	MAZDA-IDXR292270W-3K-240V-GRY-PH-EM-A1480 X B68 X C72MM	70W	3000	240V	GREY	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
247	MAZDA-IDXR292270W-3K-240V-GRY-10VDIM-A1480 X B68 X C72MM	70W	3000	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
248	MAZDA-IDXR292270W-3K-240V-GRY-10VDIM-EM-A1480 X B68 X C72MM	70W	3000	240V	GREY	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
249	MAZDA-IDXR292270W-4K-240V-GRY-ND-A1480 X B68 X C72MM	70W	4000	240V	GREY	NON EMERGENCY	ON - OFF	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
250	MAZDA-IDXR292270W-4K-240V-GRY-ND-EM-A1480 X B68 X C72MM	70W	4000	240V	GREY	3 HOUR EMERGENCY BACKUP	ON - OFF	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
251	MAZDA-IDXR292270W-4K-240V-GRY-DA-A1480 X B68 X C72MM	70W	4000	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
252	MAZDA-IDXR292270W-4K-240V-GRY-DA-EM-A1480 X B68 X C72MM	70W	4000	240V	GREY	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
253	MAZDA-IDXR292270W-4K-240V-GRY-PH-A1480 X B68 X C72MM	70W	4000	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
254	MAZDA-IDXR292270W-4K-240V-GRY-PH-EM-A1480 X B68 X C72MM	70W	4000	240V	GREY	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
255	MAZDA-IDXR292270W-4K-240V-GRY-10VDIM-A1480 X B68 X C72MM	70W	4000	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
256	MAZDA-IDXR292270W-4K-240V-GRY-10VDIM-EM-A1480 X B68 X C72MM	70W	4000	240V	GREY	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
257	MAZDA-IDXR292270W-5K-240V-GRY-ND-A1480 X B68 X C72MM	70W	5000	240V	GREY	NON EMERGENCY	ON - OFF	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	



DATASHEET

GENERATED ON: 04 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
258	MAZDA-IDXR292270W-5K-240V-GRY-ND-EM-A1480 X B68 X C72MM	70W	5000	240V	GREY	3 HOUR EMERGENCY BACKUP	ON - OFF	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
259	MAZDA-IDXR292270W-5K-240V-GRY-DA-A1480 X B68 X C72MM	70W	5000	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
260	MAZDA-IDXR292270W-5K-240V-GRY-DA-EM-A1480 X B68 X C72MM	70W	5000	240V	GREY	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
261	MAZDA-IDXR292270W-5K-240V-GRY-PH-A1480 X B68 X C72MM	70W	5000	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
262	MAZDA-IDXR292270W-5K-240V-GRY-PH-EM-A1480 X B68 X C72MM	70W	5000	240V	GREY	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
263	MAZDA-IDXR292270W-5K-240V-GRY-10VDIM-A1480 X B68 X C72MM	70W	5000	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
264	MAZDA-IDXR292270W-5K-240V-GRY-10VDIM-EM-A1480 X B68 X C72MM	70W	5000	240V	GREY	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
265	MAZDA-IDXR292270W-6K-240V-GRY-ND-A1480 X B68 X C72MM	70W	6000	240V	GREY	NON EMERGENCY	ON - OFF	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
266	MAZDA-IDXR292270W-6K-240V-GRY-ND-EM-A1480 X B68 X C72MM	70W	6000	240V	GREY	3 HOUR EMERGENCY BACKUP	ON - OFF	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
267	MAZDA-IDXR292270W-6K-240V-GRY-DA-A1480 X B68 X C72MM	70W	6000	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
268	MAZDA-IDXR292270W-6K-240V-GRY-DA-EM-A1480 X B68 X C72MM	70W	6000	240V	GREY	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
269	MAZDA-IDXR292270W-6K-240V-GRY-PH-A1480 X B68 X C72MM	70W	6000	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
270	MAZDA-IDXR292270W-6K-240V-GRY-PH-EM-A1480 X B68 X C72MM	70W	6000	240V	GREY	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
271	MAZDA-IDXR292270W-6K-240V-GRY-10VDIM-A1480 X B68 X C72MM	70W	6000	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
272	MAZDA-IDXR292270W-6K-240V-GRY-10VDIM-EM-A1480 X B68 X C72MM	70W	6000	240V	GREY	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
273	MAZDA-IDXR292270W-2.7K-240V-GRY-ND-A1480 X B68 X C72MM	70W	2700	240V	GREY	NON EMERGENCY	ON - OFF	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
274	MAZDA-IDXR292270W-2.7K-240V-GRY-ND-EM-A1480 X B68 X C72MM	70W	2700	240V	GREY	3 HOUR EMERGENCY BACKUP	ON - OFF	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
275	MAZDA-IDXR292270W-2.7K-240V-GRY-DA-A1480 X B68 X C72MM	70W	2700	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
276	MAZDA-IDXR292270W-2.7K-240V-GRY-DA-EM-A1480 X B68 X C72MM	70W	2700	240V	GREY	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
277	MAZDA-IDXR292270W-2.7K-240V-GRY-PH-A1480 X B68 X C72MM	70W	2700	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
278	MAZDA-IDXR292270W-2.7K-240V-GRY-PH-EM-A1480 X B68 X C72MM	70W	2700	240V	GREY	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	



DATASHEET

GENERATED ON: 04 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
279	MAZDA-IDXR292270W-2.7K-240V-GRY-10VDIM-A1480 X B68 X C72MM	70W	2700	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
280	MAZDA-IDXR292270W-2.7K-240V-GRY-10VDIM-EM-A1480 X B68 X C72MM	70W	2700	240V	GREY	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
281	MAZDA-IDXR292270W-6.5K-240V-GRY-ND-A1480 X B68 X C72MM	70W	6500	240V	GREY	NON EMERGENCY	ON - OFF	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
282	MAZDA-IDXR292270W-6.5K-240V-GRY-ND-EM-A1480 X B68 X C72MM	70W	6500	240V	GREY	3 HOUR EMERGENCY BACKUP	ON - OFF	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
283	MAZDA-IDXR292270W-6.5K-240V-GRY-DA-A1480 X B68 X C72MM	70W	6500	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
284	MAZDA-IDXR292270W-6.5K-240V-GRY-DA-EM-A1480 X B68 X C72MM	70W	6500	240V	GREY	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
285	MAZDA-IDXR292270W-6.5K-240V-GRY-PH-A1480 X B68 X C72MM	70W	6500	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
286	MAZDA-IDXR292270W-6.5K-240V-GRY-PH-EM-A1480 X B68 X C72MM	70W	6500	240V	GREY	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
287	MAZDA-IDXR292270W-6.5K-240V-GRY-10VDIM-A1480 X B68 X C72MM	70W	6500	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	
288	MAZDA-IDXR292270W-6.5K-240V-GRY-10VDIM-EM-A1480 X B68 X C72MM	70W	6500	240V	GREY	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	120	A1480 X B68 X C72MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1480 X B68 X C72MM	