



RANA

MAZDA Model: IDXR2910 INDUSTRIAL & TRIPROOF LIGHT

Rana Tri-Proof is IP66 luminaire for mounting on ceiling. Made of UV-stabilised polycarbonate. Rana LED waterproof is a very hardy luminaire, especially suitable for pig farms and the like. The LED compartment is IP66K protected to withstand ammonia gasses in such environments. The luminaire housing is made of hard UV-stabilised and anti-chemical coated polycarbonate. The coating is resistant to ammonia, washing detergents etc, and makes the it suitable also for car wash halls and similar. It is easy to install by just snapping into mounting clips and using the unique one-hand closing mechanism at both ends. The looping options with double cable gland in each end and through wiring gives full flexibility for larger installations.

ALL AVAILABLE VARIANTS

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
1	MAZDA-IDXR291020W-3K-240V-GRY-ND-A650 X B97 X C82MM	20W	3000	240V	GREY	NON EMERGENCY	ON - OFF	120	A650 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A650 X B97 X C82MM	
2	MAZDA-IDXR291020W-3K-240V-GRY-ND-EM-A650 X B97 X C82MM	20W	3000	240V	GREY	3 HOUR EMERGENCY BACKUP	ON - OFF	120	A650 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A650 X B97 X C82MM	
3	MAZDA-IDXR291020W-3K-240V-GRY-DA-A650 X B97 X C82MM	20W	3000	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	120	A650 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A650 X B97 X C82MM	
4	MAZDA-IDXR291020W-3K-240V-GRY-DA-EM-A650 X B97 X C82MM	20W	3000	240V	GREY	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	120	A650 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A650 X B97 X C82MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
5	MAZDA-IDXR291020W-3K-240V-GRY-PH-A650 X B97 X C82MM	20W	3000	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	120	A650 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A650 X B97 X C82MM	
6	MAZDA-IDXR291020W-3K-240V-GRY-PH-EM-A650 X B97 X C82MM	20W	3000	240V	GREY	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	120	A650 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A650 X B97 X C82MM	
7	MAZDA-IDXR291020W-3K-240V-GRY-10VDIM-A650 X B97 X C82MM	20W	3000	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	120	A650 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A650 X B97 X C82MM	
8	MAZDA-IDXR291020W-3K-240V-GRY-10VDIM-EM-A650 X B97 X C82MM	20W	3000	240V	GREY	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	120	A650 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A650 X B97 X C82MM	
9	MAZDA-IDXR291020W-4K-240V-GRY-ND-A650 X B97 X C82MM	20W	4000	240V	GREY	NON EMERGENCY	ON - OFF	120	A650 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A650 X B97 X C82MM	
10	MAZDA-IDXR291020W-4K-240V-GRY-ND-EM-A650 X B97 X C82MM	20W	4000	240V	GREY	3 HOUR EMERGENCY BACKUP	ON - OFF	120	A650 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A650 X B97 X C82MM	
11	MAZDA-IDXR291020W-4K-240V-GRY-DA-A650 X B97 X C82MM	20W	4000	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	120	A650 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A650 X B97 X C82MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
12	MAZDA-IDXR291020W-4K-240V-GRY-DA-EM-A650 X B97 X C82MM	20W	4000	240V	GREY	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	120	A650 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A650 X B97 X C82MM	
13	MAZDA-IDXR291020W-4K-240V-GRY-PH-A650 X B97 X C82MM	20W	4000	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	120	A650 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A650 X B97 X C82MM	
14	MAZDA-IDXR291020W-4K-240V-GRY-PH-EM-A650 X B97 X C82MM	20W	4000	240V	GREY	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	120	A650 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A650 X B97 X C82MM	
15	MAZDA-IDXR291020W-4K-240V-GRY-10VDIM-A650 X B97 X C82MM	20W	4000	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	120	A650 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A650 X B97 X C82MM	
16	MAZDA-IDXR291020W-4K-240V-GRY-10VDIM-EM-A650 X B97 X C82MM	20W	4000	240V	GREY	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	120	A650 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A650 X B97 X C82MM	
17	MAZDA-IDXR291020W-5K-240V-GRY-ND-A650 X B97 X C82MM	20W	5000	240V	GREY	NON EMERGENCY	ON - OFF	120	A650 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A650 X B97 X C82MM	
18	MAZDA-IDXR291020W-5K-240V-GRY-ND-EM-A650 X B97 X C82MM	20W	5000	240V	GREY	3 HOUR EMERGENCY BACKUP	ON - OFF	120	A650 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A650 X B97 X C82MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
19	MAZDA-IDXR291020W-5K-240V-GRY-DA-A650 X B97 X C82MM	20W	5000	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	120	A650 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A650 X B97 X C82MM	
20	MAZDA-IDXR291020W-5K-240V-GRY-DA-EM-A650 X B97 X C82MM	20W	5000	240V	GREY	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	120	A650 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A650 X B97 X C82MM	
21	MAZDA-IDXR291020W-5K-240V-GRY-PH-A650 X B97 X C82MM	20W	5000	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	120	A650 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A650 X B97 X C82MM	
22	MAZDA-IDXR291020W-5K-240V-GRY-PH-EM-A650 X B97 X C82MM	20W	5000	240V	GREY	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	120	A650 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A650 X B97 X C82MM	
23	MAZDA-IDXR291020W-5K-240V-GRY-10VDIM-A650 X B97 X C82MM	20W	5000	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	120	A650 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A650 X B97 X C82MM	
24	MAZDA-IDXR291020W-5K-240V-GRY-10VDIM-EM-A650 X B97 X C82MM	20W	5000	240V	GREY	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	120	A650 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A650 X B97 X C82MM	
25	MAZDA-IDXR291020W-6K-240V-GRY-ND-A650 X B97 X C82MM	20W	6000	240V	GREY	NON EMERGENCY	ON - OFF	120	A650 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A650 X B97 X C82MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
26	MAZDA-IDXR291020W-6K-240V-GRY-ND-EM-A650 X B97 X C82MM	20W	6000	240V	GREY	3 HOUR EMERGENCY BACKUP	ON - OFF	120	A650 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A650 X B97 X C82MM	
27	MAZDA-IDXR291020W-6K-240V-GRY-DA-A650 X B97 X C82MM	20W	6000	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	120	A650 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A650 X B97 X C82MM	
28	MAZDA-IDXR291020W-6K-240V-GRY-DA-EM-A650 X B97 X C82MM	20W	6000	240V	GREY	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	120	A650 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A650 X B97 X C82MM	
29	MAZDA-IDXR291020W-6K-240V-GRY-PH-A650 X B97 X C82MM	20W	6000	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	120	A650 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A650 X B97 X C82MM	
30	MAZDA-IDXR291020W-6K-240V-GRY-PH-EM-A650 X B97 X C82MM	20W	6000	240V	GREY	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	120	A650 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A650 X B97 X C82MM	
31	MAZDA-IDXR291020W-6K-240V-GRY-10VDIM-A650 X B97 X C82MM	20W	6000	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	120	A650 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A650 X B97 X C82MM	
32	MAZDA-IDXR291020W-6K-240V-GRY-10VDIM-EM-A650 X B97 X C82MM	20W	6000	240V	GREY	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	120	A650 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A650 X B97 X C82MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
33	MAZDA-IDXR291020W-2.7K-240V-GRY-ND-A650 X B97 X C82MM	20W	2700	240V	GREY	NON EMERGENCY	ON - OFF	120	A650 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A650 X B97 X C82MM	
34	MAZDA-IDXR291020W-2.7K-240V-GRY-ND-EM-A650 X B97 X C82MM	20W	2700	240V	GREY	3 HOUR EMERGENCY BACKUP	ON - OFF	120	A650 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A650 X B97 X C82MM	
35	MAZDA-IDXR291020W-2.7K-240V-GRY-DA-A650 X B97 X C82MM	20W	2700	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	120	A650 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A650 X B97 X C82MM	
36	MAZDA-IDXR291020W-2.7K-240V-GRY-DA-EM-A650 X B97 X C82MM	20W	2700	240V	GREY	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	120	A650 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A650 X B97 X C82MM	
37	MAZDA-IDXR291020W-2.7K-240V-GRY-PH-A650 X B97 X C82MM	20W	2700	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	120	A650 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A650 X B97 X C82MM	
38	MAZDA-IDXR291020W-2.7K-240V-GRY-PH-EM-A650 X B97 X C82MM	20W	2700	240V	GREY	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	120	A650 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A650 X B97 X C82MM	
39	MAZDA-IDXR291020W-2.7K-240V-GRY-10VDIM-A650 X B97 X C82MM	20W	2700	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	120	A650 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A650 X B97 X C82MM	



DATASHEET

GENERATED ON: 03 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
40	MAZDA-IDXR291020W-2.7K-240V-GRY-10VDIM-EM-A650 X B97 X C82MM	20W	2700	240V	GREY	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	120	A650 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A650 X B97 X C82MM	
41	MAZDA-IDXR291020W-6.5K-240V-GRY-ND-A650 X B97 X C82MM	20W	6500	240V	GREY	NON EMERGENCY	ON - OFF	120	A650 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A650 X B97 X C82MM	
42	MAZDA-IDXR291020W-6.5K-240V-GRY-ND-EM-A650 X B97 X C82MM	20W	6500	240V	GREY	3 HOUR EMERGENCY BACKUP	ON - OFF	120	A650 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A650 X B97 X C82MM	
43	MAZDA-IDXR291020W-6.5K-240V-GRY-DA-A650 X B97 X C82MM	20W	6500	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	120	A650 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A650 X B97 X C82MM	
44	MAZDA-IDXR291020W-6.5K-240V-GRY-DA-EM-A650 X B97 X C82MM	20W	6500	240V	GREY	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	120	A650 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A650 X B97 X C82MM	
45	MAZDA-IDXR291020W-6.5K-240V-GRY-PH-A650 X B97 X C82MM	20W	6500	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	120	A650 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A650 X B97 X C82MM	
46	MAZDA-IDXR291020W-6.5K-240V-GRY-PH-EM-A650 X B97 X C82MM	20W	6500	240V	GREY	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	120	A650 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A650 X B97 X C82MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
47	MAZDA-IDXR291020W-6.5K-240V-GRY-10VDIM-A650 X B97 X C82MM	20W	6500	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	120	A650 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A650 X B97 X C82MM	
48	MAZDA-IDXR291020W-6.5K-240V-GRY-10VDIM-EM-A650 X B97 X C82MM	20W	6500	240V	GREY	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	120	A650 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A650 X B97 X C82MM	
49	MAZDA-IDXR291036W-3K-240V-GRY-ND-A1220 X B97 X C82MM	36W	3000	240V	GREY	NON EMERGENCY	ON - OFF	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
50	MAZDA-IDXR291036W-3K-240V-GRY-ND-EM-A1220 X B97 X C82MM	36W	3000	240V	GREY	3 HOUR EMERGENCY BACKUP	ON - OFF	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
51	MAZDA-IDXR291036W-3K-240V-GRY-DA-A1220 X B97 X C82MM	36W	3000	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
52	MAZDA-IDXR291036W-3K-240V-GRY-DA-EM-A1220 X B97 X C82MM	36W	3000	240V	GREY	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
53	MAZDA-IDXR291036W-3K-240V-GRY-PH-A1220 X B97 X C82MM	36W	3000	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
54	MAZDA-IDXR291036W-3K-240V-GRY-PH-EM-A1220 X B97 X C82MM	36W	3000	240V	GREY	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
55	MAZDA-IDXR291036W-3K-240V-GRY-10VDIM-A1220 X B97 X C82MM	36W	3000	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
56	MAZDA-IDXR291036W-3K-240V-GRY-10VDIM-EM-A1220 X B97 X C82MM	36W	3000	240V	GREY	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
57	MAZDA-IDXR291036W-4K-240V-GRY-ND-A1220 X B97 X C82MM	36W	4000	240V	GREY	NON EMERGENCY	ON - OFF	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
58	MAZDA-IDXR291036W-4K-240V-GRY-ND-EM-A1220 X B97 X C82MM	36W	4000	240V	GREY	3 HOUR EMERGENCY BACKUP	ON - OFF	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
59	MAZDA-IDXR291036W-4K-240V-GRY-DA-A1220 X B97 X C82MM	36W	4000	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
60	MAZDA-IDXR291036W-4K-240V-GRY-DA-EM-A1220 X B97 X C82MM	36W	4000	240V	GREY	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
61	MAZDA-IDXR291036W-4K-240V-GRY-PH-A1220 X B97 X C82MM	36W	4000	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
62	MAZDA-IDXR291036W-4K-240V-GRY-PH-EM-A1220 X B97 X C82MM	36W	4000	240V	GREY	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
63	MAZDA-IDXR291036W-4K-240V-GRY-10VDIM-A1220 X B97 X C82MM	36W	4000	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
64	MAZDA-IDXR291036W-4K-240V-GRY-10VDIM-EM-A1220 X B97 X C82MM	36W	4000	240V	GREY	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
65	MAZDA-IDXR291036W-5K-240V-GRY-ND-A1220 X B97 X C82MM	36W	5000	240V	GREY	NON EMERGENCY	ON - OFF	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
66	MAZDA-IDXR291036W-5K-240V-GRY-ND-EM-A1220 X B97 X C82MM	36W	5000	240V	GREY	3 HOUR EMERGENCY BACKUP	ON - OFF	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
67	MAZDA-IDXR291036W-5K-240V-GRY-DA-A1220 X B97 X C82MM	36W	5000	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
68	MAZDA-IDXR291036W-5K-240V-GRY-DA-EM-A1220 X B97 X C82MM	36W	5000	240V	GREY	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
69	MAZDA-IDXR291036W-5K-240V-GRY-PH-A1220 X B97 X C82MM	36W	5000	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
70	MAZDA-IDXR291036W-5K-240V-GRY-PH-EM-A1220 X B97 X C82MM	36W	5000	240V	GREY	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
71	MAZDA-IDXR291036W-5K-240V-GRY-10VDIM-A1220 X B97 X C82MM	36W	5000	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
72	MAZDA-IDXR291036W-5K-240V-GRY-10VDIM-EM-A1220 X B97 X C82MM	36W	5000	240V	GREY	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
73	MAZDA-IDXR291036W-6K-240V-GRY-ND-A1220 X B97 X C82MM	36W	6000	240V	GREY	NON EMERGENCY	ON - OFF	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
74	MAZDA-IDXR291036W-6K-240V-GRY-ND-EM-A1220 X B97 X C82MM	36W	6000	240V	GREY	3 HOUR EMERGENCY BACKUP	ON - OFF	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
75	MAZDA-IDXR291036W-6K-240V-GRY-DA-A1220 X B97 X C82MM	36W	6000	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
76	MAZDA-IDXR291036W-6K-240V-GRY-DA-EM-A1220 X B97 X C82MM	36W	6000	240V	GREY	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
77	MAZDA-IDXR291036W-6K-240V-GRY-PH-A1220 X B97 X C82MM	36W	6000	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
78	MAZDA-IDXR291036W-6K-240V-GRY-PH-EM-A1220 X B97 X C82MM	36W	6000	240V	GREY	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
79	MAZDA-IDXR291036W-6K-240V-GRY-10VDIM-A1220 X B97 X C82MM	36W	6000	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
80	MAZDA-IDXR291036W-6K-240V-GRY-10VDIM-EM-A1220 X B97 X C82MM	36W	6000	240V	GREY	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
81	MAZDA-IDXR291036W-2.7K-240V-GRY-ND-A1220 X B97 X C82MM	36W	2700	240V	GREY	NON EMERGENCY	ON - OFF	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
82	MAZDA-IDXR291036W-2.7K-240V-GRY-ND-EM-A1220 X B97 X C82MM	36W	2700	240V	GREY	3 HOUR EMERGENCY BACKUP	ON - OFF	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
83	MAZDA-IDXR291036W-2.7K-240V-GRY-DA-A1220 X B97 X C82MM	36W	2700	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
84	MAZDA-IDXR291036W-2.7K-240V-GRY-DA-EM-A1220 X B97 X C82MM	36W	2700	240V	GREY	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
85	MAZDA-IDXR291036W-2.7K-240V-GRY-PH-A1220 X B97 X C82MM	36W	2700	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
86	MAZDA-IDXR291036W-2.7K-240V-GRY-PH-EM-A1220 X B97 X C82MM	36W	2700	240V	GREY	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
87	MAZDA-IDXR291036W-2.7K-240V-GRY-10VDIM-A1220 X B97 X C82MM	36W	2700	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
88	MAZDA-IDXR291036W-2.7K-240V-GRY-10VDIM-EM-A1220 X B97 X C82MM	36W	2700	240V	GREY	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
89	MAZDA-IDXR291036W-6.5K-240V-GRY-ND-A1220 X B97 X C82MM	36W	6500	240V	GREY	NON EMERGENCY	ON - OFF	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
90	MAZDA-IDXR291036W-6.5K-240V-GRY-ND-EM-A1220 X B97 X C82MM	36W	6500	240V	GREY	3 HOUR EMERGENCY BACKUP	ON - OFF	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
91	MAZDA-IDXR291036W-6.5K-240V-GRY-DA-A1220 X B97 X C82MM	36W	6500	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
92	MAZDA-IDXR291036W-6.5K-240V-GRY-DA-EM-A1220 X B97 X C82MM	36W	6500	240V	GREY	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
93	MAZDA-IDXR291036W-6.5K-240V-GRY-PH-A1220 X B97 X C82MM	36W	6500	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
94	MAZDA-IDXR291036W-6.5K-240V-GRY-PH-EM-A1220 X B97 X C82MM	36W	6500	240V	GREY	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
95	MAZDA-IDXR291036W-6.5K-240V-GRY-10VDIM-A1220 X B97 X C82MM	36W	6500	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
96	MAZDA-IDXR291036W-6.5K-240V-GRY-10VDIM-EM-A1220 X B97 X C82MM	36W	6500	240V	GREY	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
97	MAZDA-IDXR291040W-3K-240V-GRY-ND-A1220 X B97 X C82MM	40W	3000	240V	GREY	NON EMERGENCY	ON - OFF	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
98	MAZDA-IDXR291040W-3K-240V-GRY-ND-EM-A1220 X B97 X C82MM	40W	3000	240V	GREY	3 HOUR EMERGENCY BACKUP	ON - OFF	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
99	MAZDA-IDXR291040W-3K-240V-GRY-DA-A1220 X B97 X C82MM	40W	3000	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
100	MAZDA-IDXR291040W-3K-240V-GRY-DA-EM-A1220 X B97 X C82MM	40W	3000	240V	GREY	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
101	MAZDA-IDXR291040W-3K-240V-GRY-PH-A1220 X B97 X C82MM	40W	3000	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
102	MAZDA-IDXR291040W-3K-240V-GRY-PH-EM-A1220 X B97 X C82MM	40W	3000	240V	GREY	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
103	MAZDA-IDXR291040W-3K-240V-GRY-10VDIM-A1220 X B97 X C82MM	40W	3000	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
104	MAZDA-IDXR291040W-3K-240V-GRY-10VDIM-EM-A1220 X B97 X C82MM	40W	3000	240V	GREY	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
105	MAZDA-IDXR291040W-4K-240V-GRY-ND-A1220 X B97 X C82MM	40W	4000	240V	GREY	NON EMERGENCY	ON - OFF	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
106	MAZDA-IDXR291040W-4K-240V-GRY-ND-EM-A1220 X B97 X C82MM	40W	4000	240V	GREY	3 HOUR EMERGENCY BACKUP	ON - OFF	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
107	MAZDA-IDXR291040W-4K-240V-GRY-DA-A1220 X B97 X C82MM	40W	4000	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
108	MAZDA-IDXR291040W-4K-240V-GRY-DA-EM-A1220 X B97 X C82MM	40W	4000	240V	GREY	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
109	MAZDA-IDXR291040W-4K-240V-GRY-PH-A1220 X B97 X C82MM	40W	4000	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
110	MAZDA-IDXR291040W-4K-240V-GRY-PH-EM-A1220 X B97 X C82MM	40W	4000	240V	GREY	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
111	MAZDA-IDXR291040W-4K-240V-GRY-10VDIM-A1220 X B97 X C82MM	40W	4000	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
112	MAZDA-IDXR291040W-4K-240V-GRY-10VDIM-EM-A1220 X B97 X C82MM	40W	4000	240V	GREY	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
113	MAZDA-IDXR291040W-5K-240V-GRY-ND-A1220 X B97 X C82MM	40W	5000	240V	GREY	NON EMERGENCY	ON - OFF	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
114	MAZDA-IDXR291040W-5K-240V-GRY-ND-EM-A1220 X B97 X C82MM	40W	5000	240V	GREY	3 HOUR EMERGENCY BACKUP	ON - OFF	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
115	MAZDA-IDXR291040W-5K-240V-GRY-DA-A1220 X B97 X C82MM	40W	5000	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
116	MAZDA-IDXR291040W-5K-240V-GRY-DA-EM-A1220 X B97 X C82MM	40W	5000	240V	GREY	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
117	MAZDA-IDXR291040W-5K-240V-GRY-PH-A1220 X B97 X C82MM	40W	5000	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
118	MAZDA-IDXR291040W-5K-240V-GRY-PH-EM-A1220 X B97 X C82MM	40W	5000	240V	GREY	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
119	MAZDA-IDXR291040W-5K-240V-GRY-10VDIM-A1220 X B97 X C82MM	40W	5000	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
120	MAZDA-IDXR291040W-5K-240V-GRY-10VDIM-EM-A1220 X B97 X C82MM	40W	5000	240V	GREY	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
121	MAZDA-IDXR291040W-6K-240V-GRY-ND-A1220 X B97 X C82MM	40W	6000	240V	GREY	NON EMERGENCY	ON - OFF	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
122	MAZDA-IDXR291040W-6K-240V-GRY-ND-EM-A1220 X B97 X C82MM	40W	6000	240V	GREY	3 HOUR EMERGENCY BACKUP	ON - OFF	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
123	MAZDA-IDXR291040W-6K-240V-GRY-DA-A1220 X B97 X C82MM	40W	6000	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	



DATASHEET

GENERATED ON: 03 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
124	MAZDA-IDXR291040W-6K-240V-GRY-DA-EM-A1220 X B97 X C82MM	40W	6000	240V	GREY	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
125	MAZDA-IDXR291040W-6K-240V-GRY-PH-A1220 X B97 X C82MM	40W	6000	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
126	MAZDA-IDXR291040W-6K-240V-GRY-PH-EM-A1220 X B97 X C82MM	40W	6000	240V	GREY	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
127	MAZDA-IDXR291040W-6K-240V-GRY-10VDIM-A1220 X B97 X C82MM	40W	6000	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
128	MAZDA-IDXR291040W-6K-240V-GRY-10VDIM-EM-A1220 X B97 X C82MM	40W	6000	240V	GREY	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
129	MAZDA-IDXR291040W-2.7K-240V-GRY-ND-A1220 X B97 X C82MM	40W	2700	240V	GREY	NON EMERGENCY	ON - OFF	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
130	MAZDA-IDXR291040W-2.7K-240V-GRY-ND-EM-A1220 X B97 X C82MM	40W	2700	240V	GREY	3 HOUR EMERGENCY BACKUP	ON - OFF	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	



DATASHEET

GENERATED ON: 03 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
131	MAZDA-IDXR291040W-2.7K-240V-GRY-DA-A1220 X B97 X C82MM	40W	2700	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
132	MAZDA-IDXR291040W-2.7K-240V-GRY-DA-EM-A1220 X B97 X C82MM	40W	2700	240V	GREY	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
133	MAZDA-IDXR291040W-2.7K-240V-GRY-PH-A1220 X B97 X C82MM	40W	2700	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
134	MAZDA-IDXR291040W-2.7K-240V-GRY-PH-EM-A1220 X B97 X C82MM	40W	2700	240V	GREY	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
135	MAZDA-IDXR291040W-2.7K-240V-GRY-10VDIM-A1220 X B97 X C82MM	40W	2700	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
136	MAZDA-IDXR291040W-2.7K-240V-GRY-10VDIM-EM-A1220 X B97 X C82MM	40W	2700	240V	GREY	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
137	MAZDA-IDXR291040W-6.5K-240V-GRY-ND-A1220 X B97 X C82MM	40W	6500	240V	GREY	NON EMERGENCY	ON - OFF	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
138	MAZDA-IDXR291040W-6.5K-240V-GRY-ND-EM-A1220 X B97 X C82MM	40W	6500	240V	GREY	3 HOUR EMERGENCY BACKUP	ON - OFF	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
139	MAZDA-IDXR291040W-6.5K-240V-GRY-DA-A1220 X B97 X C82MM	40W	6500	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
140	MAZDA-IDXR291040W-6.5K-240V-GRY-DA-EM-A1220 X B97 X C82MM	40W	6500	240V	GREY	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
141	MAZDA-IDXR291040W-6.5K-240V-GRY-PH-A1220 X B97 X C82MM	40W	6500	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
142	MAZDA-IDXR291040W-6.5K-240V-GRY-PH-EM-A1220 X B97 X C82MM	40W	6500	240V	GREY	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
143	MAZDA-IDXR291040W-6.5K-240V-GRY-10VDIM-A1220 X B97 X C82MM	40W	6500	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
144	MAZDA-IDXR291040W-6.5K-240V-GRY-10VDIM-EM-A1220 X B97 X C82MM	40W	6500	240V	GREY	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
145	MAZDA-IDXR291050W-3K-240V-GRY-ND-A1220 X B97 X C82MM	50W	3000	240V	GREY	NON EMERGENCY	ON - OFF	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
146	MAZDA-IDXR291050W-3K-240V-GRY-ND-EM-A1220 X B97 X C82MM	50W	3000	240V	GREY	3 HOUR EMERGENCY BACKUP	ON - OFF	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
147	MAZDA-IDXR291050W-3K-240V-GRY-DA-A1220 X B97 X C82MM	50W	3000	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
148	MAZDA-IDXR291050W-3K-240V-GRY-DA-EM-A1220 X B97 X C82MM	50W	3000	240V	GREY	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
149	MAZDA-IDXR291050W-3K-240V-GRY-PH-A1220 X B97 X C82MM	50W	3000	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	
150	MAZDA-IDXR291050W-3K-240V-GRY-PH-EM-A1220 X B97 X C82MM	50W	3000	240V	GREY	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	120	A1220 X B97 X C82MM	INJECTION MOULDED, IN GREY POLYCARBONATE, VANDAL RESISTANT, UV STABILIZED, HIGH MECHANICAL RESISTANCE DUE TO THE FRAME REINFORCED BY INTERNAL RIBBING	IK08	A1220 X B97 X C82MM	