DATASHEET

GENERATED ON: 15 Nov 2026 | SYS.REF: MAZDA-LED



TANK

MAZDA Model: FXR30200 Flood Light

Tank LED Flood Lights are broad-beamed, high-intensity artificial lights. They are often used to illuminate outdoor playing fields while an outdoor sports event is being held during low-light conditions. The white beam of light produced by it is very much similar to daylight. When used in stadiums, it makes the spectators feel as though it is day time. Tank LED Flood Lights are impervious to temperature fluctuations and environmental conditions. Unlike some other lights, LEDs remain stable & functional even in freezing conditions. This makes them all the more ideal for cold warehouses and storage areas.
Being free of Mercury, Lead and Carbon Emissions, Tank LED Flood Lights do not give out any harmful emissions such as carbon. As a result, they are much friendlier to the environment and also to the health of people nearby. What's more, they do not emanate heat and conserve the maximum amount of electricity, which also leads to longevity and safety. It is of IP Rate 67, which means its excellent performance in waterproof, Energy Friendly. LED flood lights eliminate the need for frequent bulb replacements, and you can save as much as %80 on electricity costs, Una ected by Weather and Temperature Changes. Tank LED flood lights are impervious to temperature fluctuations and environmental conditions.

ALL AVAILABLE VARIANTS

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions Price
1	MAZDA-FXR3020050W-3K-240V-BL-ND-A352 X B175 X C104 MM	50W	3000	240V	BLACK / GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A352 X B175 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B175 X C104 MM
2	MAZDA-FXR3020050W-3K-240V-BL-DA-A352 X B175 X C104 MM	50W	3000	240V	BLACK / GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A352 X B175 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B175 X C104 MM
3	MAZDA-FXR3020050W-3K-240V-BL-PH-A352 X B175 X C104 MM	50W	3000	240V	BLACK / GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A352 X B175 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B175 X C104 MM
4	MAZDA-FXR3020050W-3K-240V-BL-10VDIM-A352 X B175 X C104 MM	50W	3000	240V	BLACK / GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A352 X B175 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B175 X C104 MM
5	MAZDA-FXR3020050W-4K-240V-BL-ND-A352 X B175 X C104 MM	50W	4000	240V	BLACK / GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A352 X B175 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B175 X C104 MM
6	MAZDA-FXR3020050W-4K-240V-BL-DA-A352 X B175 X C104 MM	50W	4000	240V	BLACK / GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A352 X B175 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B175 X C104 MM
7	MAZDA-FXR3020050W-4K-240V-BL-PH-A352 X B175 X C104 MM	50W	4000	240V	BLACK / GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A352 X B175 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B175 X C104 MM
8	MAZDA-FXR3020050W-4K-240V-BL-10VDIM-A352 X B175 X C104 MM	50W	4000	240V	BLACK / GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A352 X B175 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B175 X C104 MM
9	MAZDA-FXR3020050W-5K-240V-BL-ND-A352 X B175 X C104 MM	50W	5000	240V	BLACK / GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A352 X B175 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B175 X C104 MM
10	MAZDA-FXR3020050W-5K-240V-BL-DA-A352 X B175 X C104 MM	50W	5000	240V	BLACK / GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A352 X B175 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B175 X C104 MM
11	MAZDA-FXR3020050W-5K-240V-BL-PH-A352 X B175 X C104 MM	50W	5000	240V	BLACK / GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A352 X B175 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B175 X C104 MM
12	MAZDA-FXR3020050W-5K-240V-BL-10VDIM-A352 X B175 X C104 MM	50W	5000	240V	BLACK / GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A352 X B175 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B175 X C104 MM
13	MAZDA-FXR3020050W-6K-240V-BL-ND-A352 X B175 X C104 MM	50W	6000	240V	BLACK / GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A352 X B175 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B175 X C104 MM

DATASHEET

GENERATED ON: 15 Nov 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions Price
14	MAZDA-FXR3020050W-6K-240V-BL-DA-A352 X B175 X C104 MM	50W	6000	240V	BLACK / GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A352 X B175 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B175 X C104 MM
15	MAZDA-FXR3020050W-6K-240V-BL-PH-A352 X B175 X C104 MM	50W	6000	240V	BLACK / GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A352 X B175 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B175 X C104 MM
16	MAZDA-FXR3020050W-6K-240V-BL-10VDIM-A352 X B175 X C104 MM	50W	6000	240V	BLACK / GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A352 X B175 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B175 X C104 MM
17	MAZDA-FXR3020050W-2.7K-240V-BL-ND-A352 X B175 X C104 MM	50W	2700	240V	BLACK / GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A352 X B175 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B175 X C104 MM
18	MAZDA-FXR3020050W-2.7K-240V-BL-DA-A352 X B175 X C104 MM	50W	2700	240V	BLACK / GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A352 X B175 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B175 X C104 MM
19	MAZDA-FXR3020050W-2.7K-240V-BL-PH-A352 X B175 X C104 MM	50W	2700	240V	BLACK / GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A352 X B175 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B175 X C104 MM
20	MAZDA-FXR3020050W-2.7K-240V-BL-10VDIM-A352 X B175 X C104 MM	50W	2700	240V	BLACK / GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A352 X B175 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B175 X C104 MM
21	MAZDA-FXR3020050W-6.5K-240V-BL-ND-A352 X B175 X C104 MM	50W	6500	240V	BLACK / GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A352 X B175 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B175 X C104 MM
22	MAZDA-FXR3020050W-6.5K-240V-BL-DA-A352 X B175 X C104 MM	50W	6500	240V	BLACK / GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A352 X B175 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B175 X C104 MM
23	MAZDA-FXR3020050W-6.5K-240V-BL-PH-A352 X B175 X C104 MM	50W	6500	240V	BLACK / GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A352 X B175 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B175 X C104 MM
24	MAZDA-FXR3020050W-6.5K-240V-BL-10VDIM-A352 X B175 X C104 MM	50W	6500	240V	BLACK / GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A352 X B175 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B175 X C104 MM
25	MAZDA-FXR30200100W-3K-240V-BL-ND-A352 X B211 X C104 MM	100W	3000	240V	BLACK / GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A352 X B211 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B211 X C104 MM
26	MAZDA-FXR30200100W-3K-240V-BL-DA-A352 X B211 X C104 MM	100W	3000	240V	BLACK / GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A352 X B211 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B211 X C104 MM
27	MAZDA-FXR30200100W-3K-240V-BL-PH-A352 X B211 X C104 MM	100W	3000	240V	BLACK / GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A352 X B211 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B211 X C104 MM
28	MAZDA-FXR30200100W-3K-240V-BL-10VDIM-A352 X B211 X C104 MM	100W	3000	240V	BLACK / GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A352 X B211 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B211 X C104 MM
29	MAZDA-FXR30200100W-4K-240V-BL-ND-A352 X B211 X C104 MM	100W	4000	240V	BLACK / GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A352 X B211 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B211 X C104 MM
30	MAZDA-FXR30200100W-4K-240V-BL-DA-A352 X B211 X C104 MM	100W	4000	240V	BLACK / GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A352 X B211 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B211 X C104 MM
31	MAZDA-FXR30200100W-4K-240V-BL-PH-A352 X B211 X C104 MM	100W	4000	240V	BLACK / GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A352 X B211 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B211 X C104 MM
32	MAZDA-FXR30200100W-4K-240V-BL-10VDIM-A352 X B211 X C104 MM	100W	4000	240V	BLACK / GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A352 X B211 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B211 X C104 MM
33	MAZDA-FXR30200100W-5K-240V-BL-ND-A352 X B211 X C104 MM	100W	5000	240V	BLACK / GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A352 X B211 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B211 X C104 MM
34	MAZDA-FXR30200100W-5K-240V-BL-DA-A352 X B211 X C104 MM	100W	5000	240V	BLACK / GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A352 X B211 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B211 X C104 MM
35	MAZDA-FXR30200100W-5K-240V-BL-PH-A352 X B211 X C104 MM	100W	5000	240V	BLACK / GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A352 X B211 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B211 X C104 MM
36	MAZDA-FXR30200100W-5K-240V-BL-10VDIM-A352 X B211 X C104 MM	100W	5000	240V	BLACK / GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A352 X B211 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B211 X C104 MM
37	MAZDA-FXR30200100W-6K-240V-BL-ND-A352 X B211 X C104 MM	100W	6000	240V	BLACK / GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A352 X B211 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B211 X C104 MM
38	MAZDA-FXR30200100W-6K-240V-BL-DA-A352 X B211 X C104 MM	100W	6000	240V	BLACK / GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A352 X B211 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B211 X C104 MM
39	MAZDA-FXR30200100W-6K-240V-BL-PH-A352 X B211 X C104 MM	100W	6000	240V	BLACK / GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A352 X B211 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B211 X C104 MM
40	MAZDA-FXR30200100W-6K-240V-BL-10VDIM-A352 X B211 X C104 MM	100W	6000	240V	BLACK / GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A352 X B211 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B211 X C104 MM

DATASHEET

GENERATED ON: 15 Nov 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions Price
41	MAZDA-FXR30200100W-2.7K-240V-BL-ND-A352 X B211 X C104 MM	100W	2700	240V	BLACK / GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A352 X B211 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B211 X C104 MM
42	MAZDA-FXR30200100W-2.7K-240V-BL-DA-A352 X B211 X C104 MM	100W	2700	240V	BLACK / GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A352 X B211 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B211 X C104 MM
43	MAZDA-FXR30200100W-2.7K-240V-BL-PH-A352 X B211 X C104 MM	100W	2700	240V	BLACK / GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A352 X B211 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B211 X C104 MM
44	MAZDA-FXR30200100W-2.7K-240V-BL-10VDIM-A352 X B211 X C104 MM	100W	2700	240V	BLACK / GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A352 X B211 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B211 X C104 MM
45	MAZDA-FXR30200100W-6.5K-240V-BL-ND-A352 X B211 X C104 MM	100W	6500	240V	BLACK / GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A352 X B211 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B211 X C104 MM
46	MAZDA-FXR30200100W-6.5K-240V-BL-DA-A352 X B211 X C104 MM	100W	6500	240V	BLACK / GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A352 X B211 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B211 X C104 MM
47	MAZDA-FXR30200100W-6.5K-240V-BL-PH-A352 X B211 X C104 MM	100W	6500	240V	BLACK / GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A352 X B211 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B211 X C104 MM
48	MAZDA-FXR30200100W-6.5K-240V-BL-10VDIM-A352 X B211 X C104 MM	100W	6500	240V	BLACK / GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A352 X B211 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B211 X C104 MM
49	MAZDA-FXR30200150W-3K-240V-BL-ND-A352 X B255 X C104 MM	150W	3000	240V	BLACK / GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A352 X B255 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B255 X C104 MM
50	MAZDA-FXR30200150W-3K-240V-BL-DA-A352 X B255 X C104 MM	150W	3000	240V	BLACK / GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A352 X B255 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B255 X C104 MM
51	MAZDA-FXR30200150W-3K-240V-BL-PH-A352 X B255 X C104 MM	150W	3000	240V	BLACK / GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A352 X B255 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B255 X C104 MM
52	MAZDA-FXR30200150W-3K-240V-BL-10VDIM-A352 X B255 X C104 MM	150W	3000	240V	BLACK / GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A352 X B255 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B255 X C104 MM
53	MAZDA-FXR30200150W-4K-240V-BL-ND-A352 X B255 X C104 MM	150W	4000	240V	BLACK / GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A352 X B255 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B255 X C104 MM
54	MAZDA-FXR30200150W-4K-240V-BL-DA-A352 X B255 X C104 MM	150W	4000	240V	BLACK / GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A352 X B255 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B255 X C104 MM
55	MAZDA-FXR30200150W-4K-240V-BL-PH-A352 X B255 X C104 MM	150W	4000	240V	BLACK / GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A352 X B255 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B255 X C104 MM
56	MAZDA-FXR30200150W-4K-240V-BL-10VDIM-A352 X B255 X C104 MM	150W	4000	240V	BLACK / GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A352 X B255 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B255 X C104 MM
57	MAZDA-FXR30200150W-5K-240V-BL-ND-A352 X B255 X C104 MM	150W	5000	240V	BLACK / GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A352 X B255 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B255 X C104 MM
58	MAZDA-FXR30200150W-5K-240V-BL-DA-A352 X B255 X C104 MM	150W	5000	240V	BLACK / GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A352 X B255 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B255 X C104 MM
59	MAZDA-FXR30200150W-5K-240V-BL-PH-A352 X B255 X C104 MM	150W	5000	240V	BLACK / GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A352 X B255 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B255 X C104 MM
60	MAZDA-FXR30200150W-5K-240V-BL-10VDIM-A352 X B255 X C104 MM	150W	5000	240V	BLACK / GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A352 X B255 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B255 X C104 MM
61	MAZDA-FXR30200150W-6K-240V-BL-ND-A352 X B255 X C104 MM	150W	6000	240V	BLACK / GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A352 X B255 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B255 X C104 MM
62	MAZDA-FXR30200150W-6K-240V-BL-DA-A352 X B255 X C104 MM	150W	6000	240V	BLACK / GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A352 X B255 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B255 X C104 MM
63	MAZDA-FXR30200150W-6K-240V-BL-PH-A352 X B255 X C104 MM	150W	6000	240V	BLACK / GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A352 X B255 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B255 X C104 MM
64	MAZDA-FXR30200150W-6K-240V-BL-10VDIM-A352 X B255 X C104 MM	150W	6000	240V	BLACK / GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A352 X B255 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B255 X C104 MM
65	MAZDA-FXR30200150W-2.7K-240V-BL-ND-A352 X B255 X C104 MM	150W	2700	240V	BLACK / GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A352 X B255 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B255 X C104 MM
66	MAZDA-FXR30200150W-2.7K-240V-BL-DA-A352 X B255 X C104 MM	150W	2700	240V	BLACK / GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A352 X B255 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B255 X C104 MM
67	MAZDA-FXR30200150W-2.7K-240V-BL-PH-A352 X B255 X C104 MM	150W	2700	240V	BLACK / GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A352 X B255 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B255 X C104 MM

DATASHEET

GENERATED ON: 15 Nov 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions Price
68	MAZDA-FXR30200150W-2.7K-240V-BL-10VDIM-A352 X B255 X C104 MM	150W	2700	240V	BLACK / GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A352 X B255 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B255 X C104 MM
69	MAZDA-FXR30200150W-6.5K-240V-BL-ND-A352 X B255 X C104 MM	150W	6500	240V	BLACK / GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A352 X B255 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B255 X C104 MM
70	MAZDA-FXR30200150W-6.5K-240V-BL-DA-A352 X B255 X C104 MM	150W	6500	240V	BLACK / GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A352 X B255 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B255 X C104 MM
71	MAZDA-FXR30200150W-6.5K-240V-BL-PH-A352 X B255 X C104 MM	150W	6500	240V	BLACK / GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A352 X B255 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B255 X C104 MM
72	MAZDA-FXR30200150W-6.5K-240V-BL-10VDIM-A352 X B255 X C104 MM	150W	6500	240V	BLACK / GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A352 X B255 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B255 X C104 MM
73	MAZDA-FXR30200200W-3K-240V-BL-ND-A352 X B336 X C104 MM	200W	3000	240V	BLACK / GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A352 X B336 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B336 X C104 MM
74	MAZDA-FXR30200200W-3K-240V-BL-DA-A352 X B336 X C104 MM	200W	3000	240V	BLACK / GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A352 X B336 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B336 X C104 MM
75	MAZDA-FXR30200200W-3K-240V-BL-PH-A352 X B336 X C104 MM	200W	3000	240V	BLACK / GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A352 X B336 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B336 X C104 MM
76	MAZDA-FXR30200200W-3K-240V-BL-10VDIM-A352 X B336 X C104 MM	200W	3000	240V	BLACK / GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A352 X B336 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B336 X C104 MM
77	MAZDA-FXR30200200W-4K-240V-BL-ND-A352 X B336 X C104 MM	200W	4000	240V	BLACK / GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A352 X B336 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B336 X C104 MM
78	MAZDA-FXR30200200W-4K-240V-BL-DA-A352 X B336 X C104 MM	200W	4000	240V	BLACK / GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A352 X B336 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B336 X C104 MM
79	MAZDA-FXR30200200W-4K-240V-BL-PH-A352 X B336 X C104 MM	200W	4000	240V	BLACK / GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A352 X B336 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B336 X C104 MM
80	MAZDA-FXR30200200W-4K-240V-BL-10VDIM-A352 X B336 X C104 MM	200W	4000	240V	BLACK / GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A352 X B336 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B336 X C104 MM
81	MAZDA-FXR30200200W-5K-240V-BL-ND-A352 X B336 X C104 MM	200W	5000	240V	BLACK / GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A352 X B336 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B336 X C104 MM
82	MAZDA-FXR30200200W-5K-240V-BL-DA-A352 X B336 X C104 MM	200W	5000	240V	BLACK / GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A352 X B336 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B336 X C104 MM
83	MAZDA-FXR30200200W-5K-240V-BL-PH-A352 X B336 X C104 MM	200W	5000	240V	BLACK / GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A352 X B336 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B336 X C104 MM
84	MAZDA-FXR30200200W-5K-240V-BL-10VDIM-A352 X B336 X C104 MM	200W	5000	240V	BLACK / GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A352 X B336 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B336 X C104 MM
85	MAZDA-FXR30200200W-6K-240V-BL-ND-A352 X B336 X C104 MM	200W	6000	240V	BLACK / GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A352 X B336 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B336 X C104 MM
86	MAZDA-FXR30200200W-6K-240V-BL-DA-A352 X B336 X C104 MM	200W	6000	240V	BLACK / GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A352 X B336 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B336 X C104 MM
87	MAZDA-FXR30200200W-6K-240V-BL-PH-A352 X B336 X C104 MM	200W	6000	240V	BLACK / GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A352 X B336 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B336 X C104 MM
88	MAZDA-FXR30200200W-6K-240V-BL-10VDIM-A352 X B336 X C104 MM	200W	6000	240V	BLACK / GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A352 X B336 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B336 X C104 MM
89	MAZDA-FXR30200200W-2.7K-240V-BL-ND-A352 X B336 X C104 MM	200W	2700	240V	BLACK / GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A352 X B336 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B336 X C104 MM
90	MAZDA-FXR30200200W-2.7K-240V-BL-DA-A352 X B336 X C104 MM	200W	2700	240V	BLACK / GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A352 X B336 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B336 X C104 MM
91	MAZDA-FXR30200200W-2.7K-240V-BL-PH-A352 X B336 X C104 MM	200W	2700	240V	BLACK / GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A352 X B336 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B336 X C104 MM
92	MAZDA-FXR30200200W-2.7K-240V-BL-10VDIM-A352 X B336 X C104 MM	200W	2700	240V	BLACK / GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A352 X B336 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B336 X C104 MM
93	MAZDA-FXR30200200W-6.5K-240V-BL-ND-A352 X B336 X C104 MM	200W	6500	240V	BLACK / GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A352 X B336 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B336 X C104 MM
94	MAZDA-FXR30200200W-6.5K-240V-BL-DA-A352 X B336 X C104 MM	200W	6500	240V	BLACK / GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A352 X B336 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B336 X C104 MM

DATASHEET

GENERATED ON: 15 Nov 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
95	MAZDA-FXR30200200W-6.5K-240V-BL-PH-A352 X B336 X C104 MM	200W	6500	240V	BLACK / GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A352 X B336 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B336 X C104 MM	
96	MAZDA-FXR30200200W-6.5K-240V-BL-10VDIM-A352 X B336 X C104 MM	200W	6500	240V	BLACK / GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A352 X B336 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B336 X C104 MM	
97	MAZDA-FXR30200250W-3K-240V-BL-ND-A352 X B416 X C104 MM	250W	3000	240V	BLACK / GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A352 X B416 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B416 X C104 MM	
98	MAZDA-FXR30200250W-3K-240V-BL-DA-A352 X B416 X C104 MM	250W	3000	240V	BLACK / GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A352 X B416 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B416 X C104 MM	
99	MAZDA-FXR30200250W-3K-240V-BL-PH-A352 X B416 X C104 MM	250W	3000	240V	BLACK / GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A352 X B416 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B416 X C104 MM	
100	MAZDA-FXR30200250W-3K-240V-BL-10VDIM-A352 X B416 X C104 MM	250W	3000	240V	BLACK / GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A352 X B416 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B416 X C104 MM	
101	MAZDA-FXR30200250W-4K-240V-BL-ND-A352 X B416 X C104 MM	250W	4000	240V	BLACK / GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A352 X B416 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B416 X C104 MM	
102	MAZDA-FXR30200250W-4K-240V-BL-DA-A352 X B416 X C104 MM	250W	4000	240V	BLACK / GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A352 X B416 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B416 X C104 MM	
103	MAZDA-FXR30200250W-4K-240V-BL-PH-A352 X B416 X C104 MM	250W	4000	240V	BLACK / GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A352 X B416 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B416 X C104 MM	
104	MAZDA-FXR30200250W-4K-240V-BL-10VDIM-A352 X B416 X C104 MM	250W	4000	240V	BLACK / GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A352 X B416 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B416 X C104 MM	
105	MAZDA-FXR30200250W-5K-240V-BL-ND-A352 X B416 X C104 MM	250W	5000	240V	BLACK / GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A352 X B416 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B416 X C104 MM	
106	MAZDA-FXR30200250W-5K-240V-BL-DA-A352 X B416 X C104 MM	250W	5000	240V	BLACK / GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A352 X B416 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B416 X C104 MM	
107	MAZDA-FXR30200250W-5K-240V-BL-PH-A352 X B416 X C104 MM	250W	5000	240V	BLACK / GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A352 X B416 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B416 X C104 MM	
108	MAZDA-FXR30200250W-5K-240V-BL-10VDIM-A352 X B416 X C104 MM	250W	5000	240V	BLACK / GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A352 X B416 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B416 X C104 MM	
109	MAZDA-FXR30200250W-6K-240V-BL-ND-A352 X B416 X C104 MM	250W	6000	240V	BLACK / GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A352 X B416 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B416 X C104 MM	
110	MAZDA-FXR30200250W-6K-240V-BL-DA-A352 X B416 X C104 MM	250W	6000	240V	BLACK / GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A352 X B416 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B416 X C104 MM	
111	MAZDA-FXR30200250W-6K-240V-BL-PH-A352 X B416 X C104 MM	250W	6000	240V	BLACK / GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A352 X B416 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B416 X C104 MM	
112	MAZDA-FXR30200250W-6K-240V-BL-10VDIM-A352 X B416 X C104 MM	250W	6000	240V	BLACK / GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A352 X B416 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B416 X C104 MM	
113	MAZDA-FXR30200250W-2.7K-240V-BL-ND-A352 X B416 X C104 MM	250W	2700	240V	BLACK / GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A352 X B416 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B416 X C104 MM	
114	MAZDA-FXR30200250W-2.7K-240V-BL-DA-A352 X B416 X C104 MM	250W	2700	240V	BLACK / GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A352 X B416 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B416 X C104 MM	
115	MAZDA-FXR30200250W-2.7K-240V-BL-PH-A352 X B416 X C104 MM	250W	2700	240V	BLACK / GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A352 X B416 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B416 X C104 MM	
116	MAZDA-FXR30200250W-2.7K-240V-BL-10VDIM-A352 X B416 X C104 MM	250W	2700	240V	BLACK / GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A352 X B416 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B416 X C104 MM	
117	MAZDA-FXR30200250W-6.5K-240V-BL-ND-A352 X B416 X C104 MM	250W	6500	240V	BLACK / GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A352 X B416 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B416 X C104 MM	
118	MAZDA-FXR30200250W-6.5K-240V-BL-DA-A352 X B416 X C104 MM	250W	6500	240V	BLACK / GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A352 X B416 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B416 X C104 MM	
119	MAZDA-FXR30200250W-6.5K-240V-BL-PH-A352 X B416 X C104 MM	250W	6500	240V	BLACK / GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A352 X B416 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B416 X C104 MM	
120	MAZDA-FXR30200250W-6.5K-240V-BL-10VDIM-A352 X B416 X C104 MM	250W	6500	240V	BLACK / GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A352 X B416 X C104 MM	DIE CAST ALUMINUM	IP67	A352 X B416 X C104 MM	
121	MAZDA-FXR30200400W-3K-240V-BL-ND-A665 X B315 X C110 MM	400W	3000	240V	BLACK / GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A665 X B315 X C110 MM	DIE CAST ALUMINUM	IP67	A665 X B315 X C110 MM	

DATASHEET

GENERATED ON: 15 Nov 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions Price
122	MAZDA-FXR30200400W-3K-240V-BL-DA-A665 X B315 X C110 MM	400W	3000	240V	BLACK / GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A665 X B315 X C110 MM	DIE CAST ALUMINUM	IP67	A665 X B315 X C110 MM
123	MAZDA-FXR30200400W-3K-240V-BL-PH-A665 X B315 X C110 MM	400W	3000	240V	BLACK / GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A665 X B315 X C110 MM	DIE CAST ALUMINUM	IP67	A665 X B315 X C110 MM
124	MAZDA-FXR30200400W-3K-240V-BL-10VDIM-A665 X B315 X C110 MM	400W	3000	240V	BLACK / GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A665 X B315 X C110 MM	DIE CAST ALUMINUM	IP67	A665 X B315 X C110 MM
125	MAZDA-FXR30200400W-4K-240V-BL-ND-A665 X B315 X C110 MM	400W	4000	240V	BLACK / GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A665 X B315 X C110 MM	DIE CAST ALUMINUM	IP67	A665 X B315 X C110 MM
126	MAZDA-FXR30200400W-4K-240V-BL-DA-A665 X B315 X C110 MM	400W	4000	240V	BLACK / GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A665 X B315 X C110 MM	DIE CAST ALUMINUM	IP67	A665 X B315 X C110 MM
127	MAZDA-FXR30200400W-4K-240V-BL-PH-A665 X B315 X C110 MM	400W	4000	240V	BLACK / GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A665 X B315 X C110 MM	DIE CAST ALUMINUM	IP67	A665 X B315 X C110 MM
128	MAZDA-FXR30200400W-4K-240V-BL-10VDIM-A665 X B315 X C110 MM	400W	4000	240V	BLACK / GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A665 X B315 X C110 MM	DIE CAST ALUMINUM	IP67	A665 X B315 X C110 MM
129	MAZDA-FXR30200400W-5K-240V-BL-ND-A665 X B315 X C110 MM	400W	5000	240V	BLACK / GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A665 X B315 X C110 MM	DIE CAST ALUMINUM	IP67	A665 X B315 X C110 MM
130	MAZDA-FXR30200400W-5K-240V-BL-DA-A665 X B315 X C110 MM	400W	5000	240V	BLACK / GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A665 X B315 X C110 MM	DIE CAST ALUMINUM	IP67	A665 X B315 X C110 MM
131	MAZDA-FXR30200400W-5K-240V-BL-PH-A665 X B315 X C110 MM	400W	5000	240V	BLACK / GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A665 X B315 X C110 MM	DIE CAST ALUMINUM	IP67	A665 X B315 X C110 MM
132	MAZDA-FXR30200400W-5K-240V-BL-10VDIM-A665 X B315 X C110 MM	400W	5000	240V	BLACK / GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A665 X B315 X C110 MM	DIE CAST ALUMINUM	IP67	A665 X B315 X C110 MM
133	MAZDA-FXR30200400W-6K-240V-BL-ND-A665 X B315 X C110 MM	400W	6000	240V	BLACK / GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A665 X B315 X C110 MM	DIE CAST ALUMINUM	IP67	A665 X B315 X C110 MM
134	MAZDA-FXR30200400W-6K-240V-BL-DA-A665 X B315 X C110 MM	400W	6000	240V	BLACK / GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A665 X B315 X C110 MM	DIE CAST ALUMINUM	IP67	A665 X B315 X C110 MM
135	MAZDA-FXR30200400W-6K-240V-BL-PH-A665 X B315 X C110 MM	400W	6000	240V	BLACK / GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A665 X B315 X C110 MM	DIE CAST ALUMINUM	IP67	A665 X B315 X C110 MM
136	MAZDA-FXR30200400W-6K-240V-BL-10VDIM-A665 X B315 X C110 MM	400W	6000	240V	BLACK / GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A665 X B315 X C110 MM	DIE CAST ALUMINUM	IP67	A665 X B315 X C110 MM
137	MAZDA-FXR30200400W-2.7K-240V-BL-ND-A665 X B315 X C110 MM	400W	2700	240V	BLACK / GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A665 X B315 X C110 MM	DIE CAST ALUMINUM	IP67	A665 X B315 X C110 MM
138	MAZDA-FXR30200400W-2.7K-240V-BL-DA-A665 X B315 X C110 MM	400W	2700	240V	BLACK / GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A665 X B315 X C110 MM	DIE CAST ALUMINUM	IP67	A665 X B315 X C110 MM
139	MAZDA-FXR30200400W-2.7K-240V-BL-PH-A665 X B315 X C110 MM	400W	2700	240V	BLACK / GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A665 X B315 X C110 MM	DIE CAST ALUMINUM	IP67	A665 X B315 X C110 MM
140	MAZDA-FXR30200400W-2.7K-240V-BL-10VDIM-A665 X B315 X C110 MM	400W	2700	240V	BLACK / GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A665 X B315 X C110 MM	DIE CAST ALUMINUM	IP67	A665 X B315 X C110 MM
141	MAZDA-FXR30200400W-6.5K-240V-BL-ND-A665 X B315 X C110 MM	400W	6500	240V	BLACK / GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A665 X B315 X C110 MM	DIE CAST ALUMINUM	IP67	A665 X B315 X C110 MM
142	MAZDA-FXR30200400W-6.5K-240V-BL-DA-A665 X B315 X C110 MM	400W	6500	240V	BLACK / GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A665 X B315 X C110 MM	DIE CAST ALUMINUM	IP67	A665 X B315 X C110 MM
143	MAZDA-FXR30200400W-6.5K-240V-BL-PH-A665 X B315 X C110 MM	400W	6500	240V	BLACK / GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A665 X B315 X C110 MM	DIE CAST ALUMINUM	IP67	A665 X B315 X C110 MM
144	MAZDA-FXR30200400W-6.5K-240V-BL-10VDIM-A665 X B315 X C110 MM	400W	6500	240V	BLACK / GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A665 X B315 X C110 MM	DIE CAST ALUMINUM	IP67	A665 X B315 X C110 MM
145	MAZDA-FXR30200500W-3K-240V-BL-ND-A684 X B477 X C105 MM	500W	3000	240V	BLACK / GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A684 X B477 X C105 MM	DIE CAST ALUMINUM	IP67	A684 X B477 X C105 MM
146	MAZDA-FXR30200500W-3K-240V-BL-DA-A684 X B477 X C105 MM	500W	3000	240V	BLACK / GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A684 X B477 X C105 MM	DIE CAST ALUMINUM	IP67	A684 X B477 X C105 MM
147	MAZDA-FXR30200500W-3K-240V-BL-PH-A684 X B477 X C105 MM	500W	3000	240V	BLACK / GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A684 X B477 X C105 MM	DIE CAST ALUMINUM	IP67	A684 X B477 X C105 MM
148	MAZDA-FXR30200500W-3K-240V-BL-10VDIM-A684 X B477 X C105 MM	500W	3000	240V	BLACK / GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A684 X B477 X C105 MM	DIE CAST ALUMINUM	IP67	A684 X B477 X C105 MM

DATASHEET

GENERATED ON: 15 Nov 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions Price
149	MAZDA-FXR30200500W-4K-240V-BL-ND-A684 X B477 X C105 MM	500W	4000	240V	BLACK / GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A684 X B477 X C105 MM	DIE CAST ALUMINUM	IP67	A684 X B477 X C105 MM
150	MAZDA-FXR30200500W-4K-240V-BL-DA-A684 X B477 X C105 MM	500W	4000	240V	BLACK / GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A684 X B477 X C105 MM	DIE CAST ALUMINUM	IP67	A684 X B477 X C105 MM
151	MAZDA-FXR30200500W-4K-240V-BL-PH-A684 X B477 X C105 MM	500W	4000	240V	BLACK / GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A684 X B477 X C105 MM	DIE CAST ALUMINUM	IP67	A684 X B477 X C105 MM
152	MAZDA-FXR30200500W-4K-240V-BL-10VDIM-A684 X B477 X C105 MM	500W	4000	240V	BLACK / GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A684 X B477 X C105 MM	DIE CAST ALUMINUM	IP67	A684 X B477 X C105 MM
153	MAZDA-FXR30200500W-5K-240V-BL-ND-A684 X B477 X C105 MM	500W	5000	240V	BLACK / GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A684 X B477 X C105 MM	DIE CAST ALUMINUM	IP67	A684 X B477 X C105 MM
154	MAZDA-FXR30200500W-5K-240V-BL-DA-A684 X B477 X C105 MM	500W	5000	240V	BLACK / GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A684 X B477 X C105 MM	DIE CAST ALUMINUM	IP67	A684 X B477 X C105 MM
155	MAZDA-FXR30200500W-5K-240V-BL-PH-A684 X B477 X C105 MM	500W	5000	240V	BLACK / GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A684 X B477 X C105 MM	DIE CAST ALUMINUM	IP67	A684 X B477 X C105 MM
156	MAZDA-FXR30200500W-5K-240V-BL-10VDIM-A684 X B477 X C105 MM	500W	5000	240V	BLACK / GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A684 X B477 X C105 MM	DIE CAST ALUMINUM	IP67	A684 X B477 X C105 MM
157	MAZDA-FXR30200500W-6K-240V-BL-ND-A684 X B477 X C105 MM	500W	6000	240V	BLACK / GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A684 X B477 X C105 MM	DIE CAST ALUMINUM	IP67	A684 X B477 X C105 MM
158	MAZDA-FXR30200500W-6K-240V-BL-DA-A684 X B477 X C105 MM	500W	6000	240V	BLACK / GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A684 X B477 X C105 MM	DIE CAST ALUMINUM	IP67	A684 X B477 X C105 MM
159	MAZDA-FXR30200500W-6K-240V-BL-PH-A684 X B477 X C105 MM	500W	6000	240V	BLACK / GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A684 X B477 X C105 MM	DIE CAST ALUMINUM	IP67	A684 X B477 X C105 MM
160	MAZDA-FXR30200500W-6K-240V-BL-10VDIM-A684 X B477 X C105 MM	500W	6000	240V	BLACK / GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A684 X B477 X C105 MM	DIE CAST ALUMINUM	IP67	A684 X B477 X C105 MM
161	MAZDA-FXR30200500W-2.7K-240V-BL-ND-A684 X B477 X C105 MM	500W	2700	240V	BLACK / GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A684 X B477 X C105 MM	DIE CAST ALUMINUM	IP67	A684 X B477 X C105 MM
162	MAZDA-FXR30200500W-2.7K-240V-BL-DA-A684 X B477 X C105 MM	500W	2700	240V	BLACK / GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A684 X B477 X C105 MM	DIE CAST ALUMINUM	IP67	A684 X B477 X C105 MM
163	MAZDA-FXR30200500W-2.7K-240V-BL-PH-A684 X B477 X C105 MM	500W	2700	240V	BLACK / GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A684 X B477 X C105 MM	DIE CAST ALUMINUM	IP67	A684 X B477 X C105 MM
164	MAZDA-FXR30200500W-2.7K-240V-BL-10VDIM-A684 X B477 X C105 MM	500W	2700	240V	BLACK / GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A684 X B477 X C105 MM	DIE CAST ALUMINUM	IP67	A684 X B477 X C105 MM
165	MAZDA-FXR30200500W-6.5K-240V-BL-ND-A684 X B477 X C105 MM	500W	6500	240V	BLACK / GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A684 X B477 X C105 MM	DIE CAST ALUMINUM	IP67	A684 X B477 X C105 MM
166	MAZDA-FXR30200500W-6.5K-240V-BL-DA-A684 X B477 X C105 MM	500W	6500	240V	BLACK / GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A684 X B477 X C105 MM	DIE CAST ALUMINUM	IP67	A684 X B477 X C105 MM
167	MAZDA-FXR30200500W-6.5K-240V-BL-PH-A684 X B477 X C105 MM	500W	6500	240V	BLACK / GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A684 X B477 X C105 MM	DIE CAST ALUMINUM	IP67	A684 X B477 X C105 MM
168	MAZDA-FXR30200500W-6.5K-240V-BL-10VDIM-A684 X B477 X C105 MM	500W	6500	240V	BLACK / GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A684 X B477 X C105 MM	DIE CAST ALUMINUM	IP67	A684 X B477 X C105 MM
169	MAZDA-FXR30200600W-3K-240V-BL-ND-A684 X B477 X C105 MM	600W	3000	240V	BLACK / GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A684 X B477 X C105 MM	DIE CAST ALUMINUM	IP67	A684 X B477 X C105 MM
170	MAZDA-FXR30200600W-3K-240V-BL-DA-A684 X B477 X C105 MM	600W	3000	240V	BLACK / GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A684 X B477 X C105 MM	DIE CAST ALUMINUM	IP67	A684 X B477 X C105 MM
171	MAZDA-FXR30200600W-3K-240V-BL-PH-A684 X B477 X C105 MM	600W	3000	240V	BLACK / GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A684 X B477 X C105 MM	DIE CAST ALUMINUM	IP67	A684 X B477 X C105 MM
172	MAZDA-FXR30200600W-3K-240V-BL-10VDIM-A684 X B477 X C105 MM	600W	3000	240V	BLACK / GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A684 X B477 X C105 MM	DIE CAST ALUMINUM	IP67	A684 X B477 X C105 MM
173	MAZDA-FXR30200600W-4K-240V-BL-ND-A684 X B477 X C105 MM	600W	4000	240V	BLACK / GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A684 X B477 X C105 MM	DIE CAST ALUMINUM	IP67	A684 X B477 X C105 MM
174	MAZDA-FXR30200600W-4K-240V-BL-DA-A684 X B477 X C105 MM	600W	4000	240V	BLACK / GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A684 X B477 X C105 MM	DIE CAST ALUMINUM	IP67	A684 X B477 X C105 MM
175	MAZDA-FXR30200600W-4K-240V-BL-PH-A684 X B477 X C105 MM	600W	4000	240V	BLACK / GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A684 X B477 X C105 MM	DIE CAST ALUMINUM	IP67	A684 X B477 X C105 MM

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
176	**MAZDA-FXR30200600W-4K-240V-BL-10VDIM-A684 X B477 X C105 MM**	600W	4000	240V	BLACK / GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A684 X B477 X C105 MM	DIE CAST ALUMINUM	IP67	A684 X B477 X C105 MM	
177	**MAZDA-FXR30200600W-5K-240V-BL-ND-A684 X B477 X C105 MM**	600W	5000	240V	BLACK / GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A684 X B477 X C105 MM	DIE CAST ALUMINUM	IP67	A684 X B477 X C105 MM	
178	**MAZDA-FXR30200600W-5K-240V-BL-DA-A684 X B477 X C105 MM**	600W	5000	240V	BLACK / GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A684 X B477 X C105 MM	DIE CAST ALUMINUM	IP67	A684 X B477 X C105 MM	
179	**MAZDA-FXR30200600W-5K-240V-BL-PH-A684 X B477 X C105 MM**	600W	5000	240V	BLACK / GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A684 X B477 X C105 MM	DIE CAST ALUMINUM	IP67	A684 X B477 X C105 MM	
180	**MAZDA-FXR30200600W-5K-240V-BL-10VDIM-A684 X B477 X C105 MM**	600W	5000	240V	BLACK / GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A684 X B477 X C105 MM	DIE CAST ALUMINUM	IP67	A684 X B477 X C105 MM	
181	**MAZDA-FXR30200600W-6K-240V-BL-ND-A684 X B477 X C105 MM**	600W	6000	240V	BLACK / GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A684 X B477 X C105 MM	DIE CAST ALUMINUM	IP67	A684 X B477 X C105 MM	
182	**MAZDA-FXR30200600W-6K-240V-BL-DA-A684 X B477 X C105 MM**	600W	6000	240V	BLACK / GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A684 X B477 X C105 MM	DIE CAST ALUMINUM	IP67	A684 X B477 X C105 MM	
183	**MAZDA-FXR30200600W-6K-240V-BL-PH-A684 X B477 X C105 MM**	600W	6000	240V	BLACK / GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A684 X B477 X C105 MM	DIE CAST ALUMINUM	IP67	A684 X B477 X C105 MM	
184	**MAZDA-FXR30200600W-6K-240V-BL-10VDIM-A684 X B477 X C105 MM**	600W	6000	240V	BLACK / GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A684 X B477 X C105 MM	DIE CAST ALUMINUM	IP67	A684 X B477 X C105 MM	
185	**MAZDA-FXR30200600W-2.7K-240V-BL-ND-A684 X B477 X C105 MM**	600W	2700	240V	BLACK / GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A684 X B477 X C105 MM	DIE CAST ALUMINUM	IP67	A684 X B477 X C105 MM	
186	**MAZDA-FXR30200600W-2.7K-240V-BL-DA-A684 X B477 X C105 MM**	600W	2700	240V	BLACK / GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A684 X B477 X C105 MM	DIE CAST ALUMINUM	IP67	A684 X B477 X C105 MM	
187	**MAZDA-FXR30200600W-2.7K-240V-BL-PH-A684 X B477 X C105 MM**	600W	2700	240V	BLACK / GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A684 X B477 X C105 MM	DIE CAST ALUMINUM	IP67	A684 X B477 X C105 MM	
188	**MAZDA-FXR30200600W-2.7K-240V-BL-10VDIM-A684 X B477 X C105 MM**	600W	2700	240V	BLACK / GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A684 X B477 X C105 MM	DIE CAST ALUMINUM	IP67	A684 X B477 X C105 MM	
189	**MAZDA-FXR30200600W-6.5K-240V-BL-ND-A684 X B477 X C105 MM**	600W	6500	240V	BLACK / GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A684 X B477 X C105 MM	DIE CAST ALUMINUM	IP67	A684 X B477 X C105 MM	
190	**MAZDA-FXR30200600W-6.5K-240V-BL-DA-A684 X B477 X C105 MM**	600W	6500	240V	BLACK / GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A684 X B477 X C105 MM	DIE CAST ALUMINUM	IP67	A684 X B477 X C105 MM	
191	**MAZDA-FXR30200600W-6.5K-240V-BL-PH-A684 X B477 X C105 MM**	600W	6500	240V	BLACK / GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A684 X B477 X C105 MM	DIE CAST ALUMINUM	IP67	A684 X B477 X C105 MM	
192	**MAZDA-FXR30200600W-6.5K-240V-BL-10VDIM-A684 X B477 X C105 MM**	600W	6500	240V	BLACK / GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A684 X B477 X C105 MM	DIE CAST ALUMINUM	IP67	A684 X B477 X C105 MM	