



SLICK

MAZDA Model: BLXR332012 Bollard Light

Slick Bollard Light has the classic design of a bollard light, available with little differences in the top shape to satisfy the details lovers. The light source is an LED high efficiency system, which ensures high performances while saving energy. All the items have features like easy installation, very low maintenance needs and full safety for electrical systems and people

ALL AVAILABLE VARIANTS

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
1	MAZDA-BLXR33201212W-3K-AC240-WH-ND-A118 X B500 MM	12W	3000	240VAC	WHITE & BLACK	NON EMERGENCY	ON - OFF	360	A118 X B500 MM	DIE CAST ALUMINUM	IP66	A118 X B500 MM	
2	MAZDA-BLXR33201212W-3K-AC240-WH-DA-A118 X B500 MM	12W	3000	240VAC	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	360	A118 X B500 MM	DIE CAST ALUMINUM	IP66	A118 X B500 MM	
3	MAZDA-BLXR33201212W-3K-AC240-WH-PH-A118 X B500 MM	12W	3000	240VAC	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	360	A118 X B500 MM	DIE CAST ALUMINUM	IP66	A118 X B500 MM	
4	MAZDA-BLXR33201212W-3K-AC240-WH-10VDIM-A118 X B500 MM	12W	3000	240VAC	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	360	A118 X B500 MM	DIE CAST ALUMINUM	IP66	A118 X B500 MM	
5	MAZDA-BLXR33201212W-4K-AC240-WH-ND-A118 X B500 MM	12W	4000	240VAC	WHITE & BLACK	NON EMERGENCY	ON - OFF	360	A118 X B500 MM	DIE CAST ALUMINUM	IP66	A118 X B500 MM	
6	MAZDA-BLXR33201212W-4K-AC240-WH-DA-A118 X B500 MM	12W	4000	240VAC	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	360	A118 X B500 MM	DIE CAST ALUMINUM	IP66	A118 X B500 MM	
7	MAZDA-BLXR33201212W-4K-AC240-WH-PH-A118 X B500 MM	12W	4000	240VAC	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	360	A118 X B500 MM	DIE CAST ALUMINUM	IP66	A118 X B500 MM	
8	MAZDA-BLXR33201212W-4K-AC240-WH-10VDIM-A118 X B500 MM	12W	4000	240VAC	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	360	A118 X B500 MM	DIE CAST ALUMINUM	IP66	A118 X B500 MM	
9	MAZDA-BLXR33201212W-5K-AC240-WH-ND-A118 X B500 MM	12W	5000	240VAC	WHITE & BLACK	NON EMERGENCY	ON - OFF	360	A118 X B500 MM	DIE CAST ALUMINUM	IP66	A118 X B500 MM	
10	MAZDA-BLXR33201212W-5K-AC240-WH-DA-A118 X B500 MM	12W	5000	240VAC	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	360	A118 X B500 MM	DIE CAST ALUMINUM	IP66	A118 X B500 MM	
11	MAZDA-BLXR33201212W-5K-AC240-WH-PH-A118 X B500 MM	12W	5000	240VAC	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	360	A118 X B500 MM	DIE CAST ALUMINUM	IP66	A118 X B500 MM	
12	MAZDA-BLXR33201212W-5K-AC240-WH-10VDIM-A118 X B500 MM	12W	5000	240VAC	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	360	A118 X B500 MM	DIE CAST ALUMINUM	IP66	A118 X B500 MM	
13	MAZDA-BLXR33201212W-6K-AC240-WH-ND-A118 X B500 MM	12W	6000	240VAC	WHITE & BLACK	NON EMERGENCY	ON - OFF	360	A118 X B500 MM	DIE CAST ALUMINUM	IP66	A118 X B500 MM	
14	MAZDA-BLXR33201212W-6K-AC240-WH-DA-A118 X B500 MM	12W	6000	240VAC	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	360	A118 X B500 MM	DIE CAST ALUMINUM	IP66	A118 X B500 MM	
15	MAZDA-BLXR33201212W-6K-AC240-WH-PH-A118 X B500 MM	12W	6000	240VAC	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	360	A118 X B500 MM	DIE CAST ALUMINUM	IP66	A118 X B500 MM	
16	MAZDA-BLXR33201212W-6K-AC240-WH-10VDIM-A118 X B500 MM	12W	6000	240VAC	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	360	A118 X B500 MM	DIE CAST ALUMINUM	IP66	A118 X B500 MM	



DATASHEET

GENERATED ON: 04 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
17	MAZDA-BLXR33201212W-2.7K-AC240-WH-ND-A118 X B500 MM	12W	2700	240VAC	WHITE & BLACK	NON EMERGENCY	ON - OFF	360	A118 X B500 MM	DIE CAST ALUMINUM	IP66	A118 X B500 MM	
18	MAZDA-BLXR33201212W-2.7K-AC240-WH-DA-A118 X B500 MM	12W	2700	240VAC	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	360	A118 X B500 MM	DIE CAST ALUMINUM	IP66	A118 X B500 MM	
19	MAZDA-BLXR33201212W-2.7K-AC240-WH-PH-A118 X B500 MM	12W	2700	240VAC	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	360	A118 X B500 MM	DIE CAST ALUMINUM	IP66	A118 X B500 MM	
20	MAZDA-BLXR33201212W-2.7K-AC240-WH-10VDIM-A118 X B500 MM	12W	2700	240VAC	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	360	A118 X B500 MM	DIE CAST ALUMINUM	IP66	A118 X B500 MM	
21	MAZDA-BLXR33201212W-6.5K-AC240-WH-ND-A118 X B500 MM	12W	6500	240VAC	WHITE & BLACK	NON EMERGENCY	ON - OFF	360	A118 X B500 MM	DIE CAST ALUMINUM	IP66	A118 X B500 MM	
22	MAZDA-BLXR33201212W-6.5K-AC240-WH-DA-A118 X B500 MM	12W	6500	240VAC	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	360	A118 X B500 MM	DIE CAST ALUMINUM	IP66	A118 X B500 MM	
23	MAZDA-BLXR33201212W-6.5K-AC240-WH-PH-A118 X B500 MM	12W	6500	240VAC	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	360	A118 X B500 MM	DIE CAST ALUMINUM	IP66	A118 X B500 MM	
24	MAZDA-BLXR33201212W-6.5K-AC240-WH-10VDIM-A118 X B500 MM	12W	6500	240VAC	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	360	A118 X B500 MM	DIE CAST ALUMINUM	IP66	A118 X B500 MM	
25	MAZDA-BLXR33201212W-3K-AC240-WH-ND-A118 X B800 MM	12W	3000	240VAC	WHITE & BLACK	NON EMERGENCY	ON - OFF	360	A118 X B800 MM	DIE CAST ALUMINUM	IP66	A118 X B800 MM	
26	MAZDA-BLXR33201212W-3K-AC240-WH-DA-A118 X B800 MM	12W	3000	240VAC	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	360	A118 X B800 MM	DIE CAST ALUMINUM	IP66	A118 X B800 MM	
27	MAZDA-BLXR33201212W-3K-AC240-WH-PH-A118 X B800 MM	12W	3000	240VAC	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	360	A118 X B800 MM	DIE CAST ALUMINUM	IP66	A118 X B800 MM	
28	MAZDA-BLXR33201212W-3K-AC240-WH-10VDIM-A118 X B800 MM	12W	3000	240VAC	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	360	A118 X B800 MM	DIE CAST ALUMINUM	IP66	A118 X B800 MM	
29	MAZDA-BLXR33201212W-4K-AC240-WH-ND-A118 X B800 MM	12W	4000	240VAC	WHITE & BLACK	NON EMERGENCY	ON - OFF	360	A118 X B800 MM	DIE CAST ALUMINUM	IP66	A118 X B800 MM	
30	MAZDA-BLXR33201212W-4K-AC240-WH-DA-A118 X B800 MM	12W	4000	240VAC	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	360	A118 X B800 MM	DIE CAST ALUMINUM	IP66	A118 X B800 MM	
31	MAZDA-BLXR33201212W-4K-AC240-WH-PH-A118 X B800 MM	12W	4000	240VAC	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	360	A118 X B800 MM	DIE CAST ALUMINUM	IP66	A118 X B800 MM	
32	MAZDA-BLXR33201212W-4K-AC240-WH-10VDIM-A118 X B800 MM	12W	4000	240VAC	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	360	A118 X B800 MM	DIE CAST ALUMINUM	IP66	A118 X B800 MM	
33	MAZDA-BLXR33201212W-5K-AC240-WH-ND-A118 X B800 MM	12W	5000	240VAC	WHITE & BLACK	NON EMERGENCY	ON - OFF	360	A118 X B800 MM	DIE CAST ALUMINUM	IP66	A118 X B800 MM	
34	MAZDA-BLXR33201212W-5K-AC240-WH-DA-A118 X B800 MM	12W	5000	240VAC	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	360	A118 X B800 MM	DIE CAST ALUMINUM	IP66	A118 X B800 MM	
35	MAZDA-BLXR33201212W-5K-AC240-WH-PH-A118 X B800 MM	12W	5000	240VAC	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	360	A118 X B800 MM	DIE CAST ALUMINUM	IP66	A118 X B800 MM	
36	MAZDA-BLXR33201212W-5K-AC240-WH-10VDIM-A118 X B800 MM	12W	5000	240VAC	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	360	A118 X B800 MM	DIE CAST ALUMINUM	IP66	A118 X B800 MM	
37	MAZDA-BLXR33201212W-6K-AC240-WH-ND-A118 X B800 MM	12W	6000	240VAC	WHITE & BLACK	NON EMERGENCY	ON - OFF	360	A118 X B800 MM	DIE CAST ALUMINUM	IP66	A118 X B800 MM	
38	MAZDA-BLXR33201212W-6K-AC240-WH-DA-A118 X B800 MM	12W	6000	240VAC	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	360	A118 X B800 MM	DIE CAST ALUMINUM	IP66	A118 X B800 MM	
39	MAZDA-BLXR33201212W-6K-AC240-WH-PH-A118 X B800 MM	12W	6000	240VAC	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	360	A118 X B800 MM	DIE CAST ALUMINUM	IP66	A118 X B800 MM	
40	MAZDA-BLXR33201212W-6K-AC240-WH-10VDIM-A118 X B800 MM	12W	6000	240VAC	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	360	A118 X B800 MM	DIE CAST ALUMINUM	IP66	A118 X B800 MM	
41	MAZDA-BLXR33201212W-2.7K-AC240-WH-ND-A118 X B800 MM	12W	2700	240VAC	WHITE & BLACK	NON EMERGENCY	ON - OFF	360	A118 X B800 MM	DIE CAST ALUMINUM	IP66	A118 X B800 MM	
42	MAZDA-BLXR33201212W-2.7K-AC240-WH-DA-A118 X B800 MM	12W	2700	240VAC	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	360	A118 X B800 MM	DIE CAST ALUMINUM	IP66	A118 X B800 MM	
43	MAZDA-BLXR33201212W-2.7K-AC240-WH-PH-A118 X B800 MM	12W	2700	240VAC	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	360	A118 X B800 MM	DIE CAST ALUMINUM	IP66	A118 X B800 MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
44	MAZDA-BLXR33201212W-2.7K-AC240-WH-10VDIM-A118 X B800 MM	12W	2700	240VAC	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	360	A118 X B800 MM	DIE CAST ALUMINUM	IP66	A118 X B800 MM	
45	MAZDA-BLXR33201212W-6.5K-AC240-WH-ND-A118 X B800 MM	12W	6500	240VAC	WHITE & BLACK	NON EMERGENCY	ON - OFF	360	A118 X B800 MM	DIE CAST ALUMINUM	IP66	A118 X B800 MM	
46	MAZDA-BLXR33201212W-6.5K-AC240-WH-DA-A118 X B800 MM	12W	6500	240VAC	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	360	A118 X B800 MM	DIE CAST ALUMINUM	IP66	A118 X B800 MM	
47	MAZDA-BLXR33201212W-6.5K-AC240-WH-PH-A118 X B800 MM	12W	6500	240VAC	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	360	A118 X B800 MM	DIE CAST ALUMINUM	IP66	A118 X B800 MM	
48	MAZDA-BLXR33201212W-6.5K-AC240-WH-10VDIM-A118 X B800 MM	12W	6500	240VAC	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	360	A118 X B800 MM	DIE CAST ALUMINUM	IP66	A118 X B800 MM	