



DEITY

MAZDA Model: UPXR7014 Inground Light

In-ground lights are ideally suited for accenting architectural features, facades, sculptures, to highlight trees, foliage and other outdoor garden landscapes. Stainless steel finishes top ring, Aluminium die cast body and clear tough tempered glass. These fixtures can be used around decks, patio areas, pathways or driveways creating a durable and permanent outdoor lighting solution with a modern look. This particular inground light has an adjustable beam direction and impact resistance: IK10 with ingress protection IP67.

ALL AVAILABLE VARIANTS

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
1	MAZDA-UPXR701425W-3K-240V-BL-ND-A130 X B107 MM	25W	3000	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	ON - OFF	15°	A130 X B107 MM	DIE CAST ALUMINUM	IP68	A130 X B107 MM	
2	MAZDA-UPXR701425W-3K-240V-BL-DA-A130 X B107 MM	25W	3000	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°	A130 X B107 MM	DIE CAST ALUMINUM	IP68	A130 X B107 MM	
3	MAZDA-UPXR701425W-3K-240V-BL-PH-A130 X B107 MM	25W	3000	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°	A130 X B107 MM	DIE CAST ALUMINUM	IP68	A130 X B107 MM	
4	MAZDA-UPXR701425W-3K-240V-BL-10VDIM-A130 X B107 MM	25W	3000	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°	A130 X B107 MM	DIE CAST ALUMINUM	IP68	A130 X B107 MM	
5	MAZDA-UPXR701425W-4K-240V-BL-ND-A130 X B107 MM	25W	4000	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	ON - OFF	15°	A130 X B107 MM	DIE CAST ALUMINUM	IP68	A130 X B107 MM	
6	MAZDA-UPXR701425W-4K-240V-BL-DA-A130 X B107 MM	25W	4000	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°	A130 X B107 MM	DIE CAST ALUMINUM	IP68	A130 X B107 MM	
7	MAZDA-UPXR701425W-4K-240V-BL-PH-A130 X B107 MM	25W	4000	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°	A130 X B107 MM	DIE CAST ALUMINUM	IP68	A130 X B107 MM	
8	MAZDA-UPXR701425W-4K-240V-BL-10VDIM-A130 X B107 MM	25W	4000	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°	A130 X B107 MM	DIE CAST ALUMINUM	IP68	A130 X B107 MM	
9	MAZDA-UPXR701425W-5K-240V-BL-ND-A130 X B107 MM	25W	5000	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	ON - OFF	15°	A130 X B107 MM	DIE CAST ALUMINUM	IP68	A130 X B107 MM	
10	MAZDA-UPXR701425W-5K-240V-BL-DA-A130 X B107 MM	25W	5000	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°	A130 X B107 MM	DIE CAST ALUMINUM	IP68	A130 X B107 MM	



DATASHEET

GENERATED ON: 06 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
11	MAZDA-UPXR701425W-5K-240V-BL-PH-A130 X B107 MM	25W	5000	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°	A130 X B107 MM	DIE CAST ALUMINUM	IP68	A130 X B107 MM	
12	MAZDA-UPXR701425W-5K-240V-BL-10VDIM-A130 X B107 MM	25W	5000	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°	A130 X B107 MM	DIE CAST ALUMINUM	IP68	A130 X B107 MM	
13	MAZDA-UPXR701425W-6K-240V-BL-ND-A130 X B107 MM	25W	6000	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	ON - OFF	15°	A130 X B107 MM	DIE CAST ALUMINUM	IP68	A130 X B107 MM	
14	MAZDA-UPXR701425W-6K-240V-BL-DA-A130 X B107 MM	25W	6000	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°	A130 X B107 MM	DIE CAST ALUMINUM	IP68	A130 X B107 MM	
15	MAZDA-UPXR701425W-6K-240V-BL-PH-A130 X B107 MM	25W	6000	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°	A130 X B107 MM	DIE CAST ALUMINUM	IP68	A130 X B107 MM	
16	MAZDA-UPXR701425W-6K-240V-BL-10VDIM-A130 X B107 MM	25W	6000	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°	A130 X B107 MM	DIE CAST ALUMINUM	IP68	A130 X B107 MM	
17	MAZDA-UPXR701425W-2.7K-240V-BL-ND-A130 X B107 MM	25W	2700	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	ON - OFF	15°	A130 X B107 MM	DIE CAST ALUMINUM	IP68	A130 X B107 MM	
18	MAZDA-UPXR701425W-2.7K-240V-BL-DA-A130 X B107 MM	25W	2700	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°	A130 X B107 MM	DIE CAST ALUMINUM	IP68	A130 X B107 MM	
19	MAZDA-UPXR701425W-2.7K-240V-BL-PH-A130 X B107 MM	25W	2700	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°	A130 X B107 MM	DIE CAST ALUMINUM	IP68	A130 X B107 MM	
20	MAZDA-UPXR701425W-2.7K-240V-BL-10VDIM-A130 X B107 MM	25W	2700	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°	A130 X B107 MM	DIE CAST ALUMINUM	IP68	A130 X B107 MM	
21	MAZDA-UPXR701425W-6.5K-240V-BL-ND-A130 X B107 MM	25W	6500	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	ON - OFF	15°	A130 X B107 MM	DIE CAST ALUMINUM	IP68	A130 X B107 MM	
22	MAZDA-UPXR701425W-6.5K-240V-BL-DA-A130 X B107 MM	25W	6500	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°	A130 X B107 MM	DIE CAST ALUMINUM	IP68	A130 X B107 MM	
23	MAZDA-UPXR701425W-6.5K-240V-BL-PH-A130 X B107 MM	25W	6500	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°	A130 X B107 MM	DIE CAST ALUMINUM	IP68	A130 X B107 MM	
24	MAZDA-UPXR701425W-6.5K-240V-BL-10VDIM-A130 X B107 MM	25W	6500	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°	A130 X B107 MM	DIE CAST ALUMINUM	IP68	A130 X B107 MM	
25	MAZDA-UPXR701436W-3K-240V-BL-ND-A170 X B131 MM	36W	3000	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	ON - OFF	15°	A170 X B131 MM	DIE CAST ALUMINUM	IP68	A170 X B131 MM	
26	MAZDA-UPXR701436W-3K-240V-BL-DA-A170 X B131 MM	36W	3000	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°	A170 X B131 MM	DIE CAST ALUMINUM	IP68	A170 X B131 MM	



DATASHEET

GENERATED ON: 06 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
27	MAZDA-UPXR701436W-3K-240V-BL-PH-A170 X B131 MM	36W	3000	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°	A170 X B131 MM	DIE CAST ALUMINUM	IP68	A170 X B131 MM	
28	MAZDA-UPXR701436W-3K-240V-BL-10VDIM-A170 X B131 MM	36W	3000	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°	A170 X B131 MM	DIE CAST ALUMINUM	IP68	A170 X B131 MM	
29	MAZDA-UPXR701436W-4K-240V-BL-ND-A170 X B131 MM	36W	4000	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	ON - OFF	15°	A170 X B131 MM	DIE CAST ALUMINUM	IP68	A170 X B131 MM	
30	MAZDA-UPXR701436W-4K-240V-BL-DA-A170 X B131 MM	36W	4000	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°	A170 X B131 MM	DIE CAST ALUMINUM	IP68	A170 X B131 MM	
31	MAZDA-UPXR701436W-4K-240V-BL-PH-A170 X B131 MM	36W	4000	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°	A170 X B131 MM	DIE CAST ALUMINUM	IP68	A170 X B131 MM	
32	MAZDA-UPXR701436W-4K-240V-BL-10VDIM-A170 X B131 MM	36W	4000	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°	A170 X B131 MM	DIE CAST ALUMINUM	IP68	A170 X B131 MM	
33	MAZDA-UPXR701436W-5K-240V-BL-ND-A170 X B131 MM	36W	5000	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	ON - OFF	15°	A170 X B131 MM	DIE CAST ALUMINUM	IP68	A170 X B131 MM	
34	MAZDA-UPXR701436W-5K-240V-BL-DA-A170 X B131 MM	36W	5000	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°	A170 X B131 MM	DIE CAST ALUMINUM	IP68	A170 X B131 MM	
35	MAZDA-UPXR701436W-5K-240V-BL-PH-A170 X B131 MM	36W	5000	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°	A170 X B131 MM	DIE CAST ALUMINUM	IP68	A170 X B131 MM	
36	MAZDA-UPXR701436W-5K-240V-BL-10VDIM-A170 X B131 MM	36W	5000	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°	A170 X B131 MM	DIE CAST ALUMINUM	IP68	A170 X B131 MM	
37	MAZDA-UPXR701436W-6K-240V-BL-ND-A170 X B131 MM	36W	6000	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	ON - OFF	15°	A170 X B131 MM	DIE CAST ALUMINUM	IP68	A170 X B131 MM	
38	MAZDA-UPXR701436W-6K-240V-BL-DA-A170 X B131 MM	36W	6000	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°	A170 X B131 MM	DIE CAST ALUMINUM	IP68	A170 X B131 MM	
39	MAZDA-UPXR701436W-6K-240V-BL-PH-A170 X B131 MM	36W	6000	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°	A170 X B131 MM	DIE CAST ALUMINUM	IP68	A170 X B131 MM	
40	MAZDA-UPXR701436W-6K-240V-BL-10VDIM-A170 X B131 MM	36W	6000	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°	A170 X B131 MM	DIE CAST ALUMINUM	IP68	A170 X B131 MM	
41	MAZDA-UPXR701436W-2.7K-240V-BL-ND-A170 X B131 MM	36W	2700	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	ON - OFF	15°	A170 X B131 MM	DIE CAST ALUMINUM	IP68	A170 X B131 MM	
42	MAZDA-UPXR701436W-2.7K-240V-BL-DA-A170 X B131 MM	36W	2700	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°	A170 X B131 MM	DIE CAST ALUMINUM	IP68	A170 X B131 MM	



DATASHEET

GENERATED ON: 06 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
43	MAZDA-UPXR701436W-2.7K-240V-BL-PH-A170 X B131 MM	36W	2700	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°	A170 X B131 MM	DIE CAST ALUMINUM	IP68	A170 X B131 MM	
44	MAZDA-UPXR701436W-2.7K-240V-BL-10VDIM-A170 X B131 MM	36W	2700	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°	A170 X B131 MM	DIE CAST ALUMINUM	IP68	A170 X B131 MM	
45	MAZDA-UPXR701436W-6.5K-240V-BL-ND-A170 X B131 MM	36W	6500	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	ON - OFF	15°	A170 X B131 MM	DIE CAST ALUMINUM	IP68	A170 X B131 MM	
46	MAZDA-UPXR701436W-6.5K-240V-BL-DA-A170 X B131 MM	36W	6500	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°	A170 X B131 MM	DIE CAST ALUMINUM	IP68	A170 X B131 MM	
47	MAZDA-UPXR701436W-6.5K-240V-BL-PH-A170 X B131 MM	36W	6500	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°	A170 X B131 MM	DIE CAST ALUMINUM	IP68	A170 X B131 MM	
48	MAZDA-UPXR701436W-6.5K-240V-BL-10VDIM-A170 X B131 MM	36W	6500	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°	A170 X B131 MM	DIE CAST ALUMINUM	IP68	A170 X B131 MM	
49	MAZDA-UPXR701415W-3K-240V-BL-ND-A100 X B83 MM	15W	3000	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	ON - OFF	15°	A100 X B83 MM	DIE CAST ALUMINUM	IP68	A100 X B83 MM	
50	MAZDA-UPXR701415W-3K-240V-BL-DA-A100 X B83 MM	15W	3000	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°	A100 X B83 MM	DIE CAST ALUMINUM	IP68	A100 X B83 MM	
51	MAZDA-UPXR701415W-3K-240V-BL-PH-A100 X B83 MM	15W	3000	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°	A100 X B83 MM	DIE CAST ALUMINUM	IP68	A100 X B83 MM	
52	MAZDA-UPXR701415W-3K-240V-BL-10VDIM-A100 X B83 MM	15W	3000	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°	A100 X B83 MM	DIE CAST ALUMINUM	IP68	A100 X B83 MM	
53	MAZDA-UPXR701415W-4K-240V-BL-ND-A100 X B83 MM	15W	4000	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	ON - OFF	15°	A100 X B83 MM	DIE CAST ALUMINUM	IP68	A100 X B83 MM	
54	MAZDA-UPXR701415W-4K-240V-BL-DA-A100 X B83 MM	15W	4000	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°	A100 X B83 MM	DIE CAST ALUMINUM	IP68	A100 X B83 MM	
55	MAZDA-UPXR701415W-4K-240V-BL-PH-A100 X B83 MM	15W	4000	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°	A100 X B83 MM	DIE CAST ALUMINUM	IP68	A100 X B83 MM	
56	MAZDA-UPXR701415W-4K-240V-BL-10VDIM-A100 X B83 MM	15W	4000	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°	A100 X B83 MM	DIE CAST ALUMINUM	IP68	A100 X B83 MM	
57	MAZDA-UPXR701415W-5K-240V-BL-ND-A100 X B83 MM	15W	5000	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	ON - OFF	15°	A100 X B83 MM	DIE CAST ALUMINUM	IP68	A100 X B83 MM	
58	MAZDA-UPXR701415W-5K-240V-BL-DA-A100 X B83 MM	15W	5000	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°	A100 X B83 MM	DIE CAST ALUMINUM	IP68	A100 X B83 MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angle	Dimension	Material	IP	Dimensions	Price
59	MAZDA-UPXR701415W-5K-240V-BL-PH-A100 X B83 MM	15W	5000	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°	A100 X B83 MM	DIE CAST ALUMINUM	IP68	A100 X B83 MM	
60	MAZDA-UPXR701415W-5K-240V-BL-10VDIM-A100 X B83 MM	15W	5000	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°	A100 X B83 MM	DIE CAST ALUMINUM	IP68	A100 X B83 MM	
61	MAZDA-UPXR701415W-6K-240V-BL-ND-A100 X B83 MM	15W	6000	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	ON - OFF	15°	A100 X B83 MM	DIE CAST ALUMINUM	IP68	A100 X B83 MM	
62	MAZDA-UPXR701415W-6K-240V-BL-DA-A100 X B83 MM	15W	6000	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°	A100 X B83 MM	DIE CAST ALUMINUM	IP68	A100 X B83 MM	
63	MAZDA-UPXR701415W-6K-240V-BL-PH-A100 X B83 MM	15W	6000	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°	A100 X B83 MM	DIE CAST ALUMINUM	IP68	A100 X B83 MM	
64	MAZDA-UPXR701415W-6K-240V-BL-10VDIM-A100 X B83 MM	15W	6000	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°	A100 X B83 MM	DIE CAST ALUMINUM	IP68	A100 X B83 MM	
65	MAZDA-UPXR701415W-2.7K-240V-BL-ND-A100 X B83 MM	15W	2700	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	ON - OFF	15°	A100 X B83 MM	DIE CAST ALUMINUM	IP68	A100 X B83 MM	
66	MAZDA-UPXR701415W-2.7K-240V-BL-DA-A100 X B83 MM	15W	2700	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°	A100 X B83 MM	DIE CAST ALUMINUM	IP68	A100 X B83 MM	
67	MAZDA-UPXR701415W-2.7K-240V-BL-PH-A100 X B83 MM	15W	2700	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°	A100 X B83 MM	DIE CAST ALUMINUM	IP68	A100 X B83 MM	
68	MAZDA-UPXR701415W-2.7K-240V-BL-10VDIM-A100 X B83 MM	15W	2700	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°	A100 X B83 MM	DIE CAST ALUMINUM	IP68	A100 X B83 MM	
69	MAZDA-UPXR701415W-6.5K-240V-BL-ND-A100 X B83 MM	15W	6500	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	ON - OFF	15°	A100 X B83 MM	DIE CAST ALUMINUM	IP68	A100 X B83 MM	
70	MAZDA-UPXR701415W-6.5K-240V-BL-DA-A100 X B83 MM	15W	6500	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°	A100 X B83 MM	DIE CAST ALUMINUM	IP68	A100 X B83 MM	
71	MAZDA-UPXR701415W-6.5K-240V-BL-PH-A100 X B83 MM	15W	6500	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°	A100 X B83 MM	DIE CAST ALUMINUM	IP68	A100 X B83 MM	
72	MAZDA-UPXR701415W-6.5K-240V-BL-10VDIM-A100 X B83 MM	15W	6500	240V	BLACK, STAINLESS STEEL, DARK GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°	A100 X B83 MM	DIE CAST ALUMINUM	IP68	A100 X B83 MM	