



FALL

MAZDA Model: UNXR2078 Inground Light

The UNXR series is IP68 rated (fully submersible) and is a great choice for underwater lighting of water features and ponds due to its solid plate. The fixture is recessed under. This high quality product can be used in water.

ALL AVAILABLE VARIANTS

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angle	Dimension	Material	IP	Dimensions	Price
1	MAZDA-UNXR207808W-3K-12V-GR-ND-A135 X B58 X C135 MM	08W	3000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A135 X B58 X C135 MM	DIE CAST ALUMINUM	IP68	A135 X B58 X C135 MM	
2	MAZDA-UNXR207808W-3K-12V-GR-DA-A135 X B58 X C135 MM	08W	3000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A135 X B58 X C135 MM	DIE CAST ALUMINUM	IP68	A135 X B58 X C135 MM	
3	MAZDA-UNXR207808W-3K-12V-GR-PH-A135 X B58 X C135 MM	08W	3000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A135 X B58 X C135 MM	DIE CAST ALUMINUM	IP68	A135 X B58 X C135 MM	
4	MAZDA-UNXR207808W-3K-12V-GR-10VDIM-A135 X B58 X C135 MM	08W	3000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A135 X B58 X C135 MM	DIE CAST ALUMINUM	IP68	A135 X B58 X C135 MM	
5	MAZDA-UNXR207808W-4K-12V-GR-ND-A135 X B58 X C135 MM	08W	4000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A135 X B58 X C135 MM	DIE CAST ALUMINUM	IP68	A135 X B58 X C135 MM	
6	MAZDA-UNXR207808W-4K-12V-GR-DA-A135 X B58 X C135 MM	08W	4000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A135 X B58 X C135 MM	DIE CAST ALUMINUM	IP68	A135 X B58 X C135 MM	
7	MAZDA-UNXR207808W-4K-12V-GR-PH-A135 X B58 X C135 MM	08W	4000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A135 X B58 X C135 MM	DIE CAST ALUMINUM	IP68	A135 X B58 X C135 MM	
8	MAZDA-UNXR207808W-4K-12V-GR-10VDIM-A135 X B58 X C135 MM	08W	4000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A135 X B58 X C135 MM	DIE CAST ALUMINUM	IP68	A135 X B58 X C135 MM	
9	MAZDA-UNXR207808W-5K-12V-GR-ND-A135 X B58 X C135 MM	08W	5000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A135 X B58 X C135 MM	DIE CAST ALUMINUM	IP68	A135 X B58 X C135 MM	
10	MAZDA-UNXR207808W-5K-12V-GR-DA-A135 X B58 X C135 MM	08W	5000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A135 X B58 X C135 MM	DIE CAST ALUMINUM	IP68	A135 X B58 X C135 MM	
11	MAZDA-UNXR207808W-5K-12V-GR-PH-A135 X B58 X C135 MM	08W	5000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A135 X B58 X C135 MM	DIE CAST ALUMINUM	IP68	A135 X B58 X C135 MM	
12	MAZDA-UNXR207808W-5K-12V-GR-10VDIM-A135 X B58 X C135 MM	08W	5000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A135 X B58 X C135 MM	DIE CAST ALUMINUM	IP68	A135 X B58 X C135 MM	
13	MAZDA-UNXR207808W-6K-12V-GR-ND-A135 X B58 X C135 MM	08W	6000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A135 X B58 X C135 MM	DIE CAST ALUMINUM	IP68	A135 X B58 X C135 MM	
14	MAZDA-UNXR207808W-6K-12V-GR-DA-A135 X B58 X C135 MM	08W	6000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A135 X B58 X C135 MM	DIE CAST ALUMINUM	IP68	A135 X B58 X C135 MM	
15	MAZDA-UNXR207808W-6K-12V-GR-PH-A135 X B58 X C135 MM	08W	6000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A135 X B58 X C135 MM	DIE CAST ALUMINUM	IP68	A135 X B58 X C135 MM	
16	MAZDA-UNXR207808W-6K-12V-GR-10VDIM-A135 X B58 X C135 MM	08W	6000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A135 X B58 X C135 MM	DIE CAST ALUMINUM	IP68	A135 X B58 X C135 MM	
17	MAZDA-UNXR207808W-2.7K-12V-GR-ND-A135 X B58 X C135 MM	08W	2700	12V	GREY & STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A135 X B58 X C135 MM	DIE CAST ALUMINUM	IP68	A135 X B58 X C135 MM	



DATASHEET

GENERATED ON: 06 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
18	MAZDA-UNXR207808W-2.7K-12V-GR-DA-A135 X B58 X C135 MM	08W	2700	12V	GREY & STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A135 X B58 X C135 MM	DIE CAST ALUMINUM	IP68	A135 X B58 X C135 MM	
19	MAZDA-UNXR207808W-2.7K-12V-GR-PH-A135 X B58 X C135 MM	08W	2700	12V	GREY & STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A135 X B58 X C135 MM	DIE CAST ALUMINUM	IP68	A135 X B58 X C135 MM	
20	MAZDA-UNXR207808W-2.7K-12V-GR-10VDIM-A135 X B58 X C135 MM	08W	2700	12V	GREY & STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A135 X B58 X C135 MM	DIE CAST ALUMINUM	IP68	A135 X B58 X C135 MM	
21	MAZDA-UNXR207808W-6.5K-12V-GR-ND-A135 X B58 X C135 MM	08W	6500	12V	GREY & STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A135 X B58 X C135 MM	DIE CAST ALUMINUM	IP68	A135 X B58 X C135 MM	
22	MAZDA-UNXR207808W-6.5K-12V-GR-DA-A135 X B58 X C135 MM	08W	6500	12V	GREY & STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A135 X B58 X C135 MM	DIE CAST ALUMINUM	IP68	A135 X B58 X C135 MM	
23	MAZDA-UNXR207808W-6.5K-12V-GR-PH-A135 X B58 X C135 MM	08W	6500	12V	GREY & STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A135 X B58 X C135 MM	DIE CAST ALUMINUM	IP68	A135 X B58 X C135 MM	
24	MAZDA-UNXR207808W-6.5K-12V-GR-10VDIM-A135 X B58 X C135 MM	08W	6500	12V	GREY & STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A135 X B58 X C135 MM	DIE CAST ALUMINUM	IP68	A135 X B58 X C135 MM	
25	MAZDA-UNXR207812W-3K-12V-GR-ND-A180 X B77 X C165 MM	12W	3000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM	
26	MAZDA-UNXR207812W-3K-12V-GR-DA-A180 X B77 X C165 MM	12W	3000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM	
27	MAZDA-UNXR207812W-3K-12V-GR-PH-A180 X B77 X C165 MM	12W	3000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM	
28	MAZDA-UNXR207812W-3K-12V-GR-10VDIM-A180 X B77 X C165 MM	12W	3000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM	
29	MAZDA-UNXR207812W-4K-12V-GR-ND-A180 X B77 X C165 MM	12W	4000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM	
30	MAZDA-UNXR207812W-4K-12V-GR-DA-A180 X B77 X C165 MM	12W	4000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM	
31	MAZDA-UNXR207812W-4K-12V-GR-PH-A180 X B77 X C165 MM	12W	4000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM	
32	MAZDA-UNXR207812W-4K-12V-GR-10VDIM-A180 X B77 X C165 MM	12W	4000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM	
33	MAZDA-UNXR207812W-5K-12V-GR-ND-A180 X B77 X C165 MM	12W	5000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM	
34	MAZDA-UNXR207812W-5K-12V-GR-DA-A180 X B77 X C165 MM	12W	5000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM	
35	MAZDA-UNXR207812W-5K-12V-GR-PH-A180 X B77 X C165 MM	12W	5000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM	
36	MAZDA-UNXR207812W-5K-12V-GR-10VDIM-A180 X B77 X C165 MM	12W	5000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM	
37	MAZDA-UNXR207812W-6K-12V-GR-ND-A180 X B77 X C165 MM	12W	6000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM	
38	MAZDA-UNXR207812W-6K-12V-GR-DA-A180 X B77 X C165 MM	12W	6000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM	
39	MAZDA-UNXR207812W-6K-12V-GR-PH-A180 X B77 X C165 MM	12W	6000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM	
40	MAZDA-UNXR207812W-6K-12V-GR-10VDIM-A180 X B77 X C165 MM	12W	6000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM	
41	MAZDA-UNXR207812W-2.7K-12V-GR-ND-A180 X B77 X C165 MM	12W	2700	12V	GREY & STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM	
42	MAZDA-UNXR207812W-2.7K-12V-GR-DA-A180 X B77 X C165 MM	12W	2700	12V	GREY & STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM	
43	MAZDA-UNXR207812W-2.7K-12V-GR-PH-A180 X B77 X C165 MM	12W	2700	12V	GREY & STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM	
44	MAZDA-UNXR207812W-2.7K-12V-GR-10VDIM-A180 X B77 X C165 MM	12W	2700	12V	GREY & STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM	
45	MAZDA-UNXR207812W-6.5K-12V-GR-ND-A180 X B77 X C165 MM	12W	6500	12V	GREY & STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM	



DATASHEET

GENERATED ON: 06 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
46	MAZDA-UNXR207812W-6.5K-12V-GR-DA-A180 X B77 X C165 MM	12W	6500	12V	GREY & STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM	
47	MAZDA-UNXR207812W-6.5K-12V-GR-PH-A180 X B77 X C165 MM	12W	6500	12V	GREY & STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM	
48	MAZDA-UNXR207812W-6.5K-12V-GR-10VDIM-A180 X B77 X C165 MM	12W	6500	12V	GREY & STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM	
49	MAZDA-UNXR207815W-3K-12V-GR-ND-A180 X B77 X C165 MM	15W	3000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM	
50	MAZDA-UNXR207815W-3K-12V-GR-DA-A180 X B77 X C165 MM	15W	3000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM	
51	MAZDA-UNXR207815W-3K-12V-GR-PH-A180 X B77 X C165 MM	15W	3000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM	
52	MAZDA-UNXR207815W-3K-12V-GR-10VDIM-A180 X B77 X C165 MM	15W	3000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM	
53	MAZDA-UNXR207815W-4K-12V-GR-ND-A180 X B77 X C165 MM	15W	4000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM	
54	MAZDA-UNXR207815W-4K-12V-GR-DA-A180 X B77 X C165 MM	15W	4000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM	
55	MAZDA-UNXR207815W-4K-12V-GR-PH-A180 X B77 X C165 MM	15W	4000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM	
56	MAZDA-UNXR207815W-4K-12V-GR-10VDIM-A180 X B77 X C165 MM	15W	4000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM	
57	MAZDA-UNXR207815W-5K-12V-GR-ND-A180 X B77 X C165 MM	15W	5000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM	
58	MAZDA-UNXR207815W-5K-12V-GR-DA-A180 X B77 X C165 MM	15W	5000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM	
59	MAZDA-UNXR207815W-5K-12V-GR-PH-A180 X B77 X C165 MM	15W	5000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM	
60	MAZDA-UNXR207815W-5K-12V-GR-10VDIM-A180 X B77 X C165 MM	15W	5000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM	
61	MAZDA-UNXR207815W-6K-12V-GR-ND-A180 X B77 X C165 MM	15W	6000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM	
62	MAZDA-UNXR207815W-6K-12V-GR-DA-A180 X B77 X C165 MM	15W	6000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM	
63	MAZDA-UNXR207815W-6K-12V-GR-PH-A180 X B77 X C165 MM	15W	6000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM	
64	MAZDA-UNXR207815W-6K-12V-GR-10VDIM-A180 X B77 X C165 MM	15W	6000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM	
65	MAZDA-UNXR207815W-2.7K-12V-GR-ND-A180 X B77 X C165 MM	15W	2700	12V	GREY & STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM	
66	MAZDA-UNXR207815W-2.7K-12V-GR-DA-A180 X B77 X C165 MM	15W	2700	12V	GREY & STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM	
67	MAZDA-UNXR207815W-2.7K-12V-GR-PH-A180 X B77 X C165 MM	15W	2700	12V	GREY & STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM	
68	MAZDA-UNXR207815W-2.7K-12V-GR-10VDIM-A180 X B77 X C165 MM	15W	2700	12V	GREY & STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM	
69	MAZDA-UNXR207815W-6.5K-12V-GR-ND-A180 X B77 X C165 MM	15W	6500	12V	GREY & STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM	
70	MAZDA-UNXR207815W-6.5K-12V-GR-DA-A180 X B77 X C165 MM	15W	6500	12V	GREY & STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM	
71	MAZDA-UNXR207815W-6.5K-12V-GR-PH-A180 X B77 X C165 MM	15W	6500	12V	GREY & STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM	
72	MAZDA-UNXR207815W-6.5K-12V-GR-10VDIM-A180 X B77 X C165 MM	15W	6500	12V	GREY & STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM	
73	MAZDA-UNXR207824W-3K-12V-GR-ND-A205 X B75 X C200 MM	24W	3000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A205 X B75 X C200 MM	DIE CAST ALUMINUM	IP68	A205 X B75 X C200 MM	



DATASHEET

GENERATED ON: 06 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
74	MAZDA-UNXR207824W-3K-12V-GR-DA-A205 X B75 X C200 MM	24W	3000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A205 X B75 X C200 MM	DIE CAST ALUMINUM	IP68	A205 X B75 X C200 MM	
75	MAZDA-UNXR207824W-3K-12V-GR-PH-A205 X B75 X C200 MM	24W	3000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A205 X B75 X C200 MM	DIE CAST ALUMINUM	IP68	A205 X B75 X C200 MM	
76	MAZDA-UNXR207824W-3K-12V-GR-10VDIM-A205 X B75 X C200 MM	24W	3000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A205 X B75 X C200 MM	DIE CAST ALUMINUM	IP68	A205 X B75 X C200 MM	
77	MAZDA-UNXR207824W-4K-12V-GR-ND-A205 X B75 X C200 MM	24W	4000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A205 X B75 X C200 MM	DIE CAST ALUMINUM	IP68	A205 X B75 X C200 MM	
78	MAZDA-UNXR207824W-4K-12V-GR-DA-A205 X B75 X C200 MM	24W	4000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A205 X B75 X C200 MM	DIE CAST ALUMINUM	IP68	A205 X B75 X C200 MM	
79	MAZDA-UNXR207824W-4K-12V-GR-PH-A205 X B75 X C200 MM	24W	4000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A205 X B75 X C200 MM	DIE CAST ALUMINUM	IP68	A205 X B75 X C200 MM	
80	MAZDA-UNXR207824W-4K-12V-GR-10VDIM-A205 X B75 X C200 MM	24W	4000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A205 X B75 X C200 MM	DIE CAST ALUMINUM	IP68	A205 X B75 X C200 MM	
81	MAZDA-UNXR207824W-5K-12V-GR-ND-A205 X B75 X C200 MM	24W	5000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A205 X B75 X C200 MM	DIE CAST ALUMINUM	IP68	A205 X B75 X C200 MM	
82	MAZDA-UNXR207824W-5K-12V-GR-DA-A205 X B75 X C200 MM	24W	5000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A205 X B75 X C200 MM	DIE CAST ALUMINUM	IP68	A205 X B75 X C200 MM	
83	MAZDA-UNXR207824W-5K-12V-GR-PH-A205 X B75 X C200 MM	24W	5000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A205 X B75 X C200 MM	DIE CAST ALUMINUM	IP68	A205 X B75 X C200 MM	
84	MAZDA-UNXR207824W-5K-12V-GR-10VDIM-A205 X B75 X C200 MM	24W	5000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A205 X B75 X C200 MM	DIE CAST ALUMINUM	IP68	A205 X B75 X C200 MM	
85	MAZDA-UNXR207824W-6K-12V-GR-ND-A205 X B75 X C200 MM	24W	6000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A205 X B75 X C200 MM	DIE CAST ALUMINUM	IP68	A205 X B75 X C200 MM	
86	MAZDA-UNXR207824W-6K-12V-GR-DA-A205 X B75 X C200 MM	24W	6000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A205 X B75 X C200 MM	DIE CAST ALUMINUM	IP68	A205 X B75 X C200 MM	
87	MAZDA-UNXR207824W-6K-12V-GR-PH-A205 X B75 X C200 MM	24W	6000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A205 X B75 X C200 MM	DIE CAST ALUMINUM	IP68	A205 X B75 X C200 MM	
88	MAZDA-UNXR207824W-6K-12V-GR-10VDIM-A205 X B75 X C200 MM	24W	6000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A205 X B75 X C200 MM	DIE CAST ALUMINUM	IP68	A205 X B75 X C200 MM	
89	MAZDA-UNXR207824W-2.7K-12V-GR-ND-A205 X B75 X C200 MM	24W	2700	12V	GREY & STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A205 X B75 X C200 MM	DIE CAST ALUMINUM	IP68	A205 X B75 X C200 MM	
90	MAZDA-UNXR207824W-2.7K-12V-GR-DA-A205 X B75 X C200 MM	24W	2700	12V	GREY & STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A205 X B75 X C200 MM	DIE CAST ALUMINUM	IP68	A205 X B75 X C200 MM	
91	MAZDA-UNXR207824W-2.7K-12V-GR-PH-A205 X B75 X C200 MM	24W	2700	12V	GREY & STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A205 X B75 X C200 MM	DIE CAST ALUMINUM	IP68	A205 X B75 X C200 MM	
92	MAZDA-UNXR207824W-2.7K-12V-GR-10VDIM-A205 X B75 X C200 MM	24W	2700	12V	GREY & STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A205 X B75 X C200 MM	DIE CAST ALUMINUM	IP68	A205 X B75 X C200 MM	
93	MAZDA-UNXR207824W-6.5K-12V-GR-ND-A205 X B75 X C200 MM	24W	6500	12V	GREY & STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A205 X B75 X C200 MM	DIE CAST ALUMINUM	IP68	A205 X B75 X C200 MM	
94	MAZDA-UNXR207824W-6.5K-12V-GR-DA-A205 X B75 X C200 MM	24W	6500	12V	GREY & STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A205 X B75 X C200 MM	DIE CAST ALUMINUM	IP68	A205 X B75 X C200 MM	
95	MAZDA-UNXR207824W-6.5K-12V-GR-PH-A205 X B75 X C200 MM	24W	6500	12V	GREY & STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A205 X B75 X C200 MM	DIE CAST ALUMINUM	IP68	A205 X B75 X C200 MM	
96	MAZDA-UNXR207824W-6.5K-12V-GR-10VDIM-A205 X B75 X C200 MM	24W	6500	12V	GREY & STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A205 X B75 X C200 MM	DIE CAST ALUMINUM	IP68	A205 X B75 X C200 MM	
97	MAZDA-UNXR207832W-3K-12V-GR-ND-A250 X B79 X 210 MM	32W	3000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A250 X B79 X 210 MM	DIE CAST ALUMINUM	IP68	A250 X B79 X 210 MM	
98	MAZDA-UNXR207832W-3K-12V-GR-DA-A250 X B79 X 210 MM	32W	3000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A250 X B79 X 210 MM	DIE CAST ALUMINUM	IP68	A250 X B79 X 210 MM	
99	MAZDA-UNXR207832W-3K-12V-GR-PH-A250 X B79 X 210 MM	32W	3000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A250 X B79 X 210 MM	DIE CAST ALUMINUM	IP68	A250 X B79 X 210 MM	
100	MAZDA-UNXR207832W-3K-12V-GR-10VDIM-A250 X B79 X 210 MM	32W	3000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A250 X B79 X 210 MM	DIE CAST ALUMINUM	IP68	A250 X B79 X 210 MM	
101	MAZDA-UNXR207832W-4K-12V-GR-ND-A250 X B79 X 210 MM	32W	4000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A250 X B79 X 210 MM	DIE CAST ALUMINUM	IP68	A250 X B79 X 210 MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
102	MAZDA-UNXR207832W-4K-12V-GR-DA-A250 X B79 X 210 MM	32W	4000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A250 X B79 X 210 MM	DIE CAST ALUMINUM	IP68	A250 X B79 X 210 MM	
103	MAZDA-UNXR207832W-4K-12V-GR-PH-A250 X B79 X 210 MM	32W	4000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A250 X B79 X 210 MM	DIE CAST ALUMINUM	IP68	A250 X B79 X 210 MM	
104	MAZDA-UNXR207832W-4K-12V-GR-10VDIM-A250 X B79 X 210 MM	32W	4000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A250 X B79 X 210 MM	DIE CAST ALUMINUM	IP68	A250 X B79 X 210 MM	
105	MAZDA-UNXR207832W-5K-12V-GR-ND-A250 X B79 X 210 MM	32W	5000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A250 X B79 X 210 MM	DIE CAST ALUMINUM	IP68	A250 X B79 X 210 MM	
106	MAZDA-UNXR207832W-5K-12V-GR-DA-A250 X B79 X 210 MM	32W	5000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A250 X B79 X 210 MM	DIE CAST ALUMINUM	IP68	A250 X B79 X 210 MM	
107	MAZDA-UNXR207832W-5K-12V-GR-PH-A250 X B79 X 210 MM	32W	5000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A250 X B79 X 210 MM	DIE CAST ALUMINUM	IP68	A250 X B79 X 210 MM	
108	MAZDA-UNXR207832W-5K-12V-GR-10VDIM-A250 X B79 X 210 MM	32W	5000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A250 X B79 X 210 MM	DIE CAST ALUMINUM	IP68	A250 X B79 X 210 MM	
109	MAZDA-UNXR207832W-6K-12V-GR-ND-A250 X B79 X 210 MM	32W	6000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A250 X B79 X 210 MM	DIE CAST ALUMINUM	IP68	A250 X B79 X 210 MM	
110	MAZDA-UNXR207832W-6K-12V-GR-DA-A250 X B79 X 210 MM	32W	6000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A250 X B79 X 210 MM	DIE CAST ALUMINUM	IP68	A250 X B79 X 210 MM	
111	MAZDA-UNXR207832W-6K-12V-GR-PH-A250 X B79 X 210 MM	32W	6000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A250 X B79 X 210 MM	DIE CAST ALUMINUM	IP68	A250 X B79 X 210 MM	
112	MAZDA-UNXR207832W-6K-12V-GR-10VDIM-A250 X B79 X 210 MM	32W	6000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A250 X B79 X 210 MM	DIE CAST ALUMINUM	IP68	A250 X B79 X 210 MM	
113	MAZDA-UNXR207832W-2.7K-12V-GR-ND-A250 X B79 X 210 MM	32W	2700	12V	GREY & STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A250 X B79 X 210 MM	DIE CAST ALUMINUM	IP68	A250 X B79 X 210 MM	
114	MAZDA-UNXR207832W-2.7K-12V-GR-DA-A250 X B79 X 210 MM	32W	2700	12V	GREY & STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A250 X B79 X 210 MM	DIE CAST ALUMINUM	IP68	A250 X B79 X 210 MM	
115	MAZDA-UNXR207832W-2.7K-12V-GR-PH-A250 X B79 X 210 MM	32W	2700	12V	GREY & STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A250 X B79 X 210 MM	DIE CAST ALUMINUM	IP68	A250 X B79 X 210 MM	
116	MAZDA-UNXR207832W-2.7K-12V-GR-10VDIM-A250 X B79 X 210 MM	32W	2700	12V	GREY & STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A250 X B79 X 210 MM	DIE CAST ALUMINUM	IP68	A250 X B79 X 210 MM	
117	MAZDA-UNXR207832W-6.5K-12V-GR-ND-A250 X B79 X 210 MM	32W	6500	12V	GREY & STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A250 X B79 X 210 MM	DIE CAST ALUMINUM	IP68	A250 X B79 X 210 MM	
118	MAZDA-UNXR207832W-6.5K-12V-GR-DA-A250 X B79 X 210 MM	32W	6500	12V	GREY & STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A250 X B79 X 210 MM	DIE CAST ALUMINUM	IP68	A250 X B79 X 210 MM	
119	MAZDA-UNXR207832W-6.5K-12V-GR-PH-A250 X B79 X 210 MM	32W	6500	12V	GREY & STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A250 X B79 X 210 MM	DIE CAST ALUMINUM	IP68	A250 X B79 X 210 MM	
120	MAZDA-UNXR207832W-6.5K-12V-GR-10VDIM-A250 X B79 X 210 MM	32W	6500	12V	GREY & STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A250 X B79 X 210 MM	DIE CAST ALUMINUM	IP68	A250 X B79 X 210 MM	