DATASHEET

GENERATED ON: 12 Nov 2026 | SYS.REF: MAZDA-LED



FALL

MAZDA Model: UNXR2078 Inground Light

The UNXR series is IP68 rated (fully submersible) and is a great choice for underwater lighting of water features and
ponds due to its solid plate. The fixture is recessed under. This high quality product can be used in water.

ALL AVAILABLE VARIANTS

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions Price
1	MAZDA-UNXR207808W-3K-12V-GR-ND-A135 X B58 X C135 MM	08W	3000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A135 X B58 X C135 MM	DIE CAST ALUMINUM	IP68	A135 X B58 X C135 MM
2	MAZDA-UNXR207808W-3K-12V-GR-DA-A135 X B58 X C135 MM	08W	3000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A135 X B58 X C135 MM	DIE CAST ALUMINUM	IP68	A135 X B58 X C135 MM
3	MAZDA-UNXR207808W-3K-12V-GR-PH-A135 X B58 X C135 MM	08W	3000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A135 X B58 X C135 MM	DIE CAST ALUMINUM	IP68	A135 X B58 X C135 MM
4	MAZDA-UNXR207808W-3K-12V-GR-10VDIM-A135 X B58 X C135 MM	08W	3000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A135 X B58 X C135 MM	DIE CAST ALUMINUM	IP68	A135 X B58 X C135 MM
5	MAZDA-UNXR207808W-4K-12V-GR-ND-A135 X B58 X C135 MM	08W	4000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A135 X B58 X C135 MM	DIE CAST ALUMINUM	IP68	A135 X B58 X C135 MM
6	MAZDA-UNXR207808W-4K-12V-GR-DA-A135 X B58 X C135 MM	08W	4000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A135 X B58 X C135 MM	DIE CAST ALUMINUM	IP68	A135 X B58 X C135 MM
7	MAZDA-UNXR207808W-4K-12V-GR-PH-A135 X B58 X C135 MM	08W	4000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A135 X B58 X C135 MM	DIE CAST ALUMINUM	IP68	A135 X B58 X C135 MM
8	MAZDA-UNXR207808W-4K-12V-GR-10VDIM-A135 X B58 X C135 MM	08W	4000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A135 X B58 X C135 MM	DIE CAST ALUMINUM	IP68	A135 X B58 X C135 MM
9	MAZDA-UNXR207808W-5K-12V-GR-ND-A135 X B58 X C135 MM	08W	5000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A135 X B58 X C135 MM	DIE CAST ALUMINUM	IP68	A135 X B58 X C135 MM
10	MAZDA-UNXR207808W-5K-12V-GR-DA-A135 X B58 X C135 MM	08W	5000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A135 X B58 X C135 MM	DIE CAST ALUMINUM	IP68	A135 X B58 X C135 MM
11	MAZDA-UNXR207808W-5K-12V-GR-PH-A135 X B58 X C135 MM	08W	5000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A135 X B58 X C135 MM	DIE CAST ALUMINUM	IP68	A135 X B58 X C135 MM
12	MAZDA-UNXR207808W-5K-12V-GR-10VDIM-A135 X B58 X C135 MM	08W	5000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A135 X B58 X C135 MM	DIE CAST ALUMINUM	IP68	A135 X B58 X C135 MM
13	MAZDA-UNXR207808W-6K-12V-GR-ND-A135 X B58 X C135 MM	08W	6000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A135 X B58 X C135 MM	DIE CAST ALUMINUM	IP68	A135 X B58 X C135 MM
14	MAZDA-UNXR207808W-6K-12V-GR-DA-A135 X B58 X C135 MM	08W	6000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A135 X B58 X C135 MM	DIE CAST ALUMINUM	IP68	A135 X B58 X C135 MM
15	MAZDA-UNXR207808W-6K-12V-GR-PH-A135 X B58 X C135 MM	08W	6000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A135 X B58 X C135 MM	DIE CAST ALUMINUM	IP68	A135 X B58 X C135 MM
16	MAZDA-UNXR207808W-6K-12V-GR-10VDIM-A135 X B58 X C135 MM	08W	6000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A135 X B58 X C135 MM	DIE CAST ALUMINUM	IP68	A135 X B58 X C135 MM
17	MAZDA-UNXR207808W-2.7K-12V-GR-ND-A135 X B58 X C135 MM	08W	2700	12V	GREY & STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A135 X B58 X C135 MM	DIE CAST ALUMINUM	IP68	A135 X B58 X C135 MM

DATASHEET

GENERATED ON: 12 Nov 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions Price
18	MAZDA-UNXR207808W-2.7K-12V-GR-DA-A135 X B58 X C135 MM	08W	2700	12V	GREY & STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A135 X B58 X C135 MM	DIE CAST ALUMINUM	IP68	A135 X B58 X C135 MM
19	MAZDA-UNXR207808W-2.7K-12V-GR-PH-A135 X B58 X C135 MM	08W	2700	12V	GREY & STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A135 X B58 X C135 MM	DIE CAST ALUMINUM	IP68	A135 X B58 X C135 MM
20	MAZDA-UNXR207808W-2.7K-12V-GR-10VDIM-A135 X B58 X C135 MM	08W	2700	12V	GREY & STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A135 X B58 X C135 MM	DIE CAST ALUMINUM	IP68	A135 X B58 X C135 MM
21	MAZDA-UNXR207808W-6.5K-12V-GR-ND-A135 X B58 X C135 MM	08W	6500	12V	GREY & STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A135 X B58 X C135 MM	DIE CAST ALUMINUM	IP68	A135 X B58 X C135 MM
22	MAZDA-UNXR207808W-6.5K-12V-GR-DA-A135 X B58 X C135 MM	08W	6500	12V	GREY & STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A135 X B58 X C135 MM	DIE CAST ALUMINUM	IP68	A135 X B58 X C135 MM
23	MAZDA-UNXR207808W-6.5K-12V-GR-PH-A135 X B58 X C135 MM	08W	6500	12V	GREY & STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A135 X B58 X C135 MM	DIE CAST ALUMINUM	IP68	A135 X B58 X C135 MM
24	MAZDA-UNXR207808W-6.5K-12V-GR-10VDIM-A135 X B58 X C135 MM	08W	6500	12V	GREY & STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A135 X B58 X C135 MM	DIE CAST ALUMINUM	IP68	A135 X B58 X C135 MM
25	MAZDA-UNXR207812W-3K-12V-GR-ND-A180 X B77 X C165 MM	12W	3000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM
26	MAZDA-UNXR207812W-3K-12V-GR-DA-A180 X B77 X C165 MM	12W	3000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM
27	MAZDA-UNXR207812W-3K-12V-GR-PH-A180 X B77 X C165 MM	12W	3000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM
28	MAZDA-UNXR207812W-3K-12V-GR-10VDIM-A180 X B77 X C165 MM	12W	3000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM
29	MAZDA-UNXR207812W-4K-12V-GR-ND-A180 X B77 X C165 MM	12W	4000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM
30	MAZDA-UNXR207812W-4K-12V-GR-DA-A180 X B77 X C165 MM	12W	4000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM
31	MAZDA-UNXR207812W-4K-12V-GR-PH-A180 X B77 X C165 MM	12W	4000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM
32	MAZDA-UNXR207812W-4K-12V-GR-10VDIM-A180 X B77 X C165 MM	12W	4000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM
33	MAZDA-UNXR207812W-5K-12V-GR-ND-A180 X B77 X C165 MM	12W	5000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM
34	MAZDA-UNXR207812W-5K-12V-GR-DA-A180 X B77 X C165 MM	12W	5000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM
35	MAZDA-UNXR207812W-5K-12V-GR-PH-A180 X B77 X C165 MM	12W	5000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM
36	MAZDA-UNXR207812W-5K-12V-GR-10VDIM-A180 X B77 X C165 MM	12W	5000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM
37	MAZDA-UNXR207812W-6K-12V-GR-ND-A180 X B77 X C165 MM	12W	6000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM
38	MAZDA-UNXR207812W-6K-12V-GR-DA-A180 X B77 X C165 MM	12W	6000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM
39	MAZDA-UNXR207812W-6K-12V-GR-PH-A180 X B77 X C165 MM	12W	6000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM
40	MAZDA-UNXR207812W-6K-12V-GR-10VDIM-A180 X B77 X C165 MM	12W	6000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM
41	MAZDA-UNXR207812W-2.7K-12V-GR-ND-A180 X B77 X C165 MM	12W	2700	12V	GREY & STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM
42	MAZDA-UNXR207812W-2.7K-12V-GR-DA-A180 X B77 X C165 MM	12W	2700	12V	GREY & STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM
43	MAZDA-UNXR207812W-2.7K-12V-GR-PH-A180 X B77 X C165 MM	12W	2700	12V	GREY & STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM
44	MAZDA-UNXR207812W-2.7K-12V-GR-10VDIM-A180 X B77 X C165 MM	12W	2700	12V	GREY & STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM
45	MAZDA-UNXR207812W-6.5K-12V-GR-ND-A180 X B77 X C165 MM	12W	6500	12V	GREY & STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM

DATASHEET

GENERATED ON: 12 Nov 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions Price
46	MAZDA-UNXR207812W-6.5K-12V-GR-DA-A180 X B77 X C165 MM	12W	6500	12V	GREY & STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM
47	MAZDA-UNXR207812W-6.5K-12V-GR-PH-A180 X B77 X C165 MM	12W	6500	12V	GREY & STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM
48	MAZDA-UNXR207812W-6.5K-12V-GR-10VDIM-A180 X B77 X C165 MM	12W	6500	12V	GREY & STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM
49	MAZDA-UNXR207815W-3K-12V-GR-ND-A180 X B77 X C165 MM	15W	3000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM
50	MAZDA-UNXR207815W-3K-12V-GR-DA-A180 X B77 X C165 MM	15W	3000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM
51	MAZDA-UNXR207815W-3K-12V-GR-PH-A180 X B77 X C165 MM	15W	3000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM
52	MAZDA-UNXR207815W-3K-12V-GR-10VDIM-A180 X B77 X C165 MM	15W	3000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM
53	MAZDA-UNXR207815W-4K-12V-GR-ND-A180 X B77 X C165 MM	15W	4000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM
54	MAZDA-UNXR207815W-4K-12V-GR-DA-A180 X B77 X C165 MM	15W	4000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM
55	MAZDA-UNXR207815W-4K-12V-GR-PH-A180 X B77 X C165 MM	15W	4000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM
56	MAZDA-UNXR207815W-4K-12V-GR-10VDIM-A180 X B77 X C165 MM	15W	4000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM
57	MAZDA-UNXR207815W-5K-12V-GR-ND-A180 X B77 X C165 MM	15W	5000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM
58	MAZDA-UNXR207815W-5K-12V-GR-DA-A180 X B77 X C165 MM	15W	5000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM
59	MAZDA-UNXR207815W-5K-12V-GR-PH-A180 X B77 X C165 MM	15W	5000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM
60	MAZDA-UNXR207815W-5K-12V-GR-10VDIM-A180 X B77 X C165 MM	15W	5000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM
61	MAZDA-UNXR207815W-6K-12V-GR-ND-A180 X B77 X C165 MM	15W	6000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM
62	MAZDA-UNXR207815W-6K-12V-GR-DA-A180 X B77 X C165 MM	15W	6000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM
63	MAZDA-UNXR207815W-6K-12V-GR-PH-A180 X B77 X C165 MM	15W	6000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM
64	MAZDA-UNXR207815W-6K-12V-GR-10VDIM-A180 X B77 X C165 MM	15W	6000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM
65	MAZDA-UNXR207815W-2.7K-12V-GR-ND-A180 X B77 X C165 MM	15W	2700	12V	GREY & STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM
66	MAZDA-UNXR207815W-2.7K-12V-GR-DA-A180 X B77 X C165 MM	15W	2700	12V	GREY & STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM
67	MAZDA-UNXR207815W-2.7K-12V-GR-PH-A180 X B77 X C165 MM	15W	2700	12V	GREY & STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM
68	MAZDA-UNXR207815W-2.7K-12V-GR-10VDIM-A180 X B77 X C165 MM	15W	2700	12V	GREY & STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM
69	MAZDA-UNXR207815W-6.5K-12V-GR-ND-A180 X B77 X C165 MM	15W	6500	12V	GREY & STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM
70	MAZDA-UNXR207815W-6.5K-12V-GR-DA-A180 X B77 X C165 MM	15W	6500	12V	GREY & STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM
71	MAZDA-UNXR207815W-6.5K-12V-GR-PH-A180 X B77 X C165 MM	15W	6500	12V	GREY & STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM
72	MAZDA-UNXR207815W-6.5K-12V-GR-10VDIM-A180 X B77 X C165 MM	15W	6500	12V	GREY & STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A180 X B77 X C165 MM	DIE CAST ALUMINUM	IP68	A180 X B77 X C165 MM
73	MAZDA-UNXR207824W-3K-12V-GR-ND-A205 X B75 X C200 MM	24W	3000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A205 X B75 X C200 MM	DIE CAST ALUMINUM	IP68	A205 X B75 X C200 MM

DATASHEET

GENERATED ON: 12 Nov 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions Price
74	MAZDA-UNXR207824W-3K-12V-GR-DA-A205 X B75 X C200 MM	24W	3000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A205 X B75 X C200 MM	DIE CAST ALUMINUM	IP68	A205 X B75 X C200 MM
75	MAZDA-UNXR207824W-3K-12V-GR-PH-A205 X B75 X C200 MM	24W	3000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A205 X B75 X C200 MM	DIE CAST ALUMINUM	IP68	A205 X B75 X C200 MM
76	MAZDA-UNXR207824W-3K-12V-GR-10VDIM-A205 X B75 X C200 MM	24W	3000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A205 X B75 X C200 MM	DIE CAST ALUMINUM	IP68	A205 X B75 X C200 MM
77	MAZDA-UNXR207824W-4K-12V-GR-ND-A205 X B75 X C200 MM	24W	4000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A205 X B75 X C200 MM	DIE CAST ALUMINUM	IP68	A205 X B75 X C200 MM
78	MAZDA-UNXR207824W-4K-12V-GR-DA-A205 X B75 X C200 MM	24W	4000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A205 X B75 X C200 MM	DIE CAST ALUMINUM	IP68	A205 X B75 X C200 MM
79	MAZDA-UNXR207824W-4K-12V-GR-PH-A205 X B75 X C200 MM	24W	4000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A205 X B75 X C200 MM	DIE CAST ALUMINUM	IP68	A205 X B75 X C200 MM
80	MAZDA-UNXR207824W-4K-12V-GR-10VDIM-A205 X B75 X C200 MM	24W	4000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A205 X B75 X C200 MM	DIE CAST ALUMINUM	IP68	A205 X B75 X C200 MM
81	MAZDA-UNXR207824W-5K-12V-GR-ND-A205 X B75 X C200 MM	24W	5000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A205 X B75 X C200 MM	DIE CAST ALUMINUM	IP68	A205 X B75 X C200 MM
82	MAZDA-UNXR207824W-5K-12V-GR-DA-A205 X B75 X C200 MM	24W	5000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A205 X B75 X C200 MM	DIE CAST ALUMINUM	IP68	A205 X B75 X C200 MM
83	MAZDA-UNXR207824W-5K-12V-GR-PH-A205 X B75 X C200 MM	24W	5000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A205 X B75 X C200 MM	DIE CAST ALUMINUM	IP68	A205 X B75 X C200 MM
84	MAZDA-UNXR207824W-5K-12V-GR-10VDIM-A205 X B75 X C200 MM	24W	5000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A205 X B75 X C200 MM	DIE CAST ALUMINUM	IP68	A205 X B75 X C200 MM
85	MAZDA-UNXR207824W-6K-12V-GR-ND-A205 X B75 X C200 MM	24W	6000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A205 X B75 X C200 MM	DIE CAST ALUMINUM	IP68	A205 X B75 X C200 MM
86	MAZDA-UNXR207824W-6K-12V-GR-DA-A205 X B75 X C200 MM	24W	6000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A205 X B75 X C200 MM	DIE CAST ALUMINUM	IP68	A205 X B75 X C200 MM
87	MAZDA-UNXR207824W-6K-12V-GR-PH-A205 X B75 X C200 MM	24W	6000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A205 X B75 X C200 MM	DIE CAST ALUMINUM	IP68	A205 X B75 X C200 MM
88	MAZDA-UNXR207824W-6K-12V-GR-10VDIM-A205 X B75 X C200 MM	24W	6000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A205 X B75 X C200 MM	DIE CAST ALUMINUM	IP68	A205 X B75 X C200 MM
89	MAZDA-UNXR207824W-2.7K-12V-GR-ND-A205 X B75 X C200 MM	24W	2700	12V	GREY & STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A205 X B75 X C200 MM	DIE CAST ALUMINUM	IP68	A205 X B75 X C200 MM
90	MAZDA-UNXR207824W-2.7K-12V-GR-DA-A205 X B75 X C200 MM	24W	2700	12V	GREY & STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A205 X B75 X C200 MM	DIE CAST ALUMINUM	IP68	A205 X B75 X C200 MM
91	MAZDA-UNXR207824W-2.7K-12V-GR-PH-A205 X B75 X C200 MM	24W	2700	12V	GREY & STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A205 X B75 X C200 MM	DIE CAST ALUMINUM	IP68	A205 X B75 X C200 MM
92	MAZDA-UNXR207824W-2.7K-12V-GR-10VDIM-A205 X B75 X C200 MM	24W	2700	12V	GREY & STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A205 X B75 X C200 MM	DIE CAST ALUMINUM	IP68	A205 X B75 X C200 MM
93	MAZDA-UNXR207824W-6.5K-12V-GR-ND-A205 X B75 X C200 MM	24W	6500	12V	GREY & STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A205 X B75 X C200 MM	DIE CAST ALUMINUM	IP68	A205 X B75 X C200 MM
94	MAZDA-UNXR207824W-6.5K-12V-GR-DA-A205 X B75 X C200 MM	24W	6500	12V	GREY & STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A205 X B75 X C200 MM	DIE CAST ALUMINUM	IP68	A205 X B75 X C200 MM
95	MAZDA-UNXR207824W-6.5K-12V-GR-PH-A205 X B75 X C200 MM	24W	6500	12V	GREY & STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A205 X B75 X C200 MM	DIE CAST ALUMINUM	IP68	A205 X B75 X C200 MM
96	MAZDA-UNXR207824W-6.5K-12V-GR-10VDIM-A205 X B75 X C200 MM	24W	6500	12V	GREY & STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A205 X B75 X C200 MM	DIE CAST ALUMINUM	IP68	A205 X B75 X C200 MM
97	MAZDA-UNXR207832W-3K-12V-GR-ND-A250 X B79 X 210 MM	32W	3000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A250 X B79 X 210 MM	DIE CAST ALUMINUM	IP68	A250 X B79 X 210 MM
98	MAZDA-UNXR207832W-3K-12V-GR-DA-A250 X B79 X 210 MM	32W	3000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A250 X B79 X 210 MM	DIE CAST ALUMINUM	IP68	A250 X B79 X 210 MM
99	MAZDA-UNXR207832W-3K-12V-GR-PH-A250 X B79 X 210 MM	32W	3000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A250 X B79 X 210 MM	DIE CAST ALUMINUM	IP68	A250 X B79 X 210 MM
100	MAZDA-UNXR207832W-3K-12V-GR-10VDIM-A250 X B79 X 210 MM	32W	3000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A250 X B79 X 210 MM	DIE CAST ALUMINUM	IP68	A250 X B79 X 210 MM
101	MAZDA-UNXR207832W-4K-12V-GR-ND-A250 X B79 X 210 MM	32W	4000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A250 X B79 X 210 MM	DIE CAST ALUMINUM	IP68	A250 X B79 X 210 MM

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions Price
102	**MAZDA-UNXR207832W-4K-12V-GR-DA-A250 X B79 X 210 MM**	32W	4000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A250 X B79 X 210 MM	DIE CAST ALUMINUM	IP68	A250 X B79 X 210 MM
103	**MAZDA-UNXR207832W-4K-12V-GR-PH-A250 X B79 X 210 MM**	32W	4000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A250 X B79 X 210 MM	DIE CAST ALUMINUM	IP68	A250 X B79 X 210 MM
104	**MAZDA-UNXR207832W-4K-12V-GR-10VDIM-A250 X B79 X 210 MM**	32W	4000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A250 X B79 X 210 MM	DIE CAST ALUMINUM	IP68	A250 X B79 X 210 MM
105	**MAZDA-UNXR207832W-5K-12V-GR-ND-A250 X B79 X 210 MM**	32W	5000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A250 X B79 X 210 MM	DIE CAST ALUMINUM	IP68	A250 X B79 X 210 MM
106	**MAZDA-UNXR207832W-5K-12V-GR-DA-A250 X B79 X 210 MM**	32W	5000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A250 X B79 X 210 MM	DIE CAST ALUMINUM	IP68	A250 X B79 X 210 MM
107	**MAZDA-UNXR207832W-5K-12V-GR-PH-A250 X B79 X 210 MM**	32W	5000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A250 X B79 X 210 MM	DIE CAST ALUMINUM	IP68	A250 X B79 X 210 MM
108	**MAZDA-UNXR207832W-5K-12V-GR-10VDIM-A250 X B79 X 210 MM**	32W	5000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A250 X B79 X 210 MM	DIE CAST ALUMINUM	IP68	A250 X B79 X 210 MM
109	**MAZDA-UNXR207832W-6K-12V-GR-ND-A250 X B79 X 210 MM**	32W	6000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A250 X B79 X 210 MM	DIE CAST ALUMINUM	IP68	A250 X B79 X 210 MM
110	**MAZDA-UNXR207832W-6K-12V-GR-DA-A250 X B79 X 210 MM**	32W	6000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A250 X B79 X 210 MM	DIE CAST ALUMINUM	IP68	A250 X B79 X 210 MM
111	**MAZDA-UNXR207832W-6K-12V-GR-PH-A250 X B79 X 210 MM**	32W	6000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A250 X B79 X 210 MM	DIE CAST ALUMINUM	IP68	A250 X B79 X 210 MM
112	**MAZDA-UNXR207832W-6K-12V-GR-10VDIM-A250 X B79 X 210 MM**	32W	6000	12V	GREY & STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A250 X B79 X 210 MM	DIE CAST ALUMINUM	IP68	A250 X B79 X 210 MM
113	**MAZDA-UNXR207832W-2.7K-12V-GR-ND-A250 X B79 X 210 MM**	32W	2700	12V	GREY & STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A250 X B79 X 210 MM	DIE CAST ALUMINUM	IP68	A250 X B79 X 210 MM
114	**MAZDA-UNXR207832W-2.7K-12V-GR-DA-A250 X B79 X 210 MM**	32W	2700	12V	GREY & STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A250 X B79 X 210 MM	DIE CAST ALUMINUM	IP68	A250 X B79 X 210 MM
115	**MAZDA-UNXR207832W-2.7K-12V-GR-PH-A250 X B79 X 210 MM**	32W	2700	12V	GREY & STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A250 X B79 X 210 MM	DIE CAST ALUMINUM	IP68	A250 X B79 X 210 MM
116	**MAZDA-UNXR207832W-2.7K-12V-GR-10VDIM-A250 X B79 X 210 MM**	32W	2700	12V	GREY & STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A250 X B79 X 210 MM	DIE CAST ALUMINUM	IP68	A250 X B79 X 210 MM
117	**MAZDA-UNXR207832W-6.5K-12V-GR-ND-A250 X B79 X 210 MM**	32W	6500	12V	GREY & STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A250 X B79 X 210 MM	DIE CAST ALUMINUM	IP68	A250 X B79 X 210 MM
118	**MAZDA-UNXR207832W-6.5K-12V-GR-DA-A250 X B79 X 210 MM**	32W	6500	12V	GREY & STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A250 X B79 X 210 MM	DIE CAST ALUMINUM	IP68	A250 X B79 X 210 MM
119	**MAZDA-UNXR207832W-6.5K-12V-GR-PH-A250 X B79 X 210 MM**	32W	6500	12V	GREY & STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A250 X B79 X 210 MM	DIE CAST ALUMINUM	IP68	A250 X B79 X 210 MM
120	**MAZDA-UNXR207832W-6.5K-12V-GR-10VDIM-A250 X B79 X 210 MM**	32W	6500	12V	GREY & STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A250 X B79 X 210 MM	DIE CAST ALUMINUM	IP68	A250 X B79 X 210 MM