



BSTAR

MAZDA Model: SXR1816 Spot Light

Bstar Recessed spotlight with die-cast aluminium body, die-cast aluminium heat sink, solid springs and chrome reflector. COB high power LED chip provides perfect combination of high lighting efficiency, comfortable lighting and humanization design, made by high quality aluminum profile. The item is very professional and it has all the characteristics to be involved in any kind of architectural or design project

ALL AVAILABLE VARIANTS

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
1	MAZDA-SXR181610W-3K-240V-WH-ND-A86 X B55 X C70MM	10W	3000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A86 X B55 X C70MM	DIE CAST ALUMINUM	IP54	1200LM	A86 X B55 X C70MM	
2	MAZDA-SXR181610W-3K-240V-WH-ND-EM-A86 X B55 X C70MM	10W	3000	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A86 X B55 X C70MM	DIE CAST ALUMINUM	IP54	1200LM	A86 X B55 X C70MM	
3	MAZDA-SXR181610W-3K-240V-WH-DA-A86 X B55 X C70MM	10W	3000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A86 X B55 X C70MM	DIE CAST ALUMINUM	IP54	1200LM	A86 X B55 X C70MM	
4	MAZDA-SXR181610W-3K-240V-WH-DA-EM-A86 X B55 X C70MM	10W	3000	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A86 X B55 X C70MM	DIE CAST ALUMINUM	IP54	1200LM	A86 X B55 X C70MM	
5	MAZDA-SXR181610W-3K-240V-WH-PH-A86 X B55 X C70MM	10W	3000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A86 X B55 X C70MM	DIE CAST ALUMINUM	IP54	1200LM	A86 X B55 X C70MM	
6	MAZDA-SXR181610W-3K-240V-WH-PH-EM-A86 X B55 X C70MM	10W	3000	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A86 X B55 X C70MM	DIE CAST ALUMINUM	IP54	1200LM	A86 X B55 X C70MM	
7	MAZDA-SXR181610W-3K-240V-WH-10VDIM-A86 X B55 X C70MM	10W	3000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A86 X B55 X C70MM	DIE CAST ALUMINUM	IP54	1200LM	A86 X B55 X C70MM	
8	MAZDA-SXR181610W-3K-240V-WH-10VDIM-EM-A86 X B55 X C70MM	10W	3000	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A86 X B55 X C70MM	DIE CAST ALUMINUM	IP54	1200LM	A86 X B55 X C70MM	
9	MAZDA-SXR181610W-4K-240V-WH-ND-A86 X B55 X C70MM	10W	4000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A86 X B55 X C70MM	DIE CAST ALUMINUM	IP54	1200LM	A86 X B55 X C70MM	
10	MAZDA-SXR181610W-4K-240V-WH-ND-EM-A86 X B55 X C70MM	10W	4000	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A86 X B55 X C70MM	DIE CAST ALUMINUM	IP54	1200LM	A86 X B55 X C70MM	
11	MAZDA-SXR181610W-4K-240V-WH-DA-A86 X B55 X C70MM	10W	4000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A86 X B55 X C70MM	DIE CAST ALUMINUM	IP54	1200LM	A86 X B55 X C70MM	
12	MAZDA-SXR181610W-4K-240V-WH-DA-EM-A86 X B55 X C70MM	10W	4000	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A86 X B55 X C70MM	DIE CAST ALUMINUM	IP54	1200LM	A86 X B55 X C70MM	
13	MAZDA-SXR181610W-4K-240V-WH-PH-A86 X B55 X C70MM	10W	4000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A86 X B55 X C70MM	DIE CAST ALUMINUM	IP54	1200LM	A86 X B55 X C70MM	
14	MAZDA-SXR181610W-4K-240V-WH-PH-EM-A86 X B55 X C70MM	10W	4000	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A86 X B55 X C70MM	DIE CAST ALUMINUM	IP54	1200LM	A86 X B55 X C70MM	
15	MAZDA-SXR181610W-4K-240V-WH-10VDIM-A86 X B55 X C70MM	10W	4000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A86 X B55 X C70MM	DIE CAST ALUMINUM	IP54	1200LM	A86 X B55 X C70MM	
16	MAZDA-SXR181610W-4K-240V-WH-10VDIM-EM-A86 X B55 X C70MM	10W	4000	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A86 X B55 X C70MM	DIE CAST ALUMINUM	IP54	1200LM	A86 X B55 X C70MM	
17	MAZDA-SXR181610W-5K-240V-WH-ND-A86 X B55 X C70MM	10W	5000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A86 X B55 X C70MM	DIE CAST ALUMINUM	IP54	1200LM	A86 X B55 X C70MM	



DATASHEET

GENERATED ON: 14 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
18	MAZDA-SXR181610W-5K-240V-WH-ND-EM-A86 X B55 X C70MM	10W	5000	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A86 X B55 X C70MM	DIE CAST ALUMINUM	IP54	1200LM	A86 X B55 X C70MM	
19	MAZDA-SXR181610W-5K-240V-WH-DA-A86 X B55 X C70MM	10W	5000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A86 X B55 X C70MM	DIE CAST ALUMINUM	IP54	1200LM	A86 X B55 X C70MM	
20	MAZDA-SXR181610W-5K-240V-WH-DA-EM-A86 X B55 X C70MM	10W	5000	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A86 X B55 X C70MM	DIE CAST ALUMINUM	IP54	1200LM	A86 X B55 X C70MM	
21	MAZDA-SXR181610W-5K-240V-WH-PH-A86 X B55 X C70MM	10W	5000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A86 X B55 X C70MM	DIE CAST ALUMINUM	IP54	1200LM	A86 X B55 X C70MM	
22	MAZDA-SXR181610W-5K-240V-WH-PH-EM-A86 X B55 X C70MM	10W	5000	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A86 X B55 X C70MM	DIE CAST ALUMINUM	IP54	1200LM	A86 X B55 X C70MM	
23	MAZDA-SXR181610W-5K-240V-WH-10VDIM-A86 X B55 X C70MM	10W	5000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A86 X B55 X C70MM	DIE CAST ALUMINUM	IP54	1200LM	A86 X B55 X C70MM	
24	MAZDA-SXR181610W-5K-240V-WH-10VDIM-EM-A86 X B55 X C70MM	10W	5000	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A86 X B55 X C70MM	DIE CAST ALUMINUM	IP54	1200LM	A86 X B55 X C70MM	
25	MAZDA-SXR181610W-6K-240V-WH-ND-A86 X B55 X C70MM	10W	6000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A86 X B55 X C70MM	DIE CAST ALUMINUM	IP54	1200LM	A86 X B55 X C70MM	
26	MAZDA-SXR181610W-6K-240V-WH-ND-EM-A86 X B55 X C70MM	10W	6000	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A86 X B55 X C70MM	DIE CAST ALUMINUM	IP54	1200LM	A86 X B55 X C70MM	
27	MAZDA-SXR181610W-6K-240V-WH-DA-A86 X B55 X C70MM	10W	6000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A86 X B55 X C70MM	DIE CAST ALUMINUM	IP54	1200LM	A86 X B55 X C70MM	
28	MAZDA-SXR181610W-6K-240V-WH-DA-EM-A86 X B55 X C70MM	10W	6000	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A86 X B55 X C70MM	DIE CAST ALUMINUM	IP54	1200LM	A86 X B55 X C70MM	
29	MAZDA-SXR181610W-6K-240V-WH-PH-A86 X B55 X C70MM	10W	6000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A86 X B55 X C70MM	DIE CAST ALUMINUM	IP54	1200LM	A86 X B55 X C70MM	
30	MAZDA-SXR181610W-6K-240V-WH-PH-EM-A86 X B55 X C70MM	10W	6000	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A86 X B55 X C70MM	DIE CAST ALUMINUM	IP54	1200LM	A86 X B55 X C70MM	
31	MAZDA-SXR181610W-6K-240V-WH-10VDIM-A86 X B55 X C70MM	10W	6000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A86 X B55 X C70MM	DIE CAST ALUMINUM	IP54	1200LM	A86 X B55 X C70MM	
32	MAZDA-SXR181610W-6K-240V-WH-10VDIM-EM-A86 X B55 X C70MM	10W	6000	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A86 X B55 X C70MM	DIE CAST ALUMINUM	IP54	1200LM	A86 X B55 X C70MM	
33	MAZDA-SXR181610W-2.7K-240V-WH-ND-A86 X B55 X C70MM	10W	2700	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A86 X B55 X C70MM	DIE CAST ALUMINUM	IP54	1200LM	A86 X B55 X C70MM	
34	MAZDA-SXR181610W-2.7K-240V-WH-ND-EM-A86 X B55 X C70MM	10W	2700	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A86 X B55 X C70MM	DIE CAST ALUMINUM	IP54	1200LM	A86 X B55 X C70MM	
35	MAZDA-SXR181610W-2.7K-240V-WH-DA-A86 X B55 X C70MM	10W	2700	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A86 X B55 X C70MM	DIE CAST ALUMINUM	IP54	1200LM	A86 X B55 X C70MM	
36	MAZDA-SXR181610W-2.7K-240V-WH-DA-EM-A86 X B55 X C70MM	10W	2700	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A86 X B55 X C70MM	DIE CAST ALUMINUM	IP54	1200LM	A86 X B55 X C70MM	
37	MAZDA-SXR181610W-2.7K-240V-WH-PH-A86 X B55 X C70MM	10W	2700	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A86 X B55 X C70MM	DIE CAST ALUMINUM	IP54	1200LM	A86 X B55 X C70MM	
38	MAZDA-SXR181610W-2.7K-240V-WH-PH-EM-A86 X B55 X C70MM	10W	2700	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A86 X B55 X C70MM	DIE CAST ALUMINUM	IP54	1200LM	A86 X B55 X C70MM	
39	MAZDA-SXR181610W-2.7K-240V-WH-10VDIM-A86 X B55 X C70MM	10W	2700	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A86 X B55 X C70MM	DIE CAST ALUMINUM	IP54	1200LM	A86 X B55 X C70MM	
40	MAZDA-SXR181610W-2.7K-240V-WH-10VDIM-EM-A86 X B55 X C70MM	10W	2700	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A86 X B55 X C70MM	DIE CAST ALUMINUM	IP54	1200LM	A86 X B55 X C70MM	
41	MAZDA-SXR181610W-6.5K-240V-WH-ND-A86 X B55 X C70MM	10W	6500	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A86 X B55 X C70MM	DIE CAST ALUMINUM	IP54	1200LM	A86 X B55 X C70MM	
42	MAZDA-SXR181610W-6.5K-240V-WH-ND-EM-A86 X B55 X C70MM	10W	6500	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A86 X B55 X C70MM	DIE CAST ALUMINUM	IP54	1200LM	A86 X B55 X C70MM	
43	MAZDA-SXR181610W-6.5K-240V-WH-DA-A86 X B55 X C70MM	10W	6500	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A86 X B55 X C70MM	DIE CAST ALUMINUM	IP54	1200LM	A86 X B55 X C70MM	
44	MAZDA-SXR181610W-6.5K-240V-WH-DA-EM-A86 X B55 X C70MM	10W	6500	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A86 X B55 X C70MM	DIE CAST ALUMINUM	IP54	1200LM	A86 X B55 X C70MM	
45	MAZDA-SXR181610W-6.5K-240V-WH-PH-A86 X B55 X C70MM	10W	6500	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A86 X B55 X C70MM	DIE CAST ALUMINUM	IP54	1200LM	A86 X B55 X C70MM	



DATASHEET

GENERATED ON: 14 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
46	MAZDA-SXR181610W-6.5K-240V-WH-PH-EM-A86 X B55 X C70MM	10W	6500	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A86 X B55 X C70MM	DIE CAST ALUMINUM	IP54	1200LM	A86 X B55 X C70MM	
47	MAZDA-SXR181610W-6.5K-240V-WH-10VDIM-A86 X B55 X C70MM	10W	6500	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A86 X B55 X C70MM	DIE CAST ALUMINUM	IP54	1200LM	A86 X B55 X C70MM	
48	MAZDA-SXR181610W-6.5K-240V-WH-10VDIM-EM-A86 X B55 X C70MM	10W	6500	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A86 X B55 X C70MM	DIE CAST ALUMINUM	IP54	1200LM	A86 X B55 X C70MM	
49	MAZDA-SXR181615W-3K-240V-WH-ND-A101 X B60 X C85MM	15W	3000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A101 X B60 X C85MM	DIE CAST ALUMINUM	IP54	1200LM	A101 X B60 X C85MM	
50	MAZDA-SXR181615W-3K-240V-WH-ND-EM-A101 X B60 X C85MM	15W	3000	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A101 X B60 X C85MM	DIE CAST ALUMINUM	IP54	1200LM	A101 X B60 X C85MM	
51	MAZDA-SXR181615W-3K-240V-WH-DA-A101 X B60 X C85MM	15W	3000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A101 X B60 X C85MM	DIE CAST ALUMINUM	IP54	1200LM	A101 X B60 X C85MM	
52	MAZDA-SXR181615W-3K-240V-WH-DA-EM-A101 X B60 X C85MM	15W	3000	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A101 X B60 X C85MM	DIE CAST ALUMINUM	IP54	1200LM	A101 X B60 X C85MM	
53	MAZDA-SXR181615W-3K-240V-WH-PH-A101 X B60 X C85MM	15W	3000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A101 X B60 X C85MM	DIE CAST ALUMINUM	IP54	1200LM	A101 X B60 X C85MM	
54	MAZDA-SXR181615W-3K-240V-WH-PH-EM-A101 X B60 X C85MM	15W	3000	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A101 X B60 X C85MM	DIE CAST ALUMINUM	IP54	1200LM	A101 X B60 X C85MM	
55	MAZDA-SXR181615W-3K-240V-WH-10VDIM-A101 X B60 X C85MM	15W	3000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A101 X B60 X C85MM	DIE CAST ALUMINUM	IP54	1200LM	A101 X B60 X C85MM	
56	MAZDA-SXR181615W-3K-240V-WH-10VDIM-EM-A101 X B60 X C85MM	15W	3000	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A101 X B60 X C85MM	DIE CAST ALUMINUM	IP54	1200LM	A101 X B60 X C85MM	
57	MAZDA-SXR181615W-4K-240V-WH-ND-A101 X B60 X C85MM	15W	4000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A101 X B60 X C85MM	DIE CAST ALUMINUM	IP54	1200LM	A101 X B60 X C85MM	
58	MAZDA-SXR181615W-4K-240V-WH-ND-EM-A101 X B60 X C85MM	15W	4000	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A101 X B60 X C85MM	DIE CAST ALUMINUM	IP54	1200LM	A101 X B60 X C85MM	
59	MAZDA-SXR181615W-4K-240V-WH-DA-A101 X B60 X C85MM	15W	4000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A101 X B60 X C85MM	DIE CAST ALUMINUM	IP54	1200LM	A101 X B60 X C85MM	
60	MAZDA-SXR181615W-4K-240V-WH-DA-EM-A101 X B60 X C85MM	15W	4000	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A101 X B60 X C85MM	DIE CAST ALUMINUM	IP54	1200LM	A101 X B60 X C85MM	
61	MAZDA-SXR181615W-4K-240V-WH-PH-A101 X B60 X C85MM	15W	4000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A101 X B60 X C85MM	DIE CAST ALUMINUM	IP54	1200LM	A101 X B60 X C85MM	
62	MAZDA-SXR181615W-4K-240V-WH-PH-EM-A101 X B60 X C85MM	15W	4000	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A101 X B60 X C85MM	DIE CAST ALUMINUM	IP54	1200LM	A101 X B60 X C85MM	
63	MAZDA-SXR181615W-4K-240V-WH-10VDIM-A101 X B60 X C85MM	15W	4000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A101 X B60 X C85MM	DIE CAST ALUMINUM	IP54	1200LM	A101 X B60 X C85MM	
64	MAZDA-SXR181615W-4K-240V-WH-10VDIM-EM-A101 X B60 X C85MM	15W	4000	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A101 X B60 X C85MM	DIE CAST ALUMINUM	IP54	1200LM	A101 X B60 X C85MM	
65	MAZDA-SXR181615W-5K-240V-WH-ND-A101 X B60 X C85MM	15W	5000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A101 X B60 X C85MM	DIE CAST ALUMINUM	IP54	1200LM	A101 X B60 X C85MM	
66	MAZDA-SXR181615W-5K-240V-WH-ND-EM-A101 X B60 X C85MM	15W	5000	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A101 X B60 X C85MM	DIE CAST ALUMINUM	IP54	1200LM	A101 X B60 X C85MM	
67	MAZDA-SXR181615W-5K-240V-WH-DA-A101 X B60 X C85MM	15W	5000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A101 X B60 X C85MM	DIE CAST ALUMINUM	IP54	1200LM	A101 X B60 X C85MM	
68	MAZDA-SXR181615W-5K-240V-WH-DA-EM-A101 X B60 X C85MM	15W	5000	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A101 X B60 X C85MM	DIE CAST ALUMINUM	IP54	1200LM	A101 X B60 X C85MM	
69	MAZDA-SXR181615W-5K-240V-WH-PH-A101 X B60 X C85MM	15W	5000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A101 X B60 X C85MM	DIE CAST ALUMINUM	IP54	1200LM	A101 X B60 X C85MM	
70	MAZDA-SXR181615W-5K-240V-WH-PH-EM-A101 X B60 X C85MM	15W	5000	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A101 X B60 X C85MM	DIE CAST ALUMINUM	IP54	1200LM	A101 X B60 X C85MM	
71	MAZDA-SXR181615W-5K-240V-WH-10VDIM-A101 X B60 X C85MM	15W	5000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A101 X B60 X C85MM	DIE CAST ALUMINUM	IP54	1200LM	A101 X B60 X C85MM	
72	MAZDA-SXR181615W-5K-240V-WH-10VDIM-EM-A101 X B60 X C85MM	15W	5000	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A101 X B60 X C85MM	DIE CAST ALUMINUM	IP54	1200LM	A101 X B60 X C85MM	
73	MAZDA-SXR181615W-6K-240V-WH-ND-A101 X B60 X C85MM	15W	6000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A101 X B60 X C85MM	DIE CAST ALUMINUM	IP54	1200LM	A101 X B60 X C85MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
74	MAZDA-SXR181615W-6K-240V-WH-ND-EM-A101 X B60 X C85MM	15W	6000	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A101 X B60 X C85MM	DIE CAST ALUMINUM	IP54	1200LM	A101 X B60 X C85MM	
75	MAZDA-SXR181615W-6K-240V-WH-DA-A101 X B60 X C85MM	15W	6000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A101 X B60 X C85MM	DIE CAST ALUMINUM	IP54	1200LM	A101 X B60 X C85MM	
76	MAZDA-SXR181615W-6K-240V-WH-DA-EM-A101 X B60 X C85MM	15W	6000	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A101 X B60 X C85MM	DIE CAST ALUMINUM	IP54	1200LM	A101 X B60 X C85MM	
77	MAZDA-SXR181615W-6K-240V-WH-PH-A101 X B60 X C85MM	15W	6000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A101 X B60 X C85MM	DIE CAST ALUMINUM	IP54	1200LM	A101 X B60 X C85MM	
78	MAZDA-SXR181615W-6K-240V-WH-PH-EM-A101 X B60 X C85MM	15W	6000	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A101 X B60 X C85MM	DIE CAST ALUMINUM	IP54	1200LM	A101 X B60 X C85MM	
79	MAZDA-SXR181615W-6K-240V-WH-10VDIM-A101 X B60 X C85MM	15W	6000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A101 X B60 X C85MM	DIE CAST ALUMINUM	IP54	1200LM	A101 X B60 X C85MM	
80	MAZDA-SXR181615W-6K-240V-WH-10VDIM-EM-A101 X B60 X C85MM	15W	6000	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A101 X B60 X C85MM	DIE CAST ALUMINUM	IP54	1200LM	A101 X B60 X C85MM	
81	MAZDA-SXR181615W-2.7K-240V-WH-ND-A101 X B60 X C85MM	15W	2700	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A101 X B60 X C85MM	DIE CAST ALUMINUM	IP54	1200LM	A101 X B60 X C85MM	
82	MAZDA-SXR181615W-2.7K-240V-WH-ND-EM-A101 X B60 X C85MM	15W	2700	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A101 X B60 X C85MM	DIE CAST ALUMINUM	IP54	1200LM	A101 X B60 X C85MM	
83	MAZDA-SXR181615W-2.7K-240V-WH-DA-A101 X B60 X C85MM	15W	2700	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A101 X B60 X C85MM	DIE CAST ALUMINUM	IP54	1200LM	A101 X B60 X C85MM	
84	MAZDA-SXR181615W-2.7K-240V-WH-DA-EM-A101 X B60 X C85MM	15W	2700	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A101 X B60 X C85MM	DIE CAST ALUMINUM	IP54	1200LM	A101 X B60 X C85MM	
85	MAZDA-SXR181615W-2.7K-240V-WH-PH-A101 X B60 X C85MM	15W	2700	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A101 X B60 X C85MM	DIE CAST ALUMINUM	IP54	1200LM	A101 X B60 X C85MM	
86	MAZDA-SXR181615W-2.7K-240V-WH-PH-EM-A101 X B60 X C85MM	15W	2700	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A101 X B60 X C85MM	DIE CAST ALUMINUM	IP54	1200LM	A101 X B60 X C85MM	
87	MAZDA-SXR181615W-2.7K-240V-WH-10VDIM-A101 X B60 X C85MM	15W	2700	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A101 X B60 X C85MM	DIE CAST ALUMINUM	IP54	1200LM	A101 X B60 X C85MM	
88	MAZDA-SXR181615W-2.7K-240V-WH-10VDIM-EM-A101 X B60 X C85MM	15W	2700	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A101 X B60 X C85MM	DIE CAST ALUMINUM	IP54	1200LM	A101 X B60 X C85MM	
89	MAZDA-SXR181615W-6.5K-240V-WH-ND-A101 X B60 X C85MM	15W	6500	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A101 X B60 X C85MM	DIE CAST ALUMINUM	IP54	1200LM	A101 X B60 X C85MM	
90	MAZDA-SXR181615W-6.5K-240V-WH-ND-EM-A101 X B60 X C85MM	15W	6500	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A101 X B60 X C85MM	DIE CAST ALUMINUM	IP54	1200LM	A101 X B60 X C85MM	
91	MAZDA-SXR181615W-6.5K-240V-WH-DA-A101 X B60 X C85MM	15W	6500	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A101 X B60 X C85MM	DIE CAST ALUMINUM	IP54	1200LM	A101 X B60 X C85MM	
92	MAZDA-SXR181615W-6.5K-240V-WH-DA-EM-A101 X B60 X C85MM	15W	6500	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A101 X B60 X C85MM	DIE CAST ALUMINUM	IP54	1200LM	A101 X B60 X C85MM	
93	MAZDA-SXR181615W-6.5K-240V-WH-PH-A101 X B60 X C85MM	15W	6500	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A101 X B60 X C85MM	DIE CAST ALUMINUM	IP54	1200LM	A101 X B60 X C85MM	
94	MAZDA-SXR181615W-6.5K-240V-WH-PH-EM-A101 X B60 X C85MM	15W	6500	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A101 X B60 X C85MM	DIE CAST ALUMINUM	IP54	1200LM	A101 X B60 X C85MM	
95	MAZDA-SXR181615W-6.5K-240V-WH-10VDIM-A101 X B60 X C85MM	15W	6500	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A101 X B60 X C85MM	DIE CAST ALUMINUM	IP54	1200LM	A101 X B60 X C85MM	
96	MAZDA-SXR181615W-6.5K-240V-WH-10VDIM-EM-A101 X B60 X C85MM	15W	6500	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A101 X B60 X C85MM	DIE CAST ALUMINUM	IP54	1200LM	A101 X B60 X C85MM	