



KEEPER A

MAZDA Model: SXR1890 Spot Light

LED Spot Light Attractive exclusive downlight for indoor or outdoor use, particularly well suited to basic lighting due to its very low unified glare rating. Well integrated LED chip and associated dimmable driver. Made of die-cast powder-coated aluminium. Low recessed downlight with hole size. This unique design skillfully prevent the human eyes contact with the light sources directly, makes the light more soft. Meanwhile the light efficiency with perfect accent lighting performance. That makes it become the priority selected product for commercial lighting. Great cooling fins heat sink design increases the interface between heat sink and air, which makes the heat dissipating performance outstanding and extend the service life of the downlight. Suitable for commercial and residential applications like office, supermarket, shop, school, hotel, restaurant, workshop, warehouse, home etc

ALL AVAILABLE VARIANTS

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
1	MAZDA-SXR189007W-3K-240V-BK-ND-A60 X B48 X C55MM	07W	3000	240V	BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
2	MAZDA-SXR189007W-3K-240V-BK-ND-EM-A60 X B48 X C55MM	07W	3000	240V	BLACK	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
3	MAZDA-SXR189007W-3K-240V-WH-ND-A60 X B48 X C55MM	07W	3000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
4	MAZDA-SXR189007W-3K-240V-WH-ND-EM-A60 X B48 X C55MM	07W	3000	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
5	MAZDA-SXR189007W-3K-240V-BK-DA-A60 X B48 X C55MM	07W	3000	240V	BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
6	MAZDA-SXR189007W-3K-240V-BK-DA-EM-A60 X B48 X C55MM	07W	3000	240V	BLACK	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
7	MAZDA-SXR189007W-3K-240V-WH-DA-A60 X B48 X C55MM	07W	3000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
8	MAZDA-SXR189007W-3K-240V-WH-DA-EM-A60 X B48 X C55MM	07W	3000	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
9	MAZDA-SXR189007W-3K-240V-BK-PH-A60 X B48 X C55MM	07W	3000	240V	BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
10	MAZDA-SXR189007W-3K-240V-BK-PH-EM-A60 X B48 X C55MM	07W	3000	240V	BLACK	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
11	MAZDA-SXR189007W-3K-240V-WH-PH-A60 X B48 X C55MM	07W	3000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
12	MAZDA-SXR189007W-3K-240V-WH-PH-EM-A60 X B48 X C55MM	07W	3000	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
13	MAZDA-SXR189007W-3K-240V-BK-10VDIM-A60 X B48 X C55MM	07W	3000	240V	BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
14	MAZDA-SXR189007W-3K-240V-BK-10VDIM-EM-A60 X B48 X C55MM	07W	3000	240V	BLACK	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
15	MAZDA-SXR189007W-3K-240V-WH-10VDIM-A60 X B48 X C55MM	07W	3000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
16	MAZDA-SXR189007W-3K-240V-WH-10VDIM-EM-A60 X B48 X C55MM	07W	3000	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
17	MAZDA-SXR189007W-4K-240V-BK-ND-A60 X B48 X C55MM	07W	4000	240V	BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	



DATASHEET

GENERATED ON: 14 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
18	MAZDA-SXR189007W-4K-240V-BK-ND-EM-A60 X B48 X C55MM	07W	4000	240V	BLACK	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
19	MAZDA-SXR189007W-4K-240V-WH-ND-A60 X B48 X C55MM	07W	4000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
20	MAZDA-SXR189007W-4K-240V-WH-ND-EM-A60 X B48 X C55MM	07W	4000	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
21	MAZDA-SXR189007W-4K-240V-BK-DA-A60 X B48 X C55MM	07W	4000	240V	BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
22	MAZDA-SXR189007W-4K-240V-BK-DA-EM-A60 X B48 X C55MM	07W	4000	240V	BLACK	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
23	MAZDA-SXR189007W-4K-240V-WH-DA-A60 X B48 X C55MM	07W	4000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
24	MAZDA-SXR189007W-4K-240V-WH-DA-EM-A60 X B48 X C55MM	07W	4000	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
25	MAZDA-SXR189007W-4K-240V-BK-PH-A60 X B48 X C55MM	07W	4000	240V	BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
26	MAZDA-SXR189007W-4K-240V-BK-PH-EM-A60 X B48 X C55MM	07W	4000	240V	BLACK	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
27	MAZDA-SXR189007W-4K-240V-WH-PH-A60 X B48 X C55MM	07W	4000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
28	MAZDA-SXR189007W-4K-240V-WH-PH-EM-A60 X B48 X C55MM	07W	4000	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
29	MAZDA-SXR189007W-4K-240V-BK-10VDIM-A60 X B48 X C55MM	07W	4000	240V	BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
30	MAZDA-SXR189007W-4K-240V-BK-10VDIM-EM-A60 X B48 X C55MM	07W	4000	240V	BLACK	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
31	MAZDA-SXR189007W-4K-240V-WH-10VDIM-A60 X B48 X C55MM	07W	4000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
32	MAZDA-SXR189007W-4K-240V-WH-10VDIM-EM-A60 X B48 X C55MM	07W	4000	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
33	MAZDA-SXR189007W-5K-240V-BK-ND-A60 X B48 X C55MM	07W	5000	240V	BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
34	MAZDA-SXR189007W-5K-240V-BK-ND-EM-A60 X B48 X C55MM	07W	5000	240V	BLACK	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
35	MAZDA-SXR189007W-5K-240V-WH-ND-A60 X B48 X C55MM	07W	5000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
36	MAZDA-SXR189007W-5K-240V-WH-ND-EM-A60 X B48 X C55MM	07W	5000	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
37	MAZDA-SXR189007W-5K-240V-BK-DA-A60 X B48 X C55MM	07W	5000	240V	BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
38	MAZDA-SXR189007W-5K-240V-BK-DA-EM-A60 X B48 X C55MM	07W	5000	240V	BLACK	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
39	MAZDA-SXR189007W-5K-240V-WH-DA-A60 X B48 X C55MM	07W	5000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
40	MAZDA-SXR189007W-5K-240V-WH-DA-EM-A60 X B48 X C55MM	07W	5000	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
41	MAZDA-SXR189007W-5K-240V-BK-PH-A60 X B48 X C55MM	07W	5000	240V	BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
42	MAZDA-SXR189007W-5K-240V-BK-PH-EM-A60 X B48 X C55MM	07W	5000	240V	BLACK	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
43	MAZDA-SXR189007W-5K-240V-WH-PH-A60 X B48 X C55MM	07W	5000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
44	MAZDA-SXR189007W-5K-240V-WH-PH-EM-A60 X B48 X C55MM	07W	5000	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
45	MAZDA-SXR189007W-5K-240V-BK-10VDIM-A60 X B48 X C55MM	07W	5000	240V	BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	



DATASHEET

GENERATED ON: 14 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
46	MAZDA-SXR189007W-5K-240V-BK-10VDIM-EM-A60 X B48 X C55MM	07W	5000	240V	BLACK	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
47	MAZDA-SXR189007W-5K-240V-WH-10VDIM-A60 X B48 X C55MM	07W	5000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
48	MAZDA-SXR189007W-5K-240V-WH-10VDIM-EM-A60 X B48 X C55MM	07W	5000	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
49	MAZDA-SXR189007W-6K-240V-BK-ND-A60 X B48 X C55MM	07W	6000	240V	BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
50	MAZDA-SXR189007W-6K-240V-BK-ND-EM-A60 X B48 X C55MM	07W	6000	240V	BLACK	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
51	MAZDA-SXR189007W-6K-240V-WH-ND-A60 X B48 X C55MM	07W	6000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
52	MAZDA-SXR189007W-6K-240V-WH-ND-EM-A60 X B48 X C55MM	07W	6000	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
53	MAZDA-SXR189007W-6K-240V-BK-DA-A60 X B48 X C55MM	07W	6000	240V	BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
54	MAZDA-SXR189007W-6K-240V-BK-DA-EM-A60 X B48 X C55MM	07W	6000	240V	BLACK	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
55	MAZDA-SXR189007W-6K-240V-WH-DA-A60 X B48 X C55MM	07W	6000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
56	MAZDA-SXR189007W-6K-240V-WH-DA-EM-A60 X B48 X C55MM	07W	6000	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
57	MAZDA-SXR189007W-6K-240V-BK-PH-A60 X B48 X C55MM	07W	6000	240V	BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
58	MAZDA-SXR189007W-6K-240V-BK-PH-EM-A60 X B48 X C55MM	07W	6000	240V	BLACK	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
59	MAZDA-SXR189007W-6K-240V-WH-PH-A60 X B48 X C55MM	07W	6000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
60	MAZDA-SXR189007W-6K-240V-WH-PH-EM-A60 X B48 X C55MM	07W	6000	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
61	MAZDA-SXR189007W-6K-240V-BK-10VDIM-A60 X B48 X C55MM	07W	6000	240V	BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
62	MAZDA-SXR189007W-6K-240V-BK-10VDIM-EM-A60 X B48 X C55MM	07W	6000	240V	BLACK	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
63	MAZDA-SXR189007W-6K-240V-WH-10VDIM-A60 X B48 X C55MM	07W	6000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
64	MAZDA-SXR189007W-6K-240V-WH-10VDIM-EM-A60 X B48 X C55MM	07W	6000	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
65	MAZDA-SXR189007W-2.7K-240V-BK-ND-A60 X B48 X C55MM	07W	2700	240V	BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
66	MAZDA-SXR189007W-2.7K-240V-BK-ND-EM-A60 X B48 X C55MM	07W	2700	240V	BLACK	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
67	MAZDA-SXR189007W-2.7K-240V-WH-ND-A60 X B48 X C55MM	07W	2700	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
68	MAZDA-SXR189007W-2.7K-240V-WH-ND-EM-A60 X B48 X C55MM	07W	2700	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
69	MAZDA-SXR189007W-2.7K-240V-BK-DA-A60 X B48 X C55MM	07W	2700	240V	BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
70	MAZDA-SXR189007W-2.7K-240V-BK-DA-EM-A60 X B48 X C55MM	07W	2700	240V	BLACK	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
71	MAZDA-SXR189007W-2.7K-240V-WH-DA-A60 X B48 X C55MM	07W	2700	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
72	MAZDA-SXR189007W-2.7K-240V-WH-DA-EM-A60 X B48 X C55MM	07W	2700	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
73	MAZDA-SXR189007W-2.7K-240V-BK-PH-A60 X B48 X C55MM	07W	2700	240V	BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	



DATASHEET

GENERATED ON: 14 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
74	MAZDA-SXR189007W-2.7K-240V-BK-PH-EM-A60 X B48 X C55MM	07W	2700	240V	BLACK	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
75	MAZDA-SXR189007W-2.7K-240V-WH-PH-A60 X B48 X C55MM	07W	2700	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
76	MAZDA-SXR189007W-2.7K-240V-WH-PH-EM-A60 X B48 X C55MM	07W	2700	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
77	MAZDA-SXR189007W-2.7K-240V-BK-10VDIM-A60 X B48 X C55MM	07W	2700	240V	BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
78	MAZDA-SXR189007W-2.7K-240V-BK-10VDIM-EM-A60 X B48 X C55MM	07W	2700	240V	BLACK	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
79	MAZDA-SXR189007W-2.7K-240V-WH-10VDIM-A60 X B48 X C55MM	07W	2700	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
80	MAZDA-SXR189007W-2.7K-240V-WH-10VDIM-EM-A60 X B48 X C55MM	07W	2700	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
81	MAZDA-SXR189007W-6.5K-240V-BK-ND-A60 X B48 X C55MM	07W	6500	240V	BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
82	MAZDA-SXR189007W-6.5K-240V-BK-ND-EM-A60 X B48 X C55MM	07W	6500	240V	BLACK	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
83	MAZDA-SXR189007W-6.5K-240V-WH-ND-A60 X B48 X C55MM	07W	6500	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
84	MAZDA-SXR189007W-6.5K-240V-WH-ND-EM-A60 X B48 X C55MM	07W	6500	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
85	MAZDA-SXR189007W-6.5K-240V-BK-DA-A60 X B48 X C55MM	07W	6500	240V	BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
86	MAZDA-SXR189007W-6.5K-240V-BK-DA-EM-A60 X B48 X C55MM	07W	6500	240V	BLACK	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
87	MAZDA-SXR189007W-6.5K-240V-WH-DA-A60 X B48 X C55MM	07W	6500	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
88	MAZDA-SXR189007W-6.5K-240V-WH-DA-EM-A60 X B48 X C55MM	07W	6500	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
89	MAZDA-SXR189007W-6.5K-240V-BK-PH-A60 X B48 X C55MM	07W	6500	240V	BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
90	MAZDA-SXR189007W-6.5K-240V-BK-PH-EM-A60 X B48 X C55MM	07W	6500	240V	BLACK	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
91	MAZDA-SXR189007W-6.5K-240V-WH-PH-A60 X B48 X C55MM	07W	6500	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
92	MAZDA-SXR189007W-6.5K-240V-WH-PH-EM-A60 X B48 X C55MM	07W	6500	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
93	MAZDA-SXR189007W-6.5K-240V-BK-10VDIM-A60 X B48 X C55MM	07W	6500	240V	BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
94	MAZDA-SXR189007W-6.5K-240V-BK-10VDIM-EM-A60 X B48 X C55MM	07W	6500	240V	BLACK	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
95	MAZDA-SXR189007W-6.5K-240V-WH-10VDIM-A60 X B48 X C55MM	07W	6500	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
96	MAZDA-SXR189007W-6.5K-240V-WH-10VDIM-EM-A60 X B48 X C55MM	07W	6500	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A60 X B48 X C55MM	DIE CAST ALUMINUM	IP44	840LM	A60 X B48 X C55MM	
97	MAZDA-SXR189012W-3K-240V-BK-ND-A82 X B62 X C75MM	12W	3000	240V	BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
98	MAZDA-SXR189012W-3K-240V-BK-ND-EM-A82 X B62 X C75MM	12W	3000	240V	BLACK	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
99	MAZDA-SXR189012W-3K-240V-WH-ND-A82 X B62 X C75MM	12W	3000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
100	MAZDA-SXR189012W-3K-240V-WH-ND-EM-A82 X B62 X C75MM	12W	3000	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
101	MAZDA-SXR189012W-3K-240V-BK-DA-A82 X B62 X C75MM	12W	3000	240V	BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	



DATASHEET

GENERATED ON: 14 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
102	MAZDA-SXR189012W-3K-240V-BK-DA-EM-A82 X B62 X C75MM	12W	3000	240V	BLACK	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
103	MAZDA-SXR189012W-3K-240V-WH-DA-A82 X B62 X C75MM	12W	3000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
104	MAZDA-SXR189012W-3K-240V-WH-DA-EM-A82 X B62 X C75MM	12W	3000	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
105	MAZDA-SXR189012W-3K-240V-BK-PH-A82 X B62 X C75MM	12W	3000	240V	BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
106	MAZDA-SXR189012W-3K-240V-BK-PH-EM-A82 X B62 X C75MM	12W	3000	240V	BLACK	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
107	MAZDA-SXR189012W-3K-240V-WH-PH-A82 X B62 X C75MM	12W	3000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
108	MAZDA-SXR189012W-3K-240V-WH-PH-EM-A82 X B62 X C75MM	12W	3000	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
109	MAZDA-SXR189012W-3K-240V-BK-10VDIM-A82 X B62 X C75MM	12W	3000	240V	BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
110	MAZDA-SXR189012W-3K-240V-BK-10VDIM-EM-A82 X B62 X C75MM	12W	3000	240V	BLACK	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
111	MAZDA-SXR189012W-3K-240V-WH-10VDIM-A82 X B62 X C75MM	12W	3000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
112	MAZDA-SXR189012W-3K-240V-WH-10VDIM-EM-A82 X B62 X C75MM	12W	3000	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
113	MAZDA-SXR189012W-4K-240V-BK-ND-A82 X B62 X C75MM	12W	4000	240V	BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
114	MAZDA-SXR189012W-4K-240V-BK-ND-EM-A82 X B62 X C75MM	12W	4000	240V	BLACK	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
115	MAZDA-SXR189012W-4K-240V-WH-ND-A82 X B62 X C75MM	12W	4000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
116	MAZDA-SXR189012W-4K-240V-WH-ND-EM-A82 X B62 X C75MM	12W	4000	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
117	MAZDA-SXR189012W-4K-240V-BK-DA-A82 X B62 X C75MM	12W	4000	240V	BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
118	MAZDA-SXR189012W-4K-240V-BK-DA-EM-A82 X B62 X C75MM	12W	4000	240V	BLACK	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
119	MAZDA-SXR189012W-4K-240V-WH-DA-A82 X B62 X C75MM	12W	4000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
120	MAZDA-SXR189012W-4K-240V-WH-DA-EM-A82 X B62 X C75MM	12W	4000	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
121	MAZDA-SXR189012W-4K-240V-BK-PH-A82 X B62 X C75MM	12W	4000	240V	BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
122	MAZDA-SXR189012W-4K-240V-BK-PH-EM-A82 X B62 X C75MM	12W	4000	240V	BLACK	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
123	MAZDA-SXR189012W-4K-240V-WH-PH-A82 X B62 X C75MM	12W	4000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
124	MAZDA-SXR189012W-4K-240V-WH-PH-EM-A82 X B62 X C75MM	12W	4000	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
125	MAZDA-SXR189012W-4K-240V-BK-10VDIM-A82 X B62 X C75MM	12W	4000	240V	BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
126	MAZDA-SXR189012W-4K-240V-BK-10VDIM-EM-A82 X B62 X C75MM	12W	4000	240V	BLACK	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
127	MAZDA-SXR189012W-4K-240V-WH-10VDIM-A82 X B62 X C75MM	12W	4000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
128	MAZDA-SXR189012W-4K-240V-WH-10VDIM-EM-A82 X B62 X C75MM	12W	4000	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
129	MAZDA-SXR189012W-5K-240V-BK-ND-A82 X B62 X C75MM	12W	5000	240V	BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	



DATASHEET

GENERATED ON: 14 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
130	MAZDA-SXR189012W-5K-240V-BK-ND-EM-A82 X B62 X C75MM	12W	5000	240V	BLACK	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
131	MAZDA-SXR189012W-5K-240V-WH-ND-A82 X B62 X C75MM	12W	5000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
132	MAZDA-SXR189012W-5K-240V-WH-ND-EM-A82 X B62 X C75MM	12W	5000	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
133	MAZDA-SXR189012W-5K-240V-BK-DA-A82 X B62 X C75MM	12W	5000	240V	BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
134	MAZDA-SXR189012W-5K-240V-BK-DA-EM-A82 X B62 X C75MM	12W	5000	240V	BLACK	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
135	MAZDA-SXR189012W-5K-240V-WH-DA-A82 X B62 X C75MM	12W	5000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
136	MAZDA-SXR189012W-5K-240V-WH-DA-EM-A82 X B62 X C75MM	12W	5000	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
137	MAZDA-SXR189012W-5K-240V-BK-PH-A82 X B62 X C75MM	12W	5000	240V	BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
138	MAZDA-SXR189012W-5K-240V-BK-PH-EM-A82 X B62 X C75MM	12W	5000	240V	BLACK	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
139	MAZDA-SXR189012W-5K-240V-WH-PH-A82 X B62 X C75MM	12W	5000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
140	MAZDA-SXR189012W-5K-240V-WH-PH-EM-A82 X B62 X C75MM	12W	5000	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
141	MAZDA-SXR189012W-5K-240V-BK-10VDIM-A82 X B62 X C75MM	12W	5000	240V	BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
142	MAZDA-SXR189012W-5K-240V-BK-10VDIM-EM-A82 X B62 X C75MM	12W	5000	240V	BLACK	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
143	MAZDA-SXR189012W-5K-240V-WH-10VDIM-A82 X B62 X C75MM	12W	5000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
144	MAZDA-SXR189012W-5K-240V-WH-10VDIM-EM-A82 X B62 X C75MM	12W	5000	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
145	MAZDA-SXR189012W-6K-240V-BK-ND-A82 X B62 X C75MM	12W	6000	240V	BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
146	MAZDA-SXR189012W-6K-240V-BK-ND-EM-A82 X B62 X C75MM	12W	6000	240V	BLACK	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
147	MAZDA-SXR189012W-6K-240V-WH-ND-A82 X B62 X C75MM	12W	6000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
148	MAZDA-SXR189012W-6K-240V-WH-ND-EM-A82 X B62 X C75MM	12W	6000	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
149	MAZDA-SXR189012W-6K-240V-BK-DA-A82 X B62 X C75MM	12W	6000	240V	BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
150	MAZDA-SXR189012W-6K-240V-BK-DA-EM-A82 X B62 X C75MM	12W	6000	240V	BLACK	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
151	MAZDA-SXR189012W-6K-240V-WH-DA-A82 X B62 X C75MM	12W	6000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
152	MAZDA-SXR189012W-6K-240V-WH-DA-EM-A82 X B62 X C75MM	12W	6000	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
153	MAZDA-SXR189012W-6K-240V-BK-PH-A82 X B62 X C75MM	12W	6000	240V	BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
154	MAZDA-SXR189012W-6K-240V-BK-PH-EM-A82 X B62 X C75MM	12W	6000	240V	BLACK	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
155	MAZDA-SXR189012W-6K-240V-WH-PH-A82 X B62 X C75MM	12W	6000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
156	MAZDA-SXR189012W-6K-240V-WH-PH-EM-A82 X B62 X C75MM	12W	6000	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
157	MAZDA-SXR189012W-6K-240V-BK-10VDIM-A82 X B62 X C75MM	12W	6000	240V	BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	



DATASHEET

GENERATED ON: 14 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
158	MAZDA-SXR189012W-6K-240V-BK-10VDIM-EM-A82 X B62 X C75MM	12W	6000	240V	BLACK	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
159	MAZDA-SXR189012W-6K-240V-WH-10VDIM-A82 X B62 X C75MM	12W	6000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
160	MAZDA-SXR189012W-6K-240V-WH-10VDIM-EM-A82 X B62 X C75MM	12W	6000	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
161	MAZDA-SXR189012W-2.7K-240V-BK-ND-A82 X B62 X C75MM	12W	2700	240V	BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
162	MAZDA-SXR189012W-2.7K-240V-BK-ND-EM-A82 X B62 X C75MM	12W	2700	240V	BLACK	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
163	MAZDA-SXR189012W-2.7K-240V-WH-ND-A82 X B62 X C75MM	12W	2700	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
164	MAZDA-SXR189012W-2.7K-240V-WH-ND-EM-A82 X B62 X C75MM	12W	2700	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
165	MAZDA-SXR189012W-2.7K-240V-BK-DA-A82 X B62 X C75MM	12W	2700	240V	BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
166	MAZDA-SXR189012W-2.7K-240V-BK-DA-EM-A82 X B62 X C75MM	12W	2700	240V	BLACK	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
167	MAZDA-SXR189012W-2.7K-240V-WH-DA-A82 X B62 X C75MM	12W	2700	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
168	MAZDA-SXR189012W-2.7K-240V-WH-DA-EM-A82 X B62 X C75MM	12W	2700	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
169	MAZDA-SXR189012W-2.7K-240V-BK-PH-A82 X B62 X C75MM	12W	2700	240V	BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
170	MAZDA-SXR189012W-2.7K-240V-BK-PH-EM-A82 X B62 X C75MM	12W	2700	240V	BLACK	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
171	MAZDA-SXR189012W-2.7K-240V-WH-PH-A82 X B62 X C75MM	12W	2700	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
172	MAZDA-SXR189012W-2.7K-240V-WH-PH-EM-A82 X B62 X C75MM	12W	2700	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
173	MAZDA-SXR189012W-2.7K-240V-BK-10VDIM-A82 X B62 X C75MM	12W	2700	240V	BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
174	MAZDA-SXR189012W-2.7K-240V-BK-10VDIM-EM-A82 X B62 X C75MM	12W	2700	240V	BLACK	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
175	MAZDA-SXR189012W-2.7K-240V-WH-10VDIM-A82 X B62 X C75MM	12W	2700	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
176	MAZDA-SXR189012W-2.7K-240V-WH-10VDIM-EM-A82 X B62 X C75MM	12W	2700	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
177	MAZDA-SXR189012W-6.5K-240V-BK-ND-A82 X B62 X C75MM	12W	6500	240V	BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
178	MAZDA-SXR189012W-6.5K-240V-BK-ND-EM-A82 X B62 X C75MM	12W	6500	240V	BLACK	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
179	MAZDA-SXR189012W-6.5K-240V-WH-ND-A82 X B62 X C75MM	12W	6500	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
180	MAZDA-SXR189012W-6.5K-240V-WH-ND-EM-A82 X B62 X C75MM	12W	6500	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
181	MAZDA-SXR189012W-6.5K-240V-BK-DA-A82 X B62 X C75MM	12W	6500	240V	BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
182	MAZDA-SXR189012W-6.5K-240V-BK-DA-EM-A82 X B62 X C75MM	12W	6500	240V	BLACK	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
183	MAZDA-SXR189012W-6.5K-240V-WH-DA-A82 X B62 X C75MM	12W	6500	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
184	MAZDA-SXR189012W-6.5K-240V-WH-DA-EM-A82 X B62 X C75MM	12W	6500	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
185	MAZDA-SXR189012W-6.5K-240V-BK-PH-A82 X B62 X C75MM	12W	6500	240V	BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
186	MAZDA-SXR189012W-6.5K-240V-BK-PH-EM-A82 X B62 X C75MM	12W	6500	240V	BLACK	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
187	MAZDA-SXR189012W-6.5K-240V-WH-PH-A82 X B62 X C75MM	12W	6500	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
188	MAZDA-SXR189012W-6.5K-240V-WH-PH-EM-A82 X B62 X C75MM	12W	6500	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
189	MAZDA-SXR189012W-6.5K-240V-BK-10VDIM-A82 X B62 X C75MM	12W	6500	240V	BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
190	MAZDA-SXR189012W-6.5K-240V-BK-10VDIM-EM-A82 X B62 X C75MM	12W	6500	240V	BLACK	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
191	MAZDA-SXR189012W-6.5K-240V-WH-10VDIM-A82 X B62 X C75MM	12W	6500	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	
192	MAZDA-SXR189012W-6.5K-240V-WH-10VDIM-EM-A82 X B62 X C75MM	12W	6500	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A82 X B62 X C75MM	DIE CAST ALUMINUM	IP44	1440LM	A82 X B62 X C75MM	