



KEEPER B

MAZDA Model: SXR189000 Spot Light

LED Spot Light Attractive exclusive downlight for indoor or outdoor use, particularly well suited to basic lighting due to its very low unified glare rating. Well integrated LED chip and associated dimmable driver. Made of die-cast powder-coated aluminium. Low recessed downlight with hole size. This unique design skillfully prevent the human eyes contact with the light sources directly, makes the light more soft. Meanwhile the light e ciency with perfect accent lighting performance. That makes it become the priority selected product for commercial lighting. Great cooling fins heat sink design increases the interface between heat sink and air, which makes the heat dissipating performance outstanding and extend the service life of the downlight. Suitable for commercial and residential applications like o ce, supermarket, shop, school, hotel, restaurant, workshop, warehouse, home etc.

ALL AVAILABLE VARIANTS

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angle	Dimension	Material	IP	lumen	Dimensions	Price
1	MAZDA-SXR1890007W-3K-240V-BK-ND-A85 X B69 X C75 MM	07W	3000	240V	BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
2	MAZDA-SXR1890007W-3K-240V-BK-ND-EM-A85 X B69 X C75 MM	07W	3000	240V	BLACK	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
3	MAZDA-SXR1890007W-3K-240V-WH-ND-A85 X B69 X C75 MM	07W	3000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
4	MAZDA-SXR1890007W-3K-240V-WH-ND-EM-A85 X B69 X C75 MM	07W	3000	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
5	MAZDA-SXR1890007W-3K-240V-BK-DA-A85 X B69 X C75 MM	07W	3000	240V	BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
6	MAZDA-SXR1890007W-3K-240V-BK-DA-EM-A85 X B69 X C75 MM	07W	3000	240V	BLACK	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
7	MAZDA-SXR1890007W-3K-240V-WH-DA-A85 X B69 X C75 MM	07W	3000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
8	MAZDA-SXR1890007W-3K-240V-WH-DA-EM-A85 X B69 X C75 MM	07W	3000	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
9	MAZDA-SXR1890007W-3K-240V-BK-PH-A85 X B69 X C75 MM	07W	3000	240V	BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
10	MAZDA-SXR1890007W-3K-240V-BK-PH-EM-A85 X B69 X C75 MM	07W	3000	240V	BLACK	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
11	MAZDA-SXR1890007W-3K-240V-WH-PH-A85 X B69 X C75 MM	07W	3000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
12	MAZDA-SXR1890007W-3K-240V-WH-PH-EM-A85 X B69 X C75 MM	07W	3000	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
13	MAZDA-SXR1890007W-3K-240V-BK-10VDIM-A85 X B69 X C75 MM	07W	3000	240V	BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
14	MAZDA-SXR1890007W-3K-240V-BK-10VDIM-EM-A85 X B69 X C75 MM	07W	3000	240V	BLACK	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
15	MAZDA-SXR1890007W-3K-240V-WH-10VDIM-A85 X B69 X C75 MM	07W	3000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
16	MAZDA-SXR1890007W-3K-240V-WH-10VDIM-EM-A85 X B69 X C75 MM	07W	3000	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	



DATASHEET

GENERATED ON: 14 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
17	MAZDA-SXR1890007W-4K-240V-BK-ND-A85 X B69 X C75 MM	07W	4000	240V	BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
18	MAZDA-SXR1890007W-4K-240V-BK-ND-EM-A85 X B69 X C75 MM	07W	4000	240V	BLACK	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
19	MAZDA-SXR1890007W-4K-240V-WH-ND-A85 X B69 X C75 MM	07W	4000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
20	MAZDA-SXR1890007W-4K-240V-WH-ND-EM-A85 X B69 X C75 MM	07W	4000	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
21	MAZDA-SXR1890007W-4K-240V-BK-DA-A85 X B69 X C75 MM	07W	4000	240V	BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
22	MAZDA-SXR1890007W-4K-240V-BK-DA-EM-A85 X B69 X C75 MM	07W	4000	240V	BLACK	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
23	MAZDA-SXR1890007W-4K-240V-WH-DA-A85 X B69 X C75 MM	07W	4000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
24	MAZDA-SXR1890007W-4K-240V-WH-DA-EM-A85 X B69 X C75 MM	07W	4000	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
25	MAZDA-SXR1890007W-4K-240V-BK-PH-A85 X B69 X C75 MM	07W	4000	240V	BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
26	MAZDA-SXR1890007W-4K-240V-BK-PH-EM-A85 X B69 X C75 MM	07W	4000	240V	BLACK	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
27	MAZDA-SXR1890007W-4K-240V-WH-PH-A85 X B69 X C75 MM	07W	4000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
28	MAZDA-SXR1890007W-4K-240V-WH-PH-EM-A85 X B69 X C75 MM	07W	4000	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
29	MAZDA-SXR1890007W-4K-240V-BK-10VDIM-A85 X B69 X C75 MM	07W	4000	240V	BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
30	MAZDA-SXR1890007W-4K-240V-BK-10VDIM-EM-A85 X B69 X C75 MM	07W	4000	240V	BLACK	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
31	MAZDA-SXR1890007W-4K-240V-WH-10VDIM-A85 X B69 X C75 MM	07W	4000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
32	MAZDA-SXR1890007W-4K-240V-WH-10VDIM-EM-A85 X B69 X C75 MM	07W	4000	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
33	MAZDA-SXR1890007W-5K-240V-BK-ND-A85 X B69 X C75 MM	07W	5000	240V	BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
34	MAZDA-SXR1890007W-5K-240V-BK-ND-EM-A85 X B69 X C75 MM	07W	5000	240V	BLACK	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
35	MAZDA-SXR1890007W-5K-240V-WH-ND-A85 X B69 X C75 MM	07W	5000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
36	MAZDA-SXR1890007W-5K-240V-WH-ND-EM-A85 X B69 X C75 MM	07W	5000	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
37	MAZDA-SXR1890007W-5K-240V-BK-DA-A85 X B69 X C75 MM	07W	5000	240V	BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
38	MAZDA-SXR1890007W-5K-240V-BK-DA-EM-A85 X B69 X C75 MM	07W	5000	240V	BLACK	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
39	MAZDA-SXR1890007W-5K-240V-WH-DA-A85 X B69 X C75 MM	07W	5000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
40	MAZDA-SXR1890007W-5K-240V-WH-DA-EM-A85 X B69 X C75 MM	07W	5000	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
41	MAZDA-SXR1890007W-5K-240V-BK-PH-A85 X B69 X C75 MM	07W	5000	240V	BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
42	MAZDA-SXR1890007W-5K-240V-BK-PH-EM-A85 X B69 X C75 MM	07W	5000	240V	BLACK	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
43	MAZDA-SXR1890007W-5K-240V-WH-PH-A85 X B69 X C75 MM	07W	5000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
44	MAZDA-SXR1890007W-5K-240V-WH-PH-EM-A85 X B69 X C75 MM	07W	5000	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
45	MAZDA-SXR1890007W-5K-240V-BK-10VDIM-A85 X B69 X C75 MM	07W	5000	240V	BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	



DATASHEET

GENERATED ON: 14 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
46	MAZDA-SXR1890007W-5K-240V-BK-10VDIM-EM-A85 X B69 X C75 MM	07W	5000	240V	BLACK	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
47	MAZDA-SXR1890007W-5K-240V-WH-10VDIM-A85 X B69 X C75 MM	07W	5000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
48	MAZDA-SXR1890007W-5K-240V-WH-10VDIM-EM-A85 X B69 X C75 MM	07W	5000	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
49	MAZDA-SXR1890007W-6K-240V-BK-ND-A85 X B69 X C75 MM	07W	6000	240V	BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
50	MAZDA-SXR1890007W-6K-240V-BK-ND-EM-A85 X B69 X C75 MM	07W	6000	240V	BLACK	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
51	MAZDA-SXR1890007W-6K-240V-WH-ND-A85 X B69 X C75 MM	07W	6000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
52	MAZDA-SXR1890007W-6K-240V-WH-ND-EM-A85 X B69 X C75 MM	07W	6000	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
53	MAZDA-SXR1890007W-6K-240V-BK-DA-A85 X B69 X C75 MM	07W	6000	240V	BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
54	MAZDA-SXR1890007W-6K-240V-BK-DA-EM-A85 X B69 X C75 MM	07W	6000	240V	BLACK	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
55	MAZDA-SXR1890007W-6K-240V-WH-DA-A85 X B69 X C75 MM	07W	6000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
56	MAZDA-SXR1890007W-6K-240V-WH-DA-EM-A85 X B69 X C75 MM	07W	6000	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
57	MAZDA-SXR1890007W-6K-240V-BK-PH-A85 X B69 X C75 MM	07W	6000	240V	BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
58	MAZDA-SXR1890007W-6K-240V-BK-PH-EM-A85 X B69 X C75 MM	07W	6000	240V	BLACK	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
59	MAZDA-SXR1890007W-6K-240V-WH-PH-A85 X B69 X C75 MM	07W	6000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
60	MAZDA-SXR1890007W-6K-240V-WH-PH-EM-A85 X B69 X C75 MM	07W	6000	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
61	MAZDA-SXR1890007W-6K-240V-BK-10VDIM-A85 X B69 X C75 MM	07W	6000	240V	BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
62	MAZDA-SXR1890007W-6K-240V-BK-10VDIM-EM-A85 X B69 X C75 MM	07W	6000	240V	BLACK	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
63	MAZDA-SXR1890007W-6K-240V-WH-10VDIM-A85 X B69 X C75 MM	07W	6000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
64	MAZDA-SXR1890007W-6K-240V-WH-10VDIM-EM-A85 X B69 X C75 MM	07W	6000	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
65	MAZDA-SXR1890007W-2.7K-240V-BK-ND-A85 X B69 X C75 MM	07W	2700	240V	BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
66	MAZDA-SXR1890007W-2.7K-240V-BK-ND-EM-A85 X B69 X C75 MM	07W	2700	240V	BLACK	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
67	MAZDA-SXR1890007W-2.7K-240V-WH-ND-A85 X B69 X C75 MM	07W	2700	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
68	MAZDA-SXR1890007W-2.7K-240V-WH-ND-EM-A85 X B69 X C75 MM	07W	2700	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
69	MAZDA-SXR1890007W-2.7K-240V-BK-DA-A85 X B69 X C75 MM	07W	2700	240V	BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
70	MAZDA-SXR1890007W-2.7K-240V-BK-DA-EM-A85 X B69 X C75 MM	07W	2700	240V	BLACK	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
71	MAZDA-SXR1890007W-2.7K-240V-WH-DA-A85 X B69 X C75 MM	07W	2700	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
72	MAZDA-SXR1890007W-2.7K-240V-WH-DA-EM-A85 X B69 X C75 MM	07W	2700	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
73	MAZDA-SXR1890007W-2.7K-240V-BK-PH-A85 X B69 X C75 MM	07W	2700	240V	BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
74	MAZDA-SXR1890007W-2.7K-240V-BK-PH-EM-A85 X B69 X C75 MM	07W	2700	240V	BLACK	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	



DATASHEET

GENERATED ON: 14 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
75	MAZDA-SXR1890007W-2.7K-240V-WH-PH-A85 X B69 X C75 MM	07W	2700	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
76	MAZDA-SXR1890007W-2.7K-240V-WH-PH-EM-A85 X B69 X C75 MM	07W	2700	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
77	MAZDA-SXR1890007W-2.7K-240V-BK-10VDIM-A85 X B69 X C75 MM	07W	2700	240V	BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
78	MAZDA-SXR1890007W-2.7K-240V-BK-10VDIM-EM-A85 X B69 X C75 MM	07W	2700	240V	BLACK	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
79	MAZDA-SXR1890007W-2.7K-240V-WH-10VDIM-A85 X B69 X C75 MM	07W	2700	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
80	MAZDA-SXR1890007W-2.7K-240V-WH-10VDIM-EM-A85 X B69 X C75 MM	07W	2700	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
81	MAZDA-SXR1890007W-6.5K-240V-BK-ND-A85 X B69 X C75 MM	07W	6500	240V	BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
82	MAZDA-SXR1890007W-6.5K-240V-BK-ND-EM-A85 X B69 X C75 MM	07W	6500	240V	BLACK	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
83	MAZDA-SXR1890007W-6.5K-240V-WH-ND-A85 X B69 X C75 MM	07W	6500	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
84	MAZDA-SXR1890007W-6.5K-240V-WH-ND-EM-A85 X B69 X C75 MM	07W	6500	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
85	MAZDA-SXR1890007W-6.5K-240V-BK-DA-A85 X B69 X C75 MM	07W	6500	240V	BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
86	MAZDA-SXR1890007W-6.5K-240V-BK-DA-EM-A85 X B69 X C75 MM	07W	6500	240V	BLACK	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
87	MAZDA-SXR1890007W-6.5K-240V-WH-DA-A85 X B69 X C75 MM	07W	6500	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
88	MAZDA-SXR1890007W-6.5K-240V-WH-DA-EM-A85 X B69 X C75 MM	07W	6500	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
89	MAZDA-SXR1890007W-6.5K-240V-BK-PH-A85 X B69 X C75 MM	07W	6500	240V	BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
90	MAZDA-SXR1890007W-6.5K-240V-BK-PH-EM-A85 X B69 X C75 MM	07W	6500	240V	BLACK	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
91	MAZDA-SXR1890007W-6.5K-240V-WH-PH-A85 X B69 X C75 MM	07W	6500	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
92	MAZDA-SXR1890007W-6.5K-240V-WH-PH-EM-A85 X B69 X C75 MM	07W	6500	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
93	MAZDA-SXR1890007W-6.5K-240V-BK-10VDIM-A85 X B69 X C75 MM	07W	6500	240V	BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
94	MAZDA-SXR1890007W-6.5K-240V-BK-10VDIM-EM-A85 X B69 X C75 MM	07W	6500	240V	BLACK	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
95	MAZDA-SXR1890007W-6.5K-240V-WH-10VDIM-A85 X B69 X C75 MM	07W	6500	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
96	MAZDA-SXR1890007W-6.5K-240V-WH-10VDIM-EM-A85 X B69 X C75 MM	07W	6500	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	840LM	A85 X B69 X C75 MM	
97	MAZDA-SXR1890010W-3K-240V-BK-ND-A85 X B69 X C75 MM	10W	3000	240V	BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
98	MAZDA-SXR1890010W-3K-240V-BK-ND-EM-A85 X B69 X C75 MM	10W	3000	240V	BLACK	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
99	MAZDA-SXR1890010W-3K-240V-WH-ND-A85 X B69 X C75 MM	10W	3000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
100	MAZDA-SXR1890010W-3K-240V-WH-ND-EM-A85 X B69 X C75 MM	10W	3000	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
101	MAZDA-SXR1890010W-3K-240V-BK-DA-A85 X B69 X C75 MM	10W	3000	240V	BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
102	MAZDA-SXR1890010W-3K-240V-BK-DA-EM-A85 X B69 X C75 MM	10W	3000	240V	BLACK	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
103	MAZDA-SXR1890010W-3K-240V-WH-DA-A85 X B69 X C75 MM	10W	3000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	



DATASHEET

GENERATED ON: 14 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
104	MAZDA-SXR1890010W-3K-240V-WH-DA-EM-A85 X B69 X C75 MM	10W	3000	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
105	MAZDA-SXR1890010W-3K-240V-BK-PH-A85 X B69 X C75 MM	10W	3000	240V	BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
106	MAZDA-SXR1890010W-3K-240V-BK-PH-EM-A85 X B69 X C75 MM	10W	3000	240V	BLACK	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
107	MAZDA-SXR1890010W-3K-240V-WH-PH-A85 X B69 X C75 MM	10W	3000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
108	MAZDA-SXR1890010W-3K-240V-WH-PH-EM-A85 X B69 X C75 MM	10W	3000	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
109	MAZDA-SXR1890010W-3K-240V-BK-10VDIM-A85 X B69 X C75 MM	10W	3000	240V	BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
110	MAZDA-SXR1890010W-3K-240V-BK-10VDIM-EM-A85 X B69 X C75 MM	10W	3000	240V	BLACK	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
111	MAZDA-SXR1890010W-3K-240V-WH-10VDIM-A85 X B69 X C75 MM	10W	3000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
112	MAZDA-SXR1890010W-3K-240V-WH-10VDIM-EM-A85 X B69 X C75 MM	10W	3000	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
113	MAZDA-SXR1890010W-4K-240V-BK-ND-A85 X B69 X C75 MM	10W	4000	240V	BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
114	MAZDA-SXR1890010W-4K-240V-BK-ND-EM-A85 X B69 X C75 MM	10W	4000	240V	BLACK	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
115	MAZDA-SXR1890010W-4K-240V-WH-ND-A85 X B69 X C75 MM	10W	4000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
116	MAZDA-SXR1890010W-4K-240V-WH-ND-EM-A85 X B69 X C75 MM	10W	4000	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
117	MAZDA-SXR1890010W-4K-240V-BK-DA-A85 X B69 X C75 MM	10W	4000	240V	BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
118	MAZDA-SXR1890010W-4K-240V-BK-DA-EM-A85 X B69 X C75 MM	10W	4000	240V	BLACK	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
119	MAZDA-SXR1890010W-4K-240V-WH-DA-A85 X B69 X C75 MM	10W	4000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
120	MAZDA-SXR1890010W-4K-240V-WH-DA-EM-A85 X B69 X C75 MM	10W	4000	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
121	MAZDA-SXR1890010W-4K-240V-BK-PH-A85 X B69 X C75 MM	10W	4000	240V	BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
122	MAZDA-SXR1890010W-4K-240V-BK-PH-EM-A85 X B69 X C75 MM	10W	4000	240V	BLACK	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
123	MAZDA-SXR1890010W-4K-240V-WH-PH-A85 X B69 X C75 MM	10W	4000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
124	MAZDA-SXR1890010W-4K-240V-WH-PH-EM-A85 X B69 X C75 MM	10W	4000	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
125	MAZDA-SXR1890010W-4K-240V-BK-10VDIM-A85 X B69 X C75 MM	10W	4000	240V	BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
126	MAZDA-SXR1890010W-4K-240V-BK-10VDIM-EM-A85 X B69 X C75 MM	10W	4000	240V	BLACK	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
127	MAZDA-SXR1890010W-4K-240V-WH-10VDIM-A85 X B69 X C75 MM	10W	4000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
128	MAZDA-SXR1890010W-4K-240V-WH-10VDIM-EM-A85 X B69 X C75 MM	10W	4000	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
129	MAZDA-SXR1890010W-5K-240V-BK-ND-A85 X B69 X C75 MM	10W	5000	240V	BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
130	MAZDA-SXR1890010W-5K-240V-BK-ND-EM-A85 X B69 X C75 MM	10W	5000	240V	BLACK	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
131	MAZDA-SXR1890010W-5K-240V-WH-ND-A85 X B69 X C75 MM	10W	5000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
132	MAZDA-SXR1890010W-5K-240V-WH-ND-EM-A85 X B69 X C75 MM	10W	5000	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	



DATASHEET

GENERATED ON: 14 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
133	MAZDA-SXR1890010W-5K-240V-BK-DA-A85 X B69 X C75 MM	10W	5000	240V	BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
134	MAZDA-SXR1890010W-5K-240V-BK-DA-EM-A85 X B69 X C75 MM	10W	5000	240V	BLACK	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
135	MAZDA-SXR1890010W-5K-240V-WH-DA-A85 X B69 X C75 MM	10W	5000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
136	MAZDA-SXR1890010W-5K-240V-WH-DA-EM-A85 X B69 X C75 MM	10W	5000	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
137	MAZDA-SXR1890010W-5K-240V-BK-PH-A85 X B69 X C75 MM	10W	5000	240V	BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
138	MAZDA-SXR1890010W-5K-240V-BK-PH-EM-A85 X B69 X C75 MM	10W	5000	240V	BLACK	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
139	MAZDA-SXR1890010W-5K-240V-WH-PH-A85 X B69 X C75 MM	10W	5000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
140	MAZDA-SXR1890010W-5K-240V-WH-PH-EM-A85 X B69 X C75 MM	10W	5000	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
141	MAZDA-SXR1890010W-5K-240V-BK-10VDIM-A85 X B69 X C75 MM	10W	5000	240V	BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
142	MAZDA-SXR1890010W-5K-240V-BK-10VDIM-EM-A85 X B69 X C75 MM	10W	5000	240V	BLACK	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
143	MAZDA-SXR1890010W-5K-240V-WH-10VDIM-A85 X B69 X C75 MM	10W	5000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
144	MAZDA-SXR1890010W-5K-240V-WH-10VDIM-EM-A85 X B69 X C75 MM	10W	5000	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
145	MAZDA-SXR1890010W-6K-240V-BK-ND-A85 X B69 X C75 MM	10W	6000	240V	BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
146	MAZDA-SXR1890010W-6K-240V-BK-ND-EM-A85 X B69 X C75 MM	10W	6000	240V	BLACK	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
147	MAZDA-SXR1890010W-6K-240V-WH-ND-A85 X B69 X C75 MM	10W	6000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
148	MAZDA-SXR1890010W-6K-240V-WH-ND-EM-A85 X B69 X C75 MM	10W	6000	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
149	MAZDA-SXR1890010W-6K-240V-BK-DA-A85 X B69 X C75 MM	10W	6000	240V	BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
150	MAZDA-SXR1890010W-6K-240V-BK-DA-EM-A85 X B69 X C75 MM	10W	6000	240V	BLACK	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
151	MAZDA-SXR1890010W-6K-240V-WH-DA-A85 X B69 X C75 MM	10W	6000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
152	MAZDA-SXR1890010W-6K-240V-WH-DA-EM-A85 X B69 X C75 MM	10W	6000	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
153	MAZDA-SXR1890010W-6K-240V-BK-PH-A85 X B69 X C75 MM	10W	6000	240V	BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
154	MAZDA-SXR1890010W-6K-240V-BK-PH-EM-A85 X B69 X C75 MM	10W	6000	240V	BLACK	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
155	MAZDA-SXR1890010W-6K-240V-WH-PH-A85 X B69 X C75 MM	10W	6000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
156	MAZDA-SXR1890010W-6K-240V-WH-PH-EM-A85 X B69 X C75 MM	10W	6000	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
157	MAZDA-SXR1890010W-6K-240V-BK-10VDIM-A85 X B69 X C75 MM	10W	6000	240V	BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
158	MAZDA-SXR1890010W-6K-240V-BK-10VDIM-EM-A85 X B69 X C75 MM	10W	6000	240V	BLACK	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
159	MAZDA-SXR1890010W-6K-240V-WH-10VDIM-A85 X B69 X C75 MM	10W	6000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
160	MAZDA-SXR1890010W-6K-240V-WH-10VDIM-EM-A85 X B69 X C75 MM	10W	6000	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
161	MAZDA-SXR1890010W-2.7K-240V-BK-ND-A85 X B69 X C75 MM	10W	2700	240V	BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	



DATASHEET

GENERATED ON: 14 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
162	MAZDA-SXR1890010W-2.7K-240V-BK-ND-EM-A85 X B69 X C75 MM	10W	2700	240V	BLACK	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
163	MAZDA-SXR1890010W-2.7K-240V-WH-ND-EM-A85 X B69 X C75 MM	10W	2700	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
164	MAZDA-SXR1890010W-2.7K-240V-WH-ND-EM-A85 X B69 X C75 MM	10W	2700	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
165	MAZDA-SXR1890010W-2.7K-240V-BK-DA-A85 X B69 X C75 MM	10W	2700	240V	BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
166	MAZDA-SXR1890010W-2.7K-240V-BK-DA-EM-A85 X B69 X C75 MM	10W	2700	240V	BLACK	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
167	MAZDA-SXR1890010W-2.7K-240V-WH-DA-A85 X B69 X C75 MM	10W	2700	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
168	MAZDA-SXR1890010W-2.7K-240V-WH-DA-EM-A85 X B69 X C75 MM	10W	2700	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
169	MAZDA-SXR1890010W-2.7K-240V-BK-PH-A85 X B69 X C75 MM	10W	2700	240V	BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
170	MAZDA-SXR1890010W-2.7K-240V-BK-PH-EM-A85 X B69 X C75 MM	10W	2700	240V	BLACK	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
171	MAZDA-SXR1890010W-2.7K-240V-WH-PH-A85 X B69 X C75 MM	10W	2700	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
172	MAZDA-SXR1890010W-2.7K-240V-WH-PH-EM-A85 X B69 X C75 MM	10W	2700	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
173	MAZDA-SXR1890010W-2.7K-240V-BK-10VDIM-A85 X B69 X C75 MM	10W	2700	240V	BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
174	MAZDA-SXR1890010W-2.7K-240V-BK-10VDIM-EM-A85 X B69 X C75 MM	10W	2700	240V	BLACK	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
175	MAZDA-SXR1890010W-2.7K-240V-WH-10VDIM-A85 X B69 X C75 MM	10W	2700	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
176	MAZDA-SXR1890010W-2.7K-240V-WH-10VDIM-EM-A85 X B69 X C75 MM	10W	2700	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
177	MAZDA-SXR1890010W-6.5K-240V-BK-ND-A85 X B69 X C75 MM	10W	6500	240V	BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
178	MAZDA-SXR1890010W-6.5K-240V-BK-ND-EM-A85 X B69 X C75 MM	10W	6500	240V	BLACK	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
179	MAZDA-SXR1890010W-6.5K-240V-WH-ND-A85 X B69 X C75 MM	10W	6500	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
180	MAZDA-SXR1890010W-6.5K-240V-WH-ND-EM-A85 X B69 X C75 MM	10W	6500	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
181	MAZDA-SXR1890010W-6.5K-240V-BK-DA-A85 X B69 X C75 MM	10W	6500	240V	BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
182	MAZDA-SXR1890010W-6.5K-240V-BK-DA-EM-A85 X B69 X C75 MM	10W	6500	240V	BLACK	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
183	MAZDA-SXR1890010W-6.5K-240V-WH-DA-A85 X B69 X C75 MM	10W	6500	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
184	MAZDA-SXR1890010W-6.5K-240V-WH-DA-EM-A85 X B69 X C75 MM	10W	6500	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
185	MAZDA-SXR1890010W-6.5K-240V-BK-PH-A85 X B69 X C75 MM	10W	6500	240V	BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
186	MAZDA-SXR1890010W-6.5K-240V-BK-PH-EM-A85 X B69 X C75 MM	10W	6500	240V	BLACK	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
187	MAZDA-SXR1890010W-6.5K-240V-WH-PH-A85 X B69 X C75 MM	10W	6500	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
188	MAZDA-SXR1890010W-6.5K-240V-WH-PH-EM-A85 X B69 X C75 MM	10W	6500	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
189	MAZDA-SXR1890010W-6.5K-240V-BK-10VDIM-A85 X B69 X C75 MM	10W	6500	240V	BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
190	MAZDA-SXR1890010W-6.5K-240V-BK-10VDIM-EM-A85 X B69 X C75 MM	10W	6500	240V	BLACK	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	



DATASHEET

GENERATED ON: 14 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
191	MAZDA-SXR1890010W-6.5K-240V-WH-10VDIM-A85 X B69 X C75 MM	10W	6500	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
192	MAZDA-SXR1890010W-6.5K-240V-WH-10VDIM-EM-A85 X B69 X C75 MM	10W	6500	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1200LM	A85 X B69 X C75 MM	
193	MAZDA-SXR1890012W-3K-240V-BK-ND-A85 X B69 X C75 MM	12W	3000	240V	BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
194	MAZDA-SXR1890012W-3K-240V-BK-ND-EM-A85 X B69 X C75 MM	12W	3000	240V	BLACK	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
195	MAZDA-SXR1890012W-3K-240V-WH-ND-A85 X B69 X C75 MM	12W	3000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
196	MAZDA-SXR1890012W-3K-240V-WH-ND-EM-A85 X B69 X C75 MM	12W	3000	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
197	MAZDA-SXR1890012W-3K-240V-BK-DA-A85 X B69 X C75 MM	12W	3000	240V	BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
198	MAZDA-SXR1890012W-3K-240V-BK-DA-EM-A85 X B69 X C75 MM	12W	3000	240V	BLACK	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
199	MAZDA-SXR1890012W-3K-240V-WH-DA-A85 X B69 X C75 MM	12W	3000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
200	MAZDA-SXR1890012W-3K-240V-WH-DA-EM-A85 X B69 X C75 MM	12W	3000	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
201	MAZDA-SXR1890012W-3K-240V-BK-PH-A85 X B69 X C75 MM	12W	3000	240V	BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
202	MAZDA-SXR1890012W-3K-240V-BK-PH-EM-A85 X B69 X C75 MM	12W	3000	240V	BLACK	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
203	MAZDA-SXR1890012W-3K-240V-WH-PH-A85 X B69 X C75 MM	12W	3000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
204	MAZDA-SXR1890012W-3K-240V-WH-PH-EM-A85 X B69 X C75 MM	12W	3000	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
205	MAZDA-SXR1890012W-3K-240V-BK-10VDIM-A85 X B69 X C75 MM	12W	3000	240V	BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
206	MAZDA-SXR1890012W-3K-240V-BK-10VDIM-EM-A85 X B69 X C75 MM	12W	3000	240V	BLACK	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
207	MAZDA-SXR1890012W-3K-240V-WH-10VDIM-A85 X B69 X C75 MM	12W	3000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
208	MAZDA-SXR1890012W-3K-240V-WH-10VDIM-EM-A85 X B69 X C75 MM	12W	3000	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
209	MAZDA-SXR1890012W-4K-240V-BK-ND-A85 X B69 X C75 MM	12W	4000	240V	BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
210	MAZDA-SXR1890012W-4K-240V-BK-ND-EM-A85 X B69 X C75 MM	12W	4000	240V	BLACK	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
211	MAZDA-SXR1890012W-4K-240V-WH-ND-A85 X B69 X C75 MM	12W	4000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
212	MAZDA-SXR1890012W-4K-240V-WH-ND-EM-A85 X B69 X C75 MM	12W	4000	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
213	MAZDA-SXR1890012W-4K-240V-BK-DA-A85 X B69 X C75 MM	12W	4000	240V	BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
214	MAZDA-SXR1890012W-4K-240V-BK-DA-EM-A85 X B69 X C75 MM	12W	4000	240V	BLACK	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
215	MAZDA-SXR1890012W-4K-240V-WH-DA-A85 X B69 X C75 MM	12W	4000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
216	MAZDA-SXR1890012W-4K-240V-WH-DA-EM-A85 X B69 X C75 MM	12W	4000	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
217	MAZDA-SXR1890012W-4K-240V-BK-PH-A85 X B69 X C75 MM	12W	4000	240V	BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
218	MAZDA-SXR1890012W-4K-240V-BK-PH-EM-A85 X B69 X C75 MM	12W	4000	240V	BLACK	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
219	MAZDA-SXR1890012W-4K-240V-WH-PH-A85 X B69 X C75 MM	12W	4000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	



DATASHEET

GENERATED ON: 14 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
220	MAZDA-SXR1890012W-4K-240V-WH-PH-EM-A85 X B69 X C75 MM	12W	4000	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
221	MAZDA-SXR1890012W-4K-240V-BK-10VDIM-A85 X B69 X C75 MM	12W	4000	240V	BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
222	MAZDA-SXR1890012W-4K-240V-BK-10VDIM-EM-A85 X B69 X C75 MM	12W	4000	240V	BLACK	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
223	MAZDA-SXR1890012W-4K-240V-WH-10VDIM-A85 X B69 X C75 MM	12W	4000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
224	MAZDA-SXR1890012W-4K-240V-WH-10VDIM-EM-A85 X B69 X C75 MM	12W	4000	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
225	MAZDA-SXR1890012W-5K-240V-BK-ND-A85 X B69 X C75 MM	12W	5000	240V	BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
226	MAZDA-SXR1890012W-5K-240V-BK-ND-EM-A85 X B69 X C75 MM	12W	5000	240V	BLACK	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
227	MAZDA-SXR1890012W-5K-240V-WH-ND-A85 X B69 X C75 MM	12W	5000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
228	MAZDA-SXR1890012W-5K-240V-WH-ND-EM-A85 X B69 X C75 MM	12W	5000	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
229	MAZDA-SXR1890012W-5K-240V-BK-DA-A85 X B69 X C75 MM	12W	5000	240V	BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
230	MAZDA-SXR1890012W-5K-240V-BK-DA-EM-A85 X B69 X C75 MM	12W	5000	240V	BLACK	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
231	MAZDA-SXR1890012W-5K-240V-WH-DA-A85 X B69 X C75 MM	12W	5000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
232	MAZDA-SXR1890012W-5K-240V-WH-DA-EM-A85 X B69 X C75 MM	12W	5000	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
233	MAZDA-SXR1890012W-5K-240V-BK-PH-A85 X B69 X C75 MM	12W	5000	240V	BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
234	MAZDA-SXR1890012W-5K-240V-BK-PH-EM-A85 X B69 X C75 MM	12W	5000	240V	BLACK	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
235	MAZDA-SXR1890012W-5K-240V-WH-PH-A85 X B69 X C75 MM	12W	5000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
236	MAZDA-SXR1890012W-5K-240V-WH-PH-EM-A85 X B69 X C75 MM	12W	5000	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
237	MAZDA-SXR1890012W-5K-240V-BK-10VDIM-A85 X B69 X C75 MM	12W	5000	240V	BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
238	MAZDA-SXR1890012W-5K-240V-BK-10VDIM-EM-A85 X B69 X C75 MM	12W	5000	240V	BLACK	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
239	MAZDA-SXR1890012W-5K-240V-WH-10VDIM-A85 X B69 X C75 MM	12W	5000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
240	MAZDA-SXR1890012W-5K-240V-WH-10VDIM-EM-A85 X B69 X C75 MM	12W	5000	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
241	MAZDA-SXR1890012W-6K-240V-BK-ND-A85 X B69 X C75 MM	12W	6000	240V	BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
242	MAZDA-SXR1890012W-6K-240V-BK-ND-EM-A85 X B69 X C75 MM	12W	6000	240V	BLACK	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
243	MAZDA-SXR1890012W-6K-240V-WH-ND-A85 X B69 X C75 MM	12W	6000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
244	MAZDA-SXR1890012W-6K-240V-WH-ND-EM-A85 X B69 X C75 MM	12W	6000	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
245	MAZDA-SXR1890012W-6K-240V-BK-DA-A85 X B69 X C75 MM	12W	6000	240V	BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
246	MAZDA-SXR1890012W-6K-240V-BK-DA-EM-A85 X B69 X C75 MM	12W	6000	240V	BLACK	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
247	MAZDA-SXR1890012W-6K-240V-WH-DA-A85 X B69 X C75 MM	12W	6000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
248	MAZDA-SXR1890012W-6K-240V-WH-DA-EM-A85 X B69 X C75 MM	12W	6000	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	



DATASHEET

GENERATED ON: 14 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
249	MAZDA-SXR1890012W-6K-240V-BK-PH-A85 X B69 X C75 MM	12W	6000	240V	BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
250	MAZDA-SXR1890012W-6K-240V-BK-PH-EM-A85 X B69 X C75 MM	12W	6000	240V	BLACK	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
251	MAZDA-SXR1890012W-6K-240V-WH-PH-A85 X B69 X C75 MM	12W	6000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
252	MAZDA-SXR1890012W-6K-240V-WH-PH-EM-A85 X B69 X C75 MM	12W	6000	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
253	MAZDA-SXR1890012W-6K-240V-BK-10VDIM-A85 X B69 X C75 MM	12W	6000	240V	BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
254	MAZDA-SXR1890012W-6K-240V-BK-10VDIM-EM-A85 X B69 X C75 MM	12W	6000	240V	BLACK	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
255	MAZDA-SXR1890012W-6K-240V-WH-10VDIM-A85 X B69 X C75 MM	12W	6000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
256	MAZDA-SXR1890012W-6K-240V-WH-10VDIM-EM-A85 X B69 X C75 MM	12W	6000	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
257	MAZDA-SXR1890012W-2.7K-240V-BK-ND-A85 X B69 X C75 MM	12W	2700	240V	BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
258	MAZDA-SXR1890012W-2.7K-240V-BK-ND-EM-A85 X B69 X C75 MM	12W	2700	240V	BLACK	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
259	MAZDA-SXR1890012W-2.7K-240V-WH-ND-A85 X B69 X C75 MM	12W	2700	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
260	MAZDA-SXR1890012W-2.7K-240V-WH-ND-EM-A85 X B69 X C75 MM	12W	2700	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
261	MAZDA-SXR1890012W-2.7K-240V-BK-DA-A85 X B69 X C75 MM	12W	2700	240V	BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
262	MAZDA-SXR1890012W-2.7K-240V-BK-DA-EM-A85 X B69 X C75 MM	12W	2700	240V	BLACK	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
263	MAZDA-SXR1890012W-2.7K-240V-WH-DA-A85 X B69 X C75 MM	12W	2700	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
264	MAZDA-SXR1890012W-2.7K-240V-WH-DA-EM-A85 X B69 X C75 MM	12W	2700	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
265	MAZDA-SXR1890012W-2.7K-240V-BK-PH-A85 X B69 X C75 MM	12W	2700	240V	BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
266	MAZDA-SXR1890012W-2.7K-240V-BK-PH-EM-A85 X B69 X C75 MM	12W	2700	240V	BLACK	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
267	MAZDA-SXR1890012W-2.7K-240V-WH-PH-A85 X B69 X C75 MM	12W	2700	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
268	MAZDA-SXR1890012W-2.7K-240V-WH-PH-EM-A85 X B69 X C75 MM	12W	2700	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
269	MAZDA-SXR1890012W-2.7K-240V-BK-10VDIM-A85 X B69 X C75 MM	12W	2700	240V	BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
270	MAZDA-SXR1890012W-2.7K-240V-BK-10VDIM-EM-A85 X B69 X C75 MM	12W	2700	240V	BLACK	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
271	MAZDA-SXR1890012W-2.7K-240V-WH-10VDIM-A85 X B69 X C75 MM	12W	2700	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
272	MAZDA-SXR1890012W-2.7K-240V-WH-10VDIM-EM-A85 X B69 X C75 MM	12W	2700	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
273	MAZDA-SXR1890012W-6.5K-240V-BK-ND-A85 X B69 X C75 MM	12W	6500	240V	BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
274	MAZDA-SXR1890012W-6.5K-240V-BK-ND-EM-A85 X B69 X C75 MM	12W	6500	240V	BLACK	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
275	MAZDA-SXR1890012W-6.5K-240V-WH-ND-A85 X B69 X C75 MM	12W	6500	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
276	MAZDA-SXR1890012W-6.5K-240V-WH-ND-EM-A85 X B69 X C75 MM	12W	6500	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
277	MAZDA-SXR1890012W-6.5K-240V-BK-DA-A85 X B69 X C75 MM	12W	6500	240V	BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
278	MAZDA-SXR1890012W-6.5K-240V-BK-DA-EM-A85 X B69 X C75 MM	12W	6500	240V	BLACK	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
279	MAZDA-SXR1890012W-6.5K-240V-WH-DA-A85 X B69 X C75 MM	12W	6500	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
280	MAZDA-SXR1890012W-6.5K-240V-WH-DA-EM-A85 X B69 X C75 MM	12W	6500	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
281	MAZDA-SXR1890012W-6.5K-240V-BK-PH-A85 X B69 X C75 MM	12W	6500	240V	BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
282	MAZDA-SXR1890012W-6.5K-240V-BK-PH-EM-A85 X B69 X C75 MM	12W	6500	240V	BLACK	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
283	MAZDA-SXR1890012W-6.5K-240V-WH-PH-A85 X B69 X C75 MM	12W	6500	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
284	MAZDA-SXR1890012W-6.5K-240V-WH-PH-EM-A85 X B69 X C75 MM	12W	6500	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
285	MAZDA-SXR1890012W-6.5K-240V-BK-10VDIM-A85 X B69 X C75 MM	12W	6500	240V	BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
286	MAZDA-SXR1890012W-6.5K-240V-BK-10VDIM-EM-A85 X B69 X C75 MM	12W	6500	240V	BLACK	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
287	MAZDA-SXR1890012W-6.5K-240V-WH-10VDIM-A85 X B69 X C75 MM	12W	6500	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	
288	MAZDA-SXR1890012W-6.5K-240V-WH-10VDIM-EM-A85 X B69 X C75 MM	12W	6500	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B69 X C75 MM	DIE CAST ALUMINUM	IP44	1440LM	A85 X B69 X C75 MM	