DATASHEET

GENERATED ON: 10 Nov 2026 | SYS.REF: MAZDA-LED



LOTOS

MAZDA Model: SXR18300 Spot Light

Lotos LED Spot Light has a strong light without glare, it is a perfect choice for functional observer for high-end residential or hospitality settings. This versatile, elegant architectural spot light will bring pure form, definition and quality light to any space without stealing all the attention. Attractive exclusive spot light for indoor or outdoor use, particularly well suited to basic lighting due to its very low unified glare rating. Well integrated LED chip and associated dimmable driver. Made of die-cast powder-coated aluminium

ALL AVAILABLE VARIANTS

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
1	MAZDA-SXR1830008W-3K-240V-WH-ND-A85 X B89 X C75MM	08W	3000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	960LM	A85 X B89 X C75MM	
2	MAZDA-SXR1830008W-3K-240V-WH-ND-EM-A85 X B89 X C75MM	08W	3000	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	960LM	A85 X B89 X C75MM	
3	MAZDA-SXR1830008W-3K-240V-WH-DA-A85 X B89 X C75MM	08W	3000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	960LM	A85 X B89 X C75MM	
4	MAZDA-SXR1830008W-3K-240V-WH-DA-EM-A85 X B89 X C75MM	08W	3000	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	960LM	A85 X B89 X C75MM	
5	MAZDA-SXR1830008W-3K-240V-WH-PH-A85 X B89 X C75MM	08W	3000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	960LM	A85 X B89 X C75MM	
6	MAZDA-SXR1830008W-3K-240V-WH-PH-EM-A85 X B89 X C75MM	08W	3000	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	960LM	A85 X B89 X C75MM	
7	MAZDA-SXR1830008W-3K-240V-WH-10VDIM-A85 X B89 X C75MM	08W	3000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	960LM	A85 X B89 X C75MM	
8	MAZDA-SXR1830008W-3K-240V-WH-10VDIM-EM-A85 X B89 X C75MM	08W	3000	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	960LM	A85 X B89 X C75MM	
9	MAZDA-SXR1830008W-4K-240V-WH-ND-A85 X B89 X C75MM	08W	4000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	960LM	A85 X B89 X C75MM	
10	MAZDA-SXR1830008W-4K-240V-WH-ND-EM-A85 X B89 X C75MM	08W	4000	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	960LM	A85 X B89 X C75MM	
11	MAZDA-SXR1830008W-4K-240V-WH-DA-A85 X B89 X C75MM	08W	4000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	960LM	A85 X B89 X C75MM	
12	MAZDA-SXR1830008W-4K-240V-WH-DA-EM-A85 X B89 X C75MM	08W	4000	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	960LM	A85 X B89 X C75MM	
13	MAZDA-SXR1830008W-4K-240V-WH-PH-A85 X B89 X C75MM	08W	4000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	960LM	A85 X B89 X C75MM	
14	MAZDA-SXR1830008W-4K-240V-WH-PH-EM-A85 X B89 X C75MM	08W	4000	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	960LM	A85 X B89 X C75MM	
15	MAZDA-SXR1830008W-4K-240V-WH-10VDIM-A85 X B89 X C75MM	08W	4000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	960LM	A85 X B89 X C75MM	
16	MAZDA-SXR1830008W-4K-240V-WH-10VDIM-EM-A85 X B89 X C75MM	08W	4000	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	960LM	A85 X B89 X C75MM	
17	MAZDA-SXR1830008W-5K-240V-WH-ND-A85 X B89 X C75MM	08W	5000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	960LM	A85 X B89 X C75MM	
18	MAZDA-SXR1830008W-5K-240V-WH-ND-EM-A85 X B89 X C75MM	08W	5000	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	960LM	A85 X B89 X C75MM	

DATASHEET

GENERATED ON: 10 Nov 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
19	MAZDA-SXR1830008W-5K-240V-WH-DA-A85 X B89 X C75MM	08W	5000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	960LM	A85 X B89 X C75MM	
20	MAZDA-SXR1830008W-5K-240V-WH-DA-EM-A85 X B89 X C75MM	08W	5000	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	960LM	A85 X B89 X C75MM	
21	MAZDA-SXR1830008W-5K-240V-WH-PH-A85 X B89 X C75MM	08W	5000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	960LM	A85 X B89 X C75MM	
22	MAZDA-SXR1830008W-5K-240V-WH-PH-EM-A85 X B89 X C75MM	08W	5000	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	960LM	A85 X B89 X C75MM	
23	MAZDA-SXR1830008W-5K-240V-WH-10VDIM-A85 X B89 X C75MM	08W	5000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	960LM	A85 X B89 X C75MM	
24	MAZDA-SXR1830008W-5K-240V-WH-10VDIM-EM-A85 X B89 X C75MM	08W	5000	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	960LM	A85 X B89 X C75MM	
25	MAZDA-SXR1830008W-6K-240V-WH-ND-A85 X B89 X C75MM	08W	6000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	960LM	A85 X B89 X C75MM	
26	MAZDA-SXR1830008W-6K-240V-WH-ND-EM-A85 X B89 X C75MM	08W	6000	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	960LM	A85 X B89 X C75MM	
27	MAZDA-SXR1830008W-6K-240V-WH-DA-A85 X B89 X C75MM	08W	6000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	960LM	A85 X B89 X C75MM	
28	MAZDA-SXR1830008W-6K-240V-WH-DA-EM-A85 X B89 X C75MM	08W	6000	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	960LM	A85 X B89 X C75MM	
29	MAZDA-SXR1830008W-6K-240V-WH-PH-A85 X B89 X C75MM	08W	6000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	960LM	A85 X B89 X C75MM	
30	MAZDA-SXR1830008W-6K-240V-WH-PH-EM-A85 X B89 X C75MM	08W	6000	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	960LM	A85 X B89 X C75MM	
31	MAZDA-SXR1830008W-6K-240V-WH-10VDIM-A85 X B89 X C75MM	08W	6000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	960LM	A85 X B89 X C75MM	
32	MAZDA-SXR1830008W-6K-240V-WH-10VDIM-EM-A85 X B89 X C75MM	08W	6000	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	960LM	A85 X B89 X C75MM	
33	MAZDA-SXR1830008W-2.7K-240V-WH-ND-A85 X B89 X C75MM	08W	2700	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	960LM	A85 X B89 X C75MM	
34	MAZDA-SXR1830008W-2.7K-240V-WH-ND-EM-A85 X B89 X C75MM	08W	2700	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	960LM	A85 X B89 X C75MM	
35	MAZDA-SXR1830008W-2.7K-240V-WH-DA-A85 X B89 X C75MM	08W	2700	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	960LM	A85 X B89 X C75MM	
36	MAZDA-SXR1830008W-2.7K-240V-WH-DA-EM-A85 X B89 X C75MM	08W	2700	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	960LM	A85 X B89 X C75MM	
37	MAZDA-SXR1830008W-2.7K-240V-WH-PH-A85 X B89 X C75MM	08W	2700	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	960LM	A85 X B89 X C75MM	
38	MAZDA-SXR1830008W-2.7K-240V-WH-PH-EM-A85 X B89 X C75MM	08W	2700	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	960LM	A85 X B89 X C75MM	
39	MAZDA-SXR1830008W-2.7K-240V-WH-10VDIM-A85 X B89 X C75MM	08W	2700	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	960LM	A85 X B89 X C75MM	
40	MAZDA-SXR1830008W-2.7K-240V-WH-10VDIM-EM-A85 X B89 X C75MM	08W	2700	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	960LM	A85 X B89 X C75MM	
41	MAZDA-SXR1830008W-6.5K-240V-WH-ND-A85 X B89 X C75MM	08W	6500	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	960LM	A85 X B89 X C75MM	
42	MAZDA-SXR1830008W-6.5K-240V-WH-ND-EM-A85 X B89 X C75MM	08W	6500	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	960LM	A85 X B89 X C75MM	
43	MAZDA-SXR1830008W-6.5K-240V-WH-DA-A85 X B89 X C75MM	08W	6500	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	960LM	A85 X B89 X C75MM	
44	MAZDA-SXR1830008W-6.5K-240V-WH-DA-EM-A85 X B89 X C75MM	08W	6500	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	960LM	A85 X B89 X C75MM	
45	MAZDA-SXR1830008W-6.5K-240V-WH-PH-A85 X B89 X C75MM	08W	6500	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	960LM	A85 X B89 X C75MM	
46	MAZDA-SXR1830008W-6.5K-240V-WH-PH-EM-A85 X B89 X C75MM	08W	6500	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	960LM	A85 X B89 X C75MM	
47	MAZDA-SXR1830008W-6.5K-240V-WH-10VDIM-A85 X B89 X C75MM	08W	6500	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	960LM	A85 X B89 X C75MM	

DATASHEET

GENERATED ON: 10 Nov 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
48	MAZDA-SXR1830008W-6.5K-240V-WH-10VDIM-EM-A85 X B89 X C75MM	08W	6500	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	960LM	A85 X B89 X C75MM	
49	MAZDA-SXR1830010W-3K-240V-WH-ND-A85 X B89 X C75MM	10W	3000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
50	MAZDA-SXR1830010W-3K-240V-WH-ND-EM-A85 X B89 X C75MM	10W	3000	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
51	MAZDA-SXR1830010W-3K-240V-WH-DA-A85 X B89 X C75MM	10W	3000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
52	MAZDA-SXR1830010W-3K-240V-WH-DA-EM-A85 X B89 X C75MM	10W	3000	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
53	MAZDA-SXR1830010W-3K-240V-WH-PH-A85 X B89 X C75MM	10W	3000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
54	MAZDA-SXR1830010W-3K-240V-WH-PH-EM-A85 X B89 X C75MM	10W	3000	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
55	MAZDA-SXR1830010W-3K-240V-WH-10VDIM-A85 X B89 X C75MM	10W	3000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
56	MAZDA-SXR1830010W-3K-240V-WH-10VDIM-EM-A85 X B89 X C75MM	10W	3000	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
57	MAZDA-SXR1830010W-4K-240V-WH-ND-A85 X B89 X C75MM	10W	4000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
58	MAZDA-SXR1830010W-4K-240V-WH-ND-EM-A85 X B89 X C75MM	10W	4000	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
59	MAZDA-SXR1830010W-4K-240V-WH-DA-A85 X B89 X C75MM	10W	4000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
60	MAZDA-SXR1830010W-4K-240V-WH-DA-EM-A85 X B89 X C75MM	10W	4000	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
61	MAZDA-SXR1830010W-4K-240V-WH-PH-A85 X B89 X C75MM	10W	4000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
62	MAZDA-SXR1830010W-4K-240V-WH-PH-EM-A85 X B89 X C75MM	10W	4000	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
63	MAZDA-SXR1830010W-4K-240V-WH-10VDIM-A85 X B89 X C75MM	10W	4000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
64	MAZDA-SXR1830010W-4K-240V-WH-10VDIM-EM-A85 X B89 X C75MM	10W	4000	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
65	MAZDA-SXR1830010W-5K-240V-WH-ND-A85 X B89 X C75MM	10W	5000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
66	MAZDA-SXR1830010W-5K-240V-WH-ND-EM-A85 X B89 X C75MM	10W	5000	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
67	MAZDA-SXR1830010W-5K-240V-WH-DA-A85 X B89 X C75MM	10W	5000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
68	MAZDA-SXR1830010W-5K-240V-WH-DA-EM-A85 X B89 X C75MM	10W	5000	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
69	MAZDA-SXR1830010W-5K-240V-WH-PH-A85 X B89 X C75MM	10W	5000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
70	MAZDA-SXR1830010W-5K-240V-WH-PH-EM-A85 X B89 X C75MM	10W	5000	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
71	MAZDA-SXR1830010W-5K-240V-WH-10VDIM-A85 X B89 X C75MM	10W	5000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
72	MAZDA-SXR1830010W-5K-240V-WH-10VDIM-EM-A85 X B89 X C75MM	10W	5000	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
73	MAZDA-SXR1830010W-6K-240V-WH-ND-A85 X B89 X C75MM	10W	6000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
74	MAZDA-SXR1830010W-6K-240V-WH-ND-EM-A85 X B89 X C75MM	10W	6000	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
75	MAZDA-SXR1830010W-6K-240V-WH-DA-A85 X B89 X C75MM	10W	6000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
76	MAZDA-SXR1830010W-6K-240V-WH-DA-EM-A85 X B89 X C75MM	10W	6000	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	

DATASHEET

GENERATED ON: 10 Nov 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
77	MAZDA-SXR1830010W-6K-240V-WH-PH-A85 X B89 X C75MM	10W	6000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
78	MAZDA-SXR1830010W-6K-240V-WH-PH-EM-A85 X B89 X C75MM	10W	6000	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
79	MAZDA-SXR1830010W-6K-240V-WH-10VDIM-A85 X B89 X C75MM	10W	6000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
80	MAZDA-SXR1830010W-6K-240V-WH-10VDIM-EM-A85 X B89 X C75MM	10W	6000	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
81	MAZDA-SXR1830010W-2.7K-240V-WH-ND-A85 X B89 X C75MM	10W	2700	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
82	MAZDA-SXR1830010W-2.7K-240V-WH-ND-EM-A85 X B89 X C75MM	10W	2700	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
83	MAZDA-SXR1830010W-2.7K-240V-WH-DA-A85 X B89 X C75MM	10W	2700	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
84	MAZDA-SXR1830010W-2.7K-240V-WH-DA-EM-A85 X B89 X C75MM	10W	2700	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
85	MAZDA-SXR1830010W-2.7K-240V-WH-PH-A85 X B89 X C75MM	10W	2700	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
86	MAZDA-SXR1830010W-2.7K-240V-WH-PH-EM-A85 X B89 X C75MM	10W	2700	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
87	MAZDA-SXR1830010W-2.7K-240V-WH-10VDIM-A85 X B89 X C75MM	10W	2700	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
88	MAZDA-SXR1830010W-2.7K-240V-WH-10VDIM-EM-A85 X B89 X C75MM	10W	2700	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
89	MAZDA-SXR1830010W-6.5K-240V-WH-ND-A85 X B89 X C75MM	10W	6500	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
90	MAZDA-SXR1830010W-6.5K-240V-WH-ND-EM-A85 X B89 X C75MM	10W	6500	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
91	MAZDA-SXR1830010W-6.5K-240V-WH-DA-A85 X B89 X C75MM	10W	6500	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
92	MAZDA-SXR1830010W-6.5K-240V-WH-DA-EM-A85 X B89 X C75MM	10W	6500	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
93	MAZDA-SXR1830010W-6.5K-240V-WH-PH-A85 X B89 X C75MM	10W	6500	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
94	MAZDA-SXR1830010W-6.5K-240V-WH-PH-EM-A85 X B89 X C75MM	10W	6500	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
95	MAZDA-SXR1830010W-6.5K-240V-WH-10VDIM-A85 X B89 X C75MM	10W	6500	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
96	MAZDA-SXR1830010W-6.5K-240V-WH-10VDIM-EM-A85 X B89 X C75MM	10W	6500	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
97	MAZDA-SXR1830013W-3K-240V-WH-ND-A85 X B89 X C75MM	13W	3000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
98	MAZDA-SXR1830013W-3K-240V-WH-ND-EM-A85 X B89 X C75MM	13W	3000	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
99	MAZDA-SXR1830013W-3K-240V-WH-DA-A85 X B89 X C75MM	13W	3000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
100	MAZDA-SXR1830013W-3K-240V-WH-DA-EM-A85 X B89 X C75MM	13W	3000	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
101	MAZDA-SXR1830013W-3K-240V-WH-PH-A85 X B89 X C75MM	13W	3000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
102	MAZDA-SXR1830013W-3K-240V-WH-PH-EM-A85 X B89 X C75MM	13W	3000	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
103	MAZDA-SXR1830013W-3K-240V-WH-10VDIM-A85 X B89 X C75MM	13W	3000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
104	MAZDA-SXR1830013W-3K-240V-WH-10VDIM-EM-A85 X B89 X C75MM	13W	3000	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
105	MAZDA-SXR1830013W-4K-240V-WH-ND-A85 X B89 X C75MM	13W	4000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	

DATASHEET

GENERATED ON: 10 Nov 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
106	MAZDA-SXR1830013W-4K-240V-WH-ND-EM-A85 X B89 X C75MM	13W	4000	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
107	MAZDA-SXR1830013W-4K-240V-WH-DA-A85 X B89 X C75MM	13W	4000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
108	MAZDA-SXR1830013W-4K-240V-WH-DA-EM-A85 X B89 X C75MM	13W	4000	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
109	MAZDA-SXR1830013W-4K-240V-WH-PH-A85 X B89 X C75MM	13W	4000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
110	MAZDA-SXR1830013W-4K-240V-WH-PH-EM-A85 X B89 X C75MM	13W	4000	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
111	MAZDA-SXR1830013W-4K-240V-WH-10VDIM-A85 X B89 X C75MM	13W	4000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
112	MAZDA-SXR1830013W-4K-240V-WH-10VDIM-EM-A85 X B89 X C75MM	13W	4000	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
113	MAZDA-SXR1830013W-5K-240V-WH-ND-A85 X B89 X C75MM	13W	5000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
114	MAZDA-SXR1830013W-5K-240V-WH-ND-EM-A85 X B89 X C75MM	13W	5000	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
115	MAZDA-SXR1830013W-5K-240V-WH-DA-A85 X B89 X C75MM	13W	5000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
116	MAZDA-SXR1830013W-5K-240V-WH-DA-EM-A85 X B89 X C75MM	13W	5000	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
117	MAZDA-SXR1830013W-5K-240V-WH-PH-A85 X B89 X C75MM	13W	5000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
118	MAZDA-SXR1830013W-5K-240V-WH-PH-EM-A85 X B89 X C75MM	13W	5000	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
119	MAZDA-SXR1830013W-5K-240V-WH-10VDIM-A85 X B89 X C75MM	13W	5000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
120	MAZDA-SXR1830013W-5K-240V-WH-10VDIM-EM-A85 X B89 X C75MM	13W	5000	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
121	MAZDA-SXR1830013W-6K-240V-WH-ND-A85 X B89 X C75MM	13W	6000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
122	MAZDA-SXR1830013W-6K-240V-WH-ND-EM-A85 X B89 X C75MM	13W	6000	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
123	MAZDA-SXR1830013W-6K-240V-WH-DA-A85 X B89 X C75MM	13W	6000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
124	MAZDA-SXR1830013W-6K-240V-WH-DA-EM-A85 X B89 X C75MM	13W	6000	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
125	MAZDA-SXR1830013W-6K-240V-WH-PH-A85 X B89 X C75MM	13W	6000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
126	MAZDA-SXR1830013W-6K-240V-WH-PH-EM-A85 X B89 X C75MM	13W	6000	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
127	MAZDA-SXR1830013W-6K-240V-WH-10VDIM-A85 X B89 X C75MM	13W	6000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
128	MAZDA-SXR1830013W-6K-240V-WH-10VDIM-EM-A85 X B89 X C75MM	13W	6000	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
129	MAZDA-SXR1830013W-2.7K-240V-WH-ND-A85 X B89 X C75MM	13W	2700	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
130	MAZDA-SXR1830013W-2.7K-240V-WH-ND-EM-A85 X B89 X C75MM	13W	2700	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
131	MAZDA-SXR1830013W-2.7K-240V-WH-DA-A85 X B89 X C75MM	13W	2700	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
132	MAZDA-SXR1830013W-2.7K-240V-WH-DA-EM-A85 X B89 X C75MM	13W	2700	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
133	MAZDA-SXR1830013W-2.7K-240V-WH-PH-A85 X B89 X C75MM	13W	2700	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
134	MAZDA-SXR1830013W-2.7K-240V-WH-PH-EM-A85 X B89 X C75MM	13W	2700	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	

DATASHEET

GENERATED ON: 10 Nov 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
135	MAZDA-SXR1830013W-2.7K-240V-WH-10VDIM-A85 X B89 X C75MM	13W	2700	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
136	MAZDA-SXR1830013W-2.7K-240V-WH-10VDIM-EM-A85 X B89 X C75MM	13W	2700	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
137	MAZDA-SXR1830013W-6.5K-240V-WH-ND-A85 X B89 X C75MM	13W	6500	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
138	MAZDA-SXR1830013W-6.5K-240V-WH-ND-EM-A85 X B89 X C75MM	13W	6500	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
139	MAZDA-SXR1830013W-6.5K-240V-WH-DA-A85 X B89 X C75MM	13W	6500	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
140	MAZDA-SXR1830013W-6.5K-240V-WH-DA-EM-A85 X B89 X C75MM	13W	6500	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
141	MAZDA-SXR1830013W-6.5K-240V-WH-PH-A85 X B89 X C75MM	13W	6500	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
142	MAZDA-SXR1830013W-6.5K-240V-WH-PH-EM-A85 X B89 X C75MM	13W	6500	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
143	MAZDA-SXR1830013W-6.5K-240V-WH-10VDIM-A85 X B89 X C75MM	13W	6500	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
144	MAZDA-SXR1830013W-6.5K-240V-WH-10VDIM-EM-A85 X B89 X C75MM	13W	6500	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1200LM	A85 X B89 X C75MM	
145	MAZDA-SXR1830013W-3K-240V-WH-ND-A85 X B89 X C75MM	13W	3000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1560LM	A85 X B89 X C75MM	
146	MAZDA-SXR1830013W-3K-240V-WH-ND-EM-A85 X B89 X C75MM	13W	3000	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1560LM	A85 X B89 X C75MM	
147	MAZDA-SXR1830013W-3K-240V-WH-DA-A85 X B89 X C75MM	13W	3000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1560LM	A85 X B89 X C75MM	
148	MAZDA-SXR1830013W-3K-240V-WH-DA-EM-A85 X B89 X C75MM	13W	3000	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1560LM	A85 X B89 X C75MM	
149	MAZDA-SXR1830013W-3K-240V-WH-PH-A85 X B89 X C75MM	13W	3000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1560LM	A85 X B89 X C75MM	
150	MAZDA-SXR1830013W-3K-240V-WH-PH-EM-A85 X B89 X C75MM	13W	3000	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1560LM	A85 X B89 X C75MM	
151	MAZDA-SXR1830013W-3K-240V-WH-10VDIM-A85 X B89 X C75MM	13W	3000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1560LM	A85 X B89 X C75MM	
152	MAZDA-SXR1830013W-3K-240V-WH-10VDIM-EM-A85 X B89 X C75MM	13W	3000	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1560LM	A85 X B89 X C75MM	
153	MAZDA-SXR1830013W-4K-240V-WH-ND-A85 X B89 X C75MM	13W	4000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1560LM	A85 X B89 X C75MM	
154	MAZDA-SXR1830013W-4K-240V-WH-ND-EM-A85 X B89 X C75MM	13W	4000	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1560LM	A85 X B89 X C75MM	
155	MAZDA-SXR1830013W-4K-240V-WH-DA-A85 X B89 X C75MM	13W	4000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1560LM	A85 X B89 X C75MM	
156	MAZDA-SXR1830013W-4K-240V-WH-DA-EM-A85 X B89 X C75MM	13W	4000	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1560LM	A85 X B89 X C75MM	
157	MAZDA-SXR1830013W-4K-240V-WH-PH-A85 X B89 X C75MM	13W	4000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1560LM	A85 X B89 X C75MM	
158	MAZDA-SXR1830013W-4K-240V-WH-PH-EM-A85 X B89 X C75MM	13W	4000	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1560LM	A85 X B89 X C75MM	
159	MAZDA-SXR1830013W-4K-240V-WH-10VDIM-A85 X B89 X C75MM	13W	4000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1560LM	A85 X B89 X C75MM	
160	MAZDA-SXR1830013W-4K-240V-WH-10VDIM-EM-A85 X B89 X C75MM	13W	4000	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1560LM	A85 X B89 X C75MM	
161	MAZDA-SXR1830013W-5K-240V-WH-ND-A85 X B89 X C75MM	13W	5000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1560LM	A85 X B89 X C75MM	
162	MAZDA-SXR1830013W-5K-240V-WH-ND-EM-A85 X B89 X C75MM	13W	5000	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1560LM	A85 X B89 X C75MM	
163	MAZDA-SXR1830013W-5K-240V-WH-DA-A85 X B89 X C75MM	13W	5000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1560LM	A85 X B89 X C75MM	

DATASHEET

GENERATED ON: 10 Nov 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
164	MAZDA-SXR1830013W-5K-240V-WH-DA-EM-A85 X B89 X C75MM	13W	5000	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1560LM	A85 X B89 X C75MM	
165	MAZDA-SXR1830013W-5K-240V-WH-PH-A85 X B89 X C75MM	13W	5000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1560LM	A85 X B89 X C75MM	
166	MAZDA-SXR1830013W-5K-240V-WH-PH-EM-A85 X B89 X C75MM	13W	5000	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1560LM	A85 X B89 X C75MM	
167	MAZDA-SXR1830013W-5K-240V-WH-10VDIM-A85 X B89 X C75MM	13W	5000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1560LM	A85 X B89 X C75MM	
168	MAZDA-SXR1830013W-5K-240V-WH-10VDIM-EM-A85 X B89 X C75MM	13W	5000	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1560LM	A85 X B89 X C75MM	
169	MAZDA-SXR1830013W-6K-240V-WH-ND-A85 X B89 X C75MM	13W	6000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1560LM	A85 X B89 X C75MM	
170	MAZDA-SXR1830013W-6K-240V-WH-ND-EM-A85 X B89 X C75MM	13W	6000	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1560LM	A85 X B89 X C75MM	
171	MAZDA-SXR1830013W-6K-240V-WH-DA-A85 X B89 X C75MM	13W	6000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1560LM	A85 X B89 X C75MM	
172	MAZDA-SXR1830013W-6K-240V-WH-DA-EM-A85 X B89 X C75MM	13W	6000	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1560LM	A85 X B89 X C75MM	
173	MAZDA-SXR1830013W-6K-240V-WH-PH-A85 X B89 X C75MM	13W	6000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1560LM	A85 X B89 X C75MM	
174	MAZDA-SXR1830013W-6K-240V-WH-PH-EM-A85 X B89 X C75MM	13W	6000	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1560LM	A85 X B89 X C75MM	
175	MAZDA-SXR1830013W-6K-240V-WH-10VDIM-A85 X B89 X C75MM	13W	6000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1560LM	A85 X B89 X C75MM	
176	MAZDA-SXR1830013W-6K-240V-WH-10VDIM-EM-A85 X B89 X C75MM	13W	6000	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1560LM	A85 X B89 X C75MM	
177	MAZDA-SXR1830013W-2.7K-240V-WH-ND-A85 X B89 X C75MM	13W	2700	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1560LM	A85 X B89 X C75MM	
178	MAZDA-SXR1830013W-2.7K-240V-WH-ND-EM-A85 X B89 X C75MM	13W	2700	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1560LM	A85 X B89 X C75MM	
179	MAZDA-SXR1830013W-2.7K-240V-WH-DA-A85 X B89 X C75MM	13W	2700	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1560LM	A85 X B89 X C75MM	
180	MAZDA-SXR1830013W-2.7K-240V-WH-DA-EM-A85 X B89 X C75MM	13W	2700	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1560LM	A85 X B89 X C75MM	
181	MAZDA-SXR1830013W-2.7K-240V-WH-PH-A85 X B89 X C75MM	13W	2700	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1560LM	A85 X B89 X C75MM	
182	MAZDA-SXR1830013W-2.7K-240V-WH-PH-EM-A85 X B89 X C75MM	13W	2700	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1560LM	A85 X B89 X C75MM	
183	MAZDA-SXR1830013W-2.7K-240V-WH-10VDIM-A85 X B89 X C75MM	13W	2700	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1560LM	A85 X B89 X C75MM	
184	MAZDA-SXR1830013W-2.7K-240V-WH-10VDIM-EM-A85 X B89 X C75MM	13W	2700	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1560LM	A85 X B89 X C75MM	
185	MAZDA-SXR1830013W-6.5K-240V-WH-ND-A85 X B89 X C75MM	13W	6500	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1560LM	A85 X B89 X C75MM	
186	MAZDA-SXR1830013W-6.5K-240V-WH-ND-EM-A85 X B89 X C75MM	13W	6500	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1560LM	A85 X B89 X C75MM	
187	MAZDA-SXR1830013W-6.5K-240V-WH-DA-A85 X B89 X C75MM	13W	6500	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1560LM	A85 X B89 X C75MM	
188	MAZDA-SXR1830013W-6.5K-240V-WH-DA-EM-A85 X B89 X C75MM	13W	6500	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1560LM	A85 X B89 X C75MM	
189	MAZDA-SXR1830013W-6.5K-240V-WH-PH-A85 X B89 X C75MM	13W	6500	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1560LM	A85 X B89 X C75MM	
190	MAZDA-SXR1830013W-6.5K-240V-WH-PH-EM-A85 X B89 X C75MM	13W	6500	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1560LM	A85 X B89 X C75MM	
191	MAZDA-SXR1830013W-6.5K-240V-WH-10VDIM-A85 X B89 X C75MM	13W	6500	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1560LM	A85 X B89 X C75MM	
192	MAZDA-SXR1830013W-6.5K-240V-WH-10VDIM-EM-A85 X B89 X C75MM	13W	6500	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A85 X B89 X C75MM	DIE CAST ALUMINUM	IP54	1560LM	A85 X B89 X C75MM	

DATASHEET

GENERATED ON: 10 Nov 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
193	MAZDA-SXR1830015W-3K-240V-WH-ND-A110 X B98 X C95MM	15W	3000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A110 X B98 X C95MM	DIE CAST ALUMINUM	IP54	1800LM	A110 X B98 X C95MM	
194	MAZDA-SXR1830015W-3K-240V-WH-ND-EM-A110 X B98 X C95MM	15W	3000	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A110 X B98 X C95MM	DIE CAST ALUMINUM	IP54	1800LM	A110 X B98 X C95MM	
195	MAZDA-SXR1830015W-3K-240V-WH-DA-A110 X B98 X C95MM	15W	3000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A110 X B98 X C95MM	DIE CAST ALUMINUM	IP54	1800LM	A110 X B98 X C95MM	
196	MAZDA-SXR1830015W-3K-240V-WH-DA-EM-A110 X B98 X C95MM	15W	3000	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A110 X B98 X C95MM	DIE CAST ALUMINUM	IP54	1800LM	A110 X B98 X C95MM	
197	MAZDA-SXR1830015W-3K-240V-WH-PH-A110 X B98 X C95MM	15W	3000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A110 X B98 X C95MM	DIE CAST ALUMINUM	IP54	1800LM	A110 X B98 X C95MM	
198	MAZDA-SXR1830015W-3K-240V-WH-PH-EM-A110 X B98 X C95MM	15W	3000	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A110 X B98 X C95MM	DIE CAST ALUMINUM	IP54	1800LM	A110 X B98 X C95MM	
199	MAZDA-SXR1830015W-3K-240V-WH-10VDIM-A110 X B98 X C95MM	15W	3000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A110 X B98 X C95MM	DIE CAST ALUMINUM	IP54	1800LM	A110 X B98 X C95MM	
200	MAZDA-SXR1830015W-3K-240V-WH-10VDIM-EM-A110 X B98 X C95MM	15W	3000	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A110 X B98 X C95MM	DIE CAST ALUMINUM	IP54	1800LM	A110 X B98 X C95MM	
201	MAZDA-SXR1830015W-4K-240V-WH-ND-A110 X B98 X C95MM	15W	4000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A110 X B98 X C95MM	DIE CAST ALUMINUM	IP54	1800LM	A110 X B98 X C95MM	
202	MAZDA-SXR1830015W-4K-240V-WH-ND-EM-A110 X B98 X C95MM	15W	4000	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A110 X B98 X C95MM	DIE CAST ALUMINUM	IP54	1800LM	A110 X B98 X C95MM	
203	MAZDA-SXR1830015W-4K-240V-WH-DA-A110 X B98 X C95MM	15W	4000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A110 X B98 X C95MM	DIE CAST ALUMINUM	IP54	1800LM	A110 X B98 X C95MM	
204	MAZDA-SXR1830015W-4K-240V-WH-DA-EM-A110 X B98 X C95MM	15W	4000	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A110 X B98 X C95MM	DIE CAST ALUMINUM	IP54	1800LM	A110 X B98 X C95MM	
205	MAZDA-SXR1830015W-4K-240V-WH-PH-A110 X B98 X C95MM	15W	4000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A110 X B98 X C95MM	DIE CAST ALUMINUM	IP54	1800LM	A110 X B98 X C95MM	
206	MAZDA-SXR1830015W-4K-240V-WH-PH-EM-A110 X B98 X C95MM	15W	4000	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A110 X B98 X C95MM	DIE CAST ALUMINUM	IP54	1800LM	A110 X B98 X C95MM	
207	MAZDA-SXR1830015W-4K-240V-WH-10VDIM-A110 X B98 X C95MM	15W	4000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A110 X B98 X C95MM	DIE CAST ALUMINUM	IP54	1800LM	A110 X B98 X C95MM	
208	MAZDA-SXR1830015W-4K-240V-WH-10VDIM-EM-A110 X B98 X C95MM	15W	4000	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A110 X B98 X C95MM	DIE CAST ALUMINUM	IP54	1800LM	A110 X B98 X C95MM	
209	MAZDA-SXR1830015W-5K-240V-WH-ND-A110 X B98 X C95MM	15W	5000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A110 X B98 X C95MM	DIE CAST ALUMINUM	IP54	1800LM	A110 X B98 X C95MM	
210	MAZDA-SXR1830015W-5K-240V-WH-ND-EM-A110 X B98 X C95MM	15W	5000	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A110 X B98 X C95MM	DIE CAST ALUMINUM	IP54	1800LM	A110 X B98 X C95MM	
211	MAZDA-SXR1830015W-5K-240V-WH-DA-A110 X B98 X C95MM	15W	5000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A110 X B98 X C95MM	DIE CAST ALUMINUM	IP54	1800LM	A110 X B98 X C95MM	
212	MAZDA-SXR1830015W-5K-240V-WH-DA-EM-A110 X B98 X C95MM	15W	5000	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A110 X B98 X C95MM	DIE CAST ALUMINUM	IP54	1800LM	A110 X B98 X C95MM	
213	MAZDA-SXR1830015W-5K-240V-WH-PH-A110 X B98 X C95MM	15W	5000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A110 X B98 X C95MM	DIE CAST ALUMINUM	IP54	1800LM	A110 X B98 X C95MM	
214	MAZDA-SXR1830015W-5K-240V-WH-PH-EM-A110 X B98 X C95MM	15W	5000	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A110 X B98 X C95MM	DIE CAST ALUMINUM	IP54	1800LM	A110 X B98 X C95MM	
215	MAZDA-SXR1830015W-5K-240V-WH-10VDIM-A110 X B98 X C95MM	15W	5000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A110 X B98 X C95MM	DIE CAST ALUMINUM	IP54	1800LM	A110 X B98 X C95MM	
216	MAZDA-SXR1830015W-5K-240V-WH-10VDIM-EM-A110 X B98 X C95MM	15W	5000	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A110 X B98 X C95MM	DIE CAST ALUMINUM	IP54	1800LM	A110 X B98 X C95MM	
217	MAZDA-SXR1830015W-6K-240V-WH-ND-A110 X B98 X C95MM	15W	6000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A110 X B98 X C95MM	DIE CAST ALUMINUM	IP54	1800LM	A110 X B98 X C95MM	
218	MAZDA-SXR1830015W-6K-240V-WH-ND-EM-A110 X B98 X C95MM	15W	6000	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A110 X B98 X C95MM	DIE CAST ALUMINUM	IP54	1800LM	A110 X B98 X C95MM	
219	MAZDA-SXR1830015W-6K-240V-WH-DA-A110 X B98 X C95MM	15W	6000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A110 X B98 X C95MM	DIE CAST ALUMINUM	IP54	1800LM	A110 X B98 X C95MM	
220	MAZDA-SXR1830015W-6K-240V-WH-DA-EM-A110 X B98 X C95MM	15W	6000	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A110 X B98 X C95MM	DIE CAST ALUMINUM	IP54	1800LM	A110 X B98 X C95MM	
221	MAZDA-SXR1830015W-6K-240V-WH-PH-A110 X B98 X C95MM	15W	6000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A110 X B98 X C95MM	DIE CAST ALUMINUM	IP54	1800LM	A110 X B98 X C95MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
222	**MAZDA-SXR1830015W-6K-240V-WH-PH-EM-A110 X B98 X C95MM**	15W	6000	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A110 X B98 X C95MM	DIE CAST ALUMINUM	IP54	1800LM	A110 X B98 X C95MM	
223	**MAZDA-SXR1830015W-6K-240V-WH-10VDIM-A110 X B98 X C95MM**	15W	6000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A110 X B98 X C95MM	DIE CAST ALUMINUM	IP54	1800LM	A110 X B98 X C95MM	
224	**MAZDA-SXR1830015W-6K-240V-WH-10VDIM-EM-A110 X B98 X C95MM**	15W	6000	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A110 X B98 X C95MM	DIE CAST ALUMINUM	IP54	1800LM	A110 X B98 X C95MM	
225	**MAZDA-SXR1830015W-2.7K-240V-WH-ND-A110 X B98 X C95MM**	15W	2700	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A110 X B98 X C95MM	DIE CAST ALUMINUM	IP54	1800LM	A110 X B98 X C95MM	
226	**MAZDA-SXR1830015W-2.7K-240V-WH-ND-EM-A110 X B98 X C95MM**	15W	2700	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A110 X B98 X C95MM	DIE CAST ALUMINUM	IP54	1800LM	A110 X B98 X C95MM	
227	**MAZDA-SXR1830015W-2.7K-240V-WH-DA-A110 X B98 X C95MM**	15W	2700	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A110 X B98 X C95MM	DIE CAST ALUMINUM	IP54	1800LM	A110 X B98 X C95MM	
228	**MAZDA-SXR1830015W-2.7K-240V-WH-DA-EM-A110 X B98 X C95MM**	15W	2700	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A110 X B98 X C95MM	DIE CAST ALUMINUM	IP54	1800LM	A110 X B98 X C95MM	
229	**MAZDA-SXR1830015W-2.7K-240V-WH-PH-A110 X B98 X C95MM**	15W	2700	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A110 X B98 X C95MM	DIE CAST ALUMINUM	IP54	1800LM	A110 X B98 X C95MM	
230	**MAZDA-SXR1830015W-2.7K-240V-WH-PH-EM-A110 X B98 X C95MM**	15W	2700	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A110 X B98 X C95MM	DIE CAST ALUMINUM	IP54	1800LM	A110 X B98 X C95MM	
231	**MAZDA-SXR1830015W-2.7K-240V-WH-10VDIM-A110 X B98 X C95MM**	15W	2700	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A110 X B98 X C95MM	DIE CAST ALUMINUM	IP54	1800LM	A110 X B98 X C95MM	
232	**MAZDA-SXR1830015W-2.7K-240V-WH-10VDIM-EM-A110 X B98 X C95MM**	15W	2700	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A110 X B98 X C95MM	DIE CAST ALUMINUM	IP54	1800LM	A110 X B98 X C95MM	
233	**MAZDA-SXR1830015W-6.5K-240V-WH-ND-A110 X B98 X C95MM**	15W	6500	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A110 X B98 X C95MM	DIE CAST ALUMINUM	IP54	1800LM	A110 X B98 X C95MM	
234	**MAZDA-SXR1830015W-6.5K-240V-WH-ND-EM-A110 X B98 X C95MM**	15W	6500	240V	WHITE	3 HOUR EMERGENCY BACKUP	ON - OFF	15°, 24°, 36°	A110 X B98 X C95MM	DIE CAST ALUMINUM	IP54	1800LM	A110 X B98 X C95MM	
235	**MAZDA-SXR1830015W-6.5K-240V-WH-DA-A110 X B98 X C95MM**	15W	6500	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A110 X B98 X C95MM	DIE CAST ALUMINUM	IP54	1800LM	A110 X B98 X C95MM	
236	**MAZDA-SXR1830015W-6.5K-240V-WH-DA-EM-A110 X B98 X C95MM**	15W	6500	240V	WHITE	3 HOUR EMERGENCY BACKUP	DALI DIMMABLE DRIVER	15°, 24°, 36°	A110 X B98 X C95MM	DIE CAST ALUMINUM	IP54	1800LM	A110 X B98 X C95MM	
237	**MAZDA-SXR1830015W-6.5K-240V-WH-PH-A110 X B98 X C95MM**	15W	6500	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A110 X B98 X C95MM	DIE CAST ALUMINUM	IP54	1800LM	A110 X B98 X C95MM	
238	**MAZDA-SXR1830015W-6.5K-240V-WH-PH-EM-A110 X B98 X C95MM**	15W	6500	240V	WHITE	3 HOUR EMERGENCY BACKUP	PHASE CUT DIMMABLE	15°, 24°, 36°	A110 X B98 X C95MM	DIE CAST ALUMINUM	IP54	1800LM	A110 X B98 X C95MM	
239	**MAZDA-SXR1830015W-6.5K-240V-WH-10VDIM-A110 X B98 X C95MM**	15W	6500	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A110 X B98 X C95MM	DIE CAST ALUMINUM	IP54	1800LM	A110 X B98 X C95MM	
240	**MAZDA-SXR1830015W-6.5K-240V-WH-10VDIM-EM-A110 X B98 X C95MM**	15W	6500	240V	WHITE	3 HOUR EMERGENCY BACKUP	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A110 X B98 X C95MM	DIE CAST ALUMINUM	IP54	1800LM	A110 X B98 X C95MM	