



MAX

MAZDA Model: **DXR1745** Downlight

Transform your space with a focused wash of light. This versatile downlight is engineered to deliver high candela intensity, making it perfect for creating visual emphasis and atmosphere. Whether highlighting displays, this fixture combines energy efficiency with professional-grade lighting control

ALL AVAILABLE VARIANTS

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
1	MAZDA-DXR174515W-3K-240V-BL-ND-A95XB89XC85MM	15W	3000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A95XB89XC85MM	DIE CAST ALUMINUM	IP54	1800LM	A95XB89XC85MM	
2	MAZDA-DXR174515W-3K-240V-BL-DA-A95XB89XC85MM	15W	3000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A95XB89XC85MM	DIE CAST ALUMINUM	IP54	1800LM	A95XB89XC85MM	
3	MAZDA-DXR174515W-3K-240V-BL-PH-A95XB89XC85MM	15W	3000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A95XB89XC85MM	DIE CAST ALUMINUM	IP54	1800LM	A95XB89XC85MM	
4	MAZDA-DXR174515W-3K-240V-BL-10VDIM-A95XB89XC85MM	15W	3000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A95XB89XC85MM	DIE CAST ALUMINUM	IP54	1800LM	A95XB89XC85MM	
5	MAZDA-DXR174515W-4K-240V-BL-ND-A95XB89XC85MM	15W	4000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A95XB89XC85MM	DIE CAST ALUMINUM	IP54	1800LM	A95XB89XC85MM	
6	MAZDA-DXR174515W-4K-240V-BL-DA-A95XB89XC85MM	15W	4000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A95XB89XC85MM	DIE CAST ALUMINUM	IP54	1800LM	A95XB89XC85MM	
7	MAZDA-DXR174515W-4K-240V-BL-PH-A95XB89XC85MM	15W	4000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A95XB89XC85MM	DIE CAST ALUMINUM	IP54	1800LM	A95XB89XC85MM	
8	MAZDA-DXR174515W-4K-240V-BL-10VDIM-A95XB89XC85MM	15W	4000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A95XB89XC85MM	DIE CAST ALUMINUM	IP54	1800LM	A95XB89XC85MM	
9	MAZDA-DXR174515W-5K-240V-BL-ND-A95XB89XC85MM	15W	5000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A95XB89XC85MM	DIE CAST ALUMINUM	IP54	1800LM	A95XB89XC85MM	
10	MAZDA-DXR174515W-5K-240V-BL-DA-A95XB89XC85MM	15W	5000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A95XB89XC85MM	DIE CAST ALUMINUM	IP54	1800LM	A95XB89XC85MM	
11	MAZDA-DXR174515W-5K-240V-BL-PH-A95XB89XC85MM	15W	5000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A95XB89XC85MM	DIE CAST ALUMINUM	IP54	1800LM	A95XB89XC85MM	
12	MAZDA-DXR174515W-5K-240V-BL-10VDIM-A95XB89XC85MM	15W	5000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A95XB89XC85MM	DIE CAST ALUMINUM	IP54	1800LM	A95XB89XC85MM	
13	MAZDA-DXR174515W-6K-240V-BL-ND-A95XB89XC85MM	15W	6000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A95XB89XC85MM	DIE CAST ALUMINUM	IP54	1800LM	A95XB89XC85MM	
14	MAZDA-DXR174515W-6K-240V-BL-DA-A95XB89XC85MM	15W	6000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A95XB89XC85MM	DIE CAST ALUMINUM	IP54	1800LM	A95XB89XC85MM	
15	MAZDA-DXR174515W-6K-240V-BL-PH-A95XB89XC85MM	15W	6000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A95XB89XC85MM	DIE CAST ALUMINUM	IP54	1800LM	A95XB89XC85MM	
16	MAZDA-DXR174515W-6K-240V-BL-10VDIM-A95XB89XC85MM	15W	6000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A95XB89XC85MM	DIE CAST ALUMINUM	IP54	1800LM	A95XB89XC85MM	
17	MAZDA-DXR174515W-2.7K-240V-BL-ND-A95XB89XC85MM	15W	2700	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A95XB89XC85MM	DIE CAST ALUMINUM	IP54	1800LM	A95XB89XC85MM	
18	MAZDA-DXR174515W-2.7K-240V-BL-DA-A95XB89XC85MM	15W	2700	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A95XB89XC85MM	DIE CAST ALUMINUM	IP54	1800LM	A95XB89XC85MM	
19	MAZDA-DXR174515W-2.7K-240V-BL-PH-A95XB89XC85MM	15W	2700	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A95XB89XC85MM	DIE CAST ALUMINUM	IP54	1800LM	A95XB89XC85MM	



DATASHEET

GENERATED ON: 14 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
20	MAZDA-DXR174515W-2.7K-240V-BL-10VDIM-A95XB89XC85MM	15W	2700	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A95XB89XC85MM	DIE CAST ALUMINUM	IP54	1800LM	A95XB89XC85MM	
21	MAZDA-DXR174515W-6.5K-240V-BL-ND-A95XB89XC85MM	15W	6500	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A95XB89XC85MM	DIE CAST ALUMINUM	IP54	1800LM	A95XB89XC85MM	
22	MAZDA-DXR174515W-6.5K-240V-BL-DA-A95XB89XC85MM	15W	6500	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A95XB89XC85MM	DIE CAST ALUMINUM	IP54	1800LM	A95XB89XC85MM	
23	MAZDA-DXR174515W-6.5K-240V-BL-PH-A95XB89XC85MM	15W	6500	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A95XB89XC85MM	DIE CAST ALUMINUM	IP54	1800LM	A95XB89XC85MM	
24	MAZDA-DXR174515W-6.5K-240V-BL-10VDIM-A95XB89XC85MM	15W	6500	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A95XB89XC85MM	DIE CAST ALUMINUM	IP54	1800LM	A95XB89XC85MM	
25	MAZDA-DXR174525W-3K-240V-BL-ND-A125XB113XC115MM	25W	3000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A125XB113XC115MM	DIE CAST ALUMINUM	IP54	3000LM	A125XB113XC115MM	
26	MAZDA-DXR174525W-3K-240V-BL-DA-A125XB113XC115MM	25W	3000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A125XB113XC115MM	DIE CAST ALUMINUM	IP54	3000LM	A125XB113XC115MM	
27	MAZDA-DXR174525W-3K-240V-BL-PH-A125XB113XC115MM	25W	3000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A125XB113XC115MM	DIE CAST ALUMINUM	IP54	3000LM	A125XB113XC115MM	
28	MAZDA-DXR174525W-3K-240V-BL-10VDIM-A125XB113XC115MM	25W	3000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A125XB113XC115MM	DIE CAST ALUMINUM	IP54	3000LM	A125XB113XC115MM	
29	MAZDA-DXR174525W-4K-240V-BL-ND-A125XB113XC115MM	25W	4000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A125XB113XC115MM	DIE CAST ALUMINUM	IP54	3000LM	A125XB113XC115MM	
30	MAZDA-DXR174525W-4K-240V-BL-DA-A125XB113XC115MM	25W	4000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A125XB113XC115MM	DIE CAST ALUMINUM	IP54	3000LM	A125XB113XC115MM	
31	MAZDA-DXR174525W-4K-240V-BL-PH-A125XB113XC115MM	25W	4000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A125XB113XC115MM	DIE CAST ALUMINUM	IP54	3000LM	A125XB113XC115MM	
32	MAZDA-DXR174525W-4K-240V-BL-10VDIM-A125XB113XC115MM	25W	4000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A125XB113XC115MM	DIE CAST ALUMINUM	IP54	3000LM	A125XB113XC115MM	
33	MAZDA-DXR174525W-5K-240V-BL-ND-A125XB113XC115MM	25W	5000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A125XB113XC115MM	DIE CAST ALUMINUM	IP54	3000LM	A125XB113XC115MM	
34	MAZDA-DXR174525W-5K-240V-BL-DA-A125XB113XC115MM	25W	5000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A125XB113XC115MM	DIE CAST ALUMINUM	IP54	3000LM	A125XB113XC115MM	
35	MAZDA-DXR174525W-5K-240V-BL-PH-A125XB113XC115MM	25W	5000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A125XB113XC115MM	DIE CAST ALUMINUM	IP54	3000LM	A125XB113XC115MM	
36	MAZDA-DXR174525W-5K-240V-BL-10VDIM-A125XB113XC115MM	25W	5000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A125XB113XC115MM	DIE CAST ALUMINUM	IP54	3000LM	A125XB113XC115MM	
37	MAZDA-DXR174525W-6K-240V-BL-ND-A125XB113XC115MM	25W	6000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A125XB113XC115MM	DIE CAST ALUMINUM	IP54	3000LM	A125XB113XC115MM	
38	MAZDA-DXR174525W-6K-240V-BL-DA-A125XB113XC115MM	25W	6000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A125XB113XC115MM	DIE CAST ALUMINUM	IP54	3000LM	A125XB113XC115MM	
39	MAZDA-DXR174525W-6K-240V-BL-PH-A125XB113XC115MM	25W	6000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A125XB113XC115MM	DIE CAST ALUMINUM	IP54	3000LM	A125XB113XC115MM	
40	MAZDA-DXR174525W-6K-240V-BL-10VDIM-A125XB113XC115MM	25W	6000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A125XB113XC115MM	DIE CAST ALUMINUM	IP54	3000LM	A125XB113XC115MM	
41	MAZDA-DXR174525W-2.7K-240V-BL-ND-A125XB113XC115MM	25W	2700	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A125XB113XC115MM	DIE CAST ALUMINUM	IP54	3000LM	A125XB113XC115MM	
42	MAZDA-DXR174525W-2.7K-240V-BL-DA-A125XB113XC115MM	25W	2700	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A125XB113XC115MM	DIE CAST ALUMINUM	IP54	3000LM	A125XB113XC115MM	
43	MAZDA-DXR174525W-2.7K-240V-BL-PH-A125XB113XC115MM	25W	2700	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A125XB113XC115MM	DIE CAST ALUMINUM	IP54	3000LM	A125XB113XC115MM	
44	MAZDA-DXR174525W-2.7K-240V-BL-10VDIM-A125XB113XC115MM	25W	2700	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A125XB113XC115MM	DIE CAST ALUMINUM	IP54	3000LM	A125XB113XC115MM	
45	MAZDA-DXR174525W-6.5K-240V-BL-ND-A125XB113XC115MM	25W	6500	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A125XB113XC115MM	DIE CAST ALUMINUM	IP54	3000LM	A125XB113XC115MM	
46	MAZDA-DXR174525W-6.5K-240V-BL-DA-A125XB113XC115MM	25W	6500	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A125XB113XC115MM	DIE CAST ALUMINUM	IP54	3000LM	A125XB113XC115MM	
47	MAZDA-DXR174525W-6.5K-240V-BL-PH-A125XB113XC115MM	25W	6500	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A125XB113XC115MM	DIE CAST ALUMINUM	IP54	3000LM	A125XB113XC115MM	
48	MAZDA-DXR174525W-6.5K-240V-BL-10VDIM-A125XB113XC115MM	25W	6500	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A125XB113XC115MM	DIE CAST ALUMINUM	IP54	3000LM	A125XB113XC115MM	
49	MAZDA-DXR174535W-3K-240V-BL-ND-A151XB140XC140MM	35W	3000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	4200LM	A151XB140XC140MM	



DATASHEET

GENERATED ON: 14 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
50	MAZDA-DXR174535W-3K-240V-BL-DA-A151XB140XC140MM	35W	3000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	4200LM	A151XB140XC140MM	
51	MAZDA-DXR174535W-3K-240V-BL-PH-A151XB140XC140MM	35W	3000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	4200LM	A151XB140XC140MM	
52	MAZDA-DXR174535W-3K-240V-BL-10VDIM-A151XB140XC140MM	35W	3000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	4200LM	A151XB140XC140MM	
53	MAZDA-DXR174535W-4K-240V-BL-ND-A151XB140XC140MM	35W	4000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	4200LM	A151XB140XC140MM	
54	MAZDA-DXR174535W-4K-240V-BL-DA-A151XB140XC140MM	35W	4000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	4200LM	A151XB140XC140MM	
55	MAZDA-DXR174535W-4K-240V-BL-PH-A151XB140XC140MM	35W	4000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	4200LM	A151XB140XC140MM	
56	MAZDA-DXR174535W-4K-240V-BL-10VDIM-A151XB140XC140MM	35W	4000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	4200LM	A151XB140XC140MM	
57	MAZDA-DXR174535W-5K-240V-BL-ND-A151XB140XC140MM	35W	5000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	4200LM	A151XB140XC140MM	
58	MAZDA-DXR174535W-5K-240V-BL-DA-A151XB140XC140MM	35W	5000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	4200LM	A151XB140XC140MM	
59	MAZDA-DXR174535W-5K-240V-BL-PH-A151XB140XC140MM	35W	5000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	4200LM	A151XB140XC140MM	
60	MAZDA-DXR174535W-5K-240V-BL-10VDIM-A151XB140XC140MM	35W	5000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	4200LM	A151XB140XC140MM	
61	MAZDA-DXR174535W-6K-240V-BL-ND-A151XB140XC140MM	35W	6000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	4200LM	A151XB140XC140MM	
62	MAZDA-DXR174535W-6K-240V-BL-DA-A151XB140XC140MM	35W	6000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	4200LM	A151XB140XC140MM	
63	MAZDA-DXR174535W-6K-240V-BL-PH-A151XB140XC140MM	35W	6000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	4200LM	A151XB140XC140MM	
64	MAZDA-DXR174535W-6K-240V-BL-10VDIM-A151XB140XC140MM	35W	6000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	4200LM	A151XB140XC140MM	
65	MAZDA-DXR174535W-2.7K-240V-BL-ND-A151XB140XC140MM	35W	2700	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	4200LM	A151XB140XC140MM	
66	MAZDA-DXR174535W-2.7K-240V-BL-DA-A151XB140XC140MM	35W	2700	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	4200LM	A151XB140XC140MM	
67	MAZDA-DXR174535W-2.7K-240V-BL-PH-A151XB140XC140MM	35W	2700	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	4200LM	A151XB140XC140MM	
68	MAZDA-DXR174535W-2.7K-240V-BL-10VDIM-A151XB140XC140MM	35W	2700	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	4200LM	A151XB140XC140MM	
69	MAZDA-DXR174535W-6.5K-240V-BL-ND-A151XB140XC140MM	35W	6500	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	4200LM	A151XB140XC140MM	
70	MAZDA-DXR174535W-6.5K-240V-BL-DA-A151XB140XC140MM	35W	6500	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	4200LM	A151XB140XC140MM	
71	MAZDA-DXR174535W-6.5K-240V-BL-PH-A151XB140XC140MM	35W	6500	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	4200LM	A151XB140XC140MM	
72	MAZDA-DXR174535W-6.5K-240V-BL-10VDIM-A151XB140XC140MM	35W	6500	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	4200LM	A151XB140XC140MM	
73	MAZDA-DXR174550W-3K-240V-BL-ND-A151XB140XC140MM	50W	3000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	6000LM	A151XB140XC140MM	
74	MAZDA-DXR174550W-3K-240V-BL-DA-A151XB140XC140MM	50W	3000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	6000LM	A151XB140XC140MM	
75	MAZDA-DXR174550W-3K-240V-BL-PH-A151XB140XC140MM	50W	3000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	6000LM	A151XB140XC140MM	
76	MAZDA-DXR174550W-3K-240V-BL-10VDIM-A151XB140XC140MM	50W	3000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	6000LM	A151XB140XC140MM	
77	MAZDA-DXR174550W-4K-240V-BL-ND-A151XB140XC140MM	50W	4000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	6000LM	A151XB140XC140MM	
78	MAZDA-DXR174550W-4K-240V-BL-DA-A151XB140XC140MM	50W	4000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	6000LM	A151XB140XC140MM	
79	MAZDA-DXR174550W-4K-240V-BL-PH-A151XB140XC140MM	50W	4000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	6000LM	A151XB140XC140MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
80	MAZDA-DXR174550W-4K-240V-BL-10VDIM-A151XB140XC140MM	50W	4000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	6000LM	A151XB140XC140MM	
81	MAZDA-DXR174550W-5K-240V-BL-ND-A151XB140XC140MM	50W	5000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	6000LM	A151XB140XC140MM	
82	MAZDA-DXR174550W-5K-240V-BL-DA-A151XB140XC140MM	50W	5000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	6000LM	A151XB140XC140MM	
83	MAZDA-DXR174550W-5K-240V-BL-PH-A151XB140XC140MM	50W	5000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	6000LM	A151XB140XC140MM	
84	MAZDA-DXR174550W-5K-240V-BL-10VDIM-A151XB140XC140MM	50W	5000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	6000LM	A151XB140XC140MM	
85	MAZDA-DXR174550W-6K-240V-BL-ND-A151XB140XC140MM	50W	6000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	6000LM	A151XB140XC140MM	
86	MAZDA-DXR174550W-6K-240V-BL-DA-A151XB140XC140MM	50W	6000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	6000LM	A151XB140XC140MM	
87	MAZDA-DXR174550W-6K-240V-BL-PH-A151XB140XC140MM	50W	6000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	6000LM	A151XB140XC140MM	
88	MAZDA-DXR174550W-6K-240V-BL-10VDIM-A151XB140XC140MM	50W	6000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	6000LM	A151XB140XC140MM	
89	MAZDA-DXR174550W-2.7K-240V-BL-ND-A151XB140XC140MM	50W	2700	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	6000LM	A151XB140XC140MM	
90	MAZDA-DXR174550W-2.7K-240V-BL-DA-A151XB140XC140MM	50W	2700	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	6000LM	A151XB140XC140MM	
91	MAZDA-DXR174550W-2.7K-240V-BL-PH-A151XB140XC140MM	50W	2700	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	6000LM	A151XB140XC140MM	
92	MAZDA-DXR174550W-2.7K-240V-BL-10VDIM-A151XB140XC140MM	50W	2700	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	6000LM	A151XB140XC140MM	
93	MAZDA-DXR174550W-6.5K-240V-BL-ND-A151XB140XC140MM	50W	6500	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	6000LM	A151XB140XC140MM	
94	MAZDA-DXR174550W-6.5K-240V-BL-DA-A151XB140XC140MM	50W	6500	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	6000LM	A151XB140XC140MM	
95	MAZDA-DXR174550W-6.5K-240V-BL-PH-A151XB140XC140MM	50W	6500	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	6000LM	A151XB140XC140MM	
96	MAZDA-DXR174550W-6.5K-240V-BL-10VDIM-A151XB140XC140MM	50W	6500	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	6000LM	A151XB140XC140MM	