DATASHEET

GENERATED ON: 26 Nov 2026 | SYS.REF: MAZDA-LED



MAX

MAZDA Model: DXR1745 Downlight

Transform your space with a focused wash of light. This versatile downlight is engineered to deliver high
candela intensity, making it perfect for creating visual emphasis and atmosphere. Whether highlighting
displays, this fixture combines energy e ciency with professional-grade lighting control

ALL AVAILABLE VARIANTS

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
1	MAZDA-DXR174515W-3K-240V-BL-ND-A95XB89XC85MM	15W	3000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A95XB89XC85MM	DIE CAST ALUMINUM	IP54	1800LM	A95XB89XC85MM	
2	MAZDA-DXR174515W-3K-240V-BL-DA-A95XB89XC85MM	15W	3000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A95XB89XC85MM	DIE CAST ALUMINUM	IP54	1800LM	A95XB89XC85MM	
3	MAZDA-DXR174515W-3K-240V-BL-PH-A95XB89XC85MM	15W	3000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A95XB89XC85MM	DIE CAST ALUMINUM	IP54	1800LM	A95XB89XC85MM	
4	MAZDA-DXR174515W-3K-240V-BL-10VDIM-A95XB89XC85MM	15W	3000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A95XB89XC85MM	DIE CAST ALUMINUM	IP54	1800LM	A95XB89XC85MM	
5	MAZDA-DXR174515W-4K-240V-BL-ND-A95XB89XC85MM	15W	4000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A95XB89XC85MM	DIE CAST ALUMINUM	IP54	1800LM	A95XB89XC85MM	
6	MAZDA-DXR174515W-4K-240V-BL-DA-A95XB89XC85MM	15W	4000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A95XB89XC85MM	DIE CAST ALUMINUM	IP54	1800LM	A95XB89XC85MM	
7	MAZDA-DXR174515W-4K-240V-BL-PH-A95XB89XC85MM	15W	4000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A95XB89XC85MM	DIE CAST ALUMINUM	IP54	1800LM	A95XB89XC85MM	
8	MAZDA-DXR174515W-4K-240V-BL-10VDIM-A95XB89XC85MM	15W	4000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A95XB89XC85MM	DIE CAST ALUMINUM	IP54	1800LM	A95XB89XC85MM	
9	MAZDA-DXR174515W-5K-240V-BL-ND-A95XB89XC85MM	15W	5000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A95XB89XC85MM	DIE CAST ALUMINUM	IP54	1800LM	A95XB89XC85MM	
10	MAZDA-DXR174515W-5K-240V-BL-DA-A95XB89XC85MM	15W	5000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A95XB89XC85MM	DIE CAST ALUMINUM	IP54	1800LM	A95XB89XC85MM	
11	MAZDA-DXR174515W-5K-240V-BL-PH-A95XB89XC85MM	15W	5000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A95XB89XC85MM	DIE CAST ALUMINUM	IP54	1800LM	A95XB89XC85MM	
12	MAZDA-DXR174515W-5K-240V-BL-10VDIM-A95XB89XC85MM	15W	5000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A95XB89XC85MM	DIE CAST ALUMINUM	IP54	1800LM	A95XB89XC85MM	
13	MAZDA-DXR174515W-6K-240V-BL-ND-A95XB89XC85MM	15W	6000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A95XB89XC85MM	DIE CAST ALUMINUM	IP54	1800LM	A95XB89XC85MM	
14	MAZDA-DXR174515W-6K-240V-BL-DA-A95XB89XC85MM	15W	6000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A95XB89XC85MM	DIE CAST ALUMINUM	IP54	1800LM	A95XB89XC85MM	
15	MAZDA-DXR174515W-6K-240V-BL-PH-A95XB89XC85MM	15W	6000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A95XB89XC85MM	DIE CAST ALUMINUM	IP54	1800LM	A95XB89XC85MM	
16	MAZDA-DXR174515W-6K-240V-BL-10VDIM-A95XB89XC85MM	15W	6000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A95XB89XC85MM	DIE CAST ALUMINUM	IP54	1800LM	A95XB89XC85MM	
17	MAZDA-DXR174515W-2.7K-240V-BL-ND-A95XB89XC85MM	15W	2700	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A95XB89XC85MM	DIE CAST ALUMINUM	IP54	1800LM	A95XB89XC85MM	
18	MAZDA-DXR174515W-2.7K-240V-BL-DA-A95XB89XC85MM	15W	2700	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A95XB89XC85MM	DIE CAST ALUMINUM	IP54	1800LM	A95XB89XC85MM	
19	MAZDA-DXR174515W-2.7K-240V-BL-PH-A95XB89XC85MM	15W	2700	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A95XB89XC85MM	DIE CAST ALUMINUM	IP54	1800LM	A95XB89XC85MM	

DATASHEET

GENERATED ON: 26 Nov 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
20	MAZDA-DXR174515W-2.7K-240V-BL-10VDIM-A95XB89XC85MM	15W	2700	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A95XB89XC85MM	DIE CAST ALUMINUM	IP54	1800LM	A95XB89XC85MM	
21	MAZDA-DXR174515W-6.5K-240V-BL-ND-A95XB89XC85MM	15W	6500	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A95XB89XC85MM	DIE CAST ALUMINUM	IP54	1800LM	A95XB89XC85MM	
22	MAZDA-DXR174515W-6.5K-240V-BL-DA-A95XB89XC85MM	15W	6500	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A95XB89XC85MM	DIE CAST ALUMINUM	IP54	1800LM	A95XB89XC85MM	
23	MAZDA-DXR174515W-6.5K-240V-BL-PH-A95XB89XC85MM	15W	6500	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A95XB89XC85MM	DIE CAST ALUMINUM	IP54	1800LM	A95XB89XC85MM	
24	MAZDA-DXR174515W-6.5K-240V-BL-10VDIM-A95XB89XC85MM	15W	6500	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A95XB89XC85MM	DIE CAST ALUMINUM	IP54	1800LM	A95XB89XC85MM	
25	MAZDA-DXR174525W-3K-240V-BL-ND-A125XB113XC115MM	25W	3000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A125XB113XC115MM	DIE CAST ALUMINUM	IP54	3000LM	A125XB113XC115MM	
26	MAZDA-DXR174525W-3K-240V-BL-DA-A125XB113XC115MM	25W	3000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A125XB113XC115MM	DIE CAST ALUMINUM	IP54	3000LM	A125XB113XC115MM	
27	MAZDA-DXR174525W-3K-240V-BL-PH-A125XB113XC115MM	25W	3000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A125XB113XC115MM	DIE CAST ALUMINUM	IP54	3000LM	A125XB113XC115MM	
28	MAZDA-DXR174525W-3K-240V-BL-10VDIM-A125XB113XC115MM	25W	3000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A125XB113XC115MM	DIE CAST ALUMINUM	IP54	3000LM	A125XB113XC115MM	
29	MAZDA-DXR174525W-4K-240V-BL-ND-A125XB113XC115MM	25W	4000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A125XB113XC115MM	DIE CAST ALUMINUM	IP54	3000LM	A125XB113XC115MM	
30	MAZDA-DXR174525W-4K-240V-BL-DA-A125XB113XC115MM	25W	4000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A125XB113XC115MM	DIE CAST ALUMINUM	IP54	3000LM	A125XB113XC115MM	
31	MAZDA-DXR174525W-4K-240V-BL-PH-A125XB113XC115MM	25W	4000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A125XB113XC115MM	DIE CAST ALUMINUM	IP54	3000LM	A125XB113XC115MM	
32	MAZDA-DXR174525W-4K-240V-BL-10VDIM-A125XB113XC115MM	25W	4000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A125XB113XC115MM	DIE CAST ALUMINUM	IP54	3000LM	A125XB113XC115MM	
33	MAZDA-DXR174525W-5K-240V-BL-ND-A125XB113XC115MM	25W	5000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A125XB113XC115MM	DIE CAST ALUMINUM	IP54	3000LM	A125XB113XC115MM	
34	MAZDA-DXR174525W-5K-240V-BL-DA-A125XB113XC115MM	25W	5000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A125XB113XC115MM	DIE CAST ALUMINUM	IP54	3000LM	A125XB113XC115MM	
35	MAZDA-DXR174525W-5K-240V-BL-PH-A125XB113XC115MM	25W	5000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A125XB113XC115MM	DIE CAST ALUMINUM	IP54	3000LM	A125XB113XC115MM	
36	MAZDA-DXR174525W-5K-240V-BL-10VDIM-A125XB113XC115MM	25W	5000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A125XB113XC115MM	DIE CAST ALUMINUM	IP54	3000LM	A125XB113XC115MM	
37	MAZDA-DXR174525W-6K-240V-BL-ND-A125XB113XC115MM	25W	6000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A125XB113XC115MM	DIE CAST ALUMINUM	IP54	3000LM	A125XB113XC115MM	
38	MAZDA-DXR174525W-6K-240V-BL-DA-A125XB113XC115MM	25W	6000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A125XB113XC115MM	DIE CAST ALUMINUM	IP54	3000LM	A125XB113XC115MM	
39	MAZDA-DXR174525W-6K-240V-BL-PH-A125XB113XC115MM	25W	6000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A125XB113XC115MM	DIE CAST ALUMINUM	IP54	3000LM	A125XB113XC115MM	
40	MAZDA-DXR174525W-6K-240V-BL-10VDIM-A125XB113XC115MM	25W	6000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A125XB113XC115MM	DIE CAST ALUMINUM	IP54	3000LM	A125XB113XC115MM	
41	MAZDA-DXR174525W-2.7K-240V-BL-ND-A125XB113XC115MM	25W	2700	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A125XB113XC115MM	DIE CAST ALUMINUM	IP54	3000LM	A125XB113XC115MM	
42	MAZDA-DXR174525W-2.7K-240V-BL-DA-A125XB113XC115MM	25W	2700	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A125XB113XC115MM	DIE CAST ALUMINUM	IP54	3000LM	A125XB113XC115MM	
43	MAZDA-DXR174525W-2.7K-240V-BL-PH-A125XB113XC115MM	25W	2700	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A125XB113XC115MM	DIE CAST ALUMINUM	IP54	3000LM	A125XB113XC115MM	
44	MAZDA-DXR174525W-2.7K-240V-BL-10VDIM-A125XB113XC115MM	25W	2700	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A125XB113XC115MM	DIE CAST ALUMINUM	IP54	3000LM	A125XB113XC115MM	
45	MAZDA-DXR174525W-6.5K-240V-BL-ND-A125XB113XC115MM	25W	6500	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A125XB113XC115MM	DIE CAST ALUMINUM	IP54	3000LM	A125XB113XC115MM	
46	MAZDA-DXR174525W-6.5K-240V-BL-DA-A125XB113XC115MM	25W	6500	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A125XB113XC115MM	DIE CAST ALUMINUM	IP54	3000LM	A125XB113XC115MM	
47	MAZDA-DXR174525W-6.5K-240V-BL-PH-A125XB113XC115MM	25W	6500	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A125XB113XC115MM	DIE CAST ALUMINUM	IP54	3000LM	A125XB113XC115MM	
48	MAZDA-DXR174525W-6.5K-240V-BL-10VDIM-A125XB113XC115MM	25W	6500	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A125XB113XC115MM	DIE CAST ALUMINUM	IP54	3000LM	A125XB113XC115MM	
49	MAZDA-DXR174535W-3K-240V-BL-ND-A151XB140XC140MM	35W	3000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	4200LM	A151XB140XC140MM	

DATASHEET

GENERATED ON: 26 Nov 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
50	MAZDA-DXR174535W-3K-240V-BL-DA-A151XB140XC140MM	35W	3000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	4200LM	A151XB140XC140MM	
51	MAZDA-DXR174535W-3K-240V-BL-PH-A151XB140XC140MM	35W	3000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	4200LM	A151XB140XC140MM	
52	MAZDA-DXR174535W-3K-240V-BL-10VDIM-A151XB140XC140MM	35W	3000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	4200LM	A151XB140XC140MM	
53	MAZDA-DXR174535W-4K-240V-BL-ND-A151XB140XC140MM	35W	4000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	4200LM	A151XB140XC140MM	
54	MAZDA-DXR174535W-4K-240V-BL-DA-A151XB140XC140MM	35W	4000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	4200LM	A151XB140XC140MM	
55	MAZDA-DXR174535W-4K-240V-BL-PH-A151XB140XC140MM	35W	4000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	4200LM	A151XB140XC140MM	
56	MAZDA-DXR174535W-4K-240V-BL-10VDIM-A151XB140XC140MM	35W	4000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	4200LM	A151XB140XC140MM	
57	MAZDA-DXR174535W-5K-240V-BL-ND-A151XB140XC140MM	35W	5000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	4200LM	A151XB140XC140MM	
58	MAZDA-DXR174535W-5K-240V-BL-DA-A151XB140XC140MM	35W	5000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	4200LM	A151XB140XC140MM	
59	MAZDA-DXR174535W-5K-240V-BL-PH-A151XB140XC140MM	35W	5000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	4200LM	A151XB140XC140MM	
60	MAZDA-DXR174535W-5K-240V-BL-10VDIM-A151XB140XC140MM	35W	5000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	4200LM	A151XB140XC140MM	
61	MAZDA-DXR174535W-6K-240V-BL-ND-A151XB140XC140MM	35W	6000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	4200LM	A151XB140XC140MM	
62	MAZDA-DXR174535W-6K-240V-BL-DA-A151XB140XC140MM	35W	6000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	4200LM	A151XB140XC140MM	
63	MAZDA-DXR174535W-6K-240V-BL-PH-A151XB140XC140MM	35W	6000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	4200LM	A151XB140XC140MM	
64	MAZDA-DXR174535W-6K-240V-BL-10VDIM-A151XB140XC140MM	35W	6000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	4200LM	A151XB140XC140MM	
65	MAZDA-DXR174535W-2.7K-240V-BL-ND-A151XB140XC140MM	35W	2700	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	4200LM	A151XB140XC140MM	
66	MAZDA-DXR174535W-2.7K-240V-BL-DA-A151XB140XC140MM	35W	2700	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	4200LM	A151XB140XC140MM	
67	MAZDA-DXR174535W-2.7K-240V-BL-PH-A151XB140XC140MM	35W	2700	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	4200LM	A151XB140XC140MM	
68	MAZDA-DXR174535W-2.7K-240V-BL-10VDIM-A151XB140XC140MM	35W	2700	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	4200LM	A151XB140XC140MM	
69	MAZDA-DXR174535W-6.5K-240V-BL-ND-A151XB140XC140MM	35W	6500	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	4200LM	A151XB140XC140MM	
70	MAZDA-DXR174535W-6.5K-240V-BL-DA-A151XB140XC140MM	35W	6500	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	4200LM	A151XB140XC140MM	
71	MAZDA-DXR174535W-6.5K-240V-BL-PH-A151XB140XC140MM	35W	6500	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	4200LM	A151XB140XC140MM	
72	MAZDA-DXR174535W-6.5K-240V-BL-10VDIM-A151XB140XC140MM	35W	6500	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	4200LM	A151XB140XC140MM	
73	MAZDA-DXR174550W-3K-240V-BL-ND-A151XB140XC140MM	50W	3000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	6000LM	A151XB140XC140MM	
74	MAZDA-DXR174550W-3K-240V-BL-DA-A151XB140XC140MM	50W	3000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	6000LM	A151XB140XC140MM	
75	MAZDA-DXR174550W-3K-240V-BL-PH-A151XB140XC140MM	50W	3000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	6000LM	A151XB140XC140MM	
76	MAZDA-DXR174550W-3K-240V-BL-10VDIM-A151XB140XC140MM	50W	3000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	6000LM	A151XB140XC140MM	
77	MAZDA-DXR174550W-4K-240V-BL-ND-A151XB140XC140MM	50W	4000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	6000LM	A151XB140XC140MM	
78	MAZDA-DXR174550W-4K-240V-BL-DA-A151XB140XC140MM	50W	4000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	6000LM	A151XB140XC140MM	
79	MAZDA-DXR174550W-4K-240V-BL-PH-A151XB140XC140MM	50W	4000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	6000LM	A151XB140XC140MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
80	**MAZDA-DXR174550W-4K-240V-BL-10VDIM-A151XB140XC140MM**	50W	4000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	6000LM	A151XB140XC140MM	
81	**MAZDA-DXR174550W-5K-240V-BL-ND-A151XB140XC140MM**	50W	5000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	6000LM	A151XB140XC140MM	
82	**MAZDA-DXR174550W-5K-240V-BL-DA-A151XB140XC140MM**	50W	5000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	6000LM	A151XB140XC140MM	
83	**MAZDA-DXR174550W-5K-240V-BL-PH-A151XB140XC140MM**	50W	5000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	6000LM	A151XB140XC140MM	
84	**MAZDA-DXR174550W-5K-240V-BL-10VDIM-A151XB140XC140MM**	50W	5000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	6000LM	A151XB140XC140MM	
85	**MAZDA-DXR174550W-6K-240V-BL-ND-A151XB140XC140MM**	50W	6000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	6000LM	A151XB140XC140MM	
86	**MAZDA-DXR174550W-6K-240V-BL-DA-A151XB140XC140MM**	50W	6000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	6000LM	A151XB140XC140MM	
87	**MAZDA-DXR174550W-6K-240V-BL-PH-A151XB140XC140MM**	50W	6000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	6000LM	A151XB140XC140MM	
88	**MAZDA-DXR174550W-6K-240V-BL-10VDIM-A151XB140XC140MM**	50W	6000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	6000LM	A151XB140XC140MM	
89	**MAZDA-DXR174550W-2.7K-240V-BL-ND-A151XB140XC140MM**	50W	2700	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	6000LM	A151XB140XC140MM	
90	**MAZDA-DXR174550W-2.7K-240V-BL-DA-A151XB140XC140MM**	50W	2700	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	6000LM	A151XB140XC140MM	
91	**MAZDA-DXR174550W-2.7K-240V-BL-PH-A151XB140XC140MM**	50W	2700	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	6000LM	A151XB140XC140MM	
92	**MAZDA-DXR174550W-2.7K-240V-BL-10VDIM-A151XB140XC140MM**	50W	2700	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	6000LM	A151XB140XC140MM	
93	**MAZDA-DXR174550W-6.5K-240V-BL-ND-A151XB140XC140MM**	50W	6500	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	6000LM	A151XB140XC140MM	
94	**MAZDA-DXR174550W-6.5K-240V-BL-DA-A151XB140XC140MM**	50W	6500	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	6000LM	A151XB140XC140MM	
95	**MAZDA-DXR174550W-6.5K-240V-BL-PH-A151XB140XC140MM**	50W	6500	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	6000LM	A151XB140XC140MM	
96	**MAZDA-DXR174550W-6.5K-240V-BL-10VDIM-A151XB140XC140MM**	50W	6500	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A151XB140XC140MM	DIE CAST ALUMINUM	IP54	6000LM	A151XB140XC140MM	