



NEPTUNE

MAZDA Model: SXR1851 Downlight

Neptune Trimless led spownlight is designed for durability and stylish, Black/White/Gold reflector optional, with deep anti-glare performance. It is ok for installation at the initial design stage or as part of wider refurbishment due to the way in which it is fitted. There is square optional with 15°, 24° and 36° optional, now it is widely used for hotels, supermarkets etc

ALL AVAILABLE VARIANTS

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
1	MAZDA-SXR185107W-3K-240V-WH-ND-A130 X B75 X C100 MM	07W	3000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	700LM	A130 X B75 X C100 MM	
2	MAZDA-SXR185107W-3K-240V-WH-DA-A130 X B75 X C100 MM	07W	3000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	700LM	A130 X B75 X C100 MM	
3	MAZDA-SXR185107W-3K-240V-WH-PH-A130 X B75 X C100 MM	07W	3000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	700LM	A130 X B75 X C100 MM	
4	MAZDA-SXR185107W-3K-240V-WH-10VDIM-A130 X B75 X C100 MM	07W	3000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	700LM	A130 X B75 X C100 MM	
5	MAZDA-SXR185107W-4K-240V-WH-ND-A130 X B75 X C100 MM	07W	4000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	700LM	A130 X B75 X C100 MM	
6	MAZDA-SXR185107W-4K-240V-WH-DA-A130 X B75 X C100 MM	07W	4000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	700LM	A130 X B75 X C100 MM	
7	MAZDA-SXR185107W-4K-240V-WH-PH-A130 X B75 X C100 MM	07W	4000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	700LM	A130 X B75 X C100 MM	
8	MAZDA-SXR185107W-4K-240V-WH-10VDIM-A130 X B75 X C100 MM	07W	4000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	700LM	A130 X B75 X C100 MM	
9	MAZDA-SXR185107W-5K-240V-WH-ND-A130 X B75 X C100 MM	07W	5000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	700LM	A130 X B75 X C100 MM	
10	MAZDA-SXR185107W-5K-240V-WH-DA-A130 X B75 X C100 MM	07W	5000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	700LM	A130 X B75 X C100 MM	
11	MAZDA-SXR185107W-5K-240V-WH-PH-A130 X B75 X C100 MM	07W	5000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	700LM	A130 X B75 X C100 MM	
12	MAZDA-SXR185107W-5K-240V-WH-10VDIM-A130 X B75 X C100 MM	07W	5000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	700LM	A130 X B75 X C100 MM	
13	MAZDA-SXR185107W-6K-240V-WH-ND-A130 X B75 X C100 MM	07W	6000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	700LM	A130 X B75 X C100 MM	
14	MAZDA-SXR185107W-6K-240V-WH-DA-A130 X B75 X C100 MM	07W	6000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	700LM	A130 X B75 X C100 MM	
15	MAZDA-SXR185107W-6K-240V-WH-PH-A130 X B75 X C100 MM	07W	6000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	700LM	A130 X B75 X C100 MM	
16	MAZDA-SXR185107W-6K-240V-WH-10VDIM-A130 X B75 X C100 MM	07W	6000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	700LM	A130 X B75 X C100 MM	
17	MAZDA-SXR185107W-2.7K-240V-WH-ND-A130 X B75 X C100 MM	07W	2700	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	700LM	A130 X B75 X C100 MM	
18	MAZDA-SXR185107W-2.7K-240V-WH-DA-A130 X B75 X C100 MM	07W	2700	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	700LM	A130 X B75 X C100 MM	



DATASHEET

GENERATED ON: 14 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
19	MAZDA-SXR185107W-2.7K-240V-WH-PH-A130 X B75 X C100 MM	07W	2700	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	700LM	A130 X B75 X C100 MM	
20	MAZDA-SXR185107W-2.7K-240V-WH-10VDIM-A130 X B75 X C100 MM	07W	2700	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	700LM	A130 X B75 X C100 MM	
21	MAZDA-SXR185107W-6.5K-240V-WH-ND-A130 X B75 X C100 MM	07W	6500	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	700LM	A130 X B75 X C100 MM	
22	MAZDA-SXR185107W-6.5K-240V-WH-DA-A130 X B75 X C100 MM	07W	6500	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	700LM	A130 X B75 X C100 MM	
23	MAZDA-SXR185107W-6.5K-240V-WH-PH-A130 X B75 X C100 MM	07W	6500	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	700LM	A130 X B75 X C100 MM	
24	MAZDA-SXR185107W-6.5K-240V-WH-10VDIM-A130 X B75 X C100 MM	07W	6500	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	700LM	A130 X B75 X C100 MM	
25	MAZDA-SXR185110W-3K-240V-WH-ND-A130 X B75 X C100 MM	10W	3000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	1000LM	A130 X B75 X C100 MM	
26	MAZDA-SXR185110W-3K-240V-WH-DA-A130 X B75 X C100 MM	10W	3000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	1000LM	A130 X B75 X C100 MM	
27	MAZDA-SXR185110W-3K-240V-WH-PH-A130 X B75 X C100 MM	10W	3000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	1000LM	A130 X B75 X C100 MM	
28	MAZDA-SXR185110W-3K-240V-WH-10VDIM-A130 X B75 X C100 MM	10W	3000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	1000LM	A130 X B75 X C100 MM	
29	MAZDA-SXR185110W-4K-240V-WH-ND-A130 X B75 X C100 MM	10W	4000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	1000LM	A130 X B75 X C100 MM	
30	MAZDA-SXR185110W-4K-240V-WH-DA-A130 X B75 X C100 MM	10W	4000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	1000LM	A130 X B75 X C100 MM	
31	MAZDA-SXR185110W-4K-240V-WH-PH-A130 X B75 X C100 MM	10W	4000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	1000LM	A130 X B75 X C100 MM	
32	MAZDA-SXR185110W-4K-240V-WH-10VDIM-A130 X B75 X C100 MM	10W	4000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	1000LM	A130 X B75 X C100 MM	
33	MAZDA-SXR185110W-5K-240V-WH-ND-A130 X B75 X C100 MM	10W	5000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	1000LM	A130 X B75 X C100 MM	
34	MAZDA-SXR185110W-5K-240V-WH-DA-A130 X B75 X C100 MM	10W	5000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	1000LM	A130 X B75 X C100 MM	
35	MAZDA-SXR185110W-5K-240V-WH-PH-A130 X B75 X C100 MM	10W	5000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	1000LM	A130 X B75 X C100 MM	
36	MAZDA-SXR185110W-5K-240V-WH-10VDIM-A130 X B75 X C100 MM	10W	5000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	1000LM	A130 X B75 X C100 MM	
37	MAZDA-SXR185110W-6K-240V-WH-ND-A130 X B75 X C100 MM	10W	6000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	1000LM	A130 X B75 X C100 MM	
38	MAZDA-SXR185110W-6K-240V-WH-DA-A130 X B75 X C100 MM	10W	6000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	1000LM	A130 X B75 X C100 MM	
39	MAZDA-SXR185110W-6K-240V-WH-PH-A130 X B75 X C100 MM	10W	6000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	1000LM	A130 X B75 X C100 MM	
40	MAZDA-SXR185110W-6K-240V-WH-10VDIM-A130 X B75 X C100 MM	10W	6000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	1000LM	A130 X B75 X C100 MM	
41	MAZDA-SXR185110W-2.7K-240V-WH-ND-A130 X B75 X C100 MM	10W	2700	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	1000LM	A130 X B75 X C100 MM	
42	MAZDA-SXR185110W-2.7K-240V-WH-DA-A130 X B75 X C100 MM	10W	2700	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	1000LM	A130 X B75 X C100 MM	
43	MAZDA-SXR185110W-2.7K-240V-WH-PH-A130 X B75 X C100 MM	10W	2700	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	1000LM	A130 X B75 X C100 MM	
44	MAZDA-SXR185110W-2.7K-240V-WH-10VDIM-A130 X B75 X C100 MM	10W	2700	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	1000LM	A130 X B75 X C100 MM	
45	MAZDA-SXR185110W-6.5K-240V-WH-ND-A130 X B75 X C100 MM	10W	6500	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	1000LM	A130 X B75 X C100 MM	
46	MAZDA-SXR185110W-6.5K-240V-WH-DA-A130 X B75 X C100 MM	10W	6500	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	1000LM	A130 X B75 X C100 MM	



DATASHEET

GENERATED ON: 14 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
47	MAZDA-SXR185110W-6.5K-240V-WH-PH-A130 X B75 X C100 MM	10W	6500	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	1000LM	A130 X B75 X C100 MM	
48	MAZDA-SXR185110W-6.5K-240V-WH-10VDIM-A130 X B75 X C100 MM	10W	6500	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	1000LM	A130 X B75 X C100 MM	
49	MAZDA-SXR185115W-3K-240V-WH-ND-A130 X B75 X C100 MM	15W	3000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	1500LM	A130 X B75 X C100 MM	
50	MAZDA-SXR185115W-3K-240V-WH-DA-A130 X B75 X C100 MM	15W	3000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	1500LM	A130 X B75 X C100 MM	
51	MAZDA-SXR185115W-3K-240V-WH-PH-A130 X B75 X C100 MM	15W	3000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	1500LM	A130 X B75 X C100 MM	
52	MAZDA-SXR185115W-3K-240V-WH-10VDIM-A130 X B75 X C100 MM	15W	3000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	1500LM	A130 X B75 X C100 MM	
53	MAZDA-SXR185115W-4K-240V-WH-ND-A130 X B75 X C100 MM	15W	4000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	1500LM	A130 X B75 X C100 MM	
54	MAZDA-SXR185115W-4K-240V-WH-DA-A130 X B75 X C100 MM	15W	4000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	1500LM	A130 X B75 X C100 MM	
55	MAZDA-SXR185115W-4K-240V-WH-PH-A130 X B75 X C100 MM	15W	4000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	1500LM	A130 X B75 X C100 MM	
56	MAZDA-SXR185115W-4K-240V-WH-10VDIM-A130 X B75 X C100 MM	15W	4000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	1500LM	A130 X B75 X C100 MM	
57	MAZDA-SXR185115W-5K-240V-WH-ND-A130 X B75 X C100 MM	15W	5000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	1500LM	A130 X B75 X C100 MM	
58	MAZDA-SXR185115W-5K-240V-WH-DA-A130 X B75 X C100 MM	15W	5000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	1500LM	A130 X B75 X C100 MM	
59	MAZDA-SXR185115W-5K-240V-WH-PH-A130 X B75 X C100 MM	15W	5000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	1500LM	A130 X B75 X C100 MM	
60	MAZDA-SXR185115W-5K-240V-WH-10VDIM-A130 X B75 X C100 MM	15W	5000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	1500LM	A130 X B75 X C100 MM	
61	MAZDA-SXR185115W-6K-240V-WH-ND-A130 X B75 X C100 MM	15W	6000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	1500LM	A130 X B75 X C100 MM	
62	MAZDA-SXR185115W-6K-240V-WH-DA-A130 X B75 X C100 MM	15W	6000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	1500LM	A130 X B75 X C100 MM	
63	MAZDA-SXR185115W-6K-240V-WH-PH-A130 X B75 X C100 MM	15W	6000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	1500LM	A130 X B75 X C100 MM	
64	MAZDA-SXR185115W-6K-240V-WH-10VDIM-A130 X B75 X C100 MM	15W	6000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	1500LM	A130 X B75 X C100 MM	
65	MAZDA-SXR185115W-2.7K-240V-WH-ND-A130 X B75 X C100 MM	15W	2700	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	1500LM	A130 X B75 X C100 MM	
66	MAZDA-SXR185115W-2.7K-240V-WH-DA-A130 X B75 X C100 MM	15W	2700	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	1500LM	A130 X B75 X C100 MM	
67	MAZDA-SXR185115W-2.7K-240V-WH-PH-A130 X B75 X C100 MM	15W	2700	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	1500LM	A130 X B75 X C100 MM	
68	MAZDA-SXR185115W-2.7K-240V-WH-10VDIM-A130 X B75 X C100 MM	15W	2700	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	1500LM	A130 X B75 X C100 MM	
69	MAZDA-SXR185115W-6.5K-240V-WH-ND-A130 X B75 X C100 MM	15W	6500	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	1500LM	A130 X B75 X C100 MM	
70	MAZDA-SXR185115W-6.5K-240V-WH-DA-A130 X B75 X C100 MM	15W	6500	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	1500LM	A130 X B75 X C100 MM	
71	MAZDA-SXR185115W-6.5K-240V-WH-PH-A130 X B75 X C100 MM	15W	6500	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	1500LM	A130 X B75 X C100 MM	
72	MAZDA-SXR185115W-6.5K-240V-WH-10VDIM-A130 X B75 X C100 MM	15W	6500	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	1500LM	A130 X B75 X C100 MM	
73	MAZDA-SXR185120W-3K-240V-WH-ND-A130 X B75 X C100 MM	20W	3000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	2000LM	A130 X B75 X C100 MM	
74	MAZDA-SXR185120W-3K-240V-WH-DA-A130 X B75 X C100 MM	20W	3000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	2000LM	A130 X B75 X C100 MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	lumen	Dimensions	Price
75	MAZDA-SXR185120W-3K-240V-WH-PH-A130 X B75 X C100 MM	20W	3000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	2000LM	A130 X B75 X C100 MM	
76	MAZDA-SXR185120W-3K-240V-WH-10VDIM-A130 X B75 X C100 MM	20W	3000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	2000LM	A130 X B75 X C100 MM	
77	MAZDA-SXR185120W-4K-240V-WH-ND-A130 X B75 X C100 MM	20W	4000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	2000LM	A130 X B75 X C100 MM	
78	MAZDA-SXR185120W-4K-240V-WH-DA-A130 X B75 X C100 MM	20W	4000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	2000LM	A130 X B75 X C100 MM	
79	MAZDA-SXR185120W-4K-240V-WH-PH-A130 X B75 X C100 MM	20W	4000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	2000LM	A130 X B75 X C100 MM	
80	MAZDA-SXR185120W-4K-240V-WH-10VDIM-A130 X B75 X C100 MM	20W	4000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	2000LM	A130 X B75 X C100 MM	
81	MAZDA-SXR185120W-5K-240V-WH-ND-A130 X B75 X C100 MM	20W	5000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	2000LM	A130 X B75 X C100 MM	
82	MAZDA-SXR185120W-5K-240V-WH-DA-A130 X B75 X C100 MM	20W	5000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	2000LM	A130 X B75 X C100 MM	
83	MAZDA-SXR185120W-5K-240V-WH-PH-A130 X B75 X C100 MM	20W	5000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	2000LM	A130 X B75 X C100 MM	
84	MAZDA-SXR185120W-5K-240V-WH-10VDIM-A130 X B75 X C100 MM	20W	5000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	2000LM	A130 X B75 X C100 MM	
85	MAZDA-SXR185120W-6K-240V-WH-ND-A130 X B75 X C100 MM	20W	6000	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	2000LM	A130 X B75 X C100 MM	
86	MAZDA-SXR185120W-6K-240V-WH-DA-A130 X B75 X C100 MM	20W	6000	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	2000LM	A130 X B75 X C100 MM	
87	MAZDA-SXR185120W-6K-240V-WH-PH-A130 X B75 X C100 MM	20W	6000	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	2000LM	A130 X B75 X C100 MM	
88	MAZDA-SXR185120W-6K-240V-WH-10VDIM-A130 X B75 X C100 MM	20W	6000	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	2000LM	A130 X B75 X C100 MM	
89	MAZDA-SXR185120W-2.7K-240V-WH-ND-A130 X B75 X C100 MM	20W	2700	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	2000LM	A130 X B75 X C100 MM	
90	MAZDA-SXR185120W-2.7K-240V-WH-DA-A130 X B75 X C100 MM	20W	2700	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	2000LM	A130 X B75 X C100 MM	
91	MAZDA-SXR185120W-2.7K-240V-WH-PH-A130 X B75 X C100 MM	20W	2700	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	2000LM	A130 X B75 X C100 MM	
92	MAZDA-SXR185120W-2.7K-240V-WH-10VDIM-A130 X B75 X C100 MM	20W	2700	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	2000LM	A130 X B75 X C100 MM	
93	MAZDA-SXR185120W-6.5K-240V-WH-ND-A130 X B75 X C100 MM	20W	6500	240V	WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	2000LM	A130 X B75 X C100 MM	
94	MAZDA-SXR185120W-6.5K-240V-WH-DA-A130 X B75 X C100 MM	20W	6500	240V	WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	2000LM	A130 X B75 X C100 MM	
95	MAZDA-SXR185120W-6.5K-240V-WH-PH-A130 X B75 X C100 MM	20W	6500	240V	WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	2000LM	A130 X B75 X C100 MM	
96	MAZDA-SXR185120W-6.5K-240V-WH-10VDIM-A130 X B75 X C100 MM	20W	6500	240V	WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A130 X B75 X C100 MM	DIE CAST ALUMINUM	IP54	2000LM	A130 X B75 X C100 MM	