



HONOR

MAZDA Model: IDXR2965 HIGHBAY LIGHT

Honor LED Tri-Proof With hard anodic oxidation finished aluminum housing gets IK10, IP66 protection. With plug-in connecting design, this standard triproof light can be fixed microwave sensor easily and used as micro-wave sensor triproof light. Easy and fast. Every light has two easy fixing connectors on both sides, Customer can fix the cable into the connectors. Suitable for industrial environments

ALL AVAILABLE VARIANTS

#	Code	WATT	CCT	Voltage	Body Color	Control	Emergency Backup	Dimension	Material	IP	Dimensions	Price
1	MAZDA-IDXR296520W-3K-240V-WH-ND-A600 X B90 X C74MM	20W	3000	240V	WHITE	ON - OFF	NON EMERGENCY	A600 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A600 X B90 X C74MM	
2	MAZDA-IDXR296520W-3K-240V-WH-ND-EM-A600 X B90 X C74MM	20W	3000	240V	WHITE	ON - OFF	3 HOUR EMERGENCY BACKUP	A600 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A600 X B90 X C74MM	
3	MAZDA-IDXR296520W-3K-240V-WH-DA-A600 X B90 X C74MM	20W	3000	240V	WHITE	DALI DIMMABLE DRIVER	NON EMERGENCY	A600 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A600 X B90 X C74MM	
4	MAZDA-IDXR296520W-3K-240V-WH-DA-EM-A600 X B90 X C74MM	20W	3000	240V	WHITE	DALI DIMMABLE DRIVER	3 HOUR EMERGENCY BACKUP	A600 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A600 X B90 X C74MM	
5	MAZDA-IDXR296520W-3K-240V-WH-PH-A600 X B90 X C74MM	20W	3000	240V	WHITE	PHASE CUT DIMMABLE	NON EMERGENCY	A600 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A600 X B90 X C74MM	

#	Code	WATT	CCT	Voltage	Body Color	Control	Emergency Backup	Dimension	Material	IP	Dimensions	Price
6	MAZDA-IDXR296520W-3K-240V-WH-PH-EM-A600 X B90 X C74MM	20W	3000	240V	WHITE	PHASE CUT DIMMABLE	3 HOUR EMERGENCY BACKUP	A600 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A600 X B90 X C74MM	
7	MAZDA-IDXR296520W-3K-240V-WH-10VDIM-A600 X B90 X C74MM	20W	3000	240V	WHITE	0/1-10 V DIMMABLE DRIVER	NON EMERGENCY	A600 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A600 X B90 X C74MM	
8	MAZDA-IDXR296520W-3K-240V-WH-10VDIM-EM-A600 X B90 X C74MM	20W	3000	240V	WHITE	0/1-10 V DIMMABLE DRIVER	3 HOUR EMERGENCY BACKUP	A600 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A600 X B90 X C74MM	
9	MAZDA-IDXR296520W-4K-240V-WH-ND-A600 X B90 X C74MM	20W	4000	240V	WHITE	ON - OFF	NON EMERGENCY	A600 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A600 X B90 X C74MM	
10	MAZDA-IDXR296520W-4K-240V-WH-ND-EM-A600 X B90 X C74MM	20W	4000	240V	WHITE	ON - OFF	3 HOUR EMERGENCY BACKUP	A600 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A600 X B90 X C74MM	
11	MAZDA-IDXR296520W-4K-240V-WH-DA-A600 X B90 X C74MM	20W	4000	240V	WHITE	DALI DIMMABLE DRIVER	NON EMERGENCY	A600 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A600 X B90 X C74MM	
12	MAZDA-IDXR296520W-4K-240V-WH-DA-EM-A600 X B90 X C74MM	20W	4000	240V	WHITE	DALI DIMMABLE DRIVER	3 HOUR EMERGENCY BACKUP	A600 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A600 X B90 X C74MM	
13	MAZDA-IDXR296520W-4K-240V-WH-PH-A600 X B90 X C74MM	20W	4000	240V	WHITE	PHASE CUT DIMMABLE	NON EMERGENCY	A600 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A600 X B90 X C74MM	

#	Code	WATT	CCT	Voltage	Body Color	Control	Emergency Backup	Dimension	Material	IP	Dimensions	Price
14	MAZDA-IDXR296520W-4K-240V-WH-PH-EM-A600 X B90 X C74MM	20W	4000	240V	WHITE	PHASE CUT DIMMABLE	3 HOUR EMERGENCY BACKUP	A600 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A600 X B90 X C74MM	
15	MAZDA-IDXR296520W-4K-240V-WH-10VDIM-A600 X B90 X C74MM	20W	4000	240V	WHITE	0/1-10 V DIMMABLE DRIVER	NON EMERGENCY	A600 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A600 X B90 X C74MM	
16	MAZDA-IDXR296520W-4K-240V-WH-10VDIM-EM-A600 X B90 X C74MM	20W	4000	240V	WHITE	0/1-10 V DIMMABLE DRIVER	3 HOUR EMERGENCY BACKUP	A600 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A600 X B90 X C74MM	
17	MAZDA-IDXR296520W-5K-240V-WH-ND-A600 X B90 X C74MM	20W	5000	240V	WHITE	ON - OFF	NON EMERGENCY	A600 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A600 X B90 X C74MM	
18	MAZDA-IDXR296520W-5K-240V-WH-ND-EM-A600 X B90 X C74MM	20W	5000	240V	WHITE	ON - OFF	3 HOUR EMERGENCY BACKUP	A600 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A600 X B90 X C74MM	
19	MAZDA-IDXR296520W-5K-240V-WH-DA-A600 X B90 X C74MM	20W	5000	240V	WHITE	DALI DIMMABLE DRIVER	NON EMERGENCY	A600 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A600 X B90 X C74MM	
20	MAZDA-IDXR296520W-5K-240V-WH-DA-EM-A600 X B90 X C74MM	20W	5000	240V	WHITE	DALI DIMMABLE DRIVER	3 HOUR EMERGENCY BACKUP	A600 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A600 X B90 X C74MM	
21	MAZDA-IDXR296520W-5K-240V-WH-PH-A600 X B90 X C74MM	20W	5000	240V	WHITE	PHASE CUT DIMMABLE	NON EMERGENCY	A600 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A600 X B90 X C74MM	

#	Code	WATT	CCT	Voltage	Body Color	Control	Emergency Backup	Dimension	Material	IP	Dimensions	Price
22	MAZDA-IDXR296520W-5K-240V-WH-PH-EM-A600 X B90 X C74MM	20W	5000	240V	WHITE	PHASE CUT DIMMABLE	3 HOUR EMERGENCY BACKUP	A600 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A600 X B90 X C74MM	
23	MAZDA-IDXR296520W-5K-240V-WH-10VDIM-A600 X B90 X C74MM	20W	5000	240V	WHITE	0/1-10 V DIMMABLE DRIVER	NON EMERGENCY	A600 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A600 X B90 X C74MM	
24	MAZDA-IDXR296520W-5K-240V-WH-10VDIM-EM-A600 X B90 X C74MM	20W	5000	240V	WHITE	0/1-10 V DIMMABLE DRIVER	3 HOUR EMERGENCY BACKUP	A600 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A600 X B90 X C74MM	
25	MAZDA-IDXR296520W-6K-240V-WH-ND-A600 X B90 X C74MM	20W	6000	240V	WHITE	ON - OFF	NON EMERGENCY	A600 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A600 X B90 X C74MM	
26	MAZDA-IDXR296520W-6K-240V-WH-ND-EM-A600 X B90 X C74MM	20W	6000	240V	WHITE	ON - OFF	3 HOUR EMERGENCY BACKUP	A600 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A600 X B90 X C74MM	
27	MAZDA-IDXR296520W-6K-240V-WH-DA-A600 X B90 X C74MM	20W	6000	240V	WHITE	DALI DIMMABLE DRIVER	NON EMERGENCY	A600 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A600 X B90 X C74MM	
28	MAZDA-IDXR296520W-6K-240V-WH-DA-EM-A600 X B90 X C74MM	20W	6000	240V	WHITE	DALI DIMMABLE DRIVER	3 HOUR EMERGENCY BACKUP	A600 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A600 X B90 X C74MM	
29	MAZDA-IDXR296520W-6K-240V-WH-PH-A600 X B90 X C74MM	20W	6000	240V	WHITE	PHASE CUT DIMMABLE	NON EMERGENCY	A600 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A600 X B90 X C74MM	

#	Code	WATT	CCT	Voltage	Body Color	Control	Emergency Backup	Dimension	Material	IP	Dimensions	Price
30	MAZDA-IDXR296520W-6K-240V-WH-PH-EM-A600 X B90 X C74MM	20W	6000	240V	WHITE	PHASE CUT DIMMABLE	3 HOUR EMERGENCY BACKUP	A600 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A600 X B90 X C74MM	
31	MAZDA-IDXR296520W-6K-240V-WH-10VDIM-A600 X B90 X C74MM	20W	6000	240V	WHITE	0/1-10 V DIMMABLE DRIVER	NON EMERGENCY	A600 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A600 X B90 X C74MM	
32	MAZDA-IDXR296520W-6K-240V-WH-10VDIM-EM-A600 X B90 X C74MM	20W	6000	240V	WHITE	0/1-10 V DIMMABLE DRIVER	3 HOUR EMERGENCY BACKUP	A600 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A600 X B90 X C74MM	
33	MAZDA-IDXR296520W-2.7K-240V-WH-ND-A600 X B90 X C74MM	20W	2700	240V	WHITE	ON - OFF	NON EMERGENCY	A600 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A600 X B90 X C74MM	
34	MAZDA-IDXR296520W-2.7K-240V-WH-ND-EM-A600 X B90 X C74MM	20W	2700	240V	WHITE	ON - OFF	3 HOUR EMERGENCY BACKUP	A600 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A600 X B90 X C74MM	
35	MAZDA-IDXR296520W-2.7K-240V-WH-DA-A600 X B90 X C74MM	20W	2700	240V	WHITE	DALI DIMMABLE DRIVER	NON EMERGENCY	A600 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A600 X B90 X C74MM	
36	MAZDA-IDXR296520W-2.7K-240V-WH-DA-EM-A600 X B90 X C74MM	20W	2700	240V	WHITE	DALI DIMMABLE DRIVER	3 HOUR EMERGENCY BACKUP	A600 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A600 X B90 X C74MM	
37	MAZDA-IDXR296520W-2.7K-240V-WH-PH-A600 X B90 X C74MM	20W	2700	240V	WHITE	PHASE CUT DIMMABLE	NON EMERGENCY	A600 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A600 X B90 X C74MM	

#	Code	WATT	CCT	Voltage	Body Color	Control	Emergency Backup	Dimension	Material	IP	Dimensions	Price
38	MAZDA-IDXR296520W-2.7K-240V-WH-PH-EM-A600 X B90 X C74MM	20W	2700	240V	WHITE	PHASE CUT DIMMABLE	3 HOUR EMERGENCY BACKUP	A600 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A600 X B90 X C74MM	
39	MAZDA-IDXR296520W-2.7K-240V-WH-10VDIM-A600 X B90 X C74MM	20W	2700	240V	WHITE	0/1-10 V DIMMABLE DRIVER	NON EMERGENCY	A600 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A600 X B90 X C74MM	
40	MAZDA-IDXR296520W-2.7K-240V-WH-10VDIM-EM-A600 X B90 X C74MM	20W	2700	240V	WHITE	0/1-10 V DIMMABLE DRIVER	3 HOUR EMERGENCY BACKUP	A600 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A600 X B90 X C74MM	
41	MAZDA-IDXR296520W-6.5K-240V-WH-ND-A600 X B90 X C74MM	20W	6500	240V	WHITE	ON - OFF	NON EMERGENCY	A600 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A600 X B90 X C74MM	
42	MAZDA-IDXR296520W-6.5K-240V-WH-ND-EM-A600 X B90 X C74MM	20W	6500	240V	WHITE	ON - OFF	3 HOUR EMERGENCY BACKUP	A600 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A600 X B90 X C74MM	
43	MAZDA-IDXR296520W-6.5K-240V-WH-DA-A600 X B90 X C74MM	20W	6500	240V	WHITE	DALI DIMMABLE DRIVER	NON EMERGENCY	A600 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A600 X B90 X C74MM	
44	MAZDA-IDXR296520W-6.5K-240V-WH-DA-EM-A600 X B90 X C74MM	20W	6500	240V	WHITE	DALI DIMMABLE DRIVER	3 HOUR EMERGENCY BACKUP	A600 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A600 X B90 X C74MM	
45	MAZDA-IDXR296520W-6.5K-240V-WH-PH-A600 X B90 X C74MM	20W	6500	240V	WHITE	PHASE CUT DIMMABLE	NON EMERGENCY	A600 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A600 X B90 X C74MM	

#	Code	WATT	CCT	Voltage	Body Color	Control	Emergency Backup	Dimension	Material	IP	Dimensions	Price
46	MAZDA-IDXR296520W-6.5K-240V-WH-PH-EM-A600 X B90 X C74MM	20W	6500	240V	WHITE	PHASE CUT DIMMABLE	3 HOUR EMERGENCY BACKUP	A600 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A600 X B90 X C74MM	
47	MAZDA-IDXR296520W-6.5K-240V-WH-10VDIM-A600 X B90 X C74MM	20W	6500	240V	WHITE	0/1-10 V DIMMABLE DRIVER	NON EMERGENCY	A600 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A600 X B90 X C74MM	
48	MAZDA-IDXR296520W-6.5K-240V-WH-10VDIM-EM-A600 X B90 X C74MM	20W	6500	240V	WHITE	0/1-10 V DIMMABLE DRIVER	3 HOUR EMERGENCY BACKUP	A600 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A600 X B90 X C74MM	
49	MAZDA-IDXR296540W-3K-240V-WH-ND-A1200 X B90 X C74MM	40W	3000	240V	WHITE	ON - OFF	NON EMERGENCY	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
50	MAZDA-IDXR296540W-3K-240V-WH-ND-EM-A1200 X B90 X C74MM	40W	3000	240V	WHITE	ON - OFF	3 HOUR EMERGENCY BACKUP	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
51	MAZDA-IDXR296540W-3K-240V-WH-DA-A1200 X B90 X C74MM	40W	3000	240V	WHITE	DALI DIMMABLE DRIVER	NON EMERGENCY	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
52	MAZDA-IDXR296540W-3K-240V-WH-DA-EM-A1200 X B90 X C74MM	40W	3000	240V	WHITE	DALI DIMMABLE DRIVER	3 HOUR EMERGENCY BACKUP	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
53	MAZDA-IDXR296540W-3K-240V-WH-PH-A1200 X B90 X C74MM	40W	3000	240V	WHITE	PHASE CUT DIMMABLE	NON EMERGENCY	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	



DATASHEET

GENERATED ON: 15 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Control	Emergency Backup	Dimension	Material	IP	Dimensions	Price
54	MAZDA-IDXR296540W-3K-240V-WH-PH-EM-A1200 X B90 X C74MM	40W	3000	240V	WHITE	PHASE CUT DIMMABLE	3 HOUR EMERGENCY BACKUP	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
55	MAZDA-IDXR296540W-3K-240V-WH-10VDIM-A1200 X B90 X C74MM	40W	3000	240V	WHITE	0/1-10 V DIMMABLE DRIVER	NON EMERGENCY	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
56	MAZDA-IDXR296540W-3K-240V-WH-10VDIM-EM-A1200 X B90 X C74MM	40W	3000	240V	WHITE	0/1-10 V DIMMABLE DRIVER	3 HOUR EMERGENCY BACKUP	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
57	MAZDA-IDXR296540W-4K-240V-WH-ND-A1200 X B90 X C74MM	40W	4000	240V	WHITE	ON - OFF	NON EMERGENCY	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
58	MAZDA-IDXR296540W-4K-240V-WH-ND-EM-A1200 X B90 X C74MM	40W	4000	240V	WHITE	ON - OFF	3 HOUR EMERGENCY BACKUP	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
59	MAZDA-IDXR296540W-4K-240V-WH-DA-A1200 X B90 X C74MM	40W	4000	240V	WHITE	DALI DIMMABLE DRIVER	NON EMERGENCY	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
60	MAZDA-IDXR296540W-4K-240V-WH-DA-EM-A1200 X B90 X C74MM	40W	4000	240V	WHITE	DALI DIMMABLE DRIVER	3 HOUR EMERGENCY BACKUP	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
61	MAZDA-IDXR296540W-4K-240V-WH-PH-A1200 X B90 X C74MM	40W	4000	240V	WHITE	PHASE CUT DIMMABLE	NON EMERGENCY	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	

#	Code	WATT	CCT	Voltage	Body Color	Control	Emergency Backup	Dimension	Material	IP	Dimensions	Price
62	MAZDA-IDXR296540W-4K-240V-WH-PH-EM-A1200 X B90 X C74MM	40W	4000	240V	WHITE	PHASE CUT DIMMABLE	3 HOUR EMERGENCY BACKUP	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
63	MAZDA-IDXR296540W-4K-240V-WH-10VDIM-A1200 X B90 X C74MM	40W	4000	240V	WHITE	0/1-10 V DIMMABLE DRIVER	NON EMERGENCY	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
64	MAZDA-IDXR296540W-4K-240V-WH-10VDIM-EM-A1200 X B90 X C74MM	40W	4000	240V	WHITE	0/1-10 V DIMMABLE DRIVER	3 HOUR EMERGENCY BACKUP	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
65	MAZDA-IDXR296540W-5K-240V-WH-ND-A1200 X B90 X C74MM	40W	5000	240V	WHITE	ON - OFF	NON EMERGENCY	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
66	MAZDA-IDXR296540W-5K-240V-WH-ND-EM-A1200 X B90 X C74MM	40W	5000	240V	WHITE	ON - OFF	3 HOUR EMERGENCY BACKUP	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
67	MAZDA-IDXR296540W-5K-240V-WH-DA-A1200 X B90 X C74MM	40W	5000	240V	WHITE	DALI DIMMABLE DRIVER	NON EMERGENCY	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
68	MAZDA-IDXR296540W-5K-240V-WH-DA-EM-A1200 X B90 X C74MM	40W	5000	240V	WHITE	DALI DIMMABLE DRIVER	3 HOUR EMERGENCY BACKUP	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
69	MAZDA-IDXR296540W-5K-240V-WH-PH-A1200 X B90 X C74MM	40W	5000	240V	WHITE	PHASE CUT DIMMABLE	NON EMERGENCY	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	



DATASHEET

GENERATED ON: 15 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Control	Emergency Backup	Dimension	Material	IP	Dimensions	Price
70	MAZDA-IDXR296540W-5K-240V-WH-PH-EM-A1200 X B90 X C74MM	40W	5000	240V	WHITE	PHASE CUT DIMMABLE	3 HOUR EMERGENCY BACKUP	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
71	MAZDA-IDXR296540W-5K-240V-WH-10VDIM-A1200 X B90 X C74MM	40W	5000	240V	WHITE	0/1-10 V DIMMABLE DRIVER	NON EMERGENCY	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
72	MAZDA-IDXR296540W-5K-240V-WH-10VDIM-EM-A1200 X B90 X C74MM	40W	5000	240V	WHITE	0/1-10 V DIMMABLE DRIVER	3 HOUR EMERGENCY BACKUP	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
73	MAZDA-IDXR296540W-6K-240V-WH-ND-A1200 X B90 X C74MM	40W	6000	240V	WHITE	ON - OFF	NON EMERGENCY	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
74	MAZDA-IDXR296540W-6K-240V-WH-ND-EM-A1200 X B90 X C74MM	40W	6000	240V	WHITE	ON - OFF	3 HOUR EMERGENCY BACKUP	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
75	MAZDA-IDXR296540W-6K-240V-WH-DA-A1200 X B90 X C74MM	40W	6000	240V	WHITE	DALI DIMMABLE DRIVER	NON EMERGENCY	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
76	MAZDA-IDXR296540W-6K-240V-WH-DA-EM-A1200 X B90 X C74MM	40W	6000	240V	WHITE	DALI DIMMABLE DRIVER	3 HOUR EMERGENCY BACKUP	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
77	MAZDA-IDXR296540W-6K-240V-WH-PH-A1200 X B90 X C74MM	40W	6000	240V	WHITE	PHASE CUT DIMMABLE	NON EMERGENCY	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	



DATASHEET

GENERATED ON: 15 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Control	Emergency Backup	Dimension	Material	IP	Dimensions	Price
78	MAZDA-IDXR296540W-6K-240V-WH-PH-EM-A1200 X B90 X C74MM	40W	6000	240V	WHITE	PHASE CUT DIMMABLE	3 HOUR EMERGENCY BACKUP	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
79	MAZDA-IDXR296540W-6K-240V-WH-10VDIM-A1200 X B90 X C74MM	40W	6000	240V	WHITE	0/1-10 V DIMMABLE DRIVER	NON EMERGENCY	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
80	MAZDA-IDXR296540W-6K-240V-WH-10VDIM-EM-A1200 X B90 X C74MM	40W	6000	240V	WHITE	0/1-10 V DIMMABLE DRIVER	3 HOUR EMERGENCY BACKUP	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
81	MAZDA-IDXR296540W-2.7K-240V-WH-ND-A1200 X B90 X C74MM	40W	2700	240V	WHITE	ON - OFF	NON EMERGENCY	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
82	MAZDA-IDXR296540W-2.7K-240V-WH-ND-EM-A1200 X B90 X C74MM	40W	2700	240V	WHITE	ON - OFF	3 HOUR EMERGENCY BACKUP	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
83	MAZDA-IDXR296540W-2.7K-240V-WH-DA-A1200 X B90 X C74MM	40W	2700	240V	WHITE	DALI DIMMABLE DRIVER	NON EMERGENCY	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
84	MAZDA-IDXR296540W-2.7K-240V-WH-DA-EM-A1200 X B90 X C74MM	40W	2700	240V	WHITE	DALI DIMMABLE DRIVER	3 HOUR EMERGENCY BACKUP	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
85	MAZDA-IDXR296540W-2.7K-240V-WH-PH-A1200 X B90 X C74MM	40W	2700	240V	WHITE	PHASE CUT DIMMABLE	NON EMERGENCY	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	

#	Code	WATT	CCT	Voltage	Body Color	Control	Emergency Backup	Dimension	Material	IP	Dimensions	Price
86	MAZDA-IDXR296540W-2.7K-240V-WH-PH-EM-A1200 X B90 X C74MM	40W	2700	240V	WHITE	PHASE CUT DIMMABLE	3 HOUR EMERGENCY BACKUP	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
87	MAZDA-IDXR296540W-2.7K-240V-WH-10VDIM-A1200 X B90 X C74MM	40W	2700	240V	WHITE	0/1-10 V DIMMABLE DRIVER	NON EMERGENCY	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
88	MAZDA-IDXR296540W-2.7K-240V-WH-10VDIM-EM-A1200 X B90 X C74MM	40W	2700	240V	WHITE	0/1-10 V DIMMABLE DRIVER	3 HOUR EMERGENCY BACKUP	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
89	MAZDA-IDXR296540W-6.5K-240V-WH-ND-A1200 X B90 X C74MM	40W	6500	240V	WHITE	ON - OFF	NON EMERGENCY	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
90	MAZDA-IDXR296540W-6.5K-240V-WH-ND-EM-A1200 X B90 X C74MM	40W	6500	240V	WHITE	ON - OFF	3 HOUR EMERGENCY BACKUP	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
91	MAZDA-IDXR296540W-6.5K-240V-WH-DA-A1200 X B90 X C74MM	40W	6500	240V	WHITE	DALI DIMMABLE DRIVER	NON EMERGENCY	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
92	MAZDA-IDXR296540W-6.5K-240V-WH-DA-EM-A1200 X B90 X C74MM	40W	6500	240V	WHITE	DALI DIMMABLE DRIVER	3 HOUR EMERGENCY BACKUP	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
93	MAZDA-IDXR296540W-6.5K-240V-WH-PH-A1200 X B90 X C74MM	40W	6500	240V	WHITE	PHASE CUT DIMMABLE	NON EMERGENCY	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	



DATASHEET

GENERATED ON: 15 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Control	Emergency Backup	Dimension	Material	IP	Dimensions	Price
94	MAZDA-IDXR296540W-6.5K-240V-WH-PH-EM-A1200 X B90 X C74MM	40W	6500	240V	WHITE	PHASE CUT	3 HOUR EMERGENCY BACKUP	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
						DIMMABLE						
95	MAZDA-IDXR296540W-6.5K-240V-WH-10VDIM-A1200 X B90 X C74MM	40W	6500	240V	WHITE	0/1-10 V DIMMABLE DRIVER	NON EMERGENCY	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
96	MAZDA-IDXR296540W-6.5K-240V-WH-10VDIM-EM-A1200 X B90 X C74MM	40W	6500	240V	WHITE	0/1-10 V DIMMABLE DRIVER	3 HOUR EMERGENCY BACKUP	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
97	MAZDA-IDXR296560W-3K-240V-WH-ND-A1200 X B90 X C74MM	60W	3000	240V	WHITE	ON - OFF	NON EMERGENCY	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
98	MAZDA-IDXR296560W-3K-240V-WH-ND-EM-A1200 X B90 X C74MM	60W	3000	240V	WHITE	ON - OFF	3 HOUR EMERGENCY BACKUP	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
99	MAZDA-IDXR296560W-3K-240V-WH-DA-A1200 X B90 X C74MM	60W	3000	240V	WHITE	DALI DIMMABLE DRIVER	NON EMERGENCY	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
100	MAZDA-IDXR296560W-3K-240V-WH-DA-EM-A1200 X B90 X C74MM	60W	3000	240V	WHITE	DALI DIMMABLE DRIVER	3 HOUR EMERGENCY BACKUP	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
101	MAZDA-IDXR296560W-3K-240V-WH-PH-A1200 X B90 X C74MM	60W	3000	240V	WHITE	PHASE CUT	NON EMERGENCY	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
						DIMMABLE						



DATASHEET

GENERATED ON: 15 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Control	Emergency Backup	Dimension	Material	IP	Dimensions	Price
102	MAZDA-IDXR296560W-3K-240V-WH-PH-EM-A1200 X B90 X C74MM	60W	3000	240V	WHITE	PHASE CUT DIMMABLE	3 HOUR EMERGENCY BACKUP	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
103	MAZDA-IDXR296560W-3K-240V-WH-10VDIM-A1200 X B90 X C74MM	60W	3000	240V	WHITE	0/1-10 V DIMMABLE DRIVER	NON EMERGENCY	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
104	MAZDA-IDXR296560W-3K-240V-WH-10VDIM-EM-A1200 X B90 X C74MM	60W	3000	240V	WHITE	0/1-10 V DIMMABLE DRIVER	3 HOUR EMERGENCY BACKUP	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
105	MAZDA-IDXR296560W-4K-240V-WH-ND-A1200 X B90 X C74MM	60W	4000	240V	WHITE	ON - OFF	NON EMERGENCY	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
106	MAZDA-IDXR296560W-4K-240V-WH-ND-EM-A1200 X B90 X C74MM	60W	4000	240V	WHITE	ON - OFF	3 HOUR EMERGENCY BACKUP	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
107	MAZDA-IDXR296560W-4K-240V-WH-DA-A1200 X B90 X C74MM	60W	4000	240V	WHITE	DALI DIMMABLE DRIVER	NON EMERGENCY	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
108	MAZDA-IDXR296560W-4K-240V-WH-DA-EM-A1200 X B90 X C74MM	60W	4000	240V	WHITE	DALI DIMMABLE DRIVER	3 HOUR EMERGENCY BACKUP	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
109	MAZDA-IDXR296560W-4K-240V-WH-PH-A1200 X B90 X C74MM	60W	4000	240V	WHITE	PHASE CUT DIMMABLE	NON EMERGENCY	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	



DATASHEET

GENERATED ON: 15 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Control	Emergency Backup	Dimension	Material	IP	Dimensions	Price
110	MAZDA-IDXR296560W-4K-240V-WH-PH-EM-A1200 X B90 X C74MM	60W	4000	240V	WHITE	PHASE CUT DIMMABLE	3 HOUR EMERGENCY BACKUP	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
111	MAZDA-IDXR296560W-4K-240V-WH-10VDIM-A1200 X B90 X C74MM	60W	4000	240V	WHITE	0/1-10 V DIMMABLE DRIVER	NON EMERGENCY	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
112	MAZDA-IDXR296560W-4K-240V-WH-10VDIM-EM-A1200 X B90 X C74MM	60W	4000	240V	WHITE	0/1-10 V DIMMABLE DRIVER	3 HOUR EMERGENCY BACKUP	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
113	MAZDA-IDXR296560W-5K-240V-WH-ND-A1200 X B90 X C74MM	60W	5000	240V	WHITE	ON - OFF	NON EMERGENCY	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
114	MAZDA-IDXR296560W-5K-240V-WH-ND-EM-A1200 X B90 X C74MM	60W	5000	240V	WHITE	ON - OFF	3 HOUR EMERGENCY BACKUP	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
115	MAZDA-IDXR296560W-5K-240V-WH-DA-A1200 X B90 X C74MM	60W	5000	240V	WHITE	DALI DIMMABLE DRIVER	NON EMERGENCY	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
116	MAZDA-IDXR296560W-5K-240V-WH-DA-EM-A1200 X B90 X C74MM	60W	5000	240V	WHITE	DALI DIMMABLE DRIVER	3 HOUR EMERGENCY BACKUP	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
117	MAZDA-IDXR296560W-5K-240V-WH-PH-A1200 X B90 X C74MM	60W	5000	240V	WHITE	PHASE CUT DIMMABLE	NON EMERGENCY	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	

#	Code	WATT	CCT	Voltage	Body Color	Control	Emergency Backup	Dimension	Material	IP	Dimensions	Price
118	MAZDA-IDXR296560W-5K-240V-WH-PH-EM-A1200 X B90 X C74MM	60W	5000	240V	WHITE	PHASE CUT DIMMABLE	3 HOUR EMERGENCY BACKUP	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
119	MAZDA-IDXR296560W-5K-240V-WH-10VDIM-A1200 X B90 X C74MM	60W	5000	240V	WHITE	0/1-10 V DIMMABLE DRIVER	NON EMERGENCY	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
120	MAZDA-IDXR296560W-5K-240V-WH-10VDIM-EM-A1200 X B90 X C74MM	60W	5000	240V	WHITE	0/1-10 V DIMMABLE DRIVER	3 HOUR EMERGENCY BACKUP	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
121	MAZDA-IDXR296560W-6K-240V-WH-ND-A1200 X B90 X C74MM	60W	6000	240V	WHITE	ON - OFF	NON EMERGENCY	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
122	MAZDA-IDXR296560W-6K-240V-WH-ND-EM-A1200 X B90 X C74MM	60W	6000	240V	WHITE	ON - OFF	3 HOUR EMERGENCY BACKUP	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
123	MAZDA-IDXR296560W-6K-240V-WH-DA-A1200 X B90 X C74MM	60W	6000	240V	WHITE	DALI DIMMABLE DRIVER	NON EMERGENCY	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
124	MAZDA-IDXR296560W-6K-240V-WH-DA-EM-A1200 X B90 X C74MM	60W	6000	240V	WHITE	DALI DIMMABLE DRIVER	3 HOUR EMERGENCY BACKUP	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
125	MAZDA-IDXR296560W-6K-240V-WH-PH-A1200 X B90 X C74MM	60W	6000	240V	WHITE	PHASE CUT DIMMABLE	NON EMERGENCY	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	



DATASHEET

GENERATED ON: 15 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Control	Emergency Backup	Dimension	Material	IP	Dimensions	Price
126	MAZDA-IDXR296560W-6K-240V-WH-PH-EM-A1200 X B90 X C74MM	60W	6000	240V	WHITE	PHASE CUT DIMMABLE	3 HOUR EMERGENCY BACKUP	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
127	MAZDA-IDXR296560W-6K-240V-WH-10VDIM-A1200 X B90 X C74MM	60W	6000	240V	WHITE	0/1-10 V DIMMABLE DRIVER	NON EMERGENCY	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
128	MAZDA-IDXR296560W-6K-240V-WH-10VDIM-EM-A1200 X B90 X C74MM	60W	6000	240V	WHITE	0/1-10 V DIMMABLE DRIVER	3 HOUR EMERGENCY BACKUP	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
129	MAZDA-IDXR296560W-2.7K-240V-WH-ND-A1200 X B90 X C74MM	60W	2700	240V	WHITE	ON - OFF	NON EMERGENCY	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
130	MAZDA-IDXR296560W-2.7K-240V-WH-ND-EM-A1200 X B90 X C74MM	60W	2700	240V	WHITE	ON - OFF	3 HOUR EMERGENCY BACKUP	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
131	MAZDA-IDXR296560W-2.7K-240V-WH-DA-A1200 X B90 X C74MM	60W	2700	240V	WHITE	DALI DIMMABLE DRIVER	NON EMERGENCY	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
132	MAZDA-IDXR296560W-2.7K-240V-WH-DA-EM-A1200 X B90 X C74MM	60W	2700	240V	WHITE	DALI DIMMABLE DRIVER	3 HOUR EMERGENCY BACKUP	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
133	MAZDA-IDXR296560W-2.7K-240V-WH-PH-A1200 X B90 X C74MM	60W	2700	240V	WHITE	PHASE CUT DIMMABLE	NON EMERGENCY	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	



DATASHEET

GENERATED ON: 15 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Control	Emergency Backup	Dimension	Material	IP	Dimensions	Price
134	MAZDA-IDXR296560W-2.7K-240V-WH-PH-EM-A1200 X B90 X C74MM	60W	2700	240V	WHITE	PHASE CUT DIMMABLE	3 HOUR EMERGENCY BACKUP	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
135	MAZDA-IDXR296560W-2.7K-240V-WH-10VDIM-A1200 X B90 X C74MM	60W	2700	240V	WHITE	0/1-10 V DIMMABLE DRIVER	NON EMERGENCY	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
136	MAZDA-IDXR296560W-2.7K-240V-WH-10VDIM-EM-A1200 X B90 X C74MM	60W	2700	240V	WHITE	0/1-10 V DIMMABLE DRIVER	3 HOUR EMERGENCY BACKUP	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
137	MAZDA-IDXR296560W-6.5K-240V-WH-ND-A1200 X B90 X C74MM	60W	6500	240V	WHITE	ON - OFF	NON EMERGENCY	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
138	MAZDA-IDXR296560W-6.5K-240V-WH-ND-EM-A1200 X B90 X C74MM	60W	6500	240V	WHITE	ON - OFF	3 HOUR EMERGENCY BACKUP	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
139	MAZDA-IDXR296560W-6.5K-240V-WH-DA-A1200 X B90 X C74MM	60W	6500	240V	WHITE	DALI DIMMABLE DRIVER	NON EMERGENCY	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
140	MAZDA-IDXR296560W-6.5K-240V-WH-DA-EM-A1200 X B90 X C74MM	60W	6500	240V	WHITE	DALI DIMMABLE DRIVER	3 HOUR EMERGENCY BACKUP	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
141	MAZDA-IDXR296560W-6.5K-240V-WH-PH-A1200 X B90 X C74MM	60W	6500	240V	WHITE	PHASE CUT DIMMABLE	NON EMERGENCY	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	



DATASHEET

GENERATED ON: 15 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Control	Emergency Backup	Dimension	Material	IP	Dimensions	Price
142	MAZDA-IDXR296560W-6.5K-240V-WH-PH-EM-A1200 X B90 X C74MM	60W	6500	240V	WHITE	PHASE CUT DIMMABLE	3 HOUR EMERGENCY BACKUP	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
143	MAZDA-IDXR296560W-6.5K-240V-WH-10VDIM-A1200 X B90 X C74MM	60W	6500	240V	WHITE	0/1-10 V DIMMABLE DRIVER	NON EMERGENCY	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
144	MAZDA-IDXR296560W-6.5K-240V-WH-10VDIM-EM-A1200 X B90 X C74MM	60W	6500	240V	WHITE	0/1-10 V DIMMABLE DRIVER	3 HOUR EMERGENCY BACKUP	A1200 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1200 X B90 X C74MM	
145	MAZDA-IDXR296560W-3K-240V-WH-ND-A1500 X B90 X C74MM	60W	3000	240V	WHITE	ON - OFF	NON EMERGENCY	A1500 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1500 X B90 X C74MM	
146	MAZDA-IDXR296560W-3K-240V-WH-ND-EM-A1500 X B90 X C74MM	60W	3000	240V	WHITE	ON - OFF	3 HOUR EMERGENCY BACKUP	A1500 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1500 X B90 X C74MM	
147	MAZDA-IDXR296560W-3K-240V-WH-DA-A1500 X B90 X C74MM	60W	3000	240V	WHITE	DALI DIMMABLE DRIVER	NON EMERGENCY	A1500 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1500 X B90 X C74MM	
148	MAZDA-IDXR296560W-3K-240V-WH-DA-EM-A1500 X B90 X C74MM	60W	3000	240V	WHITE	DALI DIMMABLE DRIVER	3 HOUR EMERGENCY BACKUP	A1500 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1500 X B90 X C74MM	
149	MAZDA-IDXR296560W-3K-240V-WH-PH-A1500 X B90 X C74MM	60W	3000	240V	WHITE	PHASE CUT DIMMABLE	NON EMERGENCY	A1500 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1500 X B90 X C74MM	



DATASHEET

GENERATED ON: 15 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Control	Emergency Backup	Dimension	Material	IP	Dimensions	Price
150	MAZDA-IDXR296560W-3K-240V-WH-PH-EM-A1500 X B90 X C74MM	60W	3000	240V	WHITE	PHASE CUT DIMMABLE	3 HOUR EMERGENCY BACKUP	A1500 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1500 X B90 X C74MM	
151	MAZDA-IDXR296560W-3K-240V-WH-10VDIM-A1500 X B90 X C74MM	60W	3000	240V	WHITE	0/1-10 V DIMMABLE DRIVER	NON EMERGENCY	A1500 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1500 X B90 X C74MM	
152	MAZDA-IDXR296560W-3K-240V-WH-10VDIM-EM-A1500 X B90 X C74MM	60W	3000	240V	WHITE	0/1-10 V DIMMABLE DRIVER	3 HOUR EMERGENCY BACKUP	A1500 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1500 X B90 X C74MM	
153	MAZDA-IDXR296560W-4K-240V-WH-ND-A1500 X B90 X C74MM	60W	4000	240V	WHITE	ON - OFF	NON EMERGENCY	A1500 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1500 X B90 X C74MM	
154	MAZDA-IDXR296560W-4K-240V-WH-ND-EM-A1500 X B90 X C74MM	60W	4000	240V	WHITE	ON - OFF	3 HOUR EMERGENCY BACKUP	A1500 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1500 X B90 X C74MM	
155	MAZDA-IDXR296560W-4K-240V-WH-DA-A1500 X B90 X C74MM	60W	4000	240V	WHITE	DALI DIMMABLE DRIVER	NON EMERGENCY	A1500 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1500 X B90 X C74MM	
156	MAZDA-IDXR296560W-4K-240V-WH-DA-EM-A1500 X B90 X C74MM	60W	4000	240V	WHITE	DALI DIMMABLE DRIVER	3 HOUR EMERGENCY BACKUP	A1500 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1500 X B90 X C74MM	
157	MAZDA-IDXR296560W-4K-240V-WH-PH-A1500 X B90 X C74MM	60W	4000	240V	WHITE	PHASE CUT DIMMABLE	NON EMERGENCY	A1500 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1500 X B90 X C74MM	



DATASHEET

GENERATED ON: 15 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Control	Emergency Backup	Dimension	Material	IP	Dimensions	Price
158	MAZDA-IDXR296560W-4K-240V-WH-PH-EM-A1500 X B90 X C74MM	60W	4000	240V	WHITE	PHASE CUT DIMMABLE	3 HOUR EMERGENCY BACKUP	A1500 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1500 X B90 X C74MM	
159	MAZDA-IDXR296560W-4K-240V-WH-10VDIM-A1500 X B90 X C74MM	60W	4000	240V	WHITE	0/1-10 V DIMMABLE DRIVER	NON EMERGENCY	A1500 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1500 X B90 X C74MM	
160	MAZDA-IDXR296560W-4K-240V-WH-10VDIM-EM-A1500 X B90 X C74MM	60W	4000	240V	WHITE	0/1-10 V DIMMABLE DRIVER	3 HOUR EMERGENCY BACKUP	A1500 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1500 X B90 X C74MM	
161	MAZDA-IDXR296560W-5K-240V-WH-ND-A1500 X B90 X C74MM	60W	5000	240V	WHITE	ON - OFF	NON EMERGENCY	A1500 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1500 X B90 X C74MM	
162	MAZDA-IDXR296560W-5K-240V-WH-ND-EM-A1500 X B90 X C74MM	60W	5000	240V	WHITE	ON - OFF	3 HOUR EMERGENCY BACKUP	A1500 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1500 X B90 X C74MM	
163	MAZDA-IDXR296560W-5K-240V-WH-DA-A1500 X B90 X C74MM	60W	5000	240V	WHITE	DALI DIMMABLE DRIVER	NON EMERGENCY	A1500 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1500 X B90 X C74MM	
164	MAZDA-IDXR296560W-5K-240V-WH-DA-EM-A1500 X B90 X C74MM	60W	5000	240V	WHITE	DALI DIMMABLE DRIVER	3 HOUR EMERGENCY BACKUP	A1500 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1500 X B90 X C74MM	
165	MAZDA-IDXR296560W-5K-240V-WH-PH-A1500 X B90 X C74MM	60W	5000	240V	WHITE	PHASE CUT DIMMABLE	NON EMERGENCY	A1500 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1500 X B90 X C74MM	



DATASHEET

GENERATED ON: 15 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Control	Emergency Backup	Dimension	Material	IP	Dimensions	Price
166	MAZDA-IDXR296560W-5K-240V-WH-PH-EM-A1500 X B90 X C74MM	60W	5000	240V	WHITE	PHASE CUT DIMMABLE	3 HOUR EMERGENCY BACKUP	A1500 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1500 X B90 X C74MM	
167	MAZDA-IDXR296560W-5K-240V-WH-10VDIM-A1500 X B90 X C74MM	60W	5000	240V	WHITE	0/1-10 V DIMMABLE DRIVER	NON EMERGENCY	A1500 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1500 X B90 X C74MM	
168	MAZDA-IDXR296560W-5K-240V-WH-10VDIM-EM-A1500 X B90 X C74MM	60W	5000	240V	WHITE	0/1-10 V DIMMABLE DRIVER	3 HOUR EMERGENCY BACKUP	A1500 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1500 X B90 X C74MM	
169	MAZDA-IDXR296560W-6K-240V-WH-ND-A1500 X B90 X C74MM	60W	6000	240V	WHITE	ON - OFF	NON EMERGENCY	A1500 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1500 X B90 X C74MM	
170	MAZDA-IDXR296560W-6K-240V-WH-ND-EM-A1500 X B90 X C74MM	60W	6000	240V	WHITE	ON - OFF	3 HOUR EMERGENCY BACKUP	A1500 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1500 X B90 X C74MM	
171	MAZDA-IDXR296560W-6K-240V-WH-DA-A1500 X B90 X C74MM	60W	6000	240V	WHITE	DALI DIMMABLE DRIVER	NON EMERGENCY	A1500 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1500 X B90 X C74MM	
172	MAZDA-IDXR296560W-6K-240V-WH-DA-EM-A1500 X B90 X C74MM	60W	6000	240V	WHITE	DALI DIMMABLE DRIVER	3 HOUR EMERGENCY BACKUP	A1500 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1500 X B90 X C74MM	
173	MAZDA-IDXR296560W-6K-240V-WH-PH-A1500 X B90 X C74MM	60W	6000	240V	WHITE	PHASE CUT DIMMABLE	NON EMERGENCY	A1500 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1500 X B90 X C74MM	



DATASHEET

GENERATED ON: 15 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Control	Emergency Backup	Dimension	Material	IP	Dimensions	Price
174	MAZDA-IDXR296560W-6K-240V-WH-PH-EM-A1500 X B90 X C74MM	60W	6000	240V	WHITE	PHASE CUT DIMMABLE	3 HOUR EMERGENCY BACKUP	A1500 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1500 X B90 X C74MM	
175	MAZDA-IDXR296560W-6K-240V-WH-10VDIM-A1500 X B90 X C74MM	60W	6000	240V	WHITE	0/1-10 V DIMMABLE DRIVER	NON EMERGENCY	A1500 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1500 X B90 X C74MM	
176	MAZDA-IDXR296560W-6K-240V-WH-10VDIM-EM-A1500 X B90 X C74MM	60W	6000	240V	WHITE	0/1-10 V DIMMABLE DRIVER	3 HOUR EMERGENCY BACKUP	A1500 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1500 X B90 X C74MM	
177	MAZDA-IDXR296560W-2.7K-240V-WH-ND-A1500 X B90 X C74MM	60W	2700	240V	WHITE	ON - OFF	NON EMERGENCY	A1500 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1500 X B90 X C74MM	
178	MAZDA-IDXR296560W-2.7K-240V-WH-ND-EM-A1500 X B90 X C74MM	60W	2700	240V	WHITE	ON - OFF	3 HOUR EMERGENCY BACKUP	A1500 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1500 X B90 X C74MM	
179	MAZDA-IDXR296560W-2.7K-240V-WH-DA-A1500 X B90 X C74MM	60W	2700	240V	WHITE	DALI DIMMABLE DRIVER	NON EMERGENCY	A1500 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1500 X B90 X C74MM	
180	MAZDA-IDXR296560W-2.7K-240V-WH-DA-EM-A1500 X B90 X C74MM	60W	2700	240V	WHITE	DALI DIMMABLE DRIVER	3 HOUR EMERGENCY BACKUP	A1500 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1500 X B90 X C74MM	
181	MAZDA-IDXR296560W-2.7K-240V-WH-PH-A1500 X B90 X C74MM	60W	2700	240V	WHITE	PHASE CUT DIMMABLE	NON EMERGENCY	A1500 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1500 X B90 X C74MM	



#	Code	WATT	CCT	Voltage	Body Color	Control	Emergency Backup	Dimension	Material	IP	Dimensions	Price
182	MAZDA-IDXR296560W-2.7K-240V-WH-PH-EM-A1500 X B90 X C74MM	60W	2700	240V	WHITE	PHASE CUT DIMMABLE	3 HOUR EMERGENCY BACKUP	A1500 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1500 X B90 X C74MM	
183	MAZDA-IDXR296560W-2.7K-240V-WH-10VDIM-A1500 X B90 X C74MM	60W	2700	240V	WHITE	0/1-10 V DIMMABLE DRIVER	NON EMERGENCY	A1500 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1500 X B90 X C74MM	
184	MAZDA-IDXR296560W-2.7K-240V-WH-10VDIM-EM-A1500 X B90 X C74MM	60W	2700	240V	WHITE	0/1-10 V DIMMABLE DRIVER	3 HOUR EMERGENCY BACKUP	A1500 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1500 X B90 X C74MM	
185	MAZDA-IDXR296560W-6.5K-240V-WH-ND-A1500 X B90 X C74MM	60W	6500	240V	WHITE	ON - OFF	NON EMERGENCY	A1500 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1500 X B90 X C74MM	
186	MAZDA-IDXR296560W-6.5K-240V-WH-ND-EM-A1500 X B90 X C74MM	60W	6500	240V	WHITE	ON - OFF	3 HOUR EMERGENCY BACKUP	A1500 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1500 X B90 X C74MM	
187	MAZDA-IDXR296560W-6.5K-240V-WH-DA-A1500 X B90 X C74MM	60W	6500	240V	WHITE	DALI DIMMABLE DRIVER	NON EMERGENCY	A1500 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1500 X B90 X C74MM	
188	MAZDA-IDXR296560W-6.5K-240V-WH-DA-EM-A1500 X B90 X C74MM	60W	6500	240V	WHITE	DALI DIMMABLE DRIVER	3 HOUR EMERGENCY BACKUP	A1500 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1500 X B90 X C74MM	
189	MAZDA-IDXR296560W-6.5K-240V-WH-PH-A1500 X B90 X C74MM	60W	6500	240V	WHITE	PHASE CUT DIMMABLE	NON EMERGENCY	A1500 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1500 X B90 X C74MM	

#	Code	WATT	CCT	Voltage	Body Color	Control	Emergency Backup	Dimension	Material	IP	Dimensions	Price
190	MAZDA-IDXR296560W-6.5K-240V-WH-PH-EM-A1500 X B90 X C74MM	60W	6500	240V	WHITE	PHASE CUT DIMMABLE	3 HOUR EMERGENCY BACKUP	A1500 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1500 X B90 X C74MM	
191	MAZDA-IDXR296560W-6.5K-240V-WH-10VDIM-A1500 X B90 X C74MM	60W	6500	240V	WHITE	0/1-10 V DIMMABLE DRIVER	NON EMERGENCY	A1500 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1500 X B90 X C74MM	
192	MAZDA-IDXR296560W-6.5K-240V-WH-10VDIM-EM-A1500 X B90 X C74MM	60W	6500	240V	WHITE	0/1-10 V DIMMABLE DRIVER	3 HOUR EMERGENCY BACKUP	A1500 X B90 X C74MM	PURE ALUMINUM A6063 WITH CORROSION PROOF HARD ANODIC OXIDE COATING	IP66	A1500 X B90 X C74MM	