



TUBE

MAZDA Model: SIXR2325 External Wall Light

Unique Cylinder lamp adopts straightforward design with stylish appearance with high quality COB LED chip with high lumen and pure color. The color of surface ring is replaceable, which could create diversified light atmosphere according to different environment.

The AL6063 Aluminum radiator in sand blast oxidation treatment provides excellent heat dissipation and corrosion resistance. The built-in power supply with high conversion efficiency is stable and reliable. It is very suitable for star hotel, restaurant, shopping mall, villa, residence and other high-end projects

ALL AVAILABLE VARIANTS

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
1	MAZDA-SIXR232509W-3K-240V-WH-ND-A60 X B150 MM	09W	3000	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A60 X B150 MM	DIE CAST ALUMINUM	IP65	A60 X B150 MM	
2	MAZDA-SIXR232509W-3K-240V-WH-DA-A60 X B150 MM	09W	3000	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A60 X B150 MM	DIE CAST ALUMINUM	IP65	A60 X B150 MM	
3	MAZDA-SIXR232509W-3K-240V-WH-PH-A60 X B150 MM	09W	3000	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A60 X B150 MM	DIE CAST ALUMINUM	IP65	A60 X B150 MM	
4	MAZDA-SIXR232509W-3K-240V-WH-10VDIM-A60 X B150 MM	09W	3000	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A60 X B150 MM	DIE CAST ALUMINUM	IP65	A60 X B150 MM	
5	MAZDA-SIXR232509W-4K-240V-WH-ND-A60 X B150 MM	09W	4000	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A60 X B150 MM	DIE CAST ALUMINUM	IP65	A60 X B150 MM	
6	MAZDA-SIXR232509W-4K-240V-WH-DA-A60 X B150 MM	09W	4000	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A60 X B150 MM	DIE CAST ALUMINUM	IP65	A60 X B150 MM	
7	MAZDA-SIXR232509W-4K-240V-WH-PH-A60 X B150 MM	09W	4000	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A60 X B150 MM	DIE CAST ALUMINUM	IP65	A60 X B150 MM	
8	MAZDA-SIXR232509W-4K-240V-WH-10VDIM-A60 X B150 MM	09W	4000	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A60 X B150 MM	DIE CAST ALUMINUM	IP65	A60 X B150 MM	
9	MAZDA-SIXR232509W-5K-240V-WH-ND-A60 X B150 MM	09W	5000	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A60 X B150 MM	DIE CAST ALUMINUM	IP65	A60 X B150 MM	
10	MAZDA-SIXR232509W-5K-240V-WH-DA-A60 X B150 MM	09W	5000	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A60 X B150 MM	DIE CAST ALUMINUM	IP65	A60 X B150 MM	
11	MAZDA-SIXR232509W-5K-240V-WH-PH-A60 X B150 MM	09W	5000	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A60 X B150 MM	DIE CAST ALUMINUM	IP65	A60 X B150 MM	
12	MAZDA-SIXR232509W-5K-240V-WH-10VDIM-A60 X B150 MM	09W	5000	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A60 X B150 MM	DIE CAST ALUMINUM	IP65	A60 X B150 MM	
13	MAZDA-SIXR232509W-6K-240V-WH-ND-A60 X B150 MM	09W	6000	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A60 X B150 MM	DIE CAST ALUMINUM	IP65	A60 X B150 MM	
14	MAZDA-SIXR232509W-6K-240V-WH-DA-A60 X B150 MM	09W	6000	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A60 X B150 MM	DIE CAST ALUMINUM	IP65	A60 X B150 MM	
15	MAZDA-SIXR232509W-6K-240V-WH-PH-A60 X B150 MM	09W	6000	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A60 X B150 MM	DIE CAST ALUMINUM	IP65	A60 X B150 MM	
16	MAZDA-SIXR232509W-6K-240V-WH-10VDIM-A60 X B150 MM	09W	6000	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A60 X B150 MM	DIE CAST ALUMINUM	IP65	A60 X B150 MM	



DATASHEET

GENERATED ON: 17 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
17	MAZDA-SIXR232509W-2.7K-240V-WH-ND-A60 X B150 MM	09W	2700	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A60 X B150 MM	DIE CAST ALUMINUM	IP65	A60 X B150 MM	
18	MAZDA-SIXR232509W-2.7K-240V-WH-DA-A60 X B150 MM	09W	2700	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A60 X B150 MM	DIE CAST ALUMINUM	IP65	A60 X B150 MM	
19	MAZDA-SIXR232509W-2.7K-240V-WH-PH-A60 X B150 MM	09W	2700	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A60 X B150 MM	DIE CAST ALUMINUM	IP65	A60 X B150 MM	
20	MAZDA-SIXR232509W-2.7K-240V-WH-10VDIM-A60 X B150 MM	09W	2700	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A60 X B150 MM	DIE CAST ALUMINUM	IP65	A60 X B150 MM	
21	MAZDA-SIXR232509W-6.5K-240V-WH-ND-A60 X B150 MM	09W	6500	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A60 X B150 MM	DIE CAST ALUMINUM	IP65	A60 X B150 MM	
22	MAZDA-SIXR232509W-6.5K-240V-WH-DA-A60 X B150 MM	09W	6500	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A60 X B150 MM	DIE CAST ALUMINUM	IP65	A60 X B150 MM	
23	MAZDA-SIXR232509W-6.5K-240V-WH-PH-A60 X B150 MM	09W	6500	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A60 X B150 MM	DIE CAST ALUMINUM	IP65	A60 X B150 MM	
24	MAZDA-SIXR232509W-6.5K-240V-WH-10VDIM-A60 X B150 MM	09W	6500	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A60 X B150 MM	DIE CAST ALUMINUM	IP65	A60 X B150 MM	
25	MAZDA-SIXR232512W-3K-240V-WH-ND-A60 X B150 MM	12W	3000	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A60 X B150 MM	DIE CAST ALUMINUM	IP65	A60 X B150 MM	
26	MAZDA-SIXR232512W-3K-240V-WH-DA-A60 X B150 MM	12W	3000	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A60 X B150 MM	DIE CAST ALUMINUM	IP65	A60 X B150 MM	
27	MAZDA-SIXR232512W-3K-240V-WH-PH-A60 X B150 MM	12W	3000	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A60 X B150 MM	DIE CAST ALUMINUM	IP65	A60 X B150 MM	
28	MAZDA-SIXR232512W-3K-240V-WH-10VDIM-A60 X B150 MM	12W	3000	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A60 X B150 MM	DIE CAST ALUMINUM	IP65	A60 X B150 MM	
29	MAZDA-SIXR232512W-4K-240V-WH-ND-A60 X B150 MM	12W	4000	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A60 X B150 MM	DIE CAST ALUMINUM	IP65	A60 X B150 MM	
30	MAZDA-SIXR232512W-4K-240V-WH-DA-A60 X B150 MM	12W	4000	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A60 X B150 MM	DIE CAST ALUMINUM	IP65	A60 X B150 MM	
31	MAZDA-SIXR232512W-4K-240V-WH-PH-A60 X B150 MM	12W	4000	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A60 X B150 MM	DIE CAST ALUMINUM	IP65	A60 X B150 MM	
32	MAZDA-SIXR232512W-4K-240V-WH-10VDIM-A60 X B150 MM	12W	4000	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A60 X B150 MM	DIE CAST ALUMINUM	IP65	A60 X B150 MM	
33	MAZDA-SIXR232512W-5K-240V-WH-ND-A60 X B150 MM	12W	5000	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A60 X B150 MM	DIE CAST ALUMINUM	IP65	A60 X B150 MM	
34	MAZDA-SIXR232512W-5K-240V-WH-DA-A60 X B150 MM	12W	5000	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A60 X B150 MM	DIE CAST ALUMINUM	IP65	A60 X B150 MM	
35	MAZDA-SIXR232512W-5K-240V-WH-PH-A60 X B150 MM	12W	5000	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A60 X B150 MM	DIE CAST ALUMINUM	IP65	A60 X B150 MM	
36	MAZDA-SIXR232512W-5K-240V-WH-10VDIM-A60 X B150 MM	12W	5000	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A60 X B150 MM	DIE CAST ALUMINUM	IP65	A60 X B150 MM	
37	MAZDA-SIXR232512W-6K-240V-WH-ND-A60 X B150 MM	12W	6000	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A60 X B150 MM	DIE CAST ALUMINUM	IP65	A60 X B150 MM	
38	MAZDA-SIXR232512W-6K-240V-WH-DA-A60 X B150 MM	12W	6000	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A60 X B150 MM	DIE CAST ALUMINUM	IP65	A60 X B150 MM	
39	MAZDA-SIXR232512W-6K-240V-WH-PH-A60 X B150 MM	12W	6000	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A60 X B150 MM	DIE CAST ALUMINUM	IP65	A60 X B150 MM	
40	MAZDA-SIXR232512W-6K-240V-WH-10VDIM-A60 X B150 MM	12W	6000	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A60 X B150 MM	DIE CAST ALUMINUM	IP65	A60 X B150 MM	
41	MAZDA-SIXR232512W-2.7K-240V-WH-ND-A60 X B150 MM	12W	2700	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A60 X B150 MM	DIE CAST ALUMINUM	IP65	A60 X B150 MM	
42	MAZDA-SIXR232512W-2.7K-240V-WH-DA-A60 X B150 MM	12W	2700	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A60 X B150 MM	DIE CAST ALUMINUM	IP65	A60 X B150 MM	



DATASHEET

GENERATED ON: 17 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
43	MAZDA-SIXR232512W-2.7K-240V-WH-PH-A60 X B150 MM	12W	2700	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A60 X B150 MM	DIE CAST ALUMINUM	IP65	A60 X B150 MM	
44	MAZDA-SIXR232512W-2.7K-240V-WH-10VDIM-A60 X B150 MM	12W	2700	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A60 X B150 MM	DIE CAST ALUMINUM	IP65	A60 X B150 MM	
45	MAZDA-SIXR232512W-6.5K-240V-WH-ND-A60 X B150 MM	12W	6500	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A60 X B150 MM	DIE CAST ALUMINUM	IP65	A60 X B150 MM	
46	MAZDA-SIXR232512W-6.5K-240V-WH-DA-A60 X B150 MM	12W	6500	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A60 X B150 MM	DIE CAST ALUMINUM	IP65	A60 X B150 MM	
47	MAZDA-SIXR232512W-6.5K-240V-WH-PH-A60 X B150 MM	12W	6500	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A60 X B150 MM	DIE CAST ALUMINUM	IP65	A60 X B150 MM	
48	MAZDA-SIXR232512W-6.5K-240V-WH-10VDIM-A60 X B150 MM	12W	6500	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A60 X B150 MM	DIE CAST ALUMINUM	IP65	A60 X B150 MM	
49	MAZDA-SIXR232515W-3K-240V-WH-ND-A80 X B180 MM	15W	3000	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A80 X B180 MM	DIE CAST ALUMINUM	IP65	A80 X B180 MM	
50	MAZDA-SIXR232515W-3K-240V-WH-DA-A80 X B180 MM	15W	3000	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A80 X B180 MM	DIE CAST ALUMINUM	IP65	A80 X B180 MM	
51	MAZDA-SIXR232515W-3K-240V-WH-PH-A80 X B180 MM	15W	3000	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A80 X B180 MM	DIE CAST ALUMINUM	IP65	A80 X B180 MM	
52	MAZDA-SIXR232515W-3K-240V-WH-10VDIM-A80 X B180 MM	15W	3000	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A80 X B180 MM	DIE CAST ALUMINUM	IP65	A80 X B180 MM	
53	MAZDA-SIXR232515W-4K-240V-WH-ND-A80 X B180 MM	15W	4000	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A80 X B180 MM	DIE CAST ALUMINUM	IP65	A80 X B180 MM	
54	MAZDA-SIXR232515W-4K-240V-WH-DA-A80 X B180 MM	15W	4000	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A80 X B180 MM	DIE CAST ALUMINUM	IP65	A80 X B180 MM	
55	MAZDA-SIXR232515W-4K-240V-WH-PH-A80 X B180 MM	15W	4000	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A80 X B180 MM	DIE CAST ALUMINUM	IP65	A80 X B180 MM	
56	MAZDA-SIXR232515W-4K-240V-WH-10VDIM-A80 X B180 MM	15W	4000	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A80 X B180 MM	DIE CAST ALUMINUM	IP65	A80 X B180 MM	
57	MAZDA-SIXR232515W-5K-240V-WH-ND-A80 X B180 MM	15W	5000	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A80 X B180 MM	DIE CAST ALUMINUM	IP65	A80 X B180 MM	
58	MAZDA-SIXR232515W-5K-240V-WH-DA-A80 X B180 MM	15W	5000	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A80 X B180 MM	DIE CAST ALUMINUM	IP65	A80 X B180 MM	
59	MAZDA-SIXR232515W-5K-240V-WH-PH-A80 X B180 MM	15W	5000	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A80 X B180 MM	DIE CAST ALUMINUM	IP65	A80 X B180 MM	
60	MAZDA-SIXR232515W-5K-240V-WH-10VDIM-A80 X B180 MM	15W	5000	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A80 X B180 MM	DIE CAST ALUMINUM	IP65	A80 X B180 MM	
61	MAZDA-SIXR232515W-6K-240V-WH-ND-A80 X B180 MM	15W	6000	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A80 X B180 MM	DIE CAST ALUMINUM	IP65	A80 X B180 MM	
62	MAZDA-SIXR232515W-6K-240V-WH-DA-A80 X B180 MM	15W	6000	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A80 X B180 MM	DIE CAST ALUMINUM	IP65	A80 X B180 MM	
63	MAZDA-SIXR232515W-6K-240V-WH-PH-A80 X B180 MM	15W	6000	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A80 X B180 MM	DIE CAST ALUMINUM	IP65	A80 X B180 MM	
64	MAZDA-SIXR232515W-6K-240V-WH-10VDIM-A80 X B180 MM	15W	6000	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A80 X B180 MM	DIE CAST ALUMINUM	IP65	A80 X B180 MM	
65	MAZDA-SIXR232515W-2.7K-240V-WH-ND-A80 X B180 MM	15W	2700	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A80 X B180 MM	DIE CAST ALUMINUM	IP65	A80 X B180 MM	
66	MAZDA-SIXR232515W-2.7K-240V-WH-DA-A80 X B180 MM	15W	2700	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A80 X B180 MM	DIE CAST ALUMINUM	IP65	A80 X B180 MM	
67	MAZDA-SIXR232515W-2.7K-240V-WH-PH-A80 X B180 MM	15W	2700	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A80 X B180 MM	DIE CAST ALUMINUM	IP65	A80 X B180 MM	
68	MAZDA-SIXR232515W-2.7K-240V-WH-10VDIM-A80 X B180 MM	15W	2700	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A80 X B180 MM	DIE CAST ALUMINUM	IP65	A80 X B180 MM	



DATASHEET

GENERATED ON: 17 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
69	MAZDA-SIXR232515W-6.5K-240V-WH-ND-A80 X B180 MM	15W	6500	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A80 X B180 MM	DIE CAST ALUMINUM	IP65	A80 X B180 MM	
70	MAZDA-SIXR232515W-6.5K-240V-WH-DA-A80 X B180 MM	15W	6500	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A80 X B180 MM	DIE CAST ALUMINUM	IP65	A80 X B180 MM	
71	MAZDA-SIXR232515W-6.5K-240V-WH-PH-A80 X B180 MM	15W	6500	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A80 X B180 MM	DIE CAST ALUMINUM	IP65	A80 X B180 MM	
72	MAZDA-SIXR232515W-6.5K-240V-WH-10VDIM-A80 X B180 MM	15W	6500	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A80 X B180 MM	DIE CAST ALUMINUM	IP65	A80 X B180 MM	
73	MAZDA-SIXR232518W-3K-240V-WH-ND-A80 X B180 MM	18W	3000	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A80 X B180 MM	DIE CAST ALUMINUM	IP65	A80 X B180 MM	
74	MAZDA-SIXR232518W-3K-240V-WH-DA-A80 X B180 MM	18W	3000	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A80 X B180 MM	DIE CAST ALUMINUM	IP65	A80 X B180 MM	
75	MAZDA-SIXR232518W-3K-240V-WH-PH-A80 X B180 MM	18W	3000	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A80 X B180 MM	DIE CAST ALUMINUM	IP65	A80 X B180 MM	
76	MAZDA-SIXR232518W-3K-240V-WH-10VDIM-A80 X B180 MM	18W	3000	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A80 X B180 MM	DIE CAST ALUMINUM	IP65	A80 X B180 MM	
77	MAZDA-SIXR232518W-4K-240V-WH-ND-A80 X B180 MM	18W	4000	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A80 X B180 MM	DIE CAST ALUMINUM	IP65	A80 X B180 MM	
78	MAZDA-SIXR232518W-4K-240V-WH-DA-A80 X B180 MM	18W	4000	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A80 X B180 MM	DIE CAST ALUMINUM	IP65	A80 X B180 MM	
79	MAZDA-SIXR232518W-4K-240V-WH-PH-A80 X B180 MM	18W	4000	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A80 X B180 MM	DIE CAST ALUMINUM	IP65	A80 X B180 MM	
80	MAZDA-SIXR232518W-4K-240V-WH-10VDIM-A80 X B180 MM	18W	4000	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A80 X B180 MM	DIE CAST ALUMINUM	IP65	A80 X B180 MM	
81	MAZDA-SIXR232518W-5K-240V-WH-ND-A80 X B180 MM	18W	5000	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A80 X B180 MM	DIE CAST ALUMINUM	IP65	A80 X B180 MM	
82	MAZDA-SIXR232518W-5K-240V-WH-DA-A80 X B180 MM	18W	5000	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A80 X B180 MM	DIE CAST ALUMINUM	IP65	A80 X B180 MM	
83	MAZDA-SIXR232518W-5K-240V-WH-PH-A80 X B180 MM	18W	5000	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A80 X B180 MM	DIE CAST ALUMINUM	IP65	A80 X B180 MM	
84	MAZDA-SIXR232518W-5K-240V-WH-10VDIM-A80 X B180 MM	18W	5000	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A80 X B180 MM	DIE CAST ALUMINUM	IP65	A80 X B180 MM	
85	MAZDA-SIXR232518W-6K-240V-WH-ND-A80 X B180 MM	18W	6000	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A80 X B180 MM	DIE CAST ALUMINUM	IP65	A80 X B180 MM	
86	MAZDA-SIXR232518W-6K-240V-WH-DA-A80 X B180 MM	18W	6000	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A80 X B180 MM	DIE CAST ALUMINUM	IP65	A80 X B180 MM	
87	MAZDA-SIXR232518W-6K-240V-WH-PH-A80 X B180 MM	18W	6000	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A80 X B180 MM	DIE CAST ALUMINUM	IP65	A80 X B180 MM	
88	MAZDA-SIXR232518W-6K-240V-WH-10VDIM-A80 X B180 MM	18W	6000	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A80 X B180 MM	DIE CAST ALUMINUM	IP65	A80 X B180 MM	
89	MAZDA-SIXR232518W-2.7K-240V-WH-ND-A80 X B180 MM	18W	2700	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A80 X B180 MM	DIE CAST ALUMINUM	IP65	A80 X B180 MM	
90	MAZDA-SIXR232518W-2.7K-240V-WH-DA-A80 X B180 MM	18W	2700	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A80 X B180 MM	DIE CAST ALUMINUM	IP65	A80 X B180 MM	
91	MAZDA-SIXR232518W-2.7K-240V-WH-PH-A80 X B180 MM	18W	2700	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A80 X B180 MM	DIE CAST ALUMINUM	IP65	A80 X B180 MM	
92	MAZDA-SIXR232518W-2.7K-240V-WH-10VDIM-A80 X B180 MM	18W	2700	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A80 X B180 MM	DIE CAST ALUMINUM	IP65	A80 X B180 MM	
93	MAZDA-SIXR232518W-6.5K-240V-WH-ND-A80 X B180 MM	18W	6500	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A80 X B180 MM	DIE CAST ALUMINUM	IP65	A80 X B180 MM	
94	MAZDA-SIXR232518W-6.5K-240V-WH-DA-A80 X B180 MM	18W	6500	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A80 X B180 MM	DIE CAST ALUMINUM	IP65	A80 X B180 MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
95	MAZDA-SIXR232518W-6.5K-240V-WH-PH-A80 X B180 MM	18W	6500	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A80 X B180 MM	DIE CAST ALUMINUM	IP65	A80 X B180 MM	
96	MAZDA-SIXR232518W-6.5K-240V-WH-10VDIM-A80 X B180 MM	18W	6500	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A80 X B180 MM	DIE CAST ALUMINUM	IP65	A80 X B180 MM	