



MEGA

MAZDA Model: WSXR37872 External Wall Light

Mega features a durable CNC 6063# aluminum housing with a high-quality 60-80µm coating, ensuring excellent adhesion and resistance to corrosion and wear, compliant with ISO Class 1 and ASTM Class 48 standards. A precision-engineered double silicone seal gasket provides superior protection against dust and moisture. It supports multiple dimming options, allowing flexible control. Designed to perform reliably in temperatures this versatile lighting solution is ideal for various indoor and outdoor applications

ALL AVAILABLE VARIANTS

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
1	MAZDA-WSXR378722X6W-3K-240V-WH-ND-A200 X B86 X C136 MM	2X6W	3000	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
2	MAZDA-WSXR378722X6W-3K-240V-WH-DA-A200 X B86 X C136 MM	2X6W	3000	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
3	MAZDA-WSXR378722X6W-3K-240V-WH-PH-A200 X B86 X C136 MM	2X6W	3000	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
4	MAZDA-WSXR378722X6W-3K-240V-WH-10VDIM-A200 X B86 X C136 MM	2X6W	3000	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
5	MAZDA-WSXR378722X6W-4K-240V-WH-ND-A200 X B86 X C136 MM	2X6W	4000	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
6	MAZDA-WSXR378722X6W-4K-240V-WH-DA-A200 X B86 X C136 MM	2X6W	4000	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
7	MAZDA-WSXR378722X6W-4K-240V-WH-PH-A200 X B86 X C136 MM	2X6W	4000	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
8	MAZDA-WSXR378722X6W-4K-240V-WH-10VDIM-A200 X B86 X C136 MM	2X6W	4000	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
9	MAZDA-WSXR378722X6W-5K-240V-WH-ND-A200 X B86 X C136 MM	2X6W	5000	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
10	MAZDA-WSXR378722X6W-5K-240V-WH-DA-A200 X B86 X C136 MM	2X6W	5000	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
11	MAZDA-WSXR378722X6W-5K-240V-WH-PH-A200 X B86 X C136 MM	2X6W	5000	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
12	MAZDA-WSXR378722X6W-5K-240V-WH-10VDIM-A200 X B86 X C136 MM	2X6W	5000	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
13	MAZDA-WSXR378722X6W-6K-240V-WH-ND-A200 X B86 X C136 MM	2X6W	6000	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
14	MAZDA-WSXR378722X6W-6K-240V-WH-DA-A200 X B86 X C136 MM	2X6W	6000	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
15	MAZDA-WSXR378722X6W-6K-240V-WH-PH-A200 X B86 X C136 MM	2X6W	6000	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
16	MAZDA-WSXR378722X6W-6K-240V-WH-10VDIM-A200 X B86 X C136 MM	2X6W	6000	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
17	MAZDA-WSXR378722X6W-2.7K-240V-WH-ND-A200 X B86 X C136 MM	2X6W	2700	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	



DATASHEET

GENERATED ON: 16 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
18	MAZDA-WSXR378722X6W-2.7K-240V-WH-DA-A200 X B86 X C136 MM	2X6W	2700	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
19	MAZDA-WSXR378722X6W-2.7K-240V-WH-PH-A200 X B86 X C136 MM	2X6W	2700	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
20	MAZDA-WSXR378722X6W-2.7K-240V-WH-10VDIM-A200 X B86 X C136 MM	2X6W	2700	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
21	MAZDA-WSXR378722X6W-6.5K-240V-WH-ND-A200 X B86 X C136 MM	2X6W	6500	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
22	MAZDA-WSXR378722X6W-6.5K-240V-WH-DA-A200 X B86 X C136 MM	2X6W	6500	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
23	MAZDA-WSXR378722X6W-6.5K-240V-WH-PH-A200 X B86 X C136 MM	2X6W	6500	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
24	MAZDA-WSXR378722X6W-6.5K-240V-WH-10VDIM-A200 X B86 X C136 MM	2X6W	6500	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
25	MAZDA-WSXR378722X9W-3K-240V-WH-ND-A200 X B86 X C136 MM	2X9W	3000	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
26	MAZDA-WSXR378722X9W-3K-240V-WH-DA-A200 X B86 X C136 MM	2X9W	3000	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
27	MAZDA-WSXR378722X9W-3K-240V-WH-PH-A200 X B86 X C136 MM	2X9W	3000	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
28	MAZDA-WSXR378722X9W-3K-240V-WH-10VDIM-A200 X B86 X C136 MM	2X9W	3000	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
29	MAZDA-WSXR378722X9W-4K-240V-WH-ND-A200 X B86 X C136 MM	2X9W	4000	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
30	MAZDA-WSXR378722X9W-4K-240V-WH-DA-A200 X B86 X C136 MM	2X9W	4000	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
31	MAZDA-WSXR378722X9W-4K-240V-WH-PH-A200 X B86 X C136 MM	2X9W	4000	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
32	MAZDA-WSXR378722X9W-4K-240V-WH-10VDIM-A200 X B86 X C136 MM	2X9W	4000	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
33	MAZDA-WSXR378722X9W-5K-240V-WH-ND-A200 X B86 X C136 MM	2X9W	5000	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
34	MAZDA-WSXR378722X9W-5K-240V-WH-DA-A200 X B86 X C136 MM	2X9W	5000	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
35	MAZDA-WSXR378722X9W-5K-240V-WH-PH-A200 X B86 X C136 MM	2X9W	5000	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
36	MAZDA-WSXR378722X9W-5K-240V-WH-10VDIM-A200 X B86 X C136 MM	2X9W	5000	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
37	MAZDA-WSXR378722X9W-6K-240V-WH-ND-A200 X B86 X C136 MM	2X9W	6000	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
38	MAZDA-WSXR378722X9W-6K-240V-WH-DA-A200 X B86 X C136 MM	2X9W	6000	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
39	MAZDA-WSXR378722X9W-6K-240V-WH-PH-A200 X B86 X C136 MM	2X9W	6000	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
40	MAZDA-WSXR378722X9W-6K-240V-WH-10VDIM-A200 X B86 X C136 MM	2X9W	6000	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
41	MAZDA-WSXR378722X9W-2.7K-240V-WH-ND-A200 X B86 X C136 MM	2X9W	2700	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
42	MAZDA-WSXR378722X9W-2.7K-240V-WH-DA-A200 X B86 X C136 MM	2X9W	2700	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
43	MAZDA-WSXR378722X9W-2.7K-240V-WH-PH-A200 X B86 X C136 MM	2X9W	2700	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
44	MAZDA-WSXR378722X9W-2.7K-240V-WH-10VDIM-A200 X B86 X C136 MM	2X9W	2700	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
45	MAZDA-WSXR378722X9W-6.5K-240V-WH-ND-A200 X B86 X C136 MM	2X9W	6500	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	



DATASHEET

GENERATED ON: 16 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
46	MAZDA-WSXR378722X9W-6.5K-240V-WH-DA-A200 X B86 X C136 MM	2X9W	6500	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
47	MAZDA-WSXR378722X9W-6.5K-240V-WH-PH-A200 X B86 X C136 MM	2X9W	6500	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
48	MAZDA-WSXR378722X9W-6.5K-240V-WH-10VDIM-A200 X B86 X C136 MM	2X9W	6500	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
49	MAZDA-WSXR378722X12W-3K-240V-WH-ND-A200 X B86 X C136 MM	2X12W	3000	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
50	MAZDA-WSXR378722X12W-3K-240V-WH-DA-A200 X B86 X C136 MM	2X12W	3000	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
51	MAZDA-WSXR378722X12W-3K-240V-WH-PH-A200 X B86 X C136 MM	2X12W	3000	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
52	MAZDA-WSXR378722X12W-3K-240V-WH-10VDIM-A200 X B86 X C136 MM	2X12W	3000	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
53	MAZDA-WSXR378722X12W-4K-240V-WH-ND-A200 X B86 X C136 MM	2X12W	4000	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
54	MAZDA-WSXR378722X12W-4K-240V-WH-DA-A200 X B86 X C136 MM	2X12W	4000	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
55	MAZDA-WSXR378722X12W-4K-240V-WH-PH-A200 X B86 X C136 MM	2X12W	4000	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
56	MAZDA-WSXR378722X12W-4K-240V-WH-10VDIM-A200 X B86 X C136 MM	2X12W	4000	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
57	MAZDA-WSXR378722X12W-5K-240V-WH-ND-A200 X B86 X C136 MM	2X12W	5000	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
58	MAZDA-WSXR378722X12W-5K-240V-WH-DA-A200 X B86 X C136 MM	2X12W	5000	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
59	MAZDA-WSXR378722X12W-5K-240V-WH-PH-A200 X B86 X C136 MM	2X12W	5000	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
60	MAZDA-WSXR378722X12W-5K-240V-WH-10VDIM-A200 X B86 X C136 MM	2X12W	5000	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
61	MAZDA-WSXR378722X12W-6K-240V-WH-ND-A200 X B86 X C136 MM	2X12W	6000	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
62	MAZDA-WSXR378722X12W-6K-240V-WH-DA-A200 X B86 X C136 MM	2X12W	6000	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
63	MAZDA-WSXR378722X12W-6K-240V-WH-PH-A200 X B86 X C136 MM	2X12W	6000	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
64	MAZDA-WSXR378722X12W-6K-240V-WH-10VDIM-A200 X B86 X C136 MM	2X12W	6000	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
65	MAZDA-WSXR378722X12W-2.7K-240V-WH-ND-A200 X B86 X C136 MM	2X12W	2700	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
66	MAZDA-WSXR378722X12W-2.7K-240V-WH-DA-A200 X B86 X C136 MM	2X12W	2700	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
67	MAZDA-WSXR378722X12W-2.7K-240V-WH-PH-A200 X B86 X C136 MM	2X12W	2700	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
68	MAZDA-WSXR378722X12W-2.7K-240V-WH-10VDIM-A200 X B86 X C136 MM	2X12W	2700	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
69	MAZDA-WSXR378722X12W-6.5K-240V-WH-ND-A200 X B86 X C136 MM	2X12W	6500	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
70	MAZDA-WSXR378722X12W-6.5K-240V-WH-DA-A200 X B86 X C136 MM	2X12W	6500	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
71	MAZDA-WSXR378722X12W-6.5K-240V-WH-PH-A200 X B86 X C136 MM	2X12W	6500	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
72	MAZDA-WSXR378722X12W-6.5K-240V-WH-10VDIM-A200 X B86 X C136 MM	2X12W	6500	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
73	MAZDA-WSXR378722X15W-3K-240V-WH-ND-A200 X B86 X C136 MM	2X15W	3000	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	



#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
74	MAZDA-WSXR378722X15W-3K-240V-WH-DA-A200 X B86 X C136 MM	2X15W	3000	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
75	MAZDA-WSXR378722X15W-3K-240V-WH-PH-A200 X B86 X C136 MM	2X15W	3000	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
76	MAZDA-WSXR378722X15W-3K-240V-WH-10VDIM-A200 X B86 X C136 MM	2X15W	3000	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
77	MAZDA-WSXR378722X15W-4K-240V-WH-ND-A200 X B86 X C136 MM	2X15W	4000	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
78	MAZDA-WSXR378722X15W-4K-240V-WH-DA-A200 X B86 X C136 MM	2X15W	4000	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
79	MAZDA-WSXR378722X15W-4K-240V-WH-PH-A200 X B86 X C136 MM	2X15W	4000	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
80	MAZDA-WSXR378722X15W-4K-240V-WH-10VDIM-A200 X B86 X C136 MM	2X15W	4000	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
81	MAZDA-WSXR378722X15W-5K-240V-WH-ND-A200 X B86 X C136 MM	2X15W	5000	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
82	MAZDA-WSXR378722X15W-5K-240V-WH-DA-A200 X B86 X C136 MM	2X15W	5000	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
83	MAZDA-WSXR378722X15W-5K-240V-WH-PH-A200 X B86 X C136 MM	2X15W	5000	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
84	MAZDA-WSXR378722X15W-5K-240V-WH-10VDIM-A200 X B86 X C136 MM	2X15W	5000	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
85	MAZDA-WSXR378722X15W-6K-240V-WH-ND-A200 X B86 X C136 MM	2X15W	6000	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
86	MAZDA-WSXR378722X15W-6K-240V-WH-DA-A200 X B86 X C136 MM	2X15W	6000	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
87	MAZDA-WSXR378722X15W-6K-240V-WH-PH-A200 X B86 X C136 MM	2X15W	6000	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
88	MAZDA-WSXR378722X15W-6K-240V-WH-10VDIM-A200 X B86 X C136 MM	2X15W	6000	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
89	MAZDA-WSXR378722X15W-2.7K-240V-WH-ND-A200 X B86 X C136 MM	2X15W	2700	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
90	MAZDA-WSXR378722X15W-2.7K-240V-WH-DA-A200 X B86 X C136 MM	2X15W	2700	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
91	MAZDA-WSXR378722X15W-2.7K-240V-WH-PH-A200 X B86 X C136 MM	2X15W	2700	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
92	MAZDA-WSXR378722X15W-2.7K-240V-WH-10VDIM-A200 X B86 X C136 MM	2X15W	2700	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
93	MAZDA-WSXR378722X15W-6.5K-240V-WH-ND-A200 X B86 X C136 MM	2X15W	6500	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
94	MAZDA-WSXR378722X15W-6.5K-240V-WH-DA-A200 X B86 X C136 MM	2X15W	6500	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST			

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
102	MAZDA-WSXR378722X15W-4K-240V-WH-DA-A200 X B86 X C136 MM	2X15W	4000	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
103	MAZDA-WSXR378722X15W-4K-240V-WH-PH-A200 X B86 X C136 MM	2X15W	4000	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
104	MAZDA-WSXR378722X15W-4K-240V-WH-10VDIM-A200 X B86 X C136 MM	2X15W	4000	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
105	MAZDA-WSXR378722X15W-5K-240V-WH-ND-A200 X B86 X C136 MM	2X15W	5000	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
106	MAZDA-WSXR378722X15W-5K-240V-WH-DA-A200 X B86 X C136 MM	2X15W	5000	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
107	MAZDA-WSXR378722X15W-5K-240V-WH-PH-A200 X B86 X C136 MM	2X15W	5000	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
108	MAZDA-WSXR378722X15W-5K-240V-WH-10VDIM-A200 X B86 X C136 MM	2X15W	5000	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
109	MAZDA-WSXR378722X15W-6K-240V-WH-ND-A200 X B86 X C136 MM	2X15W	6000	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
110	MAZDA-WSXR378722X15W-6K-240V-WH-DA-A200 X B86 X C136 MM	2X15W	6000	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
111	MAZDA-WSXR378722X15W-6K-240V-WH-PH-A200 X B86 X C136 MM	2X15W	6000	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
112	MAZDA-WSXR378722X15W-6K-240V-WH-10VDIM-A200 X B86 X C136 MM	2X15W	6000	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
113	MAZDA-WSXR378722X15W-2.7K-240V-WH-ND-A200 X B86 X C136 MM	2X15W	2700	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
114	MAZDA-WSXR378722X15W-2.7K-240V-WH-DA-A200 X B86 X C136 MM	2X15W	2700	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
115	MAZDA-WSXR378722X15W-2.7K-240V-WH-PH-A200 X B86 X C136 MM	2X15W	2700	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
116	MAZDA-WSXR378722X15W-2.7K-240V-WH-10VDIM-A200 X B86 X C136 MM	2X15W	2700	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
117	MAZDA-WSXR378722X15W-6.5K-240V-WH-ND-A200 X B86 X C136 MM	2X15W	6500	240V	WHITE & BLACK	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
118	MAZDA-WSXR378722X15W-6.5K-240V-WH-DA-A200 X B86 X C136 MM	2X15W	6500	240V	WHITE & BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
119	MAZDA-WSXR378722X15W-6.5K-240V-WH-PH-A200 X B86 X C136 MM	2X15W	6500	240V	WHITE & BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	
120	MAZDA-WSXR378722X15W-6.5K-240V-WH-10VDIM-A200 X B86 X C136 MM	2X15W	6500	240V	WHITE & BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A200 X B86 X C136 MM	DIE CAST ALUMINUM	IP65	A200 X B86 X C136 MM	