



LUCIAN SQ

MAZDA Model: SIXR2924 External Wall Light

The LED wall light with down light effect design. Adopt aluminum housing providing excellent thermal management. IP66 for outdoor use. The ideal application areas are pillars in open plan offices, rooms meeting, areas reception, stairwells and corridors.

ALL AVAILABLE VARIANTS

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angle	Dimension	Material	IP	Dimensions	Price
1	MAZDA-SIXR292408W-3K-240V-BL-ND-A78 X B78 X C90MM	08W	3000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
2	MAZDA-SIXR292408W-3K-240V-BL-DA-A78 X B78 X C90MM	08W	3000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
3	MAZDA-SIXR292408W-3K-240V-BL-PH-A78 X B78 X C90MM	08W	3000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
4	MAZDA-SIXR292408W-3K-240V-BL-10VDIM-A78 X B78 X C90MM	08W	3000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
5	MAZDA-SIXR292408W-4K-240V-BL-ND-A78 X B78 X C90MM	08W	4000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
6	MAZDA-SIXR292408W-4K-240V-BL-DA-A78 X B78 X C90MM	08W	4000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
7	MAZDA-SIXR292408W-4K-240V-BL-PH-A78 X B78 X C90MM	08W	4000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
8	MAZDA-SIXR292408W-4K-240V-BL-10VDIM-A78 X B78 X C90MM	08W	4000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
9	MAZDA-SIXR292408W-5K-240V-BL-ND-A78 X B78 X C90MM	08W	5000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
10	MAZDA-SIXR292408W-5K-240V-BL-DA-A78 X B78 X C90MM	08W	5000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
11	MAZDA-SIXR292408W-5K-240V-BL-PH-A78 X B78 X C90MM	08W	5000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
12	MAZDA-SIXR292408W-5K-240V-BL-10VDIM-A78 X B78 X C90MM	08W	5000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
13	MAZDA-SIXR292408W-6K-240V-BL-ND-A78 X B78 X C90MM	08W	6000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
14	MAZDA-SIXR292408W-6K-240V-BL-DA-A78 X B78 X C90MM	08W	6000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
15	MAZDA-SIXR292408W-6K-240V-BL-PH-A78 X B78 X C90MM	08W	6000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
16	MAZDA-SIXR292408W-6K-240V-BL-10VDIM-A78 X B78 X C90MM	08W	6000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	



DATASHEET

GENERATED ON: 16 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
17	MAZDA-SIXR292408W-2.7K-240V-BL-ND-A78 X B78 X C90MM	08W	2700	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
18	MAZDA-SIXR292408W-2.7K-240V-BL-DA-A78 X B78 X C90MM	08W	2700	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
19	MAZDA-SIXR292408W-2.7K-240V-BL-PH-A78 X B78 X C90MM	08W	2700	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
20	MAZDA-SIXR292408W-2.7K-240V-BL-10VDIM-A78 X B78 X C90MM	08W	2700	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
21	MAZDA-SIXR292408W-6.5K-240V-BL-ND-A78 X B78 X C90MM	08W	6500	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
22	MAZDA-SIXR292408W-6.5K-240V-BL-DA-A78 X B78 X C90MM	08W	6500	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
23	MAZDA-SIXR292408W-6.5K-240V-BL-PH-A78 X B78 X C90MM	08W	6500	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
24	MAZDA-SIXR292408W-6.5K-240V-BL-10VDIM-A78 X B78 X C90MM	08W	6500	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
25	MAZDA-SIXR292410W-3K-240V-BL-ND-A78 X B78 X C90MM	10W	3000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
26	MAZDA-SIXR292410W-3K-240V-BL-DA-A78 X B78 X C90MM	10W	3000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
27	MAZDA-SIXR292410W-3K-240V-BL-PH-A78 X B78 X C90MM	10W	3000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
28	MAZDA-SIXR292410W-3K-240V-BL-10VDIM-A78 X B78 X C90MM	10W	3000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
29	MAZDA-SIXR292410W-4K-240V-BL-ND-A78 X B78 X C90MM	10W	4000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
30	MAZDA-SIXR292410W-4K-240V-BL-DA-A78 X B78 X C90MM	10W	4000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
31	MAZDA-SIXR292410W-4K-240V-BL-PH-A78 X B78 X C90MM	10W	4000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
32	MAZDA-SIXR292410W-4K-240V-BL-10VDIM-A78 X B78 X C90MM	10W	4000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
33	MAZDA-SIXR292410W-5K-240V-BL-ND-A78 X B78 X C90MM	10W	5000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
34	MAZDA-SIXR292410W-5K-240V-BL-DA-A78 X B78 X C90MM	10W	5000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
35	MAZDA-SIXR292410W-5K-240V-BL-PH-A78 X B78 X C90MM	10W	5000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
36	MAZDA-SIXR292410W-5K-240V-BL-10VDIM-A78 X B78 X C90MM	10W	5000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
37	MAZDA-SIXR292410W-6K-240V-BL-ND-A78 X B78 X C90MM	10W	6000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
38	MAZDA-SIXR292410W-6K-240V-BL-DA-A78 X B78 X C90MM	10W	6000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
39	MAZDA-SIXR292410W-6K-240V-BL-PH-A78 X B78 X C90MM	10W	6000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
40	MAZDA-SIXR292410W-6K-240V-BL-10VDIM-A78 X B78 X C90MM	10W	6000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
41	MAZDA-SIXR292410W-2.7K-240V-BL-ND-A78 X B78 X C90MM	10W	2700	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
42	MAZDA-SIXR292410W-2.7K-240V-BL-DA-A78 X B78 X C90MM	10W	2700	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	



DATASHEET

GENERATED ON: 16 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
43	MAZDA-SIXR292410W-2.7K-240V-BL-PH-A78 X B78 X C90MM	10W	2700	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
44	MAZDA-SIXR292410W-2.7K-240V-BL-10VDIM-A78 X B78 X C90MM	10W	2700	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
45	MAZDA-SIXR292410W-6.5K-240V-BL-ND-A78 X B78 X C90MM	10W	6500	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
46	MAZDA-SIXR292410W-6.5K-240V-BL-DA-A78 X B78 X C90MM	10W	6500	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
47	MAZDA-SIXR292410W-6.5K-240V-BL-PH-A78 X B78 X C90MM	10W	6500	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
48	MAZDA-SIXR292410W-6.5K-240V-BL-10VDIM-A78 X B78 X C90MM	10W	6500	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
49	MAZDA-SIXR292412W-3K-240V-BL-ND-A78 X B78 X C90MM	12W	3000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
50	MAZDA-SIXR292412W-3K-240V-BL-DA-A78 X B78 X C90MM	12W	3000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
51	MAZDA-SIXR292412W-3K-240V-BL-PH-A78 X B78 X C90MM	12W	3000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
52	MAZDA-SIXR292412W-3K-240V-BL-10VDIM-A78 X B78 X C90MM	12W	3000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
53	MAZDA-SIXR292412W-4K-240V-BL-ND-A78 X B78 X C90MM	12W	4000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
54	MAZDA-SIXR292412W-4K-240V-BL-DA-A78 X B78 X C90MM	12W	4000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
55	MAZDA-SIXR292412W-4K-240V-BL-PH-A78 X B78 X C90MM	12W	4000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
56	MAZDA-SIXR292412W-4K-240V-BL-10VDIM-A78 X B78 X C90MM	12W	4000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
57	MAZDA-SIXR292412W-5K-240V-BL-ND-A78 X B78 X C90MM	12W	5000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
58	MAZDA-SIXR292412W-5K-240V-BL-DA-A78 X B78 X C90MM	12W	5000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
59	MAZDA-SIXR292412W-5K-240V-BL-PH-A78 X B78 X C90MM	12W	5000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
60	MAZDA-SIXR292412W-5K-240V-BL-10VDIM-A78 X B78 X C90MM	12W	5000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
61	MAZDA-SIXR292412W-6K-240V-BL-ND-A78 X B78 X C90MM	12W	6000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
62	MAZDA-SIXR292412W-6K-240V-BL-DA-A78 X B78 X C90MM	12W	6000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
63	MAZDA-SIXR292412W-6K-240V-BL-PH-A78 X B78 X C90MM	12W	6000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
64	MAZDA-SIXR292412W-6K-240V-BL-10VDIM-A78 X B78 X C90MM	12W	6000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
65	MAZDA-SIXR292412W-2.7K-240V-BL-ND-A78 X B78 X C90MM	12W	2700	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
66	MAZDA-SIXR292412W-2.7K-240V-BL-DA-A78 X B78 X C90MM	12W	2700	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
67	MAZDA-SIXR292412W-2.7K-240V-BL-PH-A78 X B78 X C90MM	12W	2700	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
68	MAZDA-SIXR292412W-2.7K-240V-BL-10VDIM-A78 X B78 X C90MM	12W	2700	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	



DATASHEET

GENERATED ON: 16 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
69	MAZDA-SIXR292412W-6.5K-240V-BL-ND-A78 X B78 X C90MM	12W	6500	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
70	MAZDA-SIXR292412W-6.5K-240V-BL-DA-A78 X B78 X C90MM	12W	6500	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
71	MAZDA-SIXR292412W-6.5K-240V-BL-PH-A78 X B78 X C90MM	12W	6500	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
72	MAZDA-SIXR292412W-6.5K-240V-BL-10VDIM-A78 X B78 X C90MM	12W	6500	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
73	MAZDA-SIXR292415W-3K-240V-BL-ND-A78 X B78 X C90MM	15W	3000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
74	MAZDA-SIXR292415W-3K-240V-BL-DA-A78 X B78 X C90MM	15W	3000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
75	MAZDA-SIXR292415W-3K-240V-BL-PH-A78 X B78 X C90MM	15W	3000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
76	MAZDA-SIXR292415W-3K-240V-BL-10VDIM-A78 X B78 X C90MM	15W	3000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
77	MAZDA-SIXR292415W-4K-240V-BL-ND-A78 X B78 X C90MM	15W	4000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
78	MAZDA-SIXR292415W-4K-240V-BL-DA-A78 X B78 X C90MM	15W	4000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
79	MAZDA-SIXR292415W-4K-240V-BL-PH-A78 X B78 X C90MM	15W	4000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
80	MAZDA-SIXR292415W-4K-240V-BL-10VDIM-A78 X B78 X C90MM	15W	4000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
81	MAZDA-SIXR292415W-5K-240V-BL-ND-A78 X B78 X C90MM	15W	5000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
82	MAZDA-SIXR292415W-5K-240V-BL-DA-A78 X B78 X C90MM	15W	5000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
83	MAZDA-SIXR292415W-5K-240V-BL-PH-A78 X B78 X C90MM	15W	5000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
84	MAZDA-SIXR292415W-5K-240V-BL-10VDIM-A78 X B78 X C90MM	15W	5000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
85	MAZDA-SIXR292415W-6K-240V-BL-ND-A78 X B78 X C90MM	15W	6000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
86	MAZDA-SIXR292415W-6K-240V-BL-DA-A78 X B78 X C90MM	15W	6000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
87	MAZDA-SIXR292415W-6K-240V-BL-PH-A78 X B78 X C90MM	15W	6000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
88	MAZDA-SIXR292415W-6K-240V-BL-10VDIM-A78 X B78 X C90MM	15W	6000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
89	MAZDA-SIXR292415W-2.7K-240V-BL-ND-A78 X B78 X C90MM	15W	2700	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
90	MAZDA-SIXR292415W-2.7K-240V-BL-DA-A78 X B78 X C90MM	15W	2700	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
91	MAZDA-SIXR292415W-2.7K-240V-BL-PH-A78 X B78 X C90MM	15W	2700	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
92	MAZDA-SIXR292415W-2.7K-240V-BL-10VDIM-A78 X B78 X C90MM	15W	2700	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
93	MAZDA-SIXR292415W-6.5K-240V-BL-ND-A78 X B78 X C90MM	15W	6500	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
94	MAZDA-SIXR292415W-6.5K-240V-BL-DA-A78 X B78 X C90MM	15W	6500	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
95	MAZDA-SIXR292415W-6.5K-240V-BL-PH-A78 X B78 X C90MM	15W	6500	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	
96	MAZDA-SIXR292415W-6.5K-240V-BL-10VDIM-A78 X B78 X C90MM	15W	6500	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A78 X B78 X C90MM	DIE CAST ALUMINUM	IP54	A78 X B78 X C90MM	