



DANTI

MAZDA Model: WXR34602 External Wall Light

The LED wall light with down light effect design. Adopt aluminum housing providing excellent thermal management. IP66 for outdoor use. The ideal application areas are pillars in open plan offices, rooms meeting, areas reception, stairwells and corridors

ALL AVAILABLE VARIANTS

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
1	MAZDA-WXR346022X03W-3K-240V-BL-10VDIM-A158 X B56 X C60MM	2X03W	3000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A158 X B56 X C60MM	DIE CAST ALUMINUM	IP66	A158 X B56 X C60MM	
2	MAZDA-WXR346022X03W-3K-240V-BL-PH-A158 X B56 X C60MM	2X03W	3000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A158 X B56 X C60MM	DIE CAST ALUMINUM	IP66	A158 X B56 X C60MM	
3	MAZDA-WXR346022X03W-3K-240V-BL-DA-A158 X B56 X C60MM	2X03W	3000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A158 X B56 X C60MM	DIE CAST ALUMINUM	IP66	A158 X B56 X C60MM	
4	MAZDA-WXR346022X03W-3K-240V-BL-ND-A158 X B56 X C60MM	2X03W	3000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A158 X B56 X C60MM	DIE CAST ALUMINUM	IP66	A158 X B56 X C60MM	
5	MAZDA-WXR346022X03W-4K-240V-BL-10VDIM-A158 X B56 X C60MM	2X03W	4000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A158 X B56 X C60MM	DIE CAST ALUMINUM	IP66	A158 X B56 X C60MM	
6	MAZDA-WXR346022X03W-4K-240V-BL-PH-A158 X B56 X C60MM	2X03W	4000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A158 X B56 X C60MM	DIE CAST ALUMINUM	IP66	A158 X B56 X C60MM	
7	MAZDA-WXR346022X03W-4K-240V-BL-DA-A158 X B56 X C60MM	2X03W	4000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A158 X B56 X C60MM	DIE CAST ALUMINUM	IP66	A158 X B56 X C60MM	
8	MAZDA-WXR346022X03W-4K-240V-BL-ND-A158 X B56 X C60MM	2X03W	4000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A158 X B56 X C60MM	DIE CAST ALUMINUM	IP66	A158 X B56 X C60MM	
9	MAZDA-WXR346022X03W-5K-240V-BL-10VDIM-A158 X B56 X C60MM	2X03W	5000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A158 X B56 X C60MM	DIE CAST ALUMINUM	IP66	A158 X B56 X C60MM	
10	MAZDA-WXR346022X03W-5K-240V-BL-PH-A158 X B56 X C60MM	2X03W	5000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A158 X B56 X C60MM	DIE CAST ALUMINUM	IP66	A158 X B56 X C60MM	
11	MAZDA-WXR346022X03W-5K-240V-BL-DA-A158 X B56 X C60MM	2X03W	5000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A158 X B56 X C60MM	DIE CAST ALUMINUM	IP66	A158 X B56 X C60MM	
12	MAZDA-WXR346022X03W-5K-240V-BL-ND-A158 X B56 X C60MM	2X03W	5000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A158 X B56 X C60MM	DIE CAST ALUMINUM	IP66	A158 X B56 X C60MM	
13	MAZDA-WXR346022X03W-6K-240V-BL-10VDIM-A158 X B56 X C60MM	2X03W	6000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A158 X B56 X C60MM	DIE CAST ALUMINUM	IP66	A158 X B56 X C60MM	
14	MAZDA-WXR346022X03W-6K-240V-BL-PH-A158 X B56 X C60MM	2X03W	6000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A158 X B56 X C60MM	DIE CAST ALUMINUM	IP66	A158 X B56 X C60MM	
15	MAZDA-WXR346022X03W-6K-240V-BL-DA-A158 X B56 X C60MM	2X03W	6000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A158 X B56 X C60MM	DIE CAST ALUMINUM	IP66	A158 X B56 X C60MM	
16	MAZDA-WXR346022X03W-6K-240V-BL-ND-A158 X B56 X C60MM	2X03W	6000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A158 X B56 X C60MM	DIE CAST ALUMINUM	IP66	A158 X B56 X C60MM	
17	MAZDA-WXR346022X03W-2.7K-240V-BL-10VDIM-A158 X B56 X C60MM	2X03W	2700	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A158 X B56 X C60MM	DIE CAST ALUMINUM	IP66	A158 X B56 X C60MM	



DATASHEET

GENERATED ON: 16 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
18	MAZDA-WXR346022X03W-2.7K-240V-BL-PH-A158 X B56 X C60MM	2X03W	2700	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A158 X B56 X C60MM	DIE CAST ALUMINUM	IP66	A158 X B56 X C60MM	
19	MAZDA-WXR346022X03W-2.7K-240V-BL-DA-A158 X B56 X C60MM	2X03W	2700	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A158 X B56 X C60MM	DIE CAST ALUMINUM	IP66	A158 X B56 X C60MM	
20	MAZDA-WXR346022X03W-2.7K-240V-BL-ND-A158 X B56 X C60MM	2X03W	2700	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A158 X B56 X C60MM	DIE CAST ALUMINUM	IP66	A158 X B56 X C60MM	
21	MAZDA-WXR346022X03W-6.5K-240V-BL-10VDIM-A158 X B56 X C60MM	2X03W	6500	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A158 X B56 X C60MM	DIE CAST ALUMINUM	IP66	A158 X B56 X C60MM	
22	MAZDA-WXR346022X03W-6.5K-240V-BL-PH-A158 X B56 X C60MM	2X03W	6500	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A158 X B56 X C60MM	DIE CAST ALUMINUM	IP66	A158 X B56 X C60MM	
23	MAZDA-WXR346022X03W-6.5K-240V-BL-DA-A158 X B56 X C60MM	2X03W	6500	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A158 X B56 X C60MM	DIE CAST ALUMINUM	IP66	A158 X B56 X C60MM	
24	MAZDA-WXR346022X03W-6.5K-240V-BL-ND-A158 X B56 X C60MM	2X03W	6500	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A158 X B56 X C60MM	DIE CAST ALUMINUM	IP66	A158 X B56 X C60MM	
25	MAZDA-WXR346022X06W-3K-240V-BL-10VDIM-A158 X B56 X C60MM	2X06W	3000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A158 X B56 X C60MM	DIE CAST ALUMINUM	IP66	A158 X B56 X C60MM	
26	MAZDA-WXR346022X06W-3K-240V-BL-PH-A158 X B56 X C60MM	2X06W	3000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A158 X B56 X C60MM	DIE CAST ALUMINUM	IP66	A158 X B56 X C60MM	
27	MAZDA-WXR346022X06W-3K-240V-BL-DA-A158 X B56 X C60MM	2X06W	3000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A158 X B56 X C60MM	DIE CAST ALUMINUM	IP66	A158 X B56 X C60MM	
28	MAZDA-WXR346022X06W-3K-240V-BL-ND-A158 X B56 X C60MM	2X06W	3000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A158 X B56 X C60MM	DIE CAST ALUMINUM	IP66	A158 X B56 X C60MM	
29	MAZDA-WXR346022X06W-4K-240V-BL-10VDIM-A158 X B56 X C60MM	2X06W	4000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A158 X B56 X C60MM	DIE CAST ALUMINUM	IP66	A158 X B56 X C60MM	
30	MAZDA-WXR346022X06W-4K-240V-BL-PH-A158 X B56 X C60MM	2X06W	4000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A158 X B56 X C60MM	DIE CAST ALUMINUM	IP66	A158 X B56 X C60MM	
31	MAZDA-WXR346022X06W-4K-240V-BL-DA-A158 X B56 X C60MM	2X06W	4000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A158 X B56 X C60MM	DIE CAST ALUMINUM	IP66	A158 X B56 X C60MM	
32	MAZDA-WXR346022X06W-4K-240V-BL-ND-A158 X B56 X C60MM	2X06W	4000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A158 X B56 X C60MM	DIE CAST ALUMINUM	IP66	A158 X B56 X C60MM	
33	MAZDA-WXR346022X06W-5K-240V-BL-10VDIM-A158 X B56 X C60MM	2X06W	5000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A158 X B56 X C60MM	DIE CAST ALUMINUM	IP66	A158 X B56 X C60MM	
34	MAZDA-WXR346022X06W-5K-240V-BL-PH-A158 X B56 X C60MM	2X06W	5000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A158 X B56 X C60MM	DIE CAST ALUMINUM	IP66	A158 X B56 X C60MM	
35	MAZDA-WXR346022X06W-5K-240V-BL-DA-A158 X B56 X C60MM	2X06W	5000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A158 X B56 X C60MM	DIE CAST ALUMINUM	IP66	A158 X B56 X C60MM	
36	MAZDA-WXR346022X06W-5K-240V-BL-ND-A158 X B56 X C60MM	2X06W	5000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A158 X B56 X C60MM	DIE CAST ALUMINUM	IP66	A158 X B56 X C60MM	
37	MAZDA-WXR346022X06W-6K-240V-BL-10VDIM-A158 X B56 X C60MM	2X06W	6000	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A158 X B56 X C60MM	DIE CAST ALUMINUM	IP66	A158 X B56 X C60MM	
38	MAZDA-WXR346022X06W-6K-240V-BL-PH-A158 X B56 X C60MM	2X06W	6000	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A158 X B56 X C60MM	DIE CAST ALUMINUM	IP66	A158 X B56 X C60MM	
39	MAZDA-WXR346022X06W-6K-240V-BL-DA-A158 X B56 X C60MM	2X06W	6000	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A158 X B56 X C60MM	DIE CAST ALUMINUM	IP66	A158 X B56 X C60MM	
40	MAZDA-WXR346022X06W-6K-240V-BL-ND-A158 X B56 X C60MM	2X06W	6000	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A158 X B56 X C60MM	DIE CAST ALUMINUM	IP66	A158 X B56 X C60MM	
41	MAZDA-WXR346022X06W-2.7K-240V-BL-10VDIM-A158 X B56 X C60MM	2X06W	2700	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A158 X B56 X C60MM	DIE CAST ALUMINUM	IP66	A158 X B56 X C60MM	
42	MAZDA-WXR346022X06W-2.7K-240V-BL-PH-A158 X B56 X C60MM	2X06W	2700	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A158 X B56 X C60MM	DIE CAST ALUMINUM	IP66	A158 X B56 X C60MM	
43	MAZDA-WXR346022X06W-2.7K-240V-BL-DA-A158 X B56 X C60MM	2X06W	2700	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A158 X B56 X C60MM	DIE CAST ALUMINUM	IP66	A158 X B56 X C60MM	
44	MAZDA-WXR346022X06W-2.7K-240V-BL-ND-A158 X B56 X C60MM	2X06W	2700	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A158 X B56 X C60MM	DIE CAST ALUMINUM	IP66	A158 X B56 X C60MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
45	MAZDA-WXR346022X06W-6.5K-240V-BL-10VDIM-A158 X B56 X C60MM	2X06W	6500	240V	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A158 X B56 X C60MM	DIE CAST ALUMINUM	IP66	A158 X B56 X C60MM	
46	MAZDA-WXR346022X06W-6.5K-240V-BL-PH-A158 X B56 X C60MM	2X06W	6500	240V	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A158 X B56 X C60MM	DIE CAST ALUMINUM	IP66	A158 X B56 X C60MM	
47	MAZDA-WXR346022X06W-6.5K-240V-BL-DA-A158 X B56 X C60MM	2X06W	6500	240V	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A158 X B56 X C60MM	DIE CAST ALUMINUM	IP66	A158 X B56 X C60MM	
48	MAZDA-WXR346022X06W-6.5K-240V-BL-ND-A158 X B56 X C60MM	2X06W	6500	240V	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A158 X B56 X C60MM	DIE CAST ALUMINUM	IP66	A158 X B56 X C60MM	