



CUBE II

MAZDA Model: WSR3723 External Wall Light

The wall lamp Cube led by the Mazda LED manufacturer Light-Point is a cube from aluminium which is affixed to the wall. It is available in a choice of three classical colours. Its LED light illuminates the wall upwards and downwards. The diffusers which are adjustable by 90 degrees make it possible to vary the upwards and downwards directed diffusers. The light beams can be very concentrated, broad or very broad

ALL AVAILABLE VARIANTS

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
1	MAZDA-WSXR37232X4W-3K-240-BL-10VDIM-A165 X B130 X C123 MM	2X4W	3000	240	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A165 X B130 X C123 MM	DIE CAST ALUMINUM	IP65	A165 X B130 X C123 MM	
2	MAZDA-WSXR37232X4W-3K-240-BL-PH-A165 X B130 X C123 MM	2X4W	3000	240	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A165 X B130 X C123 MM	DIE CAST ALUMINUM	IP65	A165 X B130 X C123 MM	
3	MAZDA-WSXR37232X4W-3K-240-BL-DA-A165 X B130 X C123 MM	2X4W	3000	240	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A165 X B130 X C123 MM	DIE CAST ALUMINUM	IP65	A165 X B130 X C123 MM	
4	MAZDA-WSXR37232X4W-3K-240-BL-ND-A165 X B130 X C123 MM	2X4W	3000	240	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A165 X B130 X C123 MM	DIE CAST ALUMINUM	IP65	A165 X B130 X C123 MM	
5	MAZDA-WSXR37232X4W-4K-240-BL-10VDIM-A165 X B130 X C123 MM	2X4W	4000	240	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A165 X B130 X C123 MM	DIE CAST ALUMINUM	IP65	A165 X B130 X C123 MM	
6	MAZDA-WSXR37232X4W-4K-240-BL-PH-A165 X B130 X C123 MM	2X4W	4000	240	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A165 X B130 X C123 MM	DIE CAST ALUMINUM	IP65	A165 X B130 X C123 MM	
7	MAZDA-WSXR37232X4W-4K-240-BL-DA-A165 X B130 X C123 MM	2X4W	4000	240	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A165 X B130 X C123 MM	DIE CAST ALUMINUM	IP65	A165 X B130 X C123 MM	
8	MAZDA-WSXR37232X4W-4K-240-BL-ND-A165 X B130 X C123 MM	2X4W	4000	240	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A165 X B130 X C123 MM	DIE CAST ALUMINUM	IP65	A165 X B130 X C123 MM	
9	MAZDA-WSXR37232X4W-5K-240-BL-10VDIM-A165 X B130 X C123 MM	2X4W	5000	240	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A165 X B130 X C123 MM	DIE CAST ALUMINUM	IP65	A165 X B130 X C123 MM	
10	MAZDA-WSXR37232X4W-5K-240-BL-PH-A165 X B130 X C123 MM	2X4W	5000	240	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A165 X B130 X C123 MM	DIE CAST ALUMINUM	IP65	A165 X B130 X C123 MM	
11	MAZDA-WSXR37232X4W-5K-240-BL-DA-A165 X B130 X C123 MM	2X4W	5000	240	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A165 X B130 X C123 MM	DIE CAST ALUMINUM	IP65	A165 X B130 X C123 MM	
12	MAZDA-WSXR37232X4W-5K-240-BL-ND-A165 X B130 X C123 MM	2X4W	5000	240	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A165 X B130 X C123 MM	DIE CAST ALUMINUM	IP65	A165 X B130 X C123 MM	
13	MAZDA-WSXR37232X4W-6K-240-BL-10VDIM-A165 X B130 X C123 MM	2X4W	6000	240	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A165 X B130 X C123 MM	DIE CAST ALUMINUM	IP65	A165 X B130 X C123 MM	
14	MAZDA-WSXR37232X4W-6K-240-BL-PH-A165 X B130 X C123 MM	2X4W	6000	240	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A165 X B130 X C123 MM	DIE CAST ALUMINUM	IP65	A165 X B130 X C123 MM	
15	MAZDA-WSXR37232X4W-6K-240-BL-DA-A165 X B130 X C123 MM	2X4W	6000	240	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A165 X B130 X C123 MM	DIE CAST ALUMINUM	IP65	A165 X B130 X C123 MM	
16	MAZDA-WSXR37232X4W-6K-240-BL-ND-A165 X B130 X C123 MM	2X4W	6000	240	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A165 X B130 X C123 MM	DIE CAST ALUMINUM	IP65	A165 X B130 X C123 MM	
17	MAZDA-WSXR37232X4W-2.7K-240-BL-10VDIM-A165 X B130 X C123 MM	2X4W	2700	240	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A165 X B130 X C123 MM	DIE CAST ALUMINUM	IP65	A165 X B130 X C123 MM	
18	MAZDA-WSXR37232X4W-2.7K-240-BL-PH-A165 X B130 X C123 MM	2X4W	2700	240	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A165 X B130 X C123 MM	DIE CAST ALUMINUM	IP65	A165 X B130 X C123 MM	



DATASHEET

GENERATED ON: 16 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
19	MAZDA-WSXR37232X4W-2.7K-240-BL-DA-A165 X B130 X C123 MM	2X4W	2700	240	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A165 X B130 X C123 MM	DIE CAST ALUMINUM	IP65	A165 X B130 X C123 MM	
20	MAZDA-WSXR37232X4W-2.7K-240-BL-ND-A165 X B130 X C123 MM	2X4W	2700	240	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A165 X B130 X C123 MM	DIE CAST ALUMINUM	IP65	A165 X B130 X C123 MM	
21	MAZDA-WSXR37232X4W-6.5K-240-BL-10VDIM-A165 X B130 X C123 MM	2X4W	6500	240	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A165 X B130 X C123 MM	DIE CAST ALUMINUM	IP65	A165 X B130 X C123 MM	
22	MAZDA-WSXR37232X4W-6.5K-240-BL-PH-A165 X B130 X C123 MM	2X4W	6500	240	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A165 X B130 X C123 MM	DIE CAST ALUMINUM	IP65	A165 X B130 X C123 MM	
23	MAZDA-WSXR37232X4W-6.5K-240-BL-DA-A165 X B130 X C123 MM	2X4W	6500	240	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A165 X B130 X C123 MM	DIE CAST ALUMINUM	IP65	A165 X B130 X C123 MM	
24	MAZDA-WSXR37232X4W-6.5K-240-BL-ND-A165 X B130 X C123 MM	2X4W	6500	240	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A165 X B130 X C123 MM	DIE CAST ALUMINUM	IP65	A165 X B130 X C123 MM	
25	MAZDA-WSXR37232X7.5W-3K-240-BL-10VDIM-A165 X B130 X C123 MM	2X7.5W	3000	240	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A165 X B130 X C123 MM	DIE CAST ALUMINUM	IP65	A165 X B130 X C123 MM	
26	MAZDA-WSXR37232X7.5W-3K-240-BL-PH-A165 X B130 X C123 MM	2X7.5W	3000	240	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A165 X B130 X C123 MM	DIE CAST ALUMINUM	IP65	A165 X B130 X C123 MM	
27	MAZDA-WSXR37232X7.5W-3K-240-BL-DA-A165 X B130 X C123 MM	2X7.5W	3000	240	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A165 X B130 X C123 MM	DIE CAST ALUMINUM	IP65	A165 X B130 X C123 MM	
28	MAZDA-WSXR37232X7.5W-3K-240-BL-ND-A165 X B130 X C123 MM	2X7.5W	3000	240	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A165 X B130 X C123 MM	DIE CAST ALUMINUM	IP65	A165 X B130 X C123 MM	
29	MAZDA-WSXR37232X7.5W-4K-240-BL-10VDIM-A165 X B130 X C123 MM	2X7.5W	4000	240	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A165 X B130 X C123 MM	DIE CAST ALUMINUM	IP65	A165 X B130 X C123 MM	
30	MAZDA-WSXR37232X7.5W-4K-240-BL-PH-A165 X B130 X C123 MM	2X7.5W	4000	240	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A165 X B130 X C123 MM	DIE CAST ALUMINUM	IP65	A165 X B130 X C123 MM	
31	MAZDA-WSXR37232X7.5W-4K-240-BL-DA-A165 X B130 X C123 MM	2X7.5W	4000	240	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A165 X B130 X C123 MM	DIE CAST ALUMINUM	IP65	A165 X B130 X C123 MM	
32	MAZDA-WSXR37232X7.5W-4K-240-BL-ND-A165 X B130 X C123 MM	2X7.5W	4000	240	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A165 X B130 X C123 MM	DIE CAST ALUMINUM	IP65	A165 X B130 X C123 MM	
33	MAZDA-WSXR37232X7.5W-5K-240-BL-10VDIM-A165 X B130 X C123 MM	2X7.5W	5000	240	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A165 X B130 X C123 MM	DIE CAST ALUMINUM	IP65	A165 X B130 X C123 MM	
34	MAZDA-WSXR37232X7.5W-5K-240-BL-PH-A165 X B130 X C123 MM	2X7.5W	5000	240	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A165 X B130 X C123 MM	DIE CAST ALUMINUM	IP65	A165 X B130 X C123 MM	
35	MAZDA-WSXR37232X7.5W-5K-240-BL-DA-A165 X B130 X C123 MM	2X7.5W	5000	240	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A165 X B130 X C123 MM	DIE CAST ALUMINUM	IP65	A165 X B130 X C123 MM	
36	MAZDA-WSXR37232X7.5W-5K-240-BL-ND-A165 X B130 X C123 MM	2X7.5W	5000	240	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A165 X B130 X C123 MM	DIE CAST ALUMINUM	IP65	A165 X B130 X C123 MM	
37	MAZDA-WSXR37232X7.5W-6K-240-BL-10VDIM-A165 X B130 X C123 MM	2X7.5W	6000	240	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A165 X B130 X C123 MM	DIE CAST ALUMINUM	IP65	A165 X B130 X C123 MM	
38	MAZDA-WSXR37232X7.5W-6K-240-BL-PH-A165 X B130 X C123 MM	2X7.5W	6000	240	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A165 X B130 X C123 MM	DIE CAST ALUMINUM	IP65	A165 X B130 X C123 MM	
39	MAZDA-WSXR37232X7.5W-6K-240-BL-DA-A165 X B130 X C123 MM	2X7.5W	6000	240	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A165 X B130 X C123 MM	DIE CAST ALUMINUM	IP65	A165 X B130 X C123 MM	
40	MAZDA-WSXR37232X7.5W-6K-240-BL-ND-A165 X B130 X C123 MM	2X7.5W	6000	240	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A165 X B130 X C123 MM	DIE CAST ALUMINUM	IP65	A165 X B130 X C123 MM	
41	MAZDA-WSXR37232X7.5W-2.7K-240-BL-10VDIM-A165 X B130 X C123 MM	2X7.5W	2700	240	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A165 X B130 X C123 MM	DIE CAST ALUMINUM	IP65	A165 X B130 X C123 MM	
42	MAZDA-WSXR37232X7.5W-2.7K-240-BL-PH-A165 X B130 X C123 MM	2X7.5W	2700	240	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A165 X B130 X C123 MM	DIE CAST ALUMINUM	IP65	A165 X B130 X C123 MM	
43	MAZDA-WSXR37232X7.5W-2.7K-240-BL-DA-A165 X B130 X C123 MM	2X7.5W	2700	240	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A165 X B130 X C123 MM	DIE CAST ALUMINUM	IP65	A165 X B130 X C123 MM	
44	MAZDA-WSXR37232X7.5W-2.7K-240-BL-ND-A165 X B130 X C123 MM	2X7.5W	2700	240	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A165 X B130 X C123 MM	DIE CAST ALUMINUM	IP65	A165 X B130 X C123 MM	
45	MAZDA-WSXR37232X7.5W-6.5K-240-BL-10VDIM-A165 X B130 X C123 MM	2X7.5W	6500	240	BLACK & WHITE	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A165 X B130 X C123 MM	DIE CAST ALUMINUM	IP65	A165 X B130 X C123 MM	
46	MAZDA-WSXR37232X7.5W-6.5K-240-BL-PH-A165 X B130 X C123 MM	2X7.5W	6500	240	BLACK & WHITE	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A165 X B130 X C123 MM	DIE CAST ALUMINUM	IP65	A165 X B130 X C123 MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
47	MAZDA-WSXR37232X7.5W-6.5K-240-BL-DA-A165 X B130 X C123 MM	2X7.5W	6500	240	BLACK & WHITE	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A165 X B130 X C123 MM	DIE CAST ALUMINUM	IP65	A165 X B130 X C123 MM	
48	MAZDA-WSXR37232X7.5W-6.5K-240-BL-ND-A165 X B130 X C123 MM	2X7.5W	6500	240	BLACK & WHITE	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A165 X B130 X C123 MM	DIE CAST ALUMINUM	IP65	A165 X B130 X C123 MM	