



MARRY

MAZDA Model: LLXR5060 Wall Washer Light

High power LED wall washer light, fashion and beautiful appearance, with the design of increasing heat dissipation to fully ensure the stability and long lifespan of LED fixture. The light body adopts 6063 aluminum alloy molding, surface with anodizing treatment, lampshade adopts high strength toughened glass, resist the impact and friction, has excellent rainwater clean ability. LED light source, high flux output, excellent consistency of light color, constant current driver with PWM grey control installed inside, RGB gray level can reach to 65,536 degree equally, make the dynamic light-dimmer more softer and color richer. Powerful DMX512 interface adopts high reliable bus connect, all has the function of automatic addressing

ALL AVAILABLE VARIANTS

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
1	MAZDA-LLXR506027W-3K-240V-GRY-10VDIM-A1000 X B38 X C52MM	27W	3000	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
2	MAZDA-LLXR506027W-3K-240V-GRY-PH-A1000 X B38 X C52MM	27W	3000	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
3	MAZDA-LLXR506027W-3K-240V-GRY-DA-A1000 X B38 X C52MM	27W	3000	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
4	MAZDA-LLXR506027W-3K-240V-GRY-ND-A1000 X B38 X C52MM	27W	3000	240V	GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
5	MAZDA-LLXR506027W-4K-240V-GRY-10VDIM-A1000 X B38 X C52MM	27W	4000	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
6	MAZDA-LLXR506027W-4K-240V-GRY-PH-A1000 X B38 X C52MM	27W	4000	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
7	MAZDA-LLXR506027W-4K-240V-GRY-DA-A1000 X B38 X C52MM	27W	4000	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
8	MAZDA-LLXR506027W-4K-240V-GRY-ND-A1000 X B38 X C52MM	27W	4000	240V	GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
9	MAZDA-LLXR506027W-5K-240V-GRY-10VDIM-A1000 X B38 X C52MM	27W	5000	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
10	MAZDA-LLXR506027W-5K-240V-GRY-PH-A1000 X B38 X C52MM	27W	5000	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
11	MAZDA-LLXR506027W-5K-240V-GRY-DA-A1000 X B38 X C52MM	27W	5000	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
12	MAZDA-LLXR506027W-5K-240V-GRY-ND-A1000 X B38 X C52MM	27W	5000	240V	GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
13	MAZDA-LLXR506027W-6K-240V-GRY-10VDIM-A1000 X B38 X C52MM	27W	6000	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
14	MAZDA-LLXR506027W-6K-240V-GRY-PH-A1000 X B38 X C52MM	27W	6000	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
15	MAZDA-LLXR506027W-6K-240V-GRY-DA-A1000 X B38 X C52MM	27W	6000	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
16	MAZDA-LLXR506027W-6K-240V-GRY-ND-A1000 X B38 X C52MM	27W	6000	240V	GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
17	MAZDA-LLXR506027W-2.7K-240V-GRY-10VDIM-A1000 X B38 X C52MM	27W	2700	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	



#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
18	MAZDA-LLXR506027W-2.7K-240V-GRY-PH-A1000 X B38 X C52MM	27W	2700	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
19	MAZDA-LLXR506027W-2.7K-240V-GRY-DA-A1000 X B38 X C52MM	27W	2700	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
20	MAZDA-LLXR506027W-2.7K-240V-GRY-ND-A1000 X B38 X C52MM	27W	2700	240V	GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
21	MAZDA-LLXR506027W-6.5K-240V-GRY-10VDIM-A1000 X B38 X C52MM	27W	6500	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
22	MAZDA-LLXR506027W-6.5K-240V-GRY-PH-A1000 X B38 X C52MM	27W	6500	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
23	MAZDA-LLXR506027W-6.5K-240V-GRY-DA-A1000 X B38 X C52MM	27W	6500	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
24	MAZDA-LLXR506027W-6.5K-240V-GRY-ND-A1000 X B38 X C52MM	27W	6500	240V	GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
25	MAZDA-LLXR506054W-3K-240V-GRY-10VDIM-A1000 X B38 X C52MM	54W	3000	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
26	MAZDA-LLXR506054W-3K-240V-GRY-PH-A1000 X B38 X C52MM	54W	3000	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
27	MAZDA-LLXR506054W-3K-240V-GRY-DA-A1000 X B38 X C52MM	54W	3000	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
28	MAZDA-LLXR506054W-3K-240V-GRY-ND-A1000 X B38 X C52MM	54W	3000	240V	GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
29	MAZDA-LLXR506054W-4K-240V-GRY-10VDIM-A1000 X B38 X C52MM	54W	4000	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
30	MAZDA-LLXR506054W-4K-240V-GRY-PH-A1000 X B38 X C52MM	54W	4000	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
31	MAZDA-LLXR506054W-4K-240V-GRY-DA-A1000 X B38 X C52MM	54W	4000	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
32	MAZDA-LLXR506054W-4K-240V-GRY-ND-A1000 X B38 X C52MM	54W	4000	240V	GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
33	MAZDA-LLXR506054W-5K-240V-GRY-10VDIM-A1000 X B38 X C52MM	54W	5000	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
34	MAZDA-LLXR506054W-5K-240V-GRY-PH-A1000 X B38 X C52MM	54W	5000	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
35	MAZDA-LLXR506054W-5K-240V-GRY-DA-A1000 X B38 X C52MM	54W	5000	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
36	MAZDA-LLXR506054W-5K-240V-GRY-ND-A1000 X B38 X C52MM	54W	5000	240V	GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
37	MAZDA-LLXR506054W-6K-240V-GRY-10VDIM-A1000 X B38 X C52MM	54W	6000	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
38	MAZDA-LLXR506054W-6K-240V-GRY-PH-A1000 X B38 X C52MM	54W	6000	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
39	MAZDA-LLXR506054W-6K-240V-GRY-DA-A1000 X B38 X C52MM	54W	6000	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
40	MAZDA-LLXR506054W-6K-240V-GRY-ND-A1000 X B38 X C52MM	54W	6000	240V	GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
41	MAZDA-LLXR506054W-2.7K-240V-GRY-10VDIM-A1000 X B38 X C52MM	54W	2700	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
42	MAZDA-LLXR506054W-2.7K-240V-GRY-PH-A1000 X B38 X C52MM	54W	2700	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
43	MAZDA-LLXR506054W-2.7K-240V-GRY-DA-A1000 X B38 X C52MM	54W	2700	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
44	MAZDA-LLXR506054W-2.7K-240V-GRY-ND-A1000 X B38 X C52MM	54W	2700	240V	GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	



DATASHEET

GENERATED ON: 22 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
45	MAZDA-LLXR506054W-6.5K-240V-GRY-10VDIM-A1000 X B38 X C52MM	54W	6500	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
46	MAZDA-LLXR506054W-6.5K-240V-GRY-PH-A1000 X B38 X C52MM	54W	6500	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
47	MAZDA-LLXR506054W-6.5K-240V-GRY-DA-A1000 X B38 X C52MM	54W	6500	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
48	MAZDA-LLXR506054W-6.5K-240V-GRY-ND-A1000 X B38 X C52MM	54W	6500	240V	GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
49	MAZDA-LLXR506081W-3K-240V-GRY-10VDIM-A1000 X B38 X C52MM	81W	3000	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
50	MAZDA-LLXR506081W-3K-240V-GRY-PH-A1000 X B38 X C52MM	81W	3000	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
51	MAZDA-LLXR506081W-3K-240V-GRY-DA-A1000 X B38 X C52MM	81W	3000	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
52	MAZDA-LLXR506081W-3K-240V-GRY-ND-A1000 X B38 X C52MM	81W	3000	240V	GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
53	MAZDA-LLXR506081W-4K-240V-GRY-10VDIM-A1000 X B38 X C52MM	81W	4000	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
54	MAZDA-LLXR506081W-4K-240V-GRY-PH-A1000 X B38 X C52MM	81W	4000	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
55	MAZDA-LLXR506081W-4K-240V-GRY-DA-A1000 X B38 X C52MM	81W	4000	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
56	MAZDA-LLXR506081W-4K-240V-GRY-ND-A1000 X B38 X C52MM	81W	4000	240V	GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
57	MAZDA-LLXR506081W-5K-240V-GRY-10VDIM-A1000 X B38 X C52MM	81W	5000	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
58	MAZDA-LLXR506081W-5K-240V-GRY-PH-A1000 X B38 X C52MM	81W	5000	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
59	MAZDA-LLXR506081W-5K-240V-GRY-DA-A1000 X B38 X C52MM	81W	5000	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
60	MAZDA-LLXR506081W-5K-240V-GRY-ND-A1000 X B38 X C52MM	81W	5000	240V	GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
61	MAZDA-LLXR506081W-6K-240V-GRY-10VDIM-A1000 X B38 X C52MM	81W	6000	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
62	MAZDA-LLXR506081W-6K-240V-GRY-PH-A1000 X B38 X C52MM	81W	6000	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
63	MAZDA-LLXR506081W-6K-240V-GRY-DA-A1000 X B38 X C52MM	81W	6000	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
64	MAZDA-LLXR506081W-6K-240V-GRY-ND-A1000 X B38 X C52MM	81W	6000	240V	GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
65	MAZDA-LLXR506081W-2.7K-240V-GRY-10VDIM-A1000 X B38 X C52MM	81W	2700	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
66	MAZDA-LLXR506081W-2.7K-240V-GRY-PH-A1000 X B38 X C52MM	81W	2700	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
67	MAZDA-LLXR506081W-2.7K-240V-GRY-DA-A1000 X B38 X C52MM	81W	2700	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
68	MAZDA-LLXR506081W-2.7K-240V-GRY-ND-A1000 X B38 X C52MM	81W	2700	240V	GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
69	MAZDA-LLXR506081W-6.5K-240V-GRY-10VDIM-A1000 X B38 X C52MM	81W	6500	240V	GREY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
70	MAZDA-LLXR506081W-6.5K-240V-GRY-PH-A1000 X B38 X C52MM	81W	6500	240V	GREY	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	
71	MAZDA-LLXR506081W-6.5K-240V-GRY-DA-A1000 X B38 X C52MM	81W	6500	240V	GREY	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
72	MAZDA-LLXR506081W-6.5K-240V-GRY-ND-A1000 X B38 X C52MM	81W	6500	240V	GREY	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A1000 X B38 X C52MM	DIE CAST ALUMINUM	IP67	A1000 X B38 X C52MM	