



LESLIE

MAZDA Model: LLXR5040 Wall Washer Light

Leslie Wall Washer is 24VDC IP67 protected and IK10 linear LED luminaire for indoor and outdoor in-ground installation. It featured Entirely made of stainless steel 316Ti (resistant to corrosion) for lamp housing, built-in aluminum heat sink. Available in standard length 500mm or 1000mm, or customized length. Suitable for installation into roads, garden and parking lots. it is Anti skid toughened safety glass (ESG)-withstands loads of up to 5000KG. Delivered with male / female IP68 connectors

ALL AVAILABLE VARIANTS

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
1	MAZDA-LLXR504012W-3K-DC24V-BL-10VDIM-A500 X B95 X C65.4 MM	12W	3000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A500 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A500 X B95 X C65.4 MM	
2	MAZDA-LLXR504012W-3K-DC24V-BL-PH-A500 X B95 X C65.4 MM	12W	3000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A500 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A500 X B95 X C65.4 MM	
3	MAZDA-LLXR504012W-3K-DC24V-BL-DA-A500 X B95 X C65.4 MM	12W	3000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A500 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A500 X B95 X C65.4 MM	
4	MAZDA-LLXR504012W-3K-DC24V-BL-ND-A500 X B95 X C65.4 MM	12W	3000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A500 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A500 X B95 X C65.4 MM	
5	MAZDA-LLXR504012W-4K-DC24V-BL-10VDIM-A500 X B95 X C65.4 MM	12W	4000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A500 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A500 X B95 X C65.4 MM	
6	MAZDA-LLXR504012W-4K-DC24V-BL-PH-A500 X B95 X C65.4 MM	12W	4000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A500 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A500 X B95 X C65.4 MM	
7	MAZDA-LLXR504012W-4K-DC24V-BL-DA-A500 X B95 X C65.4 MM	12W	4000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A500 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A500 X B95 X C65.4 MM	
8	MAZDA-LLXR504012W-4K-DC24V-BL-ND-A500 X B95 X C65.4 MM	12W	4000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A500 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A500 X B95 X C65.4 MM	
9	MAZDA-LLXR504012W-5K-DC24V-BL-10VDIM-A500 X B95 X C65.4 MM	12W	5000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A500 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A500 X B95 X C65.4 MM	
10	MAZDA-LLXR504012W-5K-DC24V-BL-PH-A500 X B95 X C65.4 MM	12W	5000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A500 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A500 X B95 X C65.4 MM	
11	MAZDA-LLXR504012W-5K-DC24V-BL-DA-A500 X B95 X C65.4 MM	12W	5000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A500 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A500 X B95 X C65.4 MM	
12	MAZDA-LLXR504012W-5K-DC24V-BL-ND-A500 X B95 X C65.4 MM	12W	5000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A500 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A500 X B95 X C65.4 MM	
13	MAZDA-LLXR504012W-6K-DC24V-BL-10VDIM-A500 X B95 X C65.4 MM	12W	6000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A500 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A500 X B95 X C65.4 MM	
14	MAZDA-LLXR504012W-6K-DC24V-BL-PH-A500 X B95 X C65.4 MM	12W	6000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A500 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A500 X B95 X C65.4 MM	
15	MAZDA-LLXR504012W-6K-DC24V-BL-DA-A500 X B95 X C65.4 MM	12W	6000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A500 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A500 X B95 X C65.4 MM	
16	MAZDA-LLXR504012W-6K-DC24V-BL-ND-A500 X B95 X C65.4 MM	12W	6000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A500 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A500 X B95 X C65.4 MM	
17	MAZDA-LLXR504012W-6.5K-DC24V-BL-10VDIM-A500 X B95 X C65.4 MM	12W	6500	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A500 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A500 X B95 X C65.4 MM	
18	MAZDA-LLXR504012W-6.5K-DC24V-BL-PH-A500 X B95 X C65.4 MM	12W	6500	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A500 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A500 X B95 X C65.4 MM	



#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angle	Dimension	Material	IP	Dimensions	Price
19	MAZDA-LLXR504012W-6.5K-DC24V-BL-DA-A500 X B95 X C65.4 MM	12W	6500	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A500 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A500 X B95 X C65.4 MM	
20	MAZDA-LLXR504012W-6.5K-DC24V-BL-ND-A500 X B95 X C65.4 MM	12W	6500	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A500 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A500 X B95 X C65.4 MM	
21	MAZDA-LLXR504012W-2.7K-DC24V-BL-10VDIM-A500 X B95 X C65.4 MM	12W	2700	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A500 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A500 X B95 X C65.4 MM	
22	MAZDA-LLXR504012W-2.7K-DC24V-BL-PH-A500 X B95 X C65.4 MM	12W	2700	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A500 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A500 X B95 X C65.4 MM	
23	MAZDA-LLXR504012W-2.7K-DC24V-BL-DA-A500 X B95 X C65.4 MM	12W	2700	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A500 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A500 X B95 X C65.4 MM	
24	MAZDA-LLXR504012W-2.7K-DC24V-BL-ND-A500 X B95 X C65.4 MM	12W	2700	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A500 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A500 X B95 X C65.4 MM	
25	MAZDA-LLXR504024W-3K-DC24V-BL-10VDIM-A500 X B95 X C65.4 MM	24W	3000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A500 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A500 X B95 X C65.4 MM	
26	MAZDA-LLXR504024W-3K-DC24V-BL-PH-A500 X B95 X C65.4 MM	24W	3000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A500 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A500 X B95 X C65.4 MM	
27	MAZDA-LLXR504024W-3K-DC24V-BL-DA-A500 X B95 X C65.4 MM	24W	3000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A500 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A500 X B95 X C65.4 MM	
28	MAZDA-LLXR504024W-3K-DC24V-BL-ND-A500 X B95 X C65.4 MM	24W	3000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A500 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A500 X B95 X C65.4 MM	
29	MAZDA-LLXR504024W-4K-DC24V-BL-10VDIM-A500 X B95 X C65.4 MM	24W	4000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A500 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A500 X B95 X C65.4 MM	
30	MAZDA-LLXR504024W-4K-DC24V-BL-PH-A500 X B95 X C65.4 MM	24W	4000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A500 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A500 X B95 X C65.4 MM	
31	MAZDA-LLXR504024W-4K-DC24V-BL-DA-A500 X B95 X C65.4 MM	24W	4000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A500 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A500 X B95 X C65.4 MM	
32	MAZDA-LLXR504024W-4K-DC24V-BL-ND-A500 X B95 X C65.4 MM	24W	4000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A500 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A500 X B95 X C65.4 MM	
33	MAZDA-LLXR504024W-5K-DC24V-BL-10VDIM-A500 X B95 X C65.4 MM	24W	5000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A500 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A500 X B95 X C65.4 MM	
34	MAZDA-LLXR504024W-5K-DC24V-BL-PH-A500 X B95 X C65.4 MM	24W	5000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A500 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A500 X B95 X C65.4 MM	
35	MAZDA-LLXR504024W-5K-DC24V-BL-DA-A500 X B95 X C65.4 MM	24W	5000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A500 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A500 X B95 X C65.4 MM	
36	MAZDA-LLXR504024W-5K-DC24V-BL-ND-A500 X B95 X C65.4 MM	24W	5000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A500 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A500 X B95 X C65.4 MM	
37	MAZDA-LLXR504024W-6K-DC24V-BL-10VDIM-A500 X B95 X C65.4 MM	24W	6000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A500 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A500 X B95 X C65.4 MM	
38	MAZDA-LLXR504024W-6K-DC24V-BL-PH-A500 X B95 X C65.4 MM	24W	6000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A500 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A500 X B95 X C65.4 MM	
39	MAZDA-LLXR504024W-6K-DC24V-BL-DA-A500 X B95 X C65.4 MM	24W	6000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A500 X B95 X C65.4 MM	DIE CAST AL			



DATASHEET

GENERATED ON: 22 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
47	MAZDA-LLXR504024W-2.7K-DC24V-BL-DA-A500 X B95 X C65.4 MM	24W	2700	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A500 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A500 X B95 X C65.4 MM	
48	MAZDA-LLXR504024W-2.7K-DC24V-BL-ND-A500 X B95 X C65.4 MM	24W	2700	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A500 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A500 X B95 X C65.4 MM	
49	MAZDA-LLXR504035W-3K-DC24V-BL-10VDIM-A1000 X B95 X C65.4 MM	35W	3000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A1000 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A1000 X B95 X C65.4 MM	
50	MAZDA-LLXR504035W-3K-DC24V-BL-PH-A1000 X B95 X C65.4 MM	35W	3000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A1000 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A1000 X B95 X C65.4 MM	
51	MAZDA-LLXR504035W-3K-DC24V-BL-DA-A1000 X B95 X C65.4 MM	35W	3000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A1000 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A1000 X B95 X C65.4 MM	
52	MAZDA-LLXR504035W-3K-DC24V-BL-ND-A1000 X B95 X C65.4 MM	35W	3000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A1000 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A1000 X B95 X C65.4 MM	
53	MAZDA-LLXR504035W-4K-DC24V-BL-10VDIM-A1000 X B95 X C65.4 MM	35W	4000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A1000 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A1000 X B95 X C65.4 MM	
54	MAZDA-LLXR504035W-4K-DC24V-BL-PH-A1000 X B95 X C65.4 MM	35W	4000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A1000 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A1000 X B95 X C65.4 MM	
55	MAZDA-LLXR504035W-4K-DC24V-BL-DA-A1000 X B95 X C65.4 MM	35W	4000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A1000 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A1000 X B95 X C65.4 MM	
56	MAZDA-LLXR504035W-4K-DC24V-BL-ND-A1000 X B95 X C65.4 MM	35W	4000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A1000 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A1000 X B95 X C65.4 MM	
57	MAZDA-LLXR504035W-5K-DC24V-BL-10VDIM-A1000 X B95 X C65.4 MM	35W	5000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A1000 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A1000 X B95 X C65.4 MM	
58	MAZDA-LLXR504035W-5K-DC24V-BL-PH-A1000 X B95 X C65.4 MM	35W	5000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A1000 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A1000 X B95 X C65.4 MM	
59	MAZDA-LLXR504035W-5K-DC24V-BL-DA-A1000 X B95 X C65.4 MM	35W	5000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A1000 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A1000 X B95 X C65.4 MM	
60	MAZDA-LLXR504035W-5K-DC24V-BL-ND-A1000 X B95 X C65.4 MM	35W	5000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A1000 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A1000 X B95 X C65.4 MM	
61	MAZDA-LLXR504035W-6K-DC24V-BL-10VDIM-A1000 X B95 X C65.4 MM	35W	6000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A1000 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A1000 X B95 X C65.4 MM	
62	MAZDA-LLXR504035W-6K-DC24V-BL-PH-A1000 X B95 X C65.4 MM	35W	6000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A1000 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A1000 X B95 X C65.4 MM	
63	MAZDA-LLXR504035W-6K-DC24V-BL-DA-A1000 X B95 X C65.4 MM	35W	6000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A1000 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A1000 X B95 X C65.4 MM	
64	MAZDA-LLXR504035W-6K-DC24V-BL-ND-A1000 X B95 X C65.4 MM	35W	6000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A1000 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A1000 X B95 X C65.4 MM	
65	MAZDA-LLXR504035W-6.5K-DC24V-BL-10VDIM-A1000 X B95 X C65.4 MM	35W	6500	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A1000 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A1000 X B95 X C65.4 MM	
66	MAZDA-LLXR504035W-6.5K-DC24V-BL-PH-A1000 X B95 X C65.4 MM	35W	6500	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A1000 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A1000 X B95 X C65.4 MM	
67	MAZDA-LLXR504035W-6.5K-DC24V-BL-DA-A1000 X B95 X C65.4 MM	35W	6500	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A1000 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A1000 X B95 X C65.4 MM	
68	MAZDA-LLXR504035W-6.5K-DC24V-BL-ND-A1000 X B95 X C65.4 MM	35W	6500	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A1000 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A1000 X B95 X C65.4 MM	
69	MAZDA-LLXR504035W-2.7K-DC24V-BL-10VDIM-A1000 X B95 X C65.4 MM	35W	2700	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A1000 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A1000 X B95 X C65.4 MM	
70	MAZDA-LLXR504035W-2.7K-DC24V-BL-PH-A1000 X B95 X C65.4 MM	35W	2700	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A1000 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A1000 X B95 X C65.4 MM	
71	MAZDA-LLXR504035W-2.7K-DC24V-BL-DA-A1000 X B95 X C65.4 MM	35W	2700	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A1000 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A1000 X B95 X C65.4 MM	
72	MAZDA-LLXR504035W-2.7K-DC24V-BL-ND-A1000 X B95 X C65.4 MM	35W	2700	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A1000 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A1000 X B95 X C65.4 MM	
73	MAZDA-LLXR504048W-3K-DC24V-BL-10VDIM-A1000 X B95 X C65.4 MM	48W	3000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A1000 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A1000 X B95 X C65.4 MM	
74	MAZDA-LLXR504048W-3K-DC24V-BL-PH-A1000 X B95 X C65.4 MM	48W	3000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A1000 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A1000 X B95 X C65.4 MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
75	MAZDA-LLXR504048W-3K-DC24V-BL-DA-A1000 X B95 X C65.4 MM	48W	3000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A1000 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A1000 X B95 X C65.4 MM	
76	MAZDA-LLXR504048W-3K-DC24V-BL-ND-A1000 X B95 X C65.4 MM	48W	3000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A1000 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A1000 X B95 X C65.4 MM	
77	MAZDA-LLXR504048W-4K-DC24V-BL-10VDIM-A1000 X B95 X C65.4 MM	48W	4000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A1000 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A1000 X B95 X C65.4 MM	
78	MAZDA-LLXR504048W-4K-DC24V-BL-PH-A1000 X B95 X C65.4 MM	48W	4000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A1000 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A1000 X B95 X C65.4 MM	
79	MAZDA-LLXR504048W-4K-DC24V-BL-DA-A1000 X B95 X C65.4 MM	48W	4000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A1000 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A1000 X B95 X C65.4 MM	
80	MAZDA-LLXR504048W-4K-DC24V-BL-ND-A1000 X B95 X C65.4 MM	48W	4000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A1000 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A1000 X B95 X C65.4 MM	
81	MAZDA-LLXR504048W-5K-DC24V-BL-10VDIM-A1000 X B95 X C65.4 MM	48W	5000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A1000 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A1000 X B95 X C65.4 MM	
82	MAZDA-LLXR504048W-5K-DC24V-BL-PH-A1000 X B95 X C65.4 MM	48W	5000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A1000 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A1000 X B95 X C65.4 MM	
83	MAZDA-LLXR504048W-5K-DC24V-BL-DA-A1000 X B95 X C65.4 MM	48W	5000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A1000 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A1000 X B95 X C65.4 MM	
84	MAZDA-LLXR504048W-5K-DC24V-BL-ND-A1000 X B95 X C65.4 MM	48W	5000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A1000 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A1000 X B95 X C65.4 MM	
85	MAZDA-LLXR504048W-6K-DC24V-BL-10VDIM-A1000 X B95 X C65.4 MM	48W	6000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A1000 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A1000 X B95 X C65.4 MM	
86	MAZDA-LLXR504048W-6K-DC24V-BL-PH-A1000 X B95 X C65.4 MM	48W	6000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A1000 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A1000 X B95 X C65.4 MM	
87	MAZDA-LLXR504048W-6K-DC24V-BL-DA-A1000 X B95 X C65.4 MM	48W	6000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A1000 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A1000 X B95 X C65.4 MM	
88	MAZDA-LLXR504048W-6K-DC24V-BL-ND-A1000 X B95 X C65.4 MM	48W	6000	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A1000 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A1000 X B95 X C65.4 MM	
89	MAZDA-LLXR504048W-6.5K-DC24V-BL-10VDIM-A1000 X B95 X C65.4 MM	48W	6500	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A1000 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A1000 X B95 X C65.4 MM	
90	MAZDA-LLXR504048W-6.5K-DC24V-BL-PH-A1000 X B95 X C65.4 MM	48W	6500	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A1000 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A1000 X B95 X C65.4 MM	
91	MAZDA-LLXR504048W-6.5K-DC24V-BL-DA-A1000 X B95 X C65.4 MM	48W	6500	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A1000 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A1000 X B95 X C65.4 MM	
92	MAZDA-LLXR504048W-6.5K-DC24V-BL-ND-A1000 X B95 X C65.4 MM	48W	6500	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A1000 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A1000 X B95 X C65.4 MM	
93	MAZDA-LLXR504048W-2.7K-DC24V-BL-10VDIM-A1000 X B95 X C65.4 MM	48W	2700	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A1000 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A1000 X B95 X C65.4 MM	
94	MAZDA-LLXR504048W-2.7K-DC24V-BL-PH-A1000 X B95 X C65.4 MM	48W	2700	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A1000 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A1000 X B95 X C65.4 MM	
95	MAZDA-LLXR504048W-2.7K-DC24V-BL-DA-A1000 X B95 X C65.4 MM	48W	2700	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A1000 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A1000 X B95 X C65.4 MM	
96	MAZDA-LLXR504048W-2.7K-DC24V-BL-ND-A1000 X B95 X C65.4 MM	48W	2700	DC24V	BLACK / STAINLESS STEEL	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A1000 X B95 X C65.4 MM	DIE CAST ALUMINUM	IP67	A1000 X B95 X C65.4 MM	