



LANA

MAZDA Model: LLXR5045 Wall Washer Light

Lana is a flush mounted recessed linear lighting fixture housing is entirely made of aviation Aluminium 6063 with anti skid toughened safety tempered glass diffuser that can withstand loads of up to 1000KG. Protection system IP67.

ALL AVAILABLE VARIANTS

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
1	MAZDA-LLXR504509W-3K-DC24V-ST-10VDIM-A360 X B85 X C105 MM	09W	3000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A360 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A360 X B85 X C105 MM	
2	MAZDA-LLXR504509W-3K-DC24V-ST-PH-A360 X B85 X C105 MM	09W	3000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A360 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A360 X B85 X C105 MM	
3	MAZDA-LLXR504509W-3K-DC24V-ST-DA-A360 X B85 X C105 MM	09W	3000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A360 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A360 X B85 X C105 MM	
4	MAZDA-LLXR504509W-3K-DC24V-ST-ND-A360 X B85 X C105 MM	09W	3000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A360 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A360 X B85 X C105 MM	
5	MAZDA-LLXR504509W-4K-DC24V-ST-10VDIM-A360 X B85 X C105 MM	09W	4000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A360 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A360 X B85 X C105 MM	
6	MAZDA-LLXR504509W-4K-DC24V-ST-PH-A360 X B85 X C105 MM	09W	4000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A360 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A360 X B85 X C105 MM	
7	MAZDA-LLXR504509W-4K-DC24V-ST-DA-A360 X B85 X C105 MM	09W	4000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A360 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A360 X B85 X C105 MM	
8	MAZDA-LLXR504509W-4K-DC24V-ST-ND-A360 X B85 X C105 MM	09W	4000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A360 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A360 X B85 X C105 MM	
9	MAZDA-LLXR504509W-5K-DC24V-ST-10VDIM-A360 X B85 X C105 MM	09W	5000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A360 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A360 X B85 X C105 MM	
10	MAZDA-LLXR504509W-5K-DC24V-ST-PH-A360 X B85 X C105 MM	09W	5000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A360 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A360 X B85 X C105 MM	
11	MAZDA-LLXR504509W-5K-DC24V-ST-DA-A360 X B85 X C105 MM	09W	5000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A360 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A360 X B85 X C105 MM	
12	MAZDA-LLXR504509W-5K-DC24V-ST-ND-A360 X B85 X C105 MM	09W	5000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A360 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A360 X B85 X C105 MM	
13	MAZDA-LLXR504509W-6K-DC24V-ST-10VDIM-A360 X B85 X C105 MM	09W	6000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A360 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A360 X B85 X C105 MM	
14	MAZDA-LLXR504509W-6K-DC24V-ST-PH-A360 X B85 X C105 MM	09W	6000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A360 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A360 X B85 X C105 MM	
15	MAZDA-LLXR504509W-6K-DC24V-ST-DA-A360 X B85 X C105 MM	09W	6000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A360 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A360 X B85 X C105 MM	
16	MAZDA-LLXR504509W-6K-DC24V-ST-ND-A360 X B85 X C105 MM	09W	6000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A360 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A360 X B85 X C105 MM	
17	MAZDA-LLXR504509W-2.7K-DC24V-ST-10VDIM-A360 X B85 X C105 MM	09W	2700	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A360 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A360 X B85 X C105 MM	
18	MAZDA-LLXR504509W-2.7K-DC24V-ST-PH-A360 X B85 X C105 MM	09W	2700	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A360 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A360 X B85 X C105 MM	
19	MAZDA-LLXR504509W-2.7K-DC24V-ST-DA-A360 X B85 X C105 MM	09W	2700	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A360 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A360 X B85 X C105 MM	



DATASHEET

GENERATED ON: 22 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
20	MAZDA-LLXR504509W-2.7K-DC24V-ST-ND-A360 X B85 X C105 MM	09W	2700	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A360 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A360 X B85 X C105 MM	
21	MAZDA-LLXR504509W-6.5K-DC24V-ST-10VDIM-A360 X B85 X C105 MM	09W	6500	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A360 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A360 X B85 X C105 MM	
22	MAZDA-LLXR504509W-6.5K-DC24V-ST-PH-A360 X B85 X C105 MM	09W	6500	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A360 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A360 X B85 X C105 MM	
23	MAZDA-LLXR504509W-6.5K-DC24V-ST-DA-A360 X B85 X C105 MM	09W	6500	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A360 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A360 X B85 X C105 MM	
24	MAZDA-LLXR504509W-6.5K-DC24V-ST-ND-A360 X B85 X C105 MM	09W	6500	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A360 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A360 X B85 X C105 MM	
25	MAZDA-LLXR504518W-3K-DC24V-ST-10VDIM-A660 X B85 X C105 MM	18W	3000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A660 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A660 X B85 X C105 MM	
26	MAZDA-LLXR504518W-3K-DC24V-ST-PH-A660 X B85 X C105 MM	18W	3000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A660 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A660 X B85 X C105 MM	
27	MAZDA-LLXR504518W-3K-DC24V-ST-DA-A660 X B85 X C105 MM	18W	3000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A660 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A660 X B85 X C105 MM	
28	MAZDA-LLXR504518W-3K-DC24V-ST-ND-A660 X B85 X C105 MM	18W	3000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A660 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A660 X B85 X C105 MM	
29	MAZDA-LLXR504518W-4K-DC24V-ST-10VDIM-A660 X B85 X C105 MM	18W	4000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A660 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A660 X B85 X C105 MM	
30	MAZDA-LLXR504518W-4K-DC24V-ST-PH-A660 X B85 X C105 MM	18W	4000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A660 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A660 X B85 X C105 MM	
31	MAZDA-LLXR504518W-4K-DC24V-ST-DA-A660 X B85 X C105 MM	18W	4000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A660 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A660 X B85 X C105 MM	
32	MAZDA-LLXR504518W-4K-DC24V-ST-ND-A660 X B85 X C105 MM	18W	4000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A660 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A660 X B85 X C105 MM	
33	MAZDA-LLXR504518W-5K-DC24V-ST-10VDIM-A660 X B85 X C105 MM	18W	5000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A660 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A660 X B85 X C105 MM	
34	MAZDA-LLXR504518W-5K-DC24V-ST-PH-A660 X B85 X C105 MM	18W	5000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A660 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A660 X B85 X C105 MM	
35	MAZDA-LLXR504518W-5K-DC24V-ST-DA-A660 X B85 X C105 MM	18W	5000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A660 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A660 X B85 X C105 MM	
36	MAZDA-LLXR504518W-5K-DC24V-ST-ND-A660 X B85 X C105 MM	18W	5000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A660 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A660 X B85 X C105 MM	
37	MAZDA-LLXR504518W-6K-DC24V-ST-10VDIM-A660 X B85 X C105 MM	18W	6000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A660 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A660 X B85 X C105 MM	
38	MAZDA-LLXR504518W-6K-DC24V-ST-PH-A660 X B85 X C105 MM	18W	6000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A660 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A660 X B85 X C105 MM	
39	MAZDA-LLXR504518W-6K-DC24V-ST-DA-A660 X B85 X C105 MM	18W	6000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A660 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A660 X B85 X C105 MM	
40	MAZDA-LLXR504518W-6K-DC24V-ST-ND-A660 X B85 X C105 MM	18W	6000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A660 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A660 X B85 X C105 MM	
41	MAZDA-LLXR504518W-2.7K-DC24V-ST-10VDIM-A660 X B85 X C105 MM	18W	2700	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A660 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A660 X B85 X C105 MM	
42	MAZDA-LLXR504518W-2.7K-DC24V-ST-PH-A660 X B85 X C105 MM	18W	2700	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A660 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A660 X B85 X C105 MM	
43	MAZDA-LLXR504518W-2.7K-DC24V-ST-DA-A660 X B85 X C105 MM	18W	2700	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A660 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A660 X B85 X C105 MM	
44	MAZDA-LLXR504518W-2.7K-DC24V-ST-ND-A660 X B85 X C105 MM	18W	2700	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A660 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A660 X B85 X C105 MM	
45	MAZDA-LLXR504518W-6.5K-DC24V-ST-10VDIM-A660 X B85 X C105 MM	18W	6500	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A660 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A660 X B85 X C105 MM	
46	MAZDA-LLXR504518W-6.5K-DC24V-ST-PH-A660 X B85 X C105 MM	18W	6500	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A660 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A660 X B85 X C105 MM	
47	MAZDA-LLXR504518W-6.5K-DC24V-ST-DA-A660 X B85 X C105 MM	18W	6500	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A660 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A660 X B85 X C105 MM	



DATASHEET

GENERATED ON: 22 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
48	MAZDA-LLXR504518W-6.5K-DC24V-ST-ND-A660 X B85 X C105 MM	18W	6500	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A660 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A660 X B85 X C105 MM	
49	MAZDA-LLXR504527W-3K-DC24V-ST-10VDIM-A960 X B85 X C105 MM	27W	3000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A960 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A960 X B85 X C105 MM	
50	MAZDA-LLXR504527W-3K-DC24V-ST-PH-A960 X B85 X C105 MM	27W	3000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A960 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A960 X B85 X C105 MM	
51	MAZDA-LLXR504527W-3K-DC24V-ST-DA-A960 X B85 X C105 MM	27W	3000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A960 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A960 X B85 X C105 MM	
52	MAZDA-LLXR504527W-3K-DC24V-ST-ND-A960 X B85 X C105 MM	27W	3000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A960 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A960 X B85 X C105 MM	
53	MAZDA-LLXR504527W-4K-DC24V-ST-10VDIM-A960 X B85 X C105 MM	27W	4000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A960 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A960 X B85 X C105 MM	
54	MAZDA-LLXR504527W-4K-DC24V-ST-PH-A960 X B85 X C105 MM	27W	4000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A960 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A960 X B85 X C105 MM	
55	MAZDA-LLXR504527W-4K-DC24V-ST-DA-A960 X B85 X C105 MM	27W	4000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A960 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A960 X B85 X C105 MM	
56	MAZDA-LLXR504527W-4K-DC24V-ST-ND-A960 X B85 X C105 MM	27W	4000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A960 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A960 X B85 X C105 MM	
57	MAZDA-LLXR504527W-5K-DC24V-ST-10VDIM-A960 X B85 X C105 MM	27W	5000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A960 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A960 X B85 X C105 MM	
58	MAZDA-LLXR504527W-5K-DC24V-ST-PH-A960 X B85 X C105 MM	27W	5000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A960 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A960 X B85 X C105 MM	
59	MAZDA-LLXR504527W-5K-DC24V-ST-DA-A960 X B85 X C105 MM	27W	5000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A960 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A960 X B85 X C105 MM	
60	MAZDA-LLXR504527W-5K-DC24V-ST-ND-A960 X B85 X C105 MM	27W	5000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A960 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A960 X B85 X C105 MM	
61	MAZDA-LLXR504527W-6K-DC24V-ST-10VDIM-A960 X B85 X C105 MM	27W	6000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A960 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A960 X B85 X C105 MM	
62	MAZDA-LLXR504527W-6K-DC24V-ST-PH-A960 X B85 X C105 MM	27W	6000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A960 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A960 X B85 X C105 MM	
63	MAZDA-LLXR504527W-6K-DC24V-ST-DA-A960 X B85 X C105 MM	27W	6000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A960 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A960 X B85 X C105 MM	
64	MAZDA-LLXR504527W-6K-DC24V-ST-ND-A960 X B85 X C105 MM	27W	6000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A960 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A960 X B85 X C105 MM	
65	MAZDA-LLXR504527W-2.7K-DC24V-ST-10VDIM-A960 X B85 X C105 MM	27W	2700	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A960 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A960 X B85 X C105 MM	
66	MAZDA-LLXR504527W-2.7K-DC24V-ST-PH-A960 X B85 X C105 MM	27W	2700	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A960 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A960 X B85 X C105 MM	
67	MAZDA-LLXR504527W-2.7K-DC24V-ST-DA-A960 X B85 X C105 MM	27W	2700	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A960 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A960 X B85 X C105 MM	
68	MAZDA-LLXR504527W-2.7K-DC24V-ST-ND-A960 X B85 X C105 MM	27W	2700	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A960 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A960 X B85 X C105 MM	
69	MAZDA-LLXR504527W-6.5K-DC24V-ST-10VDIM-A960 X B85 X C105 MM	27W	6500	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A960 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A960 X B85 X C105 MM	
70	MAZDA-LLXR504527W-6.5K-DC24V-ST-PH-A960 X B85 X C105 MM	27W	6500	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A960 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A960 X B85 X C105 MM	
71	MAZDA-LLXR504527W-6.5K-DC24V-ST-DA-A960 X B85 X C105 MM	27W	6500	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A960 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A960 X B85 X C105 MM	
72	MAZDA-LLXR504527W-6.5K-DC24V-ST-ND-A960 X B85 X C105 MM	27W	6500	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A960 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A960 X B85 X C105 MM	
73	MAZDA-LLXR504536W-3K-DC24V-ST-10VDIM-A1260 X B85 X C105 MM	36W	3000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A1260 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A1260 X B85 X C105 MM	
74	MAZDA-LLXR504536W-3K-DC24V-ST-PH-A1260 X B85 X C105 MM	36W	3000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A1260 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A1260 X B85 X C105 MM	
75	MAZDA-LLXR504536W-3K-DC24V-ST-DA-A1260 X B85 X C105 MM	36W	3000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A1260 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A1260 X B85 X C105 MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angle	Dimension	Material	IP	Dimensions	Price
76	MAZDA-LLXR504536W-3K-DC24V-ST-ND-A1260 X B85 X C105 MM	36W	3000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A1260 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A1260 X B85 X C105 MM	
77	MAZDA-LLXR504536W-4K-DC24V-ST-10VDIM-A1260 X B85 X C105 MM	36W	4000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A1260 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A1260 X B85 X C105 MM	
78	MAZDA-LLXR504536W-4K-DC24V-ST-PH-A1260 X B85 X C105 MM	36W	4000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A1260 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A1260 X B85 X C105 MM	
79	MAZDA-LLXR504536W-4K-DC24V-ST-DA-A1260 X B85 X C105 MM	36W	4000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A1260 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A1260 X B85 X C105 MM	
80	MAZDA-LLXR504536W-4K-DC24V-ST-ND-A1260 X B85 X C105 MM	36W	4000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A1260 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A1260 X B85 X C105 MM	
81	MAZDA-LLXR504536W-5K-DC24V-ST-10VDIM-A1260 X B85 X C105 MM	36W	5000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A1260 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A1260 X B85 X C105 MM	
82	MAZDA-LLXR504536W-5K-DC24V-ST-PH-A1260 X B85 X C105 MM	36W	5000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A1260 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A1260 X B85 X C105 MM	
83	MAZDA-LLXR504536W-5K-DC24V-ST-DA-A1260 X B85 X C105 MM	36W	5000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A1260 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A1260 X B85 X C105 MM	
84	MAZDA-LLXR504536W-5K-DC24V-ST-ND-A1260 X B85 X C105 MM	36W	5000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A1260 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A1260 X B85 X C105 MM	
85	MAZDA-LLXR504536W-6K-DC24V-ST-10VDIM-A1260 X B85 X C105 MM	36W	6000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A1260 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A1260 X B85 X C105 MM	
86	MAZDA-LLXR504536W-6K-DC24V-ST-PH-A1260 X B85 X C105 MM	36W	6000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A1260 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A1260 X B85 X C105 MM	
87	MAZDA-LLXR504536W-6K-DC24V-ST-DA-A1260 X B85 X C105 MM	36W	6000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A1260 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A1260 X B85 X C105 MM	
88	MAZDA-LLXR504536W-6K-DC24V-ST-ND-A1260 X B85 X C105 MM	36W	6000	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A1260 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A1260 X B85 X C105 MM	
89	MAZDA-LLXR504536W-2.7K-DC24V-ST-10VDIM-A1260 X B85 X C105 MM	36W	2700	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A1260 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A1260 X B85 X C105 MM	
90	MAZDA-LLXR504536W-2.7K-DC24V-ST-PH-A1260 X B85 X C105 MM	36W	2700	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A1260 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A1260 X B85 X C105 MM	
91	MAZDA-LLXR504536W-2.7K-DC24V-ST-DA-A1260 X B85 X C105 MM	36W	2700	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A1260 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A1260 X B85 X C105 MM	
92	MAZDA-LLXR504536W-2.7K-DC24V-ST-ND-A1260 X B85 X C105 MM	36W	2700	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A1260 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A1260 X B85 X C105 MM	
93	MAZDA-LLXR504536W-6.5K-DC24V-ST-10VDIM-A1260 X B85 X C105 MM	36W	6500	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	15°, 24°, 36°	A1260 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A1260 X B85 X C105 MM	
94	MAZDA-LLXR504536W-6.5K-DC24V-ST-PH-A1260 X B85 X C105 MM	36W	6500	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	PHASE CUT DIMMABLE	15°, 24°, 36°	A1260 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A1260 X B85 X C105 MM	
95	MAZDA-LLXR504536W-6.5K-DC24V-ST-DA-A1260 X B85 X C105 MM	36W	6500	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	DALI DIMMABLE DRIVER	15°, 24°, 36°	A1260 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A1260 X B85 X C105 MM	
96	MAZDA-LLXR504536W-6.5K-DC24V-ST-ND-A1260 X B85 X C105 MM	36W	6500	DC24V	STAINLESS STEEL FINISH	NON EMERGENCY	ON - OFF	15°, 24°, 36°	A1260 X B85 X C105 MM	DIE CAST ALUMINUM	IP67	A1260 X B85 X C105 MM	