



LUNOX

MAZDA Model: UPXR6530 Inground Light

Lunox Up Light waterproof IP67 stainless steel AISI 316L in-ground High Power LED recessed luminaire with round cover plate and clear glass provided with Different Angles of Light Diffusion. Submersible projector to be recessed into the ground inside or outside using the latest high power LED technology. Symmetrical light distribution with several powers and diffusion angles available. It is a robust construction in anodized aluminum body a cover plate in 316L stainless steel with 4mm thick. HPL Bolas combines high efficiency and long life and luminosity comparable to tp the other type of floor light. Installed individually or in groups, it is an attractive solution for many facilities in the private or public sector

ALL AVAILABLE VARIANTS

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
1	MAZDA-UPXR653018W-3K-240V-BL-10VDIM-A200 X B235 MM	18W	3000	240V	BLACK, STAINLESS STEEL FINISH	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	30	A200 X B235 MM	DIE CAST ALUMINUM	IP67	A200 X B235 MM	
2	MAZDA-UPXR653018W-3K-240V-BL-PH-A200 X B235 MM	18W	3000	240V	BLACK, STAINLESS STEEL FINISH	NON EMERGENCY	PHASE CUT DIMMABLE	30	A200 X B235 MM	DIE CAST ALUMINUM	IP67	A200 X B235 MM	
3	MAZDA-UPXR653018W-3K-240V-BL-DA-A200 X B235 MM	18W	3000	240V	BLACK, STAINLESS STEEL FINISH	NON EMERGENCY	DALI DIMMABLE DRIVER	30	A200 X B235 MM	DIE CAST ALUMINUM	IP67	A200 X B235 MM	
4	MAZDA-UPXR653018W-3K-240V-BL-ND-A200 X B235 MM	18W	3000	240V	BLACK, STAINLESS STEEL FINISH	NON EMERGENCY	ON - OFF	30	A200 X B235 MM	DIE CAST ALUMINUM	IP67	A200 X B235 MM	
5	MAZDA-UPXR653018W-4K-240V-BL-10VDIM-A200 X B235 MM	18W	4000	240V	BLACK, STAINLESS STEEL FINISH	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	30	A200 X B235 MM	DIE CAST ALUMINUM	IP67	A200 X B235 MM	
6	MAZDA-UPXR653018W-4K-240V-BL-PH-A200 X B235 MM	18W	4000	240V	BLACK, STAINLESS STEEL FINISH	NON EMERGENCY	PHASE CUT DIMMABLE	30	A200 X B235 MM	DIE CAST ALUMINUM	IP67	A200 X B235 MM	
7	MAZDA-UPXR653018W-4K-240V-BL-DA-A200 X B235 MM	18W	4000	240V	BLACK, STAINLESS STEEL FINISH	NON EMERGENCY	DALI DIMMABLE DRIVER	30	A200 X B235 MM	DIE CAST ALUMINUM	IP67	A200 X B235 MM	
8	MAZDA-UPXR653018W-4K-240V-BL-ND-A200 X B235 MM	18W	4000	240V	BLACK, STAINLESS STEEL FINISH	NON EMERGENCY	ON - OFF	30	A200 X B235 MM	DIE CAST ALUMINUM	IP67	A200 X B235 MM	
9	MAZDA-UPXR653018W-5K-240V-BL-10VDIM-A200 X B235 MM	18W	5000	240V	BLACK, STAINLESS STEEL FINISH	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	30	A200 X B235 MM	DIE CAST ALUMINUM	IP67	A200 X B235 MM	
10	MAZDA-UPXR653018W-5K-240V-BL-PH-A200 X B235 MM	18W	5000	240V	BLACK, STAINLESS STEEL FINISH	NON EMERGENCY	PHASE CUT DIMMABLE	30	A200 X B235 MM	DIE CAST ALUMINUM	IP67	A200 X B235 MM	
11	MAZDA-UPXR653018W-5K-240V-BL-DA-A200 X B235 MM	18W	5000	240V	BLACK, STAINLESS STEEL FINISH	NON EMERGENCY	DALI DIMMABLE DRIVER	30	A200 X B235 MM	DIE CAST ALUMINUM	IP67	A200 X B235 MM	
12	MAZDA-UPXR653018W-5K-240V-BL-ND-A200 X B235 MM	18W	5000	240V	BLACK, STAINLESS STEEL FINISH	NON EMERGENCY	ON - OFF	30	A200 X B235 MM	DIE CAST ALUMINUM	IP67	A200 X B235 MM	



DATASHEET

GENERATED ON: 27 Sep 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
13	MAZDA-UPXR653018W-6K-240V-BL-10VDIM-A200 X B235 MM	18W	6000	240V	BLACK, STAINLESS STEEL FINISH	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	30	A200 X B235 MM	DIE CAST ALUMINUM	IP67	A200 X B235 MM	
14	MAZDA-UPXR653018W-6K-240V-BL-PH-A200 X B235 MM	18W	6000	240V	BLACK, STAINLESS STEEL FINISH	NON EMERGENCY	PHASE CUT DIMMABLE	30	A200 X B235 MM	DIE CAST ALUMINUM	IP67	A200 X B235 MM	
15	MAZDA-UPXR653018W-6K-240V-BL-DA-A200 X B235 MM	18W	6000	240V	BLACK, STAINLESS STEEL FINISH	NON EMERGENCY	DALI DIMMABLE DRIVER	30	A200 X B235 MM	DIE CAST ALUMINUM	IP67	A200 X B235 MM	
16	MAZDA-UPXR653018W-6K-240V-BL-ND-A200 X B235 MM	18W	6000	240V	BLACK, STAINLESS STEEL FINISH	NON EMERGENCY	ON - OFF	30	A200 X B235 MM	DIE CAST ALUMINUM	IP67	A200 X B235 MM	
17	MAZDA-UPXR653018W-2.7K-240V-BL-10VDIM-A200 X B235 MM	18W	2700	240V	BLACK, STAINLESS STEEL FINISH	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	30	A200 X B235 MM	DIE CAST ALUMINUM	IP67	A200 X B235 MM	
18	MAZDA-UPXR653018W-2.7K-240V-BL-PH-A200 X B235 MM	18W	2700	240V	BLACK, STAINLESS STEEL FINISH	NON EMERGENCY	PHASE CUT DIMMABLE	30	A200 X B235 MM	DIE CAST ALUMINUM	IP67	A200 X B235 MM	
19	MAZDA-UPXR653018W-2.7K-240V-BL-DA-A200 X B235 MM	18W	2700	240V	BLACK, STAINLESS STEEL FINISH	NON EMERGENCY	DALI DIMMABLE DRIVER	30	A200 X B235 MM	DIE CAST ALUMINUM	IP67	A200 X B235 MM	
20	MAZDA-UPXR653018W-2.7K-240V-BL-ND-A200 X B235 MM	18W	2700	240V	BLACK, STAINLESS STEEL FINISH	NON EMERGENCY	ON - OFF	30	A200 X B235 MM	DIE CAST ALUMINUM	IP67	A200 X B235 MM	
21	MAZDA-UPXR653018W-6.5K-240V-BL-10VDIM-A200 X B235 MM	18W	6500	240V	BLACK, STAINLESS STEEL FINISH	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	30	A200 X B235 MM	DIE CAST ALUMINUM	IP67	A200 X B235 MM	
22	MAZDA-UPXR653018W-6.5K-240V-BL-PH-A200 X B235 MM	18W	6500	240V	BLACK, STAINLESS STEEL FINISH	NON EMERGENCY	PHASE CUT DIMMABLE	30	A200 X B235 MM	DIE CAST ALUMINUM	IP67	A200 X B235 MM	
23	MAZDA-UPXR653018W-6.5K-240V-BL-DA-A200 X B235 MM	18W	6500	240V	BLACK, STAINLESS STEEL FINISH	NON EMERGENCY	DALI DIMMABLE DRIVER	30	A200 X B235 MM	DIE CAST ALUMINUM	IP67	A200 X B235 MM	
24	MAZDA-UPXR653018W-6.5K-240V-BL-ND-A200 X B235 MM	18W	6500	240V	BLACK, STAINLESS STEEL FINISH	NON EMERGENCY	ON - OFF	30	A200 X B235 MM	DIE CAST ALUMINUM	IP67	A200 X B235 MM	
25	MAZDA-UPXR653025W-3K-240V-BL-10VDIM-A200 X B235 MM	25W	3000	240V	BLACK, STAINLESS STEEL FINISH	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	30	A200 X B235 MM	DIE CAST ALUMINUM	IP67	A200 X B235 MM	
26	MAZDA-UPXR653025W-3K-240V-BL-PH-A200 X B235 MM	25W	3000	240V	BLACK, STAINLESS STEEL FINISH	NON EMERGENCY	PHASE CUT DIMMABLE	30	A200 X B235 MM	DIE CAST ALUMINUM	IP67	A200 X B235 MM	
27	MAZDA-UPXR653025W-3K-240V-BL-DA-A200 X B235 MM	25W	3000	240V	BLACK, STAINLESS STEEL FINISH	NON EMERGENCY	DALI DIMMABLE DRIVER	30	A200 X B235 MM	DIE CAST ALUMINUM	IP67	A200 X B235 MM	
28	MAZDA-UPXR653025W-3K-240V-BL-ND-A200 X B235 MM	25W	3000	240V	BLACK, STAINLESS STEEL FINISH	NON EMERGENCY	ON - OFF	30	A200 X B235 MM	DIE CAST ALUMINUM	IP67	A200 X B235 MM	
29	MAZDA-UPXR653025W-4K-240V-BL-10VDIM-A200 X B235 MM	25W	4000	240V	BLACK, STAINLESS STEEL FINISH	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	30	A200 X B235 MM	DIE CAST ALUMINUM	IP67	A200 X B235 MM	
30	MAZDA-UPXR653025W-4K-240V-BL-PH-A200 X B235 MM	25W	4000	240V	BLACK, STAINLESS STEEL FINISH	NON EMERGENCY	PHASE CUT DIMMABLE	30	A200 X B235 MM	DIE CAST ALUMINUM	IP67	A200 X B235 MM	
31	MAZDA-UPXR653025W-4K-240V-BL-DA-A200 X B235 MM	25W	4000	240V	BLACK, STAINLESS STEEL FINISH	NON EMERGENCY	DALI DIMMABLE DRIVER	30	A200 X B235 MM	DIE CAST ALUMINUM	IP67	A200 X B235 MM	
32	MAZDA-UPXR653025W-4K-240V-BL-ND-A200 X B235 MM	25W	4000	240V	BLACK, STAINLESS STEEL FINISH	NON EMERGENCY	ON - OFF	30	A200 X B235 MM	DIE CAST ALUMINUM	IP67	A200 X B235 MM	

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
33	MAZDA-UPXR653025W-5K-240V-BL-10VDIM-A200 X B235 MM	25W	5000	240V	BLACK, STAINLESS STEEL FINISH	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	30	A200 X B235 MM	DIE CAST ALUMINUM	IP67	A200 X B235 MM	
34	MAZDA-UPXR653025W-5K-240V-BL-PH-A200 X B235 MM	25W	5000	240V	BLACK, STAINLESS STEEL FINISH	NON EMERGENCY	PHASE CUT DIMMABLE	30	A200 X B235 MM	DIE CAST ALUMINUM	IP67	A200 X B235 MM	
35	MAZDA-UPXR653025W-5K-240V-BL-DA-A200 X B235 MM	25W	5000	240V	BLACK, STAINLESS STEEL FINISH	NON EMERGENCY	DALI DIMMABLE DRIVER	30	A200 X B235 MM	DIE CAST ALUMINUM	IP67	A200 X B235 MM	
36	MAZDA-UPXR653025W-5K-240V-BL-ND-A200 X B235 MM	25W	5000	240V	BLACK, STAINLESS STEEL FINISH	NON EMERGENCY	ON - OFF	30	A200 X B235 MM	DIE CAST ALUMINUM	IP67	A200 X B235 MM	
37	MAZDA-UPXR653025W-6K-240V-BL-10VDIM-A200 X B235 MM	25W	6000	240V	BLACK, STAINLESS STEEL FINISH	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	30	A200 X B235 MM	DIE CAST ALUMINUM	IP67	A200 X B235 MM	
38	MAZDA-UPXR653025W-6K-240V-BL-PH-A200 X B235 MM	25W	6000	240V	BLACK, STAINLESS STEEL FINISH	NON EMERGENCY	PHASE CUT DIMMABLE	30	A200 X B235 MM	DIE CAST ALUMINUM	IP67	A200 X B235 MM	
39	MAZDA-UPXR653025W-6K-240V-BL-DA-A200 X B235 MM	25W	6000	240V	BLACK, STAINLESS STEEL FINISH	NON EMERGENCY	DALI DIMMABLE DRIVER	30	A200 X B235 MM	DIE CAST ALUMINUM	IP67	A200 X B235 MM	
40	MAZDA-UPXR653025W-6K-240V-BL-ND-A200 X B235 MM	25W	6000	240V	BLACK, STAINLESS STEEL FINISH	NON EMERGENCY	ON - OFF	30	A200 X B235 MM	DIE CAST ALUMINUM	IP67	A200 X B235 MM	
41	MAZDA-UPXR653025W-2.7K-240V-BL-10VDIM-A200 X B235 MM	25W	2700	240V	BLACK, STAINLESS STEEL FINISH	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	30	A200 X B235 MM	DIE CAST ALUMINUM	IP67	A200 X B235 MM	
42	MAZDA-UPXR653025W-2.7K-240V-BL-PH-A200 X B235 MM	25W	2700	240V	BLACK, STAINLESS STEEL FINISH	NON EMERGENCY	PHASE CUT DIMMABLE	30	A200 X B235 MM	DIE CAST ALUMINUM	IP67	A200 X B235 MM	
43	MAZDA-UPXR653025W-2.7K-240V-BL-DA-A200 X B235 MM	25W	2700	240V	BLACK, STAINLESS STEEL FINISH	NON EMERGENCY	DALI DIMMABLE DRIVER	30	A200 X B235 MM	DIE CAST ALUMINUM	IP67	A200 X B235 MM	
44	MAZDA-UPXR653025W-2.7K-240V-BL-ND-A200 X B235 MM	25W	2700	240V	BLACK, STAINLESS STEEL FINISH	NON EMERGENCY	ON - OFF	30	A200 X B235 MM	DIE CAST ALUMINUM	IP67	A200 X B235 MM	
45	MAZDA-UPXR653025W-6.5K-240V-BL-10VDIM-A200 X B235 MM	25W	6500	240V	BLACK, STAINLESS STEEL FINISH	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	30	A200 X B235 MM	DIE CAST ALUMINUM	IP67	A200 X B235 MM	
46	MAZDA-UPXR653025W-6.5K-240V-BL-PH-A200 X B235 MM	25W	6500	240V	BLACK, STAINLESS STEEL FINISH	NON EMERGENCY	PHASE CUT DIMMABLE	30	A200 X B235 MM	DIE CAST ALUMINUM	IP67	A200 X B235 MM	
47	MAZDA-UPXR653025W-6.5K-240V-BL-DA-A200 X B235 MM	25W	6500	240V	BLACK, STAINLESS STEEL FINISH	NON EMERGENCY	DALI DIMMABLE DRIVER	30	A200 X B235 MM	DIE CAST ALUMINUM	IP67	A200 X B235 MM	
48	MAZDA-UPXR653025W-6.5K-240V-BL-ND-A200 X B235 MM	25W	6500	240V	BLACK, STAINLESS STEEL FINISH	NON EMERGENCY	ON - OFF	30	A200 X B235 MM	DIE CAST ALUMINUM	IP67	A200 X B235 MM	