DATASHEET

GENERATED ON: 15 Nov 2026 | SYS.REF: MAZDA-LED



NOVA

MAZDA Model: RMXR6580 Inground Light

Nova is a family of outdoor in-ground lights for effect lighting. They are perfect for lighting the edges of paths and other garden elements. They are made of acid-proof Stainless steel and powder coated machined aluminum, lens optical system with Static load resistance 5000 Kg. All external screws are in 316 stainless steel available 1, 2 and 4 Pathway and more.

ALL AVAILABLE VARIANTS

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions Price
1	MAZDA-RMXR658003-3K-AC240-BK-10VDIM-A60 X B110 X C40MM	03	3000	240VAC	BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM
2	MAZDA-RMXR658003-3K-AC240-DA-10VDIM-A60 X B110 X C40MM	03	3000	240VAC	DARK GRAY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM
3	MAZDA-RMXR658003-3K-AC240-ST-10VDIM-A60 X B110 X C40MM	03	3000	240VAC	STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM
4	MAZDA-RMXR658003-3K-AC240-BK-PH-A60 X B110 X C40MM	03	3000	240VAC	BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM
5	MAZDA-RMXR658003-3K-AC240-DA-PH-A60 X B110 X C40MM	03	3000	240VAC	DARK GRAY	NON EMERGENCY	PHASE CUT DIMMABLE	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM
6	MAZDA-RMXR658003-3K-AC240-ST-PH-A60 X B110 X C40MM	03	3000	240VAC	STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM
7	MAZDA-RMXR658003-3K-AC240-BK-DA-A60 X B110 X C40MM	03	3000	240VAC	BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM
8	MAZDA-RMXR658003-3K-AC240-DA-DA-A60 X B110 X C40MM	03	3000	240VAC	DARK GRAY	NON EMERGENCY	DALI DIMMABLE DRIVER	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM
9	MAZDA-RMXR658003-3K-AC240-ST-DA-A60 X B110 X C40MM	03	3000	240VAC	STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM
10	MAZDA-RMXR658003-3K-AC240-BK-ND-A60 X B110 X C40MM	03	3000	240VAC	BLACK	NON EMERGENCY	ON - OFF	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM

DATASHEET

GENERATED ON: 15 Nov 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions Price
11	**MAZDA-RMXR658003-3K-AC240-DA-ND-A60 X B110 X C40MM**	03	3000	240VAC	DARK GRAY	NON EMERGENCY	ON - OFF	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM
12	**MAZDA-RMXR658003-3K-AC240-ST-ND-A60 X B110 X C40MM**	03	3000	240VAC	STAINLESS STEEL	NON EMERGENCY	ON - OFF	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM
13	**MAZDA-RMXR658003-4K-AC240-BK-10VDIM-A60 X B110 X C40MM**	03	4000	240VAC	BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM
14	**MAZDA-RMXR658003-4K-AC240-DA-10VDIM-A60 X B110 X C40MM**	03	4000	240VAC	DARK GRAY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM
15	**MAZDA-RMXR658003-4K-AC240-ST-10VDIM-A60 X B110 X C40MM**	03	4000	240VAC	STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM
16	**MAZDA-RMXR658003-4K-AC240-BK-PH-A60 X B110 X C40MM**	03	4000	240VAC	BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM
17	**MAZDA-RMXR658003-4K-AC240-DA-PH-A60 X B110 X C40MM**	03	4000	240VAC	DARK GRAY	NON EMERGENCY	PHASE CUT DIMMABLE	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM
18	**MAZDA-RMXR658003-4K-AC240-ST-PH-A60 X B110 X C40MM**	03	4000	240VAC	STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM
19	**MAZDA-RMXR658003-4K-AC240-BK-DA-A60 X B110 X C40MM**	03	4000	240VAC	BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM
20	**MAZDA-RMXR658003-4K-AC240-DA-DA-A60 X B110 X C40MM**	03	4000	240VAC	DARK GRAY	NON EMERGENCY	DALI DIMMABLE DRIVER	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM
21	**MAZDA-RMXR658003-4K-AC240-ST-DA-A60 X B110 X C40MM**	03	4000	240VAC	STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM
22	**MAZDA-RMXR658003-4K-AC240-BK-ND-A60 X B110 X C40MM**	03	4000	240VAC	BLACK	NON EMERGENCY	ON - OFF	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM
23	**MAZDA-RMXR658003-4K-AC240-DA-ND-A60 X B110 X C40MM**	03	4000	240VAC	DARK GRAY	NON EMERGENCY	ON - OFF	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM
24	**MAZDA-RMXR658003-4K-AC240-ST-ND-A60 X B110 X C40MM**	03	4000	240VAC	STAINLESS STEEL	NON EMERGENCY	ON - OFF	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM
25	**MAZDA-RMXR658003-5K-AC240-BK-10VDIM-A60 X B110 X C40MM**	03	5000	240VAC	BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM
26	**MAZDA-RMXR658003-5K-AC240-DA-10VDIM-A60 X B110 X C40MM**	03	5000	240VAC	DARK GRAY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM
27	**MAZDA-RMXR658003-5K-AC240-ST-10VDIM-A60 X B110 X C40MM**	03	5000	240VAC	STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM

DATASHEET

GENERATED ON: 15 Nov 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
28	**MAZDA-RMXR658003-5K-AC240-BK-PH-A60 X B110 X C40MM**	03	5000	240VAC	BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM	
29	**MAZDA-RMXR658003-5K-AC240-DA-PH-A60 X B110 X C40MM**	03	5000	240VAC	DARK GRAY	NON EMERGENCY	PHASE CUT DIMMABLE	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM	
30	**MAZDA-RMXR658003-5K-AC240-ST-PH-A60 X B110 X C40MM**	03	5000	240VAC	STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM	
31	**MAZDA-RMXR658003-5K-AC240-BK-DA-A60 X B110 X C40MM**	03	5000	240VAC	BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM	
32	**MAZDA-RMXR658003-5K-AC240-DA-DA-A60 X B110 X C40MM**	03	5000	240VAC	DARK GRAY	NON EMERGENCY	DALI DIMMABLE DRIVER	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM	
33	**MAZDA-RMXR658003-5K-AC240-ST-DA-A60 X B110 X C40MM**	03	5000	240VAC	STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM	
34	**MAZDA-RMXR658003-5K-AC240-BK-ND-A60 X B110 X C40MM**	03	5000	240VAC	BLACK	NON EMERGENCY	ON - OFF	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM	
35	**MAZDA-RMXR658003-5K-AC240-DA-ND-A60 X B110 X C40MM**	03	5000	240VAC	DARK GRAY	NON EMERGENCY	ON - OFF	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM	
36	**MAZDA-RMXR658003-5K-AC240-ST-ND-A60 X B110 X C40MM**	03	5000	240VAC	STAINLESS STEEL	NON EMERGENCY	ON - OFF	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM	
37	**MAZDA-RMXR658003-6K-AC240-BK-10VDIM-A60 X B110 X C40MM**	03	6000	240VAC	BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM	
38	**MAZDA-RMXR658003-6K-AC240-DA-10VDIM-A60 X B110 X C40MM**	03	6000	240VAC	DARK GRAY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM	
39	**MAZDA-RMXR658003-6K-AC240-ST-10VDIM-A60 X B110 X C40MM**	03	6000	240VAC	STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM	
40	**MAZDA-RMXR658003-6K-AC240-BK-PH-A60 X B110 X C40MM**	03	6000	240VAC	BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM	
41	**MAZDA-RMXR658003-6K-AC240-DA-PH-A60 X B110 X C40MM**	03	6000	240VAC	DARK GRAY	NON EMERGENCY	PHASE CUT DIMMABLE	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM	
42	**MAZDA-RMXR658003-6K-AC240-ST-PH-A60 X B110 X C40MM**	03	6000	240VAC	STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM	
43	**MAZDA-RMXR658003-6K-AC240-BK-DA-A60 X B110 X C40MM**	03	6000	240VAC	BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM	
44	**MAZDA-RMXR658003-6K-AC240-DA-DA-A60 X B110 X C40MM**	03	6000	240VAC	DARK GRAY	NON EMERGENCY	DALI DIMMABLE DRIVER	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM	

DATASHEET

GENERATED ON: 15 Nov 2026 | SYS.REF: MAZDA-LED

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions Price
45	**MAZDA-RMXR658003-6K-AC240-ST-DA-A60 X B110 X C40MM**	03	6000	240VAC	STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM
46	**MAZDA-RMXR658003-6K-AC240-BK-ND-A60 X B110 X C40MM**	03	6000	240VAC	BLACK	NON EMERGENCY	ON - OFF	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM
47	**MAZDA-RMXR658003-6K-AC240-DA-ND-A60 X B110 X C40MM**	03	6000	240VAC	DARK GRAY	NON EMERGENCY	ON - OFF	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM
48	**MAZDA-RMXR658003-6K-AC240-ST-ND-A60 X B110 X C40MM**	03	6000	240VAC	STAINLESS STEEL	NON EMERGENCY	ON - OFF	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM
49	**MAZDA-RMXR658003-6.5K-AC240-BK-10VDIM-A60 X B110 X C40MM**	03	6500	240VAC	BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM
50	**MAZDA-RMXR658003-6.5K-AC240-DA-10VDIM-A60 X B110 X C40MM**	03	6500	240VAC	DARK GRAY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM
51	**MAZDA-RMXR658003-6.5K-AC240-ST-10VDIM-A60 X B110 X C40MM**	03	6500	240VAC	STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM
52	**MAZDA-RMXR658003-6.5K-AC240-BK-PH-A60 X B110 X C40MM**	03	6500	240VAC	BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM
53	**MAZDA-RMXR658003-6.5K-AC240-DA-PH-A60 X B110 X C40MM**	03	6500	240VAC	DARK GRAY	NON EMERGENCY	PHASE CUT DIMMABLE	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM
54	**MAZDA-RMXR658003-6.5K-AC240-ST-PH-A60 X B110 X C40MM**	03	6500	240VAC	STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM
55	**MAZDA-RMXR658003-6.5K-AC240-BK-DA-A60 X B110 X C40MM**	03	6500	240VAC	BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM
56	**MAZDA-RMXR658003-6.5K-AC240-DA-DA-A60 X B110 X C40MM**	03	6500	240VAC	DARK GRAY	NON EMERGENCY	DALI DIMMABLE DRIVER	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM
57	**MAZDA-RMXR658003-6.5K-AC240-ST-DA-A60 X B110 X C40MM**	03	6500	240VAC	STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM
58	**MAZDA-RMXR658003-6.5K-AC240-BK-ND-A60 X B110 X C40MM**	03	6500	240VAC	BLACK	NON EMERGENCY	ON - OFF	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM
59	**MAZDA-RMXR658003-6.5K-AC240-DA-ND-A60 X B110 X C40MM**	03	6500	240VAC	DARK GRAY	NON EMERGENCY	ON - OFF	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM
60	**MAZDA-RMXR658003-6.5K-AC240-ST-ND-A60 X B110 X C40MM**	03	6500	240VAC	STAINLESS STEEL	NON EMERGENCY	ON - OFF	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM
61	**MAZDA-RMXR658003-2.7K-AC240-BK-10VDIM-A60 X B110 X C40MM**	03	2700	240VAC	BLACK	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM

#	Code	WATT	CCT	Voltage	Body Color	Emergency Backup	Control	Beam Angel	Dimension	Material	IP	Dimensions	Price
62	**MAZDA-RMXR658003-2.7K-AC240-DA-10VDIM-A60 X B110 X C40MM**	03	2700	240VAC	DARK GRAY	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM	
63	**MAZDA-RMXR658003-2.7K-AC240-ST-10VDIM-A60 X B110 X C40MM**	03	2700	240VAC	STAINLESS STEEL	NON EMERGENCY	0/1-10 V DIMMABLE DRIVER	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM	
64	**MAZDA-RMXR658003-2.7K-AC240-BK-PH-A60 X B110 X C40MM**	03	2700	240VAC	BLACK	NON EMERGENCY	PHASE CUT DIMMABLE	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM	
65	**MAZDA-RMXR658003-2.7K-AC240-DA-PH-A60 X B110 X C40MM**	03	2700	240VAC	DARK GRAY	NON EMERGENCY	PHASE CUT DIMMABLE	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM	
66	**MAZDA-RMXR658003-2.7K-AC240-ST-PH-A60 X B110 X C40MM**	03	2700	240VAC	STAINLESS STEEL	NON EMERGENCY	PHASE CUT DIMMABLE	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM	
67	**MAZDA-RMXR658003-2.7K-AC240-BK-DA-A60 X B110 X C40MM**	03	2700	240VAC	BLACK	NON EMERGENCY	DALI DIMMABLE DRIVER	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM	
68	**MAZDA-RMXR658003-2.7K-AC240-DA-DA-A60 X B110 X C40MM**	03	2700	240VAC	DARK GRAY	NON EMERGENCY	DALI DIMMABLE DRIVER	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM	
69	**MAZDA-RMXR658003-2.7K-AC240-ST-DA-A60 X B110 X C40MM**	03	2700	240VAC	STAINLESS STEEL	NON EMERGENCY	DALI DIMMABLE DRIVER	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM	
70	**MAZDA-RMXR658003-2.7K-AC240-BK-ND-A60 X B110 X C40MM**	03	2700	240VAC	BLACK	NON EMERGENCY	ON - OFF	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM	
71	**MAZDA-RMXR658003-2.7K-AC240-DA-ND-A60 X B110 X C40MM**	03	2700	240VAC	DARK GRAY	NON EMERGENCY	ON - OFF	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM	
72	**MAZDA-RMXR658003-2.7K-AC240-ST-ND-A60 X B110 X C40MM**	03	2700	240VAC	STAINLESS STEEL	NON EMERGENCY	ON - OFF	60	A60 X B110 X C40MM	G: DIE-CAST ALUMINUM,AISI 316 STAINLESS STEEL HEAD AND SCREWS.	67	A60 X B110 X C40MM	